

Station No. 3092/3

RAINFALL at RIBBLE HEAD (STATION) ~~HA~~

51

County of W. RIDING - YORKSObserver RAILWAY EXECUTIVE FOR M.O.River Basin RIBBLE - 2 (+A)Stationmaster - Mr. M.A. Elliott (H/O SA)Type of Gauge M.O. MKT (3%) (HA)Annual Average in. based on 7790 years obs. un-weighted. Period of average 1916-50 Ref. S" " 78.65 " " 5 " " 1954-58 " " File No. E163.87/53

Diameter ...	571	486	5"							5"	
Height ...		1	1' 0"							1' 0"	
Altitude ...		31	1025'							1025'	
Year ...	1951	1952	1953	1954	1955	1956	1957	1958	1959	1960	Means
January ...				7.66	6.13	6.21	10.52	6.75	5.04	11.27	
February ...				3.81	2.95	3.03	6.08	10.75	3.08	6.23	
March ...				4.19	2.73	3.86	7.25	2.26	5.12	1.86	
April ...				2.48	5.35	1.99	1.68	3.16	4.77	5.28	
May ...				3.93	5.93	5.29	4.34	7.21	1.41	2.29	
June ...				6.61	5.12	3.08	3.04	4.88	3.87	3.50	
July ...				11.98	2.18	5.68	7.10	5.46	5.57	12.50	
August ...				10.72	1.50	14.70	7.74	6.99	1.25	3.59	
September ...				11.81	5.90	4.20	8.71	7.77	.87	3.66	
October ...				16.50	6.50	6.50	11.49	7.03	8.74	4.17	
November ...				11.83	3.19	3.61	2.67	2.20	7.78	12.52	
December ...			20/17	17.62	11.64	8.48	9.79	4.90	12.94	9.50	
TOTALS ...			n.p. inc.	109.14	59.12	66.63	80.41	69.36	60.44	76.37	

1953. Wall 35' 60' NW; ~~Wall~~ ^{fence} 4' 12' SE. Commenced 20/12/51

1956. G. Sound. Bottle neck broken. Site satisfactory.

Ins 5/4/57 R. Rudlin. G. Sound. Gxy Sol.

1956 Corrected for wind.

1958 Imps T. Hutton 24/10/58 - Satisfactory - maybe a small amount of oil but reduced to minimum by hand (t.w?) round G.

Gmp 6/1/60. T.W. Rant. new tank well and drill well around gauge to reduce wind effect - on satisfactory.

Position of Station on Ordnance One-Inch map :

No. of Map.....

National Grid Reference 766789

Date.	Lat. N.	Long.	Railway Station.	Distance Direction from gauge	Parish Church.	Distance Direction from gauge.
			<u>RIBBLEHEAD</u>	<u>NIL.</u>	<u>CHAPEL LE DALE</u>	<u>1 1/2 m. 240°</u>

Summary of Earlier Records from 10-year Sheets :

Record D, or d	1910-19	1920-30	1931-40	1941-50	1951-60