

Station No. 5545/43

RAINFALL at Loch Turret (Lower Glen Turret)

41

County of Perth

Observer J. Water Engineer Perth

River Basin 7 Tay-Farn

Type of Gauge

Annual Average in. based on years obs. un-weighted. Period of average Ref.

File No.

Diameter				880	989		5"				
Height					1		1'				
Altitude					41		1090'			1100	
Year	1941	1942	1943	1944	1945	1946	1947	1948	1949	1950	Means
January							8.75	(1.50)	6.55	(3.56)	
February							(2.80)	7.05	5.65	(6.26)	
March							(6.30)	4.15	2.65	3.05	
April							8.70	2.95	3.75	(3.59)	
May							5.05	4.20	3.10	(2.30)	
June							4.40	6.40	1.70	2.30	
July							5.60	3.55	1.85	6.74	
August							0.00	7.75	4.72	8.65	
September							6.80	6.80	2.15	9.02	
October							3.70	7.30	8.85	4.90	
November							7.15	4.30	5.01	4.31	
December							3.30	9.85	7.77	4.29	
TOTALS							62.55 w	71.80	53.75 w	58.97 w	

1947 Feb. March not obs. Dec app. into Jan '48. Farn 4', 1 1/2' diam. all round. Hills 700' 1400 yds E. Hills 600' 1200 yds W.

1950 Jan./Feb. Apr./May.

30004 40004 60004

Position of Station on reduced Ordnance Survey Map,
1 mile to 1 inch Series

No. of Map

Reference No.

Date.	Lat. N.	Long.	Railway Station.	Distance from gauge	Direction from gauge	Parish Church.	Distance from gauge.	Direction from gauge.

BRITISH RAINFALL ORGANIZATION

RAINFALL at S Loch Turret (Lower Glen Turret) Station No. 5545/4/3 51
 County of Perth Observer Water Eng. Perth
 River Basin Lay - Barn - 7 Burns, E. - Strathgairn - Strathgairn
 Type of Gauge Water Eng. Perth

Annual Average 54.6 in. based on 18 years obs. un-weighted. Period of average 1891-1909 Ref. 18604

File No.

Diameter ...	5"				880	989					
Height ...	1' 0"					1					
Altitude ...	1100'					51					
Year ...	1951	1952	1953	1954	1955	1956	1957	1958	1959	1960	Means
January ...	(6.50)	3.60	1.41	6.15	3.65	(4.65)	5.65	4.55	2.45	(6.25)	
February ...	(6.24)	(1.50)	2.05	6.35	(3.04)	2.65	4.70	3.95	2.10	(7.10)	
March ...	3.30	4.22	1.25	7.40	3.60	3.95	5.68	3.10	4.15	3.70	
April ...	3.93	2.80	2.25	1.81	2.75	(1.70)	3.90	2.00	3.70	(5.40)	
May ...	1.70	2.62	2.85	6.50	2.70	3.65	4.60	3.90	1.35	4.15	
June ...	2.75	3.28	3.32	3.08	3.30	3.80	3.00	4.10	2.05	3.40	
July ...	3.90	2.62	5.45	3.70	1.55	4.90	3.55	5.65	5.65	4.75	
August ...	6.05	5.78	2.40	4.45	1.50	6.68	5.15	4.95	2.10	6.20	
September ...	4.60	2.05	6.01	5.95	3.30	6.30	3.55	6.00	1.40	5.45	
October ...	1.74	5.05	3.40	6.60	4.75	4.00	3.05	4.20	5.60	(7.00)	
November ...	10.68	2.65	5.70	9.40	2.70	2.00	1.30	1.75	8.20	(10.80)	
December ...	6.43	3.90	6.35	4.40	(9.60)	8.40	6.40	7.75	9.05	(7.00)	
TOTALS ...	57.82	40.07	42.44	65.79	42.34	52.68	50.53	51.90	47.80	(71.20)	

1953. Inspected by Mr. Thomson 29.5.53. Good site, slight slope to S.W. New site may be selected lower down the valley if gauge is flooded when new dam is constructed. Turf wall recommended. 10/56. Turf will recur. 1953 built. Ins. 7.54. Eng. Perth. c.c. A good & slightly open site sheltered generally to the W & S and locally to the S. Open to the N.

60004 20004

20014 44004

64074

27/2/66 221266

Position of Station on Ordnance One-Inch map: No. of Map..... National Grid Reference 4784263

Date.	Lat. N.	Long.	Railway Station.	Distance Direction from gauge	Parish Church.	Distance Direction from gauge.

Summary of Earlier Records from 10-year Sheets:

Record D, or d	1910-19	1920-30	1931-40	1941-50	1951-60
				C 1947	