


1. Directional Ultrasonic Beacon Basic Specifications



項目	内容
Size	100×80×35mm
Voltage	① DC 24V (variable depending on input voltage 16V to 36V) or ② DC 5V (possible within the range of 4.5V to 9V)
Power Consumption	最大 1W
Plug Dimensions	Φ 2.1 x 5.5 x 9.5mm 
Ultrasonic element size	diameter 14mm (Japanese domestic production)
frequency	40kHz modulation
Number of ultrasonic elements	1pc.
Fixing Method	M3 Screw fastening
Color	White / Gray (option)
How to change your ID	Micro USB Micro-B Serial communication
Accessories	24V Edition : AC adapter or 5V Edition : AC adapter or DC plug to USB power cable

	<p>< Software ></p> <ul style="list-style-type: none"> • ID rewriting program (Windows version) • SDK and runtime (Android or iOS or Linux) • Received ID confirmation app (Android version) • Sample program (Android or iOS) <p>< Documentation ></p> <ul style="list-style-type: none"> • Directional Ultrasonic Beacon SDK Manual • ID Rewriting Program (BeaconIdWriter) Instruction Manual • Directional Ultrasonic Beacon Instruction Manual • Directional Ultrasonic Beacon SDK Development License • Directional Ultrasonic Beacon Product Warranty
Limitations	Cannot be used in vehicles due to license agreement