

# DeepSF: Deep CNN for mapping protein sequences to folds

Zhiyang's presentation about [1]

Zhiyang Ong

Department of Electrical and Computer Engineering  
Dwight Look College of Engineering,  
Texas A&M University  
College Station, TX

March 26, 2020

- ① Problem and Knowledge Gap
- ② Proposed Solution(s)
- ③ Experimental Results
- ④ Discussion and Muddy Points

# Table of Contents

- 1 Problem and Knowledge Gap
- 2 Proposed Solution(s)
- 3 Experimental Results
- 4 Discussion and Muddy Points

# Context of the Problem

## Background Information

Context of the problem.

- ① The structures of most ( $> 99\%$ ) proteins are unknown
- ② Protein fold recognition enables us to associate a protein sequence to a protein fold
  - Identifying protein homologs that share the same protein fold
  - With this protein fold, determine its protein structure [Tramontano2003]
  - With this protein structure, determine its protein function
    - [Osadchy2011,OConnor2010,Tramontano2003,Hegyi1999]
    - [OConnor2014a, From Contents: Unit 2, How Do Cells Decode Genetic Information into Functional Proteins?: §2.4 The Functions of Proteins Are Determined by Their Three-Dimensional Structures]
    - [OConnor2014, From Contents: Unit 2, How Do Cells Decode Genetic Information into Functional Proteins?: §2.4 The Functions of Proteins Are Determined by Their Three-Dimensional Structures]



# Problem Definition - 1

What is the problem that [1] is solving?

Problem description...

- ① Problems with sequence-based methods, especially sequence alignment methods (including profile-sequence and profile-profile alignment methods)
  - Methods for mapping protein sequences to protein folds are indirect
  - Can't explain relationship between protein sequences & protein folds, even machine learning (ML) methods
  - traditional ML methods also can't work for classifying data into large number of categories
    - multi-layer perceptron
    - support-vector machines
    - ensemble classifiers
    - kernel-based learning
- ② Other methods have methodological limitations



# Problem Definition - 2

What is the problem that [1] is solving?

Problem description... Continued.

- ① Protein fold recognition enables us to associate a protein sequence to a protein fold
  - With this protein fold, we can determine its protein structure
  - With this protein structure, we can determine its protein function

# Problem Importance

Why is it important?

Why is this problem important?

- This facilitates protein structure prediction
- Knowing about protein folds help us in protein structure prediction
- Protein structure prediction enables protein function prediction
- Knowing about protein structure and function facilitates:
  - drug/medication design [Nogrady2005, §1.6.4, pp. 54]  
[Golan2008, Chapter 1, pp. 4]
  - biotechnology [Walsh2014, Chapter 2]
  - synthetic biology [Zhao2013d, Chapter 2]
  - personalized [Cullis2015, Chapter 2, pp. 26] or precision medicine [Mousa2020, §24.3.2, pp. 778]
  - gene therapy [Wecker2010, Chapter 5, pp. 51]



# What are the Knowledge Gaps in [1]?

How would [1] address these knowledge gaps?

List of knowledge gaps:

- Lack of direct methods for mapping protein sequences to protein folds
- Methods can't explain relationship between protein sequences & protein folds



# Table of Contents

- 1 Problem and Knowledge Gap
- 2 Proposed Solution(s)**
- 3 Experimental Results
- 4 Discussion and Muddy Points

# Proposed Solution(s) - 1

What do they proposed to address the knowledge gap?

Proposed Solution(s).

- Use 1-D deep convolutional neural network (deep CNN)

# Proposed Solution(s) - 2

What do they proposed to address the knowledge gap?

Proposed Solution(s).

- Use input feature generation and label assignment from PSI-BLAST.
- Specifically, use position-specific scoring matrix
- Train all mini-batches for 100 epochs
- Distance metrics
  - 1 Euclid-D, Euclidean distance
  - 2 Manh-D, Manhattan distance
  - 3 Corr-D, Pearson's Correlation score
  - 4 KL-D, KL-Divergence



# Dataset and Methods

Which datasets were used?

- SCOP 1.75 was used for training and validation (§3.1)
- SCOP 2.06 (§3.2) and CASP (§3.3) was used for test

# Table of Contents

- ① Problem and Knowledge Gap
- ② Proposed Solution(s)
- ③ Experimental Results**
- ④ Discussion and Muddy Points

# Experimental Results - 1

How do their proposed solutions compare with existing solutions?

**Table 1.**

The prediction accuracy at family/superfamily/fold levels for top 1, top 5 and top 10 predictions of DeepSF and PSI-BLAST, on SCOP 1.75 test dataset

Level	Methods	Top1	Top5	Top10
Family (1272 proteins)	DeepSF	76.18%	94.50%	97.56%
	PSI-BLAST	96.80%	97.40%	97.60%
Superfamily (1254 proteins)	DeepSF	50.71%	77.67%	77.67%
	PSI-BLAST	42.20%	51.40%	54.60%
Fold (718 proteins)	DeepSF	40.95%	70.47%	82.45%
	PSI-BLAST	5.60%	11.60%	16.20%



# Experimental Results - 2

How do their proposed solutions compare with existing solutions?

**Table 2.**

The accuracy of DeepSF on SCOP 2.06 dataset and its subsets

DeepSF	Top1	Top5	Top10
SCOP2.06 dataset	73.00%	90.25%	94.51%
'Large' folds	79.64%	94.87%	97.81%
'Medium' folds	74.16%	75.61%	76.06%
'Small' folds	67.93%	86.86%	94.74%



# Experimental Results - 3

How do their proposed solutions compare with existing solutions?

**Table 3.**

The prediction accuracy at family/superfamily/fold level for top 1, top 5 and top 10 predictions, on SCOP 2.06 test dataset

Type	Methods	Top1	Top5	Top10
Family (742 proteins)	DeepSF	75.87%	91.77%	95.14%
	PSI-BLAST	82.20%	84.50%	85.30%
Superfamily (1754 proteins)	DeepSF	72.23%	90.08%	94.70%
	PSI-BLAST	86.90%	88.40%	89.30%
Fold (37 proteins)	DeepSF	51.35%	67.57%	72.97%
	PSI-BLAST	18.90%	35.10%	35.10%





# Experimental Results - 3

How do their proposed solutions compare with existing solutions?

**Table 3.**

The prediction accuracy at family/superfamily/fold level for top 1, top 5 and top 10 predictions, on SCOP 2.06 test dataset

Type	Methods	Top1	Top5	Top10
Family (742 proteins)	DeepSF	75.87%	91.77%	95.14%
	PSI-BLAST	82.20%	84.50%	85.30%
Superfamily (1754 proteins)	DeepSF	72.23%	90.08%	94.70%
	PSI-BLAST	86.90%	88.40%	89.30%
Fold (37 proteins)	DeepSF	51.35%	67.57%	72.97%
	PSI-BLAST	18.90%	35.10%	35.10%

**Figure:** The prediction accuracy at family/superfamily/fold levels for top 1, top 5 and top 10 predictions of DeepSF and PSI-BLAST, on SCOP 1.75 test dataset



# Experimental Results - 2

How do their proposed solutions compare with existing solutions?

Experimental Results - 2.



# Experimental Results - 3

## Benchmarking

Benchmarking of results with PSI-BLAST.

- Solution is 12.63-26.32% better than HHSearch on template-free modeling targets.
- Solution is 3.39-17.09% better on hard template-based modeling targets.

# Table of Contents

- 1 Problem and Knowledge Gap
- 2 Proposed Solution(s)
- 3 Experimental Results
- 4 Discussion and Muddy Points**

# Discussion of Experimental Results

What do the experimental results tell us?

Discuss the experimental results.

- Method is robust against:
  - 1 sequence mutation
  - 2 insertion
  - 3 deletion
  - 4 truncation
- Can solve other protein pattern recognition problems:
  - 1 protein clustering
  - 2 protein comparison
  - 3 protein ranking

# Weaknesses

What are the weaknesses of this paper?

- Poor benchmarking methodology:
  - ① Benchmarked solution (especially in Table 1) against PSI-BLAST (Altschul S.F. et al. , 1997)
  - ② Did not benchmark with other modern solutions for protein fold prediction
    - ① PFPA (2015, IEEE Transactions on NanoBioscience); DOI: 10.1109/TNB.2015.2450233
    - ② random forest (2014, BMC Bioinformatics); DOI:10.1186/1471-2105-15-S11-S14
    - ③ PFP-RFSM (2013, J. Biomedical Science and Engineering); DOI:10.4236/jbise.2013.612145
- Did not use box plots to compare methods for each protein sequence in the datasets:



# Muddy Points

What do I not understand about [1]?

What do I not understand about [1]?

- Why is it bad for top 1 predicted fold, but better for top 5 and top 10 predicted folds?

# References



Jie Hou, Badri Adhikari, and Jianlin Cheng.

DeepSF: deep convolutional neural network for mapping protein sequences to folds.

*Bioinformatics*, 34(8):1295–1303, April 15 2018.