# Making an Arduino Memory Game

A Really Simple Cyber-Physical System

#### Zhiyang Ong

Department of Electrical and Computer Engineering
Dwight Look College of Engineering,
Texas A&M University
College Station, TX

February 21, 2018



- Preamble
- **2** Expected Outcomes
- Summary
- 4 Required Components and Software Applications/Services
- **5** Schematic for Hardware Implementation
- 6 Source Code for Software Implementation
- Making and Playing the Memory Game



- 1 Preamble
- 2 Expected Outcomes
- Summary
- 4 Required Components and Software Applications/Services
- **5** Schematic for Hardware Implementation
- 6 Source Code for Software Implementation
- Making and Playing the Memory Game





### Acknowledgments

Dott. Francesco Stefanni, University of Verona

#### IEEE TAMU Officers

- Maria Theresia Tyas
- Millie Kriel
- Polina Golikova

Reference: Jerepondumie, "Make an Arduino Memory Game," in Hackster.io, Hackster, Inc., San Francisco, CA, September 15, 2017. Available online from Hackster.io at: https://www.hackster.io/Jerepondumie/make-an-arduino-memory-game-73f55e; February 18, 2018 was the last accessed date.

### Warnings!!!

- "The code is rather buggy; use is at own risk."
- Donald Chai
- "Beware of bugs in the above code.
- I have only proved it correct, not tried it."
- Donald E. Knuth

Unlike the Fantastic and Fabulous Ms. Millie Kriel, I have yet to try out this tutorial.



#### Ice Breaker

#### Name

What suggestions do you have for freshmen who are deciding what they can do this summer?

What are some of your favorite study techniques for circuit analysis (ECEN 214) and logic design (ECEN 248)?



- 1 Preamble
- 2 Expected Outcomes
- Summary
- 4 Required Components and Software Applications/Services
- **5** Schematic for Hardware Implementation
- 6 Source Code for Software Implementation
- Making and Playing the Memory Game



### **Expected Outcomes**

- Learn to understand someone else's wiring diagram
- Understanding someone else's coding style
- Learn why microcontrollers are a useful tool



- Preamble
- 2 Expected Outcomes
- Summary
- 4 Required Components and Software Applications/Services
- **5** Schematic for Hardware Implementation
- 6 Source Code for Software Implementation
- 7 Making and Playing the Memory Game



### Summary

- Cyber-physical system design
- Implement a memory game on the Arduino platform:
  - Implement simple analog circuit design on a breadboard
  - Connect breadboard to the Arduino platform
  - Program the microcontroller on the Arduino platform
- Play the memory game
- Repeat previous steps ad infinitum until you get bored.



- 1 Preamble
- 2 Expected Outcomes
- Summary
- 4 Required Components and Software Applications/Services
- **5** Schematic for Hardware Implementation
- 6 Source Code for Software Implementation
- Making and Playing the Memory Game



## Required Components and Software Applications/Services

- Software applications/services:
  - Arduino IDE

#### Table: Hardware components

Arduino UNO & Genuino UNO	1
SparkFun 330 ohm resistors	4
SparkFun 10k ohm resistors	4
SparkFun Assorted LEDs	4
(4 LEDs of different colors)	
SparkFun Mini speaker	1
(Recommended, not required)	
SparkFun breadboard (Full size)	1
Jumper wires (generic)	1



- 1 Preamble
- 2 Expected Outcomes
- Summary
- 4 Required Components and Software Applications/Services
- **5** Schematic for Hardware Implementation
- 6 Source Code for Software Implementation
- Making and Playing the Memory Game



### Schematic for Hardware Implementation




Figure: Schematic for Hardware Implementation on the Breadboard



- 1 Preamble
- 2 Expected Outcomes
- Summary
- 4 Required Components and Software Applications/Services
- **5** Schematic for Hardware Implementation
- 6 Source Code for Software Implementation
- Making and Playing the Memory Game



### Source Code for Software Implementation

```
1 #define PLAYER_WAIT_TIME 2000 // The time allowed between button presses - 2s
3 byte sequence[100];
                                 // Storage for the light sequence
4 byte curLen = 0;
                                 // Current length of the sequence
5 byte inputCount = 0;
                                 // The number of times that the player has pressed a (correct) button in a given turn
6 byte lastInput = 0:
                                 // Last input from the player
7 byte expRd = 0:
                                 // The LED that's suppose to be lit by the player
8 bool btnDwn = false;
                                 // Used to check if a button is pressed
9 bool wait = false;
                                 // Is the program waiting for the user to press a button
10 bool resetFlag = false;
                                 // Used to indicate to the program that once the player lost
  byte soundPin = 5:
                                 // Speaker output
                                 // Number of buttons/LEDs (While working on this, I was using only 2 LEDs)
   byte noPins = 4;
                                 // You could make the game harder by adding an additional LED/button/resistors combination.
  byte pins[] = {2, 13, 10, 8}: // Button input pins and LED output pins - change these vaules if you wwant to connect your buttons to other pins
                                 // The number of elements must match noPins below
   long inputTime = 0;
                                 // Timer variable for the delay between user inputs
21 void setup() {
     delav(3000);
                                 // This is to give me time to breathe after connection the arduino - can be removed if you want
     Serial.begin(9600);
                                 // Start Serial monitor. This can be removed too as long as you remove all references to Serial below
     Reset():
25 }
```

Figure: Software to Set Up the Memory Game



## Source Code for Software Implementation (2)

```
/// Sets all the pins as either INPUT or OUTPUT based on the value of 'dir'
29
   ///
   void setPinDirection(byte dir){
     for(byte i = 0; i < noPins; i++){
31
       pinMode(pins[i], dir);
32
33
34
35
   //send the same value to all the LED pins
   void writeAllPins(byte val){
     for(byte i = 0; i < noPins; i++){
38
       digitalWrite(pins[i], val);
39
40
41
```

Figure: Software Infrastructure for the Memory Game (2)



## Source Code for Software Implementation (3)

```
//Makes a (very annoving :) beep sound
  void beep(byte freq){
     analogWrite(soundPin, 2);
  delay(freg);
  analogWrite(soundPin, 0);
     delay(freq);
48
49 }
50
   111
51
   /// Flashes all the LEDs together
   /// freq is the blink speed - small number -> fast | big number -> slow
   111
  void flash(short freq){
     setPinDirection(OUTPUT); /// We're activating the LEDS now
57
     for(int i = 0; i < 5; i++){
58
     writeAllPins(HIGH);
    beep(50);
    delav(freg);
    writeAllPins(LOW);
       delay(freq);
64
```

Figure: Software Infrastructure for the Memory Game (3)



## Source Code for Software Implementation (4)

```
///This function resets all the game variables to their default values
   111
   void Reset(){
   flash(500);
70
71
   curLen = 0:
  inputCount = 0:
   lastInput = 0;
73
   expRd = 0;
74
  btnDwn = false:
76
  wait = false;
   resetFlag = false:
   }
78
79
   111
  /// User lost
   111
   void Lose(){
     flash(50);
84
85
```

Figure: Software Infrastructure for the Memory Game (4)



## Source Code for Software Implementation (5)

```
/// The arduing shows the user what must be memorized
    /// Also called after losing to show you what you last sequence was
    111
    void plavSequence(){
92
      //Loop through the stored sequence and light the appropriate LEDs in turn
      for(int i = 0; i < curlen; i++){
93
          Serial.print("Seq: ");
94
          Serial.print(i);
95
          Serial.print("Pin: ");
96
          Serial.println(sequence[i]);
97
          digitalWrite(sequence[i], HIGH);
98
99
          delav(500):
          digitalWrite(sequence[i], LOW);
100
          delay(250);
101
103
```

Figure: Software Infrastructure for the Memory Game (5)



## Source Code for Software Implementation (6)

Figure: Software Infrastructure for the Memory Game (6)



- 1 Preamble
- 2 Expected Outcomes
- Summary
- 4 Required Components and Software Applications/Services
- **5** Schematic for Hardware Implementation
- 6 Source Code for Software Implementation
- Making and Playing the Memory Game



### Making the Memory Game

- Implement the schematic on the breadboard
- Connect breadboard to the Arduino platform
- Software implementation
  - Copy source code from https://www.hackster.io/ Jerepondumie/make-an-arduino-memory-game-73f55e to your Arduino IDE.
- Debug hardware implementation
  - Check if all LEDs flash as expected.
  - During initialization of the "Simple Simon" game, it takes 3 seconds to show "5 slow flashes of all the LEDs."



### How to Play the Memory Game

- Wait for the game to initialize
  - Takes 3 seconds to show "5 slow flashes of all the LEDs."
- When a LED flashes, press the corresponding button for the flashed LED.
- You have 2 seconds to press each button.
- For a sequence of LED flashes, press their corresponding buttons in sequence.
- If all the LEDs flash rapidly, you have lost the game.
- When you lose the game,
  - The game will reset by showing "5 slow flashes of all the LFDs"



## Making the Memory Game More Challenging to Play

- Reduce the allowed reaction time for the player to press a button (for the corresponding LED that flashed).
- Add additional LEDs to the circuit to increase the sequence of flashing colored LEDs; for each additional LED:
  - Add a vertical stage in the circuit design.
  - Add a vertical stage on the breadboard.
  - Modify the array representing the input pins of the LEDs.

