

EdX and its Members use cookies and other tracking technologies for performance, analytics, and marketing purposes. By using this website, you accept this use. Learn more about these technologies in the [Privacy Policy](#).



[Course](#) > [Node C...](#) > [Node...](#) > [require...](#)

require usage

`require()` can be used to import many different types of modules, not just for local `node.js` files. You can use `require()` to do the following:

- Import core modules/packages, e.g., `const filesystem = require('fs')`
- Import npm modules/packages, e.g., `const express = require('express')`
- Import single file in a project, e.g., `const server = require('./boot/server.js')`
- Import single JSON files, e.g., `const databaseConfigs = require('./configs/database.json')`
- Import folders in a project (an alias for importing an `index.js` in that folder), e.g., `const routes = require('./routes')`

More examples:

```
const filesystem = require('fs') // core module
const express = require('express') // npm module
const server = require('./boot/server.js') // server.js file with a
const server = require('../boot/server.js') // server.js file with a
const server = require('/var/www/app/boot/server.js') // server.js f
const server = require('./boot/server') // file if there's the serve
const routes = require('../routes') // index.js inside routes folder
const databaseConfigs = require('./configs/database.json') // JSON f
```

Using `require()` with local files

To use `require()` with local files, specify the name string (the argument to `require()`) of the file you are trying to import. In general, start the name string with a `.` to specify that the file path is relative to the current folder of the `node.js` file or a `..` to specify that the file path is relative to the parent directory of the current folder. For example, `const server = require('./boot/server.js')` imports a file named `server.js` which is in a folder named `boot` that is in the current folder relative to the code file in which we write `require()`.

Using `require()` with npm or core modules/packages

To use `require()` with an npm or core module/package, enter the module/package name as the name string. There should not be `.` or `..` in the name string. For example, `const express = require('express')` imports a package named `express`. The package is in the `node_modules` folder in the root of the project if it's an installed npm package, and in the `system` folder if it's a core Node module (exact location depends on your OS and how you installed Node).

As you can see, `require()` is very versatile and can be used in many cases.

© All Rights Reserved