

EdX and its Members use cookies and other tracking technologies for performance, analytics, and marketing purposes. By using this website, you accept this use. Learn more about these technologies in the [Privacy Policy](#).



[Course](#) > [Expres...](#) > [URL Pa...](#) > [Accessi...](#)

Accessing Query String Data

Express has a built-in query string parser unlike the core `http` module in which developers need to parse query strings manually. In Express, query string data can be accessed by `req.query.name` where `name` is the key of the value in a query string. Because query string parsing is a built-in feature of Express, there is no need to install anything with npm.

For example, an URL query string value `http://webapplog.com/search?term=node.js&page=1` can be accessed with `req.query.term` and `req.query.page` in a request handler such as `app.get()` or any other:

```
app.get('/search', (req, res) => {
  db.find(
    {term: req.query.term},
    {page: req.query.page, limit: 10}, (error, results)=> {
      // error handling
      res.send(results)
    })
})
```

By default, Express.js doesn't allow developers to route by query string arguments, such as the following:

```
GET: www.webapplog.com/?id=10233
GET: www.webapplog.com/about/?author=10239
GET: www.webapplog.com/books/?id=10&ref=201
```

However, it's trivial to write your own middleware. It might look like this:

```
app.use((req, res, next) => {
  if (req.query.id) {
    // process the id, then call next() when done
  } else if (req.query.author) {
    // same approach as with id
  } else if (req.query.id && req.query.ref) {
    // process when id and ref present
  } else {
    next()
  }
})

app.get('/about', (req, res, next) => {
  // this code is executed after the query string middleware
})
```

In this middleware, if/else is used to execute different code based on the value from query string `req.query`.

© All Rights Reserved