

//java 語言

```
private static final char[] HEX_ARRAY = "0123456789ABCDEF".toCharArray();
public static String bytesToHex(byte[] bytes) {
    char[] hexChars = new char[bytes.length * 2];
    for (int j = 0; j < bytes.length; j++) {
        int v = bytes[j] & 0xFF;
        hexChars[j * 2] = HEX_ARRAY[v >>> 4];
        hexChars[j * 2 + 1] = HEX_ARRAY[v & 0x0F];
    }
    return new String(hexChars);
}
```

//kotlin 語言

```
fun data7ToDouble(bytes2Text: String):
Triple<MutableList<Double>,MutableList<Double>, MutableList<Double>>> {
    val tempListT2 = mutableListOf<Double>()
    val tempListT3 = mutableListOf<Double>()
    val tempListT4 = mutableListOf<Double>()

    var bitNum = 24
    for (i in 1..7){
        val t2 = hexToBytes((bytes2Text.substring(4+bitNum*(i-1),
4+bitNum*i)).substring(6, 12)).toDouble()
        val t3 = hexToBytes((bytes2Text.substring(4+bitNum*(i-1),
4+bitNum*i)).substring(12, 18)).toDouble()
        val t4 = hexToBytes((bytes2Text.substring(4+bitNum*(i-1),
4+bitNum*i)).substring(18, 24)).toDouble()
        tempListT2.add(t2)
        tempListT3.add(t3)
        tempListT4.add(t4)
    }
    //實際只會用到前兩個(T2 跟 T4)
    return Triple(tempListT2, tempListT4, tempListT3)
}
```

//資料解析方法: 輸入為 data(一個封包的原始資料), 輸出為解析後資料(三組不同肌群, 每組有 7 個 emg 資料, 目前只用到前兩組肌群資料)

```
val result = data7ToDouble(bytesToHex(data)) //kotlin 語言
```