



# Introduction to Internet #2

## Introduction to Internet and Web



부산대학교 정보·의생명 공학대학  
정보컴퓨터공학부



부산대학교  
PUSAN NATIONAL UNIVERSITY

# Table of Contents

## ❖ IP Addressing

## ❖ Datagram Forwarding

## ❖ Domain Name System



**Mykhailo Fedorov** @FedorovMykhailo · 14시간

@elonmusk, while you try to colonize Mars — Russia try to occupy Ukraine! While your rockets successfully land from space — Russian rockets attack Ukrainian civil people! We ask you to provide Ukraine with Starlink stations and to address sane Russians to stand.

1,690

1.4만

8.5만



Mykhailo Fedorov 님이 리트윗함




**Elon Musk** @elonmusk

@FedorovMykhailo 님에게 보내는 답글

Starlink service is now active in Ukraine. More terminals en route.

오전 7:33 · 2022년 2월 27일 · Twitter for iPhone

7.8만 리트윗 1.4만 인용한 트윗 40.2만 마음에 들어요



# 01. IP ADDRESSING


# Introduction to IP Address

❖ **IP address:** 32-bit identifier  
for host, router interface

❖ **Interface:** connection  
between host/router and  
physical link

- Router's typically have multiple interfaces
- Host typically has one or two interfaces (e.g., wired Ethernet, wireless 802.11)


❖ **IP address associated with each interface**



$$223.1.1.1 = \underbrace{11011111}_{223} \underbrace{00000001}_1 \underbrace{00000001}_1 \underbrace{00000001}_1$$

# Hierarchical Addressing

## ■ Korean postal system



출처 - <https://www.google.co.kr/url?sa=i&rct=j&q=&esrc=s&source=images&cd=&cad=rja&uact=8&ved=2ahUKEwidj-ru4lLcAhWCMN4KHT6ADjIQjRx6BAGBEAU&url=http%3A%2F%2Fwww.thedjnews.com%2Fnews%2FarticleView.html%3Fidxno%3D1493&psig=AOvVaw0Z4wtVpluH4N3PFxGbw2eQ&ust=1530701281466061>

## ■ Telephone number

+ 8 2 - 5 1 - 5 1 0 - 5 5 5 5


← country code  
← area code  
← local exchange

## ■ IP address

1 6 4 . 1 2 5 . 7 0 . 1 2 5

← host id  
← Bldg. Comp. Eng.  
← Pusan National University

# Example: Hierarchical IP Address




출처 -

[https://www.google.co.kr/url?sa=i&rct=j&q=&esrc=s&source=images&cd=&cad=rja&uact=8&ved=2ahUKEwj537vo44LcAhWVA4gKHWWiAPwQjRx6BAgBEAU&url=https%3A%2F%2Fwww.slideshare.net%2Fwelcometofacebook%2Fm06-35513859&psig=AOvVaw0kd7fRzS5vV-Is5QZC2\\_IB&ust=1530700263742351](https://www.google.co.kr/url?sa=i&rct=j&q=&esrc=s&source=images&cd=&cad=rja&uact=8&ved=2ahUKEwj537vo44LcAhWVA4gKHWWiAPwQjRx6BAgBEAU&url=https%3A%2F%2Fwww.slideshare.net%2Fwelcometofacebook%2Fm06-35513859&psig=AOvVaw0kd7fRzS5vV-Is5QZC2_IB&ust=1530700263742351)

# IP Address Class

## ❖ ICANN (Internet Corporation for Assigned Names and Numbers)

- <http://www.icann.org/>
- allocates addresses
- manages DNS
- assigns domain names, resolves disputes



- Private addresses

10.0.0.0 ~ 10.255.255.255 (10.0.0.0/8) : 1 of A class

172.16.0.0 ~ 172.31.255.255 (172.16.0.0/12) : 16 of B classes


192.168.0.0 ~ 192.168.255.255 (192.168.0.0/16) : 256 of C classes

# Subnets

❖ **Subnet:** a logical subdivision of an IP network

❖ **Why subnetting?**

- Datagram forwarding performed by routers
- Hosts in a same network can reach each other without intervening router
- Too many hosts in a network increase maintenance overhead
- “Divide and conquer”



출처 -


[https://www.google.co.kr/url?sa=i&rct=j&q=&esrc=s&source=images&cd=&cad=rja&uact=8&ved=2ahUKEwjWr4q3s4TcAhXGFogKHTNuC2gQjRx6BAgBEAU&url=http%3A%2F%2Fwww.learnCisco.net%2Fcourses%2Ficnd-1%2Flan-connections%2Fnetwork-addressing-scheme.html&psig=AOvVaw24-bw\\_TTDQV85Eh-H39lpq&ust=1530757596051182](https://www.google.co.kr/url?sa=i&rct=j&q=&esrc=s&source=images&cd=&cad=rja&uact=8&ved=2ahUKEwjWr4q3s4TcAhXGFogKHTNuC2gQjRx6BAgBEAU&url=http%3A%2F%2Fwww.learnCisco.net%2Fcourses%2Ficnd-1%2Flan-connections%2Fnetwork-addressing-scheme.html&psig=AOvVaw24-bw_TTDQV85Eh-H39lpq&ust=1530757596051182)



# Subnet Mask

## ❖ Division of IP address


- subnet part: high order bits of host id
- host part: low order bits of host id



출처 - <https://en.wikipedia.org/wiki/Subnetwork>

## ❖ How to decide the size of subnet number?


- **subnet mask**: indicating the bits that will be used as the network number
- e.g., 255.255.255.0 => 24 bits are used as the network number



# Subnetting Example

## ❖ e.g., subnet ID is 5 bits long

- $2^5 = 32$  subnets can exist
- each subnet can include  $2^{11}$  hosts
- Binary number, decimal number




출처 -

[https://www.google.co.kr/url?sa=i&rct=j&q=&esrc=s&source=images&cd=&cad=rja&uact=8&ved=2ahUKEwjut7mQroTcAhVCdt4KHcrgD1AQjRx6BAGBEAU&url=http%3A%2F%2Fwww.tcpipguide.com%2Ffree%2Ft\\_IPSubnetMasksNotationandSubnetCalculations-2.htm&psig=AOvVaw2fWCicQMjzIPoe3PYzjZn&ust=1530756208997926](https://www.google.co.kr/url?sa=i&rct=j&q=&esrc=s&source=images&cd=&cad=rja&uact=8&ved=2ahUKEwjut7mQroTcAhVCdt4KHcrgD1AQjRx6BAGBEAU&url=http%3A%2F%2Fwww.tcpipguide.com%2Ffree%2Ft_IPSubnetMasksNotationandSubnetCalculations-2.htm&psig=AOvVaw2fWCicQMjzIPoe3PYzjZn&ust=1530756208997926)

# Subnetworking Example

## ❖ An IP network can be a subnet by itself

- e.g., Class C network with subnet mask /24



subnet mask: /24



11111111 11111111 11111111 00000000




## 02. DATAGRAM FORWARDING

# IP Network = Datagram Network

## ❖ Routers: no state about end-to-end connections


- no network-level concept of “connection”



## ❖ Datagram forwarding

- **destination-based forwarding**: forward based only on destination IP address (traditional)
- **generalized forwarding**: forward based on any set of header field values (SDN)

# Destination-based Forwarding Table



# Destination-based Forwarding

*forwarding table*

Destination Address Range	Link Interface
11001000 00010111 00010000 00000000 through 11001000 00010111 00010111 11111111	0
11001000 00010111 00011000 00000000 through 11001000 00010111 00011000 11111111	1
11001000 00010111 00011001 00000000 through 11001000 00010111 00011111 11111111	2
otherwise	3

**Q:** but what happens if ranges don't divide up so nicely?

# Longest Prefix Matching

## Longest prefix matching

when looking for forwarding table entry for given destination address, use **longest** address prefix that matches destination address

Destination Address Range	Link interface
11001000 00010111 00010*** *****	0
11001000 00010111 00011000 *****	1
11001000 00010111 00011*** *****	2
otherwise	3

examples:

DA: 11001000 00010111 00010110 10100001

which interface?

DA: 11001000 00010111 00011000 10101010

which interface?



## 03. DOMAIN NAME SYSTEM


# IP Address

❖ `ipconfig` command

❖ IP address is 32-bit long,  
represented by 4 numbers  
between 0~255

❖ Hard to remember the IP address  
of a server by the numbers

❖ Instead, people use the name  
of servers such as  
`www.pusan.ac.kr`



```
C:\Users\WUSER>ipconfig

Windows IP 구성

이더넷 어댑터 로컬 영역 연결:

    연결별 DNS 접미사. . . . . : 
    링크-로컬 IPv6 주소 . . . . : fe80::d5:b845:763d:9811%11
    IPv4 주소 . . . . . : 192.168.0.4
    서브넷 마스크 . . . . . : 255.255.255.0
    기본 게이트웨이 . . . . . : 192.168.0.1

터널 어댑터 isatap.{4DC85BAF-3120-432D-A335-D412827EF7D7}:

    미디어 상태 . . . . . : 미디어 연결 끊김
    연결별 DNS 접미사. . . . . : 


터널 어댑터 Teredo Tunneling Pseudo-Interface:

    미디어 상태 . . . . . : 미디어 연결 끊김
    연결별 DNS 접미사. . . . . : 

C:\Users\WUSER>
```

# Domain Name System

- ❖ Actually, the most important part of the Internet for internetworking
- ❖ Brief view of the DNS operation



출처 - <https://help.ubnt.com/hc/en-us/articles/115005817467-Intro-to-Networking-Domain-Name-System-DNS->

# Domain Name System

## ❖ DNS services

- hostname to IP address translation
- load distribution
  - replicated Web servers: many IP addresses correspond to one name

## ❖ Distributed database system


## ❖ Why not centralize DNS?

- single point of failure
- traffic volume
- distant centralized database



Not scalable!!!

# DNS: Distributed & Hierarchical Database



*Client wants IP for www.amazon.com; 1<sup>st</sup> approximation:*


1. Client queries Root server to find com DNS server
2. Client queries com DNS server to get amazon.com DNS server
3. Client queries amazon.com DNS server to get IP address for www.amazon.com

# DNS: Root Name Servers

❖ Contacted by local name server that can not resolve name

❖ Location of root name servers

- there are 247 root servers as of fall 2011



# DNS: Top-Level Domain (TLD) Servers

- ❖ Responsible for com, org, net, edu, aero, jobs, museums, and all top-level country domains, e.g.: uk, fr, ca, jp, kr
- ❖ “Any language possible besides English alphabet” (June 20<sup>th</sup>, 2011)
- ❖ Network Solutions maintains servers for .com TLD
- ❖ Educause for .edu TLD



출처 - <https://youcanbefound.com/do-top-level-domains-tlds-matter-for-seo-com-vs-brand/>


# DNS: Authoritative Servers & Local Servers

## ❖ Authoritative Servers

- organization's own DNS server(s), providing authoritative hostname to IP mappings for organization's named hosts
- can be maintained by organization or service provider



## ❖ Local DNS servers

- does not strictly belong to hierarchy
- each ISP (residential ISP, company, university) has one
  - also called “default name server”
- when host makes DNS query, query is sent to its local DNS server
  - has local cache of recent name-to-address translation pairs
  - acts as proxy, forwards query into hierarchy





- IP address
- Subnet Mask
- DNS server



<https://www.youtube.com/watch?v=5o8CwafCxnU&list=LL0vthjKPpJZN8bPHCMoxZXA&index=11&t=4s>