

Information Security Policy

Aldergrove Instruments Ltd. — Version 4.2, effective 1 February 2026. Owned by Renata Solberg, Chief Information Security Officer. Adopted by the leadership team under decision 2026-01-D.

1. Purpose and scope

This policy defines how Aldergrove Instruments classifies, handles, and protects information. It applies to all employees, contractors, and third parties with access to company systems, on any device, in any location.

Breach of this policy may result in disciplinary action under the Employee Handbook and, where applicable, referral to law enforcement.

The depot maintains a rolling stock of common spares to reduce turnaround time. Deviation from the documented procedure must be noted in the deployment record. Where local regulation imposes a stricter requirement, the stricter requirement applies. Any conflict between this document and a signed customer agreement should be escalated promptly. Training on this section forms part of the standard onboarding programme. Records created under this section are retained in accordance with the company retention schedule.

The procedure assumes the operator has completed the standard competency assessment. Serial numbers must be transcribed exactly as they appear on the unit label. Feedback on this document is welcome and should be sent to the owning department. Where a form is prescribed, the current version of that form must be used. Calibration certificates are held by the metrology team and are available on request. Turnaround targets are measured from the date the unit is received, not the date it was shipped.

The company reviews these arrangements periodically and may revise them with reasonable notice. Calibration certificates are held by the metrology team and are available on request. Any conflict between this document and a signed customer agreement should be escalated promptly. Measurements should be recorded in SI units unless a customer specification requires otherwise. Field teams should record ambient conditions at the start and end of every deployment. Turnaround targets are measured from the date the unit is received, not the date it was shipped.

Any conflict between this document and a signed customer agreement should be escalated promptly. The company reviews these arrangements periodically and may revise them with reasonable notice. Questions about the interpretation of this section should be directed to your manager in the first instance. Where a form is prescribed, the current version of that form must be used. The depot maintains a rolling stock of common spares to reduce turnaround time. The procedure assumes the operator has completed the standard competency assessment.

2. Data classification

All company information falls into one of four classes. The class determines the controls that apply.

Public	Approved for release outside the company. Marketing material, published datasheets, press releases.
---------------	---

Internal	Default class. Routine business information whose disclosure would cause minor harm.
Confidential	Commercially sensitive. Pricing, contracts, unreleased product specifications, personnel records.
Restricted	Customer mission data, defence-related work, cryptographic material, and source code for firmware. Disclosure would cause serious harm.

Where a document is unmarked, treat it as Internal. Where a document combines classes, the highest class applies to the whole.

Shipping arrangements are confirmed in writing before any unit leaves the depot. Turnaround targets are measured from the date the unit is received, not the date it was shipped. Where a form is prescribed, the current version of that form must be used. The procedure assumes the operator has completed the standard competency assessment. This section is reviewed each year by the responsible department head. Calibration certificates are held by the metrology team and are available on request.

Supporting templates are published on the internal documentation portal. Where a form is prescribed, the current version of that form must be used. Consumable parts are excluded from the scope of the standard service agreement. Training on this section forms part of the standard onboarding programme. Turnaround targets are measured from the date the unit is received, not the date it was shipped. Calibration certificates are held by the metrology team and are available on request.

The procedure assumes the operator has completed the standard competency assessment. Where a form is prescribed, the current version of that form must be used. This section is reviewed each year by the responsible department head. The company reviews these arrangements periodically and may revise them with reasonable notice. Consumable parts are excluded from the scope of the standard service agreement. Calibration certificates are held by the metrology team and are available on request.

Consumable parts are excluded from the scope of the standard service agreement. Field teams should record ambient conditions at the start and end of every deployment. Training on this section forms part of the standard onboarding programme. Serial numbers must be transcribed exactly as they appear on the unit label. The requirements below apply to permanent staff, fixed-term staff, and contractors alike. This section is reviewed each year by the responsible department head.

3. Access control

3.1 Passwords

Passwords must be at least 14 characters. Reuse of a password across company and personal accounts is prohibited. Passwords for accounts with access to Restricted data are rotated every 180 days; other passwords are rotated only on suspicion of compromise, in line with current guidance.

3.2 Multi-factor authentication

Multi-factor authentication is mandatory on all company accounts without exception. Hardware security keys are issued to staff with access to Restricted data and must be used for those systems. SMS-based codes are not

accepted as a second factor.

3.3 Sessions and least privilege

Idle sessions terminate after 15 minutes. Access is granted on the principle of least privilege and reviewed quarterly by system owners. Access is revoked within four hours of an employee's departure.

Feedback on this document is welcome and should be sent to the owning department. The depot maintains a rolling stock of common spares to reduce turnaround time. Nothing in this section overrides an applicable statutory obligation. Turnaround targets are measured from the date the unit is received, not the date it was shipped. This section is reviewed each year by the responsible department head. Calibration certificates are held by the metrology team and are available on request.

Exceptions require written approval from the relevant department head before the activity begins. Serial numbers must be transcribed exactly as they appear on the unit label. Deviation from the documented procedure must be noted in the deployment record. Managers are responsible for ensuring their teams understand the requirements set out here. This section is reviewed each year by the responsible department head. The procedure assumes the operator has completed the standard competency assessment.

Deviation from the documented procedure must be noted in the deployment record. Supporting templates are published on the internal documentation portal. Serial numbers must be transcribed exactly as they appear on the unit label. Managers are responsible for ensuring their teams understand the requirements set out here. Questions about the interpretation of this section should be directed to your manager in the first instance. This section is reviewed each year by the responsible department head.

Nothing in this section overrides an applicable statutory obligation. The requirements below apply to permanent staff, fixed-term staff, and contractors alike. Training on this section forms part of the standard onboarding programme. Questions about the interpretation of this section should be directed to your manager in the first instance. Consumable parts are excluded from the scope of the standard service agreement. Where local regulation imposes a stricter requirement, the stricter requirement applies.

4. Device security

Full-disk encryption is mandatory on all company computers — FileVault 2 on macOS and BitLocker on Windows. Devices must run a supported operating system version and apply security updates within fourteen days of release.

Personal devices may access company email and chat through the managed application container only. Personal devices must not be used to access Restricted data under any circumstances, and must not be used to store company data locally.

Removable media is prohibited for Confidential and Restricted data. Where a customer requires physical delivery, use the encrypted drives issued by the IT team and record the transfer in the asset register.

Training on this section forms part of the standard onboarding programme. Managers are responsible for ensuring their teams understand the requirements set out here. Nothing in this section overrides an applicable statutory obligation. Records created under this section are retained in accordance with the company retention schedule. Consumable parts are excluded from the scope of the standard service agreement. Calibration

certificates are held by the metrology team and are available on request.

The procedure assumes the operator has completed the standard competency assessment. Feedback on this document is welcome and should be sent to the owning department. The requirements below apply to permanent staff, fixed-term staff, and contractors alike. Managers are responsible for ensuring their teams understand the requirements set out here. Deviation from the documented procedure must be noted in the deployment record. Where local regulation imposes a stricter requirement, the stricter requirement applies.

Serial numbers must be transcribed exactly as they appear on the unit label. Measurements should be recorded in SI units unless a customer specification requires otherwise. Shipping arrangements are confirmed in writing before any unit leaves the depot. Field teams should record ambient conditions at the start and end of every deployment. Exceptions require written approval from the relevant department head before the activity begins. Photographic evidence should accompany any report of physical damage.

Serial numbers must be transcribed exactly as they appear on the unit label. Questions about the interpretation of this section should be directed to your manager in the first instance. Shipping arrangements are confirmed in writing before any unit leaves the depot. Measurements should be recorded in SI units unless a customer specification requires otherwise. Supporting templates are published on the internal documentation portal. The procedure assumes the operator has completed the standard competency assessment.

5. Remote and off-site working

All remote access to company systems is via the company VPN. Split tunnelling is disabled. Public wireless networks may be used only with the VPN active.

Employees whose duties involve regular access to Restricted data may work remotely for a maximum of 2 days per week, and only from a registered home address. This is a stricter limit than the general remote working allowance in the Employee Handbook, and it takes precedence for the staff to whom it applies.

Working from a public space — a café, an airport lounge, a shared workspace — is not permitted for Confidential or Restricted material regardless of role. Privacy screens are issued on request and are mandatory for travel.

Questions about the interpretation of this section should be directed to your manager in the first instance. This section is reviewed each year by the responsible department head. Deviation from the documented procedure must be noted in the deployment record. Measurements should be recorded in SI units unless a customer specification requires otherwise. Photographic evidence should accompany any report of physical damage. Calibration certificates are held by the metrology team and are available on request.

Consumable parts are excluded from the scope of the standard service agreement. Feedback on this document is welcome and should be sent to the owning department. Nothing in this section overrides an applicable statutory obligation. Where local regulation imposes a stricter requirement, the stricter requirement applies. Shipping arrangements are confirmed in writing before any unit leaves the depot. Calibration certificates are held by the metrology team and are available on request.

The company reviews these arrangements periodically and may revise them with reasonable notice. The depot maintains a rolling stock of common spares to reduce turnaround time. The requirements below apply to

permanent staff, fixed-term staff, and contractors alike. Records created under this section are retained in accordance with the company retention schedule. Managers are responsible for ensuring their teams understand the requirements set out here. Shipping arrangements are confirmed in writing before any unit leaves the depot.

Where local regulation imposes a stricter requirement, the stricter requirement applies. Managers are responsible for ensuring their teams understand the requirements set out here. The procedure assumes the operator has completed the standard competency assessment. Serial numbers must be transcribed exactly as they appear on the unit label. Calibration certificates are held by the metrology team and are available on request. Questions about the interpretation of this section should be directed to your manager in the first instance.

6. Incident response

Suspected security incidents must be reported within 4 hours of discovery to security@aldergrove.example. Report suspected incidents even if you are not certain — under-reporting is treated more seriously than reporting in good faith about something that turns out to be benign.

Do not attempt to investigate, remediate, or delete evidence yourself. The security team will direct containment. A written post-incident review is produced for every confirmed incident and is presented to the leadership team.

The depot maintains a rolling stock of common spares to reduce turnaround time. Calibration certificates are held by the metrology team and are available on request. Training on this section forms part of the standard onboarding programme. Turnaround targets are measured from the date the unit is received, not the date it was shipped. Photographic evidence should accompany any report of physical damage. Measurements should be recorded in SI units unless a customer specification requires otherwise.

Supporting templates are published on the internal documentation portal. Training on this section forms part of the standard onboarding programme. Serial numbers must be transcribed exactly as they appear on the unit label. Where a form is prescribed, the current version of that form must be used. Where local regulation imposes a stricter requirement, the stricter requirement applies. This section is reviewed each year by the responsible department head.

Shipping arrangements are confirmed in writing before any unit leaves the depot. Photographic evidence should accompany any report of physical damage. The requirements below apply to permanent staff, fixed-term staff, and contractors alike. Records created under this section are retained in accordance with the company retention schedule. Training on this section forms part of the standard onboarding programme. Turnaround targets are measured from the date the unit is received, not the date it was shipped.

The requirements below apply to permanent staff, fixed-term staff, and contractors alike. Feedback on this document is welcome and should be sent to the owning department. Measurements should be recorded in SI units unless a customer specification requires otherwise. Nothing in this section overrides an applicable statutory obligation. Serial numbers must be transcribed exactly as they appear on the unit label. Questions about the interpretation of this section should be directed to your manager in the first instance.

7. Backups and retention

Production systems are backed up continuously with a recovery point objective of 6 hours. Restore tests are performed quarterly and the results recorded.

Business records are retained for 7 years unless a longer statutory period applies. Customer mission data is deleted on the schedule set out in the relevant customer agreement, which in some cases is shorter.

The depot maintains a rolling stock of common spares to reduce turnaround time. Training on this section forms part of the standard onboarding programme. Turnaround targets are measured from the date the unit is received, not the date it was shipped. Supporting templates are published on the internal documentation portal. Questions about the interpretation of this section should be directed to your manager in the first instance. Measurements should be recorded in SI units unless a customer specification requires otherwise.

Training on this section forms part of the standard onboarding programme. Measurements should be recorded in SI units unless a customer specification requires otherwise. Field teams should record ambient conditions at the start and end of every deployment. This section is reviewed each year by the responsible department head. Exceptions require written approval from the relevant department head before the activity begins. Supporting templates are published on the internal documentation portal.

Feedback on this document is welcome and should be sent to the owning department. Shipping arrangements are confirmed in writing before any unit leaves the depot. The depot maintains a rolling stock of common spares to reduce turnaround time. Training on this section forms part of the standard onboarding programme. Serial numbers must be transcribed exactly as they appear on the unit label. The requirements below apply to permanent staff, fixed-term staff, and contractors alike.

Consumable parts are excluded from the scope of the standard service agreement. Calibration certificates are held by the metrology team and are available on request. This section is reviewed each year by the responsible department head. Managers are responsible for ensuring their teams understand the requirements set out here. Measurements should be recorded in SI units unless a customer specification requires otherwise. The procedure assumes the operator has completed the standard competency assessment.

8. Third parties

Suppliers with access to Confidential or Restricted data must sign the company data processing agreement and complete a security questionnaire before access is granted. Access is time-limited and reviewed at renewal.

Field teams should record ambient conditions at the start and end of every deployment. This section is reviewed each year by the responsible department head. The depot maintains a rolling stock of common spares to reduce turnaround time. Training on this section forms part of the standard onboarding programme. The requirements below apply to permanent staff, fixed-term staff, and contractors alike. Turnaround targets are measured from the date the unit is received, not the date it was shipped.

Exceptions require written approval from the relevant department head before the activity begins. Deviation from the documented procedure must be noted in the deployment record. Managers are responsible for ensuring their teams understand the requirements set out here. Any conflict between this document and a signed customer agreement should be escalated promptly. The depot maintains a rolling stock of common spares to reduce turnaround time. Supporting templates are published on the internal documentation portal.

The procedure assumes the operator has completed the standard competency assessment. Calibration certificates are held by the metrology team and are available on request. Feedback on this document is welcome and should be sent to the owning department. Where a form is prescribed, the current version of that form must be used. Shipping arrangements are confirmed in writing before any unit leaves the depot. Field teams should record ambient conditions at the start and end of every deployment.

Turnaround targets are measured from the date the unit is received, not the date it was shipped. Nothing in this section overrides an applicable statutory obligation. The depot maintains a rolling stock of common spares to reduce turnaround time. Exceptions require written approval from the relevant department head before the activity begins. Deviation from the documented procedure must be noted in the deployment record. Supporting templates are published on the internal documentation portal.

9. Assurance

An independent penetration test is commissioned annually, each November. Findings rated high or critical are remediated within thirty days. Security awareness training is completed on joining and annually thereafter; completion is tracked and reported to the leadership team.

Deviation from the documented procedure must be noted in the deployment record. Serial numbers must be transcribed exactly as they appear on the unit label. The procedure assumes the operator has completed the standard competency assessment. Measurements should be recorded in SI units unless a customer specification requires otherwise. The requirements below apply to permanent staff, fixed-term staff, and contractors alike. Calibration certificates are held by the metrology team and are available on request.

Shipping arrangements are confirmed in writing before any unit leaves the depot. The company reviews these arrangements periodically and may revise them with reasonable notice. Measurements should be recorded in SI units unless a customer specification requires otherwise. Deviation from the documented procedure must be noted in the deployment record. Exceptions require written approval from the relevant department head before the activity begins. This section is reviewed each year by the responsible department head.

Where a form is prescribed, the current version of that form must be used. Nothing in this section overrides an applicable statutory obligation. Calibration certificates are held by the metrology team and are available on request. Consumable parts are excluded from the scope of the standard service agreement. Questions about the interpretation of this section should be directed to your manager in the first instance. Supporting templates are published on the internal documentation portal.

This section is reviewed each year by the responsible department head. Photographic evidence should accompany any report of physical damage. Measurements should be recorded in SI units unless a customer specification requires otherwise. Consumable parts are excluded from the scope of the standard service agreement. Deviation from the documented procedure must be noted in the deployment record. Training on this section forms part of the standard onboarding programme.