

Create project & scaffolding

1. New project wizard
 - Java 21
 - Maven
 - No sample code
 - Dependencies:
 - REST Jackson
 - Hibernate ORM Panache
 - PostgreSQL JDBC Driver
 - Micrometer prometheus
 - OpenTelemetry
 - OpenAPI
 - Health
 - Jib
 2. Edit `pom.xml`
 - a. Add OTel JDBC dependency (`tdd 1 - pomOtelJdbc` live template)
 - b. Add test dependencies (`tdd 2 - pomTestDeps` live template)
 3. Go into `src/main/resources/application.properties` and add base config (`tdd 3 - baseConfig` live template)
-

Create Entity

1. Start dev mode
2. Discuss `Hibernate ORM is disabled because no JPA entities were found & Dev Services for default datasource (postgresql) started`
 - Show & explain Dev UI
3. Create `Pet` class
 - Add fields (`tdd 4 - petFields` live template)
 - Add getters/setters (IntelliJ assist)
 - Add `toString/hashCode>equals` (IntelliJ assist)
 - Add constructors (`tdd 5 - petConstructors` live template)
 - Turn into JPA Entity (`tdd 6 - petAnnotations` live template)
4. *Optional*: Show data explorer that table was created
5. Add `src/main/resources/import.sql` file
 - Use `tdd 7 - importsql` live template
6. *Optional*: Refresh data explorer showing that data is now in the table

Create Repository layer tests

1. Back in dev mode console point out **Tests paused**
 - Explain **No tests found** (duh!)
2. Create `src/test/java/com/example/PetRepositoryTests.java`
 - Annotate with **@QuarkusTest**
3. Bring in test stubs with **tdd 8 - petRepositoryTests** live template
 - Notice in console that as soon as saved tests all run to success
4. Add **@TestTransaction** annotation & explain
 - Again all tests run when saving
5. Add **@Inject PetRepository**
 - Obviously this does not compile because **PetRepository** doesn't exist
 - Use IntelliJ assist to create class
6. Add **@ApplicationScoped** annotation so it can be found as a bean
7. Make **PetRepository** implement **PanacheRepository<Pet>**
8. Add method stubs with **tdd 9 - petRepository** live template
9. Return to **PetRepositoryTests** and implement **petsByKindFound** following steps:

```
// Delete everything from the repo
this.petRepository.deleteAll();

// Assert the repository is empty
assertThat(this.petRepository.count()).isZero();

// Persist a new pet to the repo
this.petRepository.persist(new Pet("fluffy", "cat"));

// Assert that finding the pets by kind returns the correct result
assertThat(this.petRepository.findPetsByKind("cat"))
    .isNotNull()
    .singleElement()
    .extracting(Pet::getName, Pet::getKind)
    .contains("fluffy", "cat");
```

10. Implement **noPetsByKindFound** following steps:

```
// Delete everything from the repo
this.petRepository.deleteAll();

// Assert the repository is empty
assertThat(this.petRepository.count()).isZero();

// Assert that finding the pets by kind returns empty
assertThat(this.petRepository.findPetsByKind("cat"))
    .isNotNull()
    .isEmpty();
```

11. Implement **adoptFoundPet** following steps:

```
// Delete everything from the repo
this.petRepository.deleteAll();

// Assert the repository is empty
assertThat(this.petRepository.count()).isZero();

// Persist some pets
this.petRepository.persist(
    new Pet("fluffy", "cat"),
    new Pet("harry", "dog")
);

// Assert that adopting a found pet is correct
assertThat(this.petRepository.adoptPetIfFound("cat", "Eric"))
    .isNotNull()
    .get()
    .extracting(Pet::getKind, Pet::getName, Pet::getAdoptedBy)
    .containsExactly("cat", "fluffy", "Eric");
```

12. Implement `noAdoptablePetFound` following steps:

```
// Delete everything from the repo
this.petRepository.deleteAll();

// Assert the repository is empty
assertThat(this.petRepository.count()).isZero();

// Persist some pets
this.petRepository.persist(
    new Pet(null, "fluffy", "cat", "Eric"),
    new Pet("harry", "dog")
);

// Assert that no pet is found for adoption
assertThat(this.petRepository.adoptPetIfFound("cat", "Eric"))
    .isNotNull()
    .isEmpty();
```

13. At this point all 4 tests should be passing

Implement Repository

```
public List<Pet> findPetsByKind(String kind) {
    Log.infof("Looking for all pets of kind '%s'", kind);
    return list("kind", kind);
}

@Transactional
public Optional<Pet> adoptPetIfFound(String kind, String owner) {
    Log.infof("Looking for an adoptable pet of kind '%s'", kind);
    var pet = find("kind = ?1 AND adoptedBy IS NULL ORDER BY RANDOM()", kind)
        .page(0, 1)
        .withLock(LockModeType.PESSIMISTIC_WRITE)
        .firstResultOptional();

    pet.ifPresentOrElse(
        p -> {
            Log.infof("Found pet for adoption: %s", pet);
            p.setAdoptedBy(owner);
            persist(p);
        },
        () -> Log.infof("No pet of kind '%s' available for adoption", kind)
    );

    return pet;
}
```

Create REST layer tests

1. Create `src/test/java/com/example/PetResourceTests.java`
 - Annotate with `@QuarkusTest`
2. Add `@InjectMock PetRepository`
3. Bring in test stubs with `tdd 10 - petResourceTests` live template
 - Notice in console that as soon as saved tests all run to success
4. Implement `getAll` method

```
// Set up mock to return a pet when repo.listAll() is called
when(this.petRepository.listAll())
    .thenReturn(List.of(new Pet(1L, "fluffy", "cat")));

// Execute GET to /pets & assert
get("/pets").then()
    .contentType(ContentType.JSON)
    .statusCode(OK.getStatusCode())
    .body("$.size()", is(1))
    .body("[0].name", is("fluffy"))
    .body("[0].kind", is("cat"))
    .body("[0].adoptedBy", blankOrNullString());

// Verify interactions
verify(this.petRepository).listAll();
verifyNoMoreInteractions(this.petRepository);
```

5. Highlight all remaining tests and implement in one shot with `tdd 11 - petResourceTestsOthers` live template

Implement REST layer

1. Create `src/main/java/com/example/PetResource.java`
2. Explain how we know what we need to create
 - `/pets` returns all `Pet`s
 - `/pets?kind={kind}` returns all `Pet`s of a certain kind
 - `/pets/{id}` returns a `Pet` given an id
 - **OR** returns a `404` if that `Pet` is not found
3. Implement methods:

```
private final PetRepository petRepository;

public PetResource(PetRepository petRepository) {
    this.petRepository = petRepository;
}

@GET
public List<Pet> getAll(@QueryParam("kind") Optional<String> kind) {
    return kind.map(this.petRepository::findPetsByKind)
        .orElseGet(this.petRepository::listAll);
}

@GET
@Path("/{id}")
public Response getPetById(@PathParam("id") Long id) {
    return this.petRepository.findByIdOptional(id)
        .map(Response::ok)
        .orElseGet(() -> Response.status(Status.NOT_FOUND))
        .build();
}
```

4. Add `@RunOnVirtualThread` to class and explain
5. *Optional*: Run `http :8080/pets` to see all pets
6. *Optional*: Run `http ":8080/pets?kind=cat"` to see all cats
7. *Optional*: Run `http ":8080/pets?kind=horse"` to see that there aren't any horses
8. *Optional*: Run `http :8080/pets/1` to see a certain pet
9. *Optional*: Run `http :8080/pets/5` to see a pet not found (`404` error)

Set up for Kafka

1. Explain that now we have to listen on Kafka for incoming adoption request messages
 - If we have an available pet, process the adoption and put the adoption message on another Kafka topic
 - If we don't have an available pet, do nothing
2. In new terminal add Kafka dependency with `quarkus ext add messaging-kafka`
3. Open `pom.xml` and add Kafka test dependencies (`tdd 12 - pomKafkaTestDeps` live template)
4. Go back to dev mode terminal to see reload
 - And also see that there is now a Kafka broker running (can verify in dev ui)
5. Go into `src/main/resources/application.properties` and add kafka config (`tdd 13 - petkafkaconfig` live template)

Create AdoptionRequest

```
@RegisterForReflection
public record AdoptionRequest(String owner, String kind) { }
```

Create AdoptionListenerTests

1. Create `src/test/java/com/example/AdoptionListenerTests.java`
2. Add `@QuarkusTest` annotation to class
3. Use `tdd 14 - adoptionListenerTests` live template to insert class outline
4. Explain that we will need an `AdoptionListener` class
 - Use IntelliJ assist to create class from field
 - Add `@ApplicationScoped` to the class to add it as a bean
5. Add fields to `AdoptionListener` with `tdd 15 - adoptionListenerFields` live template
6. Implement `adoptablePetFound` following steps:

```
// Set up mock
when(this.petRepository.adoptPetIfFound(pet.getKind(), adoptionRequest.owner()))
    .thenReturn(Optional.of(pet));

// Send request to channel
this.inMemoryConnector.source(AdoptionListener.ADOPTION_REQUESTS_CHANNEL_NAME)
    .send(adoptionRequest);

// Create sink
var sink = this.inMemoryConnector.sink(AdoptionListener.ADOPTIONS_CHANNEL_NAME);

// Wait for messages to arrive in sink
await()
    .atMost(Duration.ofSeconds(10))
    .until(() -> sink.receive().size() == 1);

// Perform assertions on received message(s)
assertThat(sink.receive())
    .isNotNull()
    .singleElement()
    .extracting(Message::getPayload)
    .usingRecursiveComparison()
    .isEqualTo(new Pet(pet.getId(), pet.getName(), pet.getKind(), adoptionRequest.owner()));

// Verify interactions
verify(this.petRepository).adoptPetIfFound(pet.getKind(), adoptionRequest.owner());
verify(this.adoptionListener).handleAdoption(any(AdoptionRequest.class));
verifyNoMoreInteractions(this.petRepository);
```

7. Notice `handleAdoption` method doesn't exist
 - Use IntelliJ assist to create it
8. Add annotations to the `handleAdoption` method using the `tdd 16 - adoptionListenerHandleAdoptionAnnotations` live template
9. Implement `adoptablePetNotFound` following steps:

```
// Set up mock
when(this.petRepository.adoptPetIfFound(pet.getKind(), adoptionRequest.owner()))
    .thenReturn(Optional.empty());

// Send request to channel
this.inMemoryConnector.source(AdoptionListener.ADOPTION_REQUESTS_CHANNEL_NAME)
    .send(adoptionRequest);

// Verify interactions (with timeout)
verify(this.petRepository, timeout(10_000)).adoptPetIfFound(pet.getKind(), adoptionRequest.owner());
verify(this.adoptionListener, timeout(10_000)).handleAdoption(any(AdoptionRequest.class));
verifyNoMoreInteractions(this.petRepository);
```

10. Tests should still be failing.
 - Now we need to implement `AdoptionListener`

Implement AdoptionListener

1. Add attributes:

```
private final PetRepository petRepository;
private final Emitter<Pet> petEmitter;

public AdoptionListener(PetRepository petRepository, @Channel(ADOPTIONS_CHANNEL_NAME) Emitter<Pet> petEmitter) {
    this.petRepository = petRepository;
    this.petEmitter = petEmitter;
}
```

2. Implement `handleAdoption`:

```
Log.infof("Handling adoption for request: %s", adoptionRequest);
this.petRepository.adoptPetIfFound(adoptionRequest.kind(), adoptionRequest.owner())
    .ifPresent(this.petEmitter::send);
```

Integration tests (if time permits)

1. Use `tdd - petResourceIT` live template for `PetResourceIT`
2. Use `tdd - adoptionListenerIT` live template for `AdoptionListenerIT``