Mobile Application Development Google Maps Android API

Waterford Institute of Technology

October 17, 2016

John Fitzgerald

Overview

- Enable launching of external Google Maps app
- Switch to embedding Google map
- Map API becomes accessible
- Begin with sample code (referenced below)
- Build on this, adding features
- Option to launch map associated with particular residence


Google Map

Use the Google Maps application



Google Map

Embed in MapActivity & access API



API features

Google Maps Android API


- Embed & display map
- Access Google Map servers
- Download map data
- Add markers, polygons, overlays
- Change zoom level
- Determine geolocation
- Select map type such as normal or hybrid



Preparatory work

Google Play Services

- Install via Android SDK Manager
- Import to MyRent workspace
- Reference in manifest file
- Reference in MyRent properties



Google Maps Android API Maps API key

Generating & using key

- Each app requires key
- Key obtainable at Google API console
- Must be registered user
- Generate key
- Add key to gradle
- Reference key in manifest
- Switch on API in console


Geolocation

LatLng stores map data

- Units are degrees
- Ranges:

 Longitude: 0 to +/- 180 ■ Latitude: 0 to +/- 90

- One degree (metres)
 - latitude approx 111
 - longitude same at equator
 - zero at poles
- Accuracy decimal places:
 - Four: 11 m (Garmin 15 m)
 - Six: 11 cm
 - Seven: 11 mm



Helpers

Data input and manipulation

- Geolocation data input as String
- Necessary convert to & from Android LatLng


```
public static LatLng latLng(Context context, String geolocation)
 String[] g = geolocation.split(",");
 return new LatLng(Double.parseDouble(g[0]), Double.parseDouble(g[1]));
public static String latLng(LatLng geo)
 return String.format("%.6f", geo.latitude) + ", "
     + String.format("%.6f", % geo.longitude);
```

Geolocation

Validation

Geolodation data input

- Validation introduced in MapHelper.latlng
- Disallows invalid geolocation
- try-catch block used



API Key - Manifest

```
<application ...>
    ...
    <!--Google MAP API key placeholder -->
    <!--Keys in build.gradle (app) -->
    <meta-data
        android:name="com.google.android.maps.v2.API_KEY"
        android:value="${google_map_key}"/>
        </application>
```


API Key - Gradle

```
buildTypes {
 release {
  minifyEnabled false
  proguardFiles getDefaultProguardFile('proguard-android.txt'
  ), 'proguard—rules.pro'
  manifestPlaceholders = [google_map_key: "Alzaxxxxxxx"]
 debug {
  manifestPlaceholders = [google map key: "Alzaxxxxxxx"]
  debuggable true
```

SHA-1 Fingerprint required to obtain key

How to obtain fingerprint

- Unique for each computer
- Create an Android project
- Use wizard Google Maps Activity
- Fingerprint in file google_maps_api.xml
- Detailed instructions lab Appendix



Google Maps Activity


SHA-1 Fingerprint required to obtain key

Obtain fingerprint for each development machine

org.wit.myrent	DD:13:DA:46:A1:35:3F: :8D:53:B5:34
org.wit.myrent	59:4E:E8:6F:3F:0C:B8:5AA:39:A9:D4

SHA-1 Fingerprint required to obtain key

Obtain fingerprint from within Android Studio



References

Google Maps

1. Android Maps API: Getting Started

https://developers.google.com/maps/documentation/android-api/start [Accessed 2016-10-11]

2. Google Maps API Key

https://developers.google.com/maps/documentation/android-api/signup

[Accessed 2016-10-13]



Except where otherwise noted, this content is licensed under a Creative Commons
Attribution-NonCommercial 3.0 License.

For more information, please see http://creativecommons.org/licenses/by-nc/3.0/



