Mobile Application Development

Higher Diploma in Science in Computer Science



Eamonn de Leastar (edeleastar@wit.ie)

Department of Computing, Maths & Physics Waterford Institute of Technology

http://www.wit.ie


http://elearning.wit.ie







Tracing the HTTP messages in a Web App

Spacebook-3 - Standard Chrome Browser




Tools-Developer tools menu option...






Tracing HTTP Request/Response

- Operate Browser as normal
- Control panel shows considerable range of diagnostic information, including:
 - Html
 - · CSS
 - Javascript
 - Network traces
 - + much more....



Simple Trace Example



http://localhost:9000 - Request


This is the actual text sent across the wire:

```
GET /login HTTP/1.1
Host: localhost:9000
Connection: keep-alive
Cache-Control: max-age=0
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8
User-Agent: Mozilla/5.0 (Macintosh; Intel Mac OS X 10_8_2) AppleWebKit/537.17
(KHTML, like Gecko) Chrome/24.0.1312.56 Safari/537.17
Accept-Encoding: gzip,deflate,sdch
Accept-Language: en-US,en;q=0.8
Accept-Charset: ISO-8859-1,utf-8;q=0.7,*;q=0.3
```

http://localhost:9000 - Response


- This is the actual text sent back from the server....
- Response is '200 ok' + the html for the page


```
HTTP/1.1 200 OK
Server: Play! Framework; 1.2.4; dev
Content-Type: text/html; charset=utf-8
Set-Cookie: PLAY FLASH=; Expires=Mon, 28-Jan-13 17:16:23 GMT; Path=/
Set-Cookie: PLAY ERRORS=; Expires=Mon, 28-Jan-13 17:16:23 GMT; Path=/
Set-Cookie: PLAY_SESSION=;Expires=Mon, 28-Jan-13 17:16:23 GMT;Path=/
Cache-Control: no-cache
Content-Length: 876
!DOCTYPE html>
<html>
 <head>
   <title> Spacebook </title>
   <link rel="stylesheet" media="screen" href="/public/bootstrap/css/</pre>
bootstrap.min.css">
 </head>
 <body>
   <div class="container-fluid">
   <div class="navbar">
     <div class="navbar-inner">
       <a class="brand pull-left" href="#">Spacebook</a>
       <a href="/signup"> Signup </a>
 <
  <a href="/login"> Login
                                               </a>
    Login to Spacebook 
 </div>
</div>
<form id="login" action="/authenticate" method="POST">
 <label>Email</label>
 <input type="text" name="email" id="email" />
 <label>Password</label>
 <input type="password" name="password" id="password" />
 <input class="formbutton" type="submit" value="Login" />
</form>
   </div>
 </body>
</html>
```




View Source

Developer Tools View of request/response






Try Submitting a Form...




 When we press the button, we are generating a request...



3 Requests?

- First one is ok this is the 'Action' from the form
- What about the other two?



/authenticate Request

```
POST /authenticate HTTP/1.1
Host: localhost:9000
Connection: keep-alive
Content-Length: 41
Cache-Control: max-age=0
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8
Origin: http://localhost:9000
User-Agent: Mozilla/5.0 (Macintosh; Intel Mac OS X 10_8_2) AppleWebKit/537.17
(KHTML, like Gecko) Chrome/24.0.1312.56 Safari/537.17
Content-Type: application/x-www-form-urlencoded
Referer: http://localhost:9000/login
Accept-Encoding: gzip, deflate, sdch
Accept-Language: en-US,en;q=0.8
Accept-Charset: ISO-8859-1, utf-8; q=0.7, *; q=0.3
Cookie: PLAY_SESSION=08b5765778d75b6fbee191f2a44c8368e25f62e4-
%00logged_in_userid%3A1%00
email=homer%40simpson.com&password=secret
```

/authenticate Request - form data

```
POST /authenticate HTTP/1.1
Host: localhost:9000
...
email=homer%40simpson.com&password=secret
```

· Request encapsulate 'form data' as a single string, separated by '&'s

/authenticate - Response

```
HTTP/1.1 302 Found
Server: Play! Framework;1.2.4;dev
Content-Type: text/plain; charset=utf-8
Location: http://localhost:9000/home
Set-Cookie: PLAY_FLASH=;Expires=Mon, 28-Jan-13 17:28:55 GMT;Path=/
Set-Cookie: PLAY_ERRORS=;Expires=Mon, 28-Jan-13 17:28:55 GMT;Path=/
Set-Cookie: PLAY_SESSION=08b5765778d75b6fbee191f2a44c8368e25f62e4-
%00logged_in_userid%3A1%00;Path=/
Cache-Control: no-cache
Content-Length: 0
```

- Response with '302 Found' (previous response was '200 ok')
- '302 Found' means the requested resource is present but at another location.
- This is provided as 'Location: http://localhost:9000/home
- Once a browser sees this response it make a second request to this new location...

/home request

```
GET /home HTTP/1.1
Host: localhost:9000
Connection: keep-alive
Cache-Control: max-age=0
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8
User-Agent: Mozilla/5.0 (Macintosh; Intel Mac OS X 10_8_2) AppleWebKit/
537.17 (KHTML, like Gecko) Chrome/24.0.1312.56 Safari/537.17
Referer: http://localhost:9000/login
Accept-Encoding: gzip,deflate,sdch
Accept-Language: en-US,en;q=0.8
Accept-Charset: ISO-8859-1,utf-8;q=0.7,*;q=0.3
Cookie: PLAY_SESSION=08b5765778d75b6fbee191f2a44c8368e25f62e4-
%00logged_in_userid%3A1%00
```

- Notice the 'logged_in_userid' field... remember that?
- What is its purpose?

```
HTTP/1.1 200 OK
Server: Play! Framework; 1.2.4; dev
Content-Type: text/html; charset=utf-8
Set-Cookie: PLAY FLASH=; Expires=Mon, 28-Jan-13 17:28:55 GMT; Path=/
Set-Cookie: PLAY ERRORS=; Expires=Mon, 28-Jan-13 17:28:55 GMT; Path=/
Set-Cookie: PLAY SESSION=08b5765778d75b6fbee191f2a44c8368e25f62e4-%00logged in userid%3A1%00;Path=/
Cache-Control: no-cache
Content-Length: 1067
<!DOCTYPE html>
<html>
 <head>
   <title> Spacebook </title>
   <link rel="stylesheet" media="screen" href="/public/bootstrap/css/bootstrap.min.css">
 </head>
 <body>
   <div class="container-fluid">
    <div class="navbar ">
     <div class="navbar-inner">
       <a class="brand pull-left" href="#">Spacebook</a>
        <a href="/home">
                           <a href="/members"> Members </a>
         <
                           <a href="/homeprofile"> Profile </a>
         <
                           <a href="/logout">
         <
                                             Logout </a>
    Spacebook Home Page for Homer Simpson 
 </div>
</div>
<div class="row-fluid">
 <div class="span4">
   >
     Homer Simpson, 0,
   <h2> Friends </h4>
   <h2> Following (0) </h2>
     ul>
            <h4> Followers </h4>
 </div>
 <div class="span8">
   <h2> Messages </h2>
 </div>
</div>
         </div>
 </body>
</html>
```


/home response

Home


'home' page...

Which in turn requests the css file


This is a '200 ok' delivering to us the




Visiting the Members Page




Visiting the Home Profile



Logging out





Except where otherwise noted, this content is licensed under a Creative Commons Attribution-NonCommercial 3.0 License.

For more information, please see http://creativecommons.org/licenses/by-nc/3.0/



