

LP-0003 — script vidéo (~7 min)

 **Tap les liens directement sur ton phone — ne pas copy-paste (les URLs sont longues et peuvent être tronquées au copy).**

- Durée totale visée : **~7 minutes**
- Langue : English
-  **ACTION** = ce que tu fais à l'écran
-  **SAY** = ce que tu lis à voix haute

Toutes les commandes de ce script ont été exécutées et vérifiées. Les sorties annoncées sont les vraies. Si quelque chose ne sort pas comme écrit, arrête et dis-le-moi plutôt que d'improviser.

Le point délicat de cette soumission : une transaction privacy est invisible sur l'explorer, et le wallet peut afficher "Transaction NOT confirmed" alors qu'elle atterrit. On ne cache pas ça — on l'explique et on lit la chaîne directement en RPC, ce qui est plus fort qu'un explorer et ne peut pas t'afficher une page vide en pleine caméra.

Pré-vol (~3 min de prep)

Terminal

 **ACTION :**

```
cd /Users/eden/data/ns.com/lp-0003  
clear
```

Agrandis la police (⌘+ plusieurs fois — le texte doit être lisible en 1080p), ferme Slack/Discord/notifications, fenêtre terminal en plein écran.

Un seul onglet browser

 **ACTION : ONGLET A (le repo)** — tap ce lien :

→ [Repo : edenbd1/lp-0003-private-airdrop-distributor](#)

Pas d'onglet block explorer. Une transaction privacy ne publie ni `program_id` ni `instruction_data`, donc l'indexeur de l'explorer n'a rien à afficher pour un claim. C'est la propriété de confidentialité qui fonctionne, pas un bug — et c'est exactement ce qu'on montre en lisant la chaîne directement, à la scène 2 et à la scène 3.

Vérif de dernière seconde (30 s, avant d'enregistrer)

 **ACTION :**

[illegible]

Tu dois voir **cinq blocs OK** et la ligne finale **VERIFIED** . Si oui → QuickTime → Screen Recording → Démarre. Sinon → stop, préviens-moi.

SCÈNE 1 — Intro (0:00 – 0:45)

 **ACTION** : Terminal vide

 **SAY** :

“Hi, I’m Eden. This is my submission for Logos Lambda Prize L-P zero-zero-zero-three — a Private Allowlist and Airdrop Distributor.”

 **SAY** :

“A distributor commits an eligibility set on chain. An eligible recipient claims their allocation — and the chain records only that a claim happened, never which address made it. An observer who knows every candidate address still cannot tell who claimed.”

 **SAY** :

“The membership proof is genuinely verified on chain, and everything is live on the public L-E-Z testnet. Let me show you, starting from a clean clone.”

SCÈNE 2 — Le demo (0:45 – 3:15)

 **ACTION** : Tape lentement :

```
./scripts/demo.sh
```

 **ACTION** : Entrée. Laisse défiler, **puis scrolle doucement vers le haut** pendant que tu parles.

 **SAY** (pendant que ça tourne) :

“This runs from a clean clone. No funded account, no local sequencer for the local steps.”

 **ACTION** : Scrolle jusqu'en haut, sur `== 0. environment`

 **SAY** :

“First line — R-I-S-C zero dev mode equals zero. Real proofs, no mock receipts. That's required by the brief, and it's the first thing I show.”

 **ACTION** : Scrolle sur `== 1.`, `== 2.`, `== 3.`

 **SAY** :

“Ten adversarial tests on the claim logic — non-members, borrowed Merkle paths, invented roots, forged nullifiers, inflated allocations, redirected destinations. Ten more on the encrypted bundle. Then six against the built verifier binary, run through the sequencer's own executor — same executor, same input order, same thirty-two megabyte session limit the chain applies. A rejection you see there is the rejection the chain performs.”

 **ACTION** : Scrolle sur `== 4.` et `== 5.`

 **SAY** :

“Now the recipient flow. The distributor publishes one encrypted bundle, padded here to eight rows so it hides how many recipients there really are. A recipient opens it with only their own secret — they scan every row, skip the padding, and keep the one row whose data reconstructs a leaf that anchors to the committed root.”

 **ACTION** : Scrolle sur `== 7. compute cost`

 **SAY** :

“Measured compute cost: a claim is three hundred thirty-three thousand user cycles, one and a half percent of the public budget.”

 **ACTION** : Scrolle sur == 8. what an observer sees — **ralentis ici**

 **SAY** (le cœur de la soumission — prends ton temps) :

“This is the whole point. On chain, a claim is a single marker address. That address is a hash of a nullifier, and the nullifier is a hash of the recipient’s secret. Someone who knows every eligible address cannot compute that nullifier, so they cannot map this marker back to any of them. That is the unlinkability property.”

 **ACTION** : Scrolle tout en bas, sur == 9. the live deployment

 **SAY** :

“And the last step reaches the public testnet and verifies a claim that is actually deployed — five checks. The transaction is privacy-preserving, its receipt is a real Succinct STARK, not a dev-mode fake, and the marker is owned by the verifier program. That receipt could not exist unless a membership proof was verified on chain.”

SCÈNE 3 – Une preuve, générée en direct (3:15 – 5:15)

 **ACTION** : Explique que le demo n'a pas *prouvé* — il a exécuté. Maintenant on génère une vraie preuve.

 **SAY :**

“The demo executed the logic; it did not prove. Proving is the expensive part, so let me generate a real one now, live, with dev mode still off.”

 ACTION : Lance un vrai claim de bout en bout (compte financé nécessaire) :

```
export RISC0_DEV_MODE=0
./scripts/deploy-and-claim.sh
```

 **SAY** (pendant que ça démarre) :

“This commits a fresh distribution and then proves and submits real claims against it. Watch the proving step — it takes about two and a half minutes per claim on this laptop, because it generates a real STARK and then the privacy circuit recursively verifies the chained call inside it.”

 **NOTE POST-PROD** : l'attente de proving (~2-3 min) doit être **accélérée en post** (×8 à ×16), MAIS le terminal doit rester visible et continu — on ne coupe pas, on accélère, pour qu'il soit clair que rien n'est truqué.

 ACTION : Quand un `tx_hash` apparaît et que le script confirme, prends-le.

 **SAY :**

“There it is — a claim landed. Real proof, dev mode off, submitted on the privacy path. Now, don’t take my script’s word for it.”

👉 **ACTION** : Copie le `tx_hash` et son nullifier depuis la sortie, puis tape (remplace les valeurs par celles à l'écran) :

[illegible]

... **SAY :**

“That’s the raw chain over R-P-C. Privacy-preserving, a Succinct STARK the sequencer verified, and the marker owned by the verifier. The block explorer would show this as *not found* — by design, because a privacy transaction publishes no data. That is why verification reads the chain directly.”

SCÈNE 4 — L'audit (5:15 – 6:15)

 **ACTION** : Reste sur le terminal

 **SAY** :

“One more thing, because I think it matters more than a feature list.”

 **SAY** :

“After the first version was deployed, I ran an adversarial audit — reviewers and tests whose job is to *break* the code, not confirm it. It found a robustness gap in my own bundle-opening code.”

 **SAY** :

“Opening a row used the raw Diffie-Hellman shared secret. A crafted low-order key would collapse that secret to the same value for every recipient, so one row injected into the open bundle would open for everyone and hand honest recipients garbage. It could never steal funds — the on-chain check rejects any forged claim — but it could grief a distribution.”

 **SAY** :

“The fix rejects those non-contributory keys, and the recipient now keeps the first row that actually anchors to the committed root, not just the first that decrypts — so junk rows are skipped. Both halves are pinned by new tests, including one that runs through the deployed binary. I wrote the finding into the git history rather than quietly patching it.”

SCÈNE 5 — Closing (6:15 – 7:00)

 **ACTION** : Passe sur l'ONGLET A (le repo)

 **SAY** :

“To summarize. Two programs deployed on the public L-E-Z testnet, byte-identical to what’s in the repository — you can check that from the deployment transaction hash. Three distributions committed, and twenty-three privacy-preserving claims landed and independently verifiable. Documented compute cost, a SPEL I-D-L, a Basecamp app, a demo script that runs from a clean clone, and green C-I with the adversarial tests running against the deployed binary on every push.”

 **SAY** :

“Repository at github dot com slash eden-b-d-one slash l-p dash zero zero zero three dash private dash airdrop dash distributor. The privacy model, with the residual leakage named rather than hidden, is in docs slash privacy dash model dot M-D. Thank you for reviewing.”

 **ACTION** : Attends 2 secondes en silence

 **ACTION** : Stop l'enregistrement



Post-recording

1. QuickTime → Export → 1080p mp4 → `lp-0003-submission.mp4`
2. Accélère la portion de proving de la scène 3 (×8 à ×16), terminal continu visible
3. YouTube Studio → tap studio.youtube.com → Upload → **Unlisted**
4. **Title** : LP-0003 Private Allowlist / Airdrop Distributor – Lambda Prize submission (edenbd1)
5. **Description** :

```
Submission demo for Logos Lambda Prize LP-0003 – Private Allowlist /  
Airdrop Distributor.
```

```
A private airdrop on the Logos Execution Zone where a recipient claims an  
allocation without revealing which address claimed, and the membership  
proof  
is genuinely verified on chain via LEZ's privacy-preserving transaction  
path.
```

```
Repo:
```

```
https://github.com/edenbd1/lp-0003-private-airdrop-distributor
```

```
In that repo:
```

```
docs/DEPLOYMENT.md      – every transaction hash, and how to re-verify  
each
```

```
docs/privacy-model.md   – the threat model, and what is deliberately not  
hidden
```

```
artifacts/e2e/claims.tsv – the 23 live claims
```

```
Public testnet:
```

```
https://testnet.lez.logos.co
```

6. Reviens avec **l'URL YouTube + "OK submit la PR"** → je prépare la PR, tu la relis, puis je l'ouvre



Cheat sheet — prononciation

- **LEZ** = “L-E-Z” (épelle)
 - **SPEL** = “spell”
 - **PDA** = “P-D-A” (épelle)
 - **RISC0** = “risk zero”
 - **nsk** = “N-S-K” (épelle)
 - **npk** = “N-P-K” (épelle)
 - **env::verify** = “env verify”
 - **STARK** = “stark”
 - **SHA256** = “SHA two fifty-six”
 - **Diffie-Hellman** = “DIFF-ee HELL-man”
 - **nullifier** = “NULL-ifier”
 - **IDL** = “I-D-L” (épelle)
 - **edenbd1** = “eden-B-D-one”
-

Timing récap

Scène	De	À	Durée
1. Intro	0:00	0:45	45s
2. demo.sh	0:45	3:15	2m30
3. Preuve en direct	3:15	5:15	2m00 (proving accéléré)
4. L'audit	5:15	6:15	1m00
5. Closing	6:15	7:00	45s
Total			~7 min

Entre 5 et 8 minutes c'est bon. Le brief demande une narration qui explique l'architecture et les décisions — pas un screencast muet. La scène 3 montre une vraie génération de preuve avec `RISC0_DEV_MODE=0`, et la scène 4 est ce qui te distingue : elle montre que tu audites ton propre travail.

Tu peux y aller. 🎬