Local goodness-of-fit measures for neural decoding

Sirui Zeng [1], Alison E. Comrie [2], Loren M. Frank [3,4,5],

Uri T. Eden [1], Eric L. Denovellis [3,5,*]

[1]Department of Mathematics and Statistics, Boston University, Boston, MA, USA

[2]Howard Hughes Medical Institute, Janelia Research Campus, Ashburn, VA, USA

[3]Departments of Physiology and Psychiatry, University of California, San Francisco, San Francisco, CA, USA

[4]Kavli Institute for Fundamental Neuroscience, University of California, San Francisco, San Francisco, CA, USA

[5]Howard Hughes Medical Institute, University of California, San Francisco, San Francisco, CA, USA

[*]Corresponding author. Email: eric.denovellis@ucsf.edu

Abstract

State-space models are widely used in neuroscience to infer latent states from observations, but validating them remains difficult. Interpretable models are necessarily simplified relative to the data, and determining the level of complexity needed to describe latent variables accurately is challenging. This challenge results from two main factors. First, because latent variables are inherently unobservable, decoding quality cannot be validated directly against observed data. Second, prediction errors caused by model misspecification can be difficult to interpret. We therefore developed metrics designed to identify localized periods when individual observations conflict with the model's accumulated estimate. Each metric assesses the consistency between the information contained in an individual observation (here, a single spike) and the information summarized by a state distribution over a chosen window of data. We use the one-step predictive distribution, which

carries forward information from all observations through the preceding time bin; more generally, the comparison could use filtering or smoothing distributions defined over other windows. The metrics fall into three categories: 1) measures of overlap between highest probability-density regions of the state distributions; 2) predictive checks based on the model-implied predictive probabilities of individual observations; and 3) the Kullback–Leibler (KL) divergence, included as a familiar baseline that quantifies difference rather than consistency. We applied these metrics to simulated data and to real rat hippocampal neural data, demonstrating their ability to identify periods of model misspecification and to provide interpretable feedback for model improvement. Together, the metrics provide complementary tools for neuroscientists to assess the local goodness-of-fit of state-space models, enabling more informed decisions about model refinement and interpretation of neural decoding results.

Keywords: Neural decoding, State-space models, Goodness-of-fit

Introduction

Internal brain states related to memory, emotion, and attention play central roles in behavior. They arise from a time-varying interplay between the external world and internal processes and are not directly observable, making them difficult to characterize.

Recordings of neural activity, including spike trains, calcium signals, and voltage traces, provide experimental measurements influenced by these latent states. State-space models make it possible to relate these measurements to estimates of the latent states themselves. Specifically, these models provide a method for relating complex, high-dimensional neural activity to estimates of low-dimensional latent states and have provided insights into neural representations and dynamics associated with taste [1], spatial location [2], and aggression [3].

State-space models aggregate information about the latent states over time. They combine the information from the data at the current time (the normalized likelihood distribution) with the accumulated information used to predict the latent state (the predictive distribution). This powerful

combination enables robust estimation of the latent state, effectively balancing current information with the accumulated history of the system and prior knowledge.

Despite the wide use of state-space models in neuroscience, methods to validate them remain underdeveloped and underused. When validation is skipped or reduced to a single pass/fail verdict, a model that fails in one behavioral period but succeeds elsewhere is accepted or rejected wholesale, and the specific assumption responsible for a misfit is never identified—so the model is never refined in a targeted way. One reason models are not refined this way is that latent states are inherently difficult to evaluate [4]: in the absence of ground truth, model validity can only be inferred indirectly, for example by comparing relative likelihoods across models, the quality of reconstructed signals, or performance on downstream tasks. Neural data are also dynamic, so model fit can vary substantially over time. Compounding this, the most common validation tools—cross-validation and "shuffle" permutation tests—typically summarize the entire recording in a single number: they report whether a model generalizes better than chance or better than a simpler alternative, but not *when* during a recording the model fits poorly or *which* of its components is responsible. Consequently, these methods can reject intentionally simplified yet scientifically meaningful models while offering little guidance for improving them. For example, analyses that decode rat movements from hippocampal place cells often ignore known features of the rat's movement (such as momentum) and known features of neurons (such as refractoriness and bursting). These omissions can produce detectable model mismatch even when the resulting decoded trajectories remain scientifically informative [5–7].

State-space models already contain rich diagnostic information in the form of distributions used to estimate the state process at each time: the normalized likelihood, which reflects information from only the current neural observation, and the predictive distribution, which aggregates information from all past observations through the state-space model structure. One potential source of targeted, temporally local diagnostic information is a direct comparison of these two distributions. We do not expect them to be identical. The predictive distribution aggregates information from many past spikes, whereas the likelihood reflects only the current observation, so the two carry different amounts of information about the state and will typically differ in shape and spread.

What matters for model assessment is therefore not whether the two distributions differ, but whether they are *consistent*. We call them consistent when they concentrate their probability mass over overlapping regions of the state space, and inconsistent when those regions are largely disjoint. Consistency is distinct from accuracy: accuracy asks whether the decoded state matches an external ground truth, which is unavailable for a latent process, whereas consistency asks only whether the two internal sources of information about that state—the accumulated past and the current observation—point to the same region. Two distributions may be broad or narrow, and the decoded state may sit far from the animal's physical location, yet still be consistent as long as their high-probability regions overlap. When instead they provide inconsistent information, the mismatch can reveal where, when, and potentially how the model fails to capture the structure of the data. Examining these discrepancies therefore provides a direct, interpretable measure of model–data agreement—analogous to a local, time-resolved goodness-of-fit test.

To address these gaps, we develop and validate a suite of local goodness-of-fit methods, each built on this comparison between the predictive distribution and the likelihood. The most familiar way to compare two distributions is to measure their divergence, and therefore we include Kullback–Leibler (KL) divergence as a natural point of reference. However, divergence measures quantify how much two distributions differ, not whether they are consistent, so they flag any mismatch, including one that arises from a broad predictive distribution or a narrow likelihood, even when the model captures the data structure well. We therefore develop two consistency-focused measures, highest probability-density (HPD) overlap and a rank-based predictive p-value derived from a predictive check, and show that they flag genuine model–data inconsistency and provide actionable feedback to neuroscientists. Using simulated and real hippocampal data, we demonstrate how each metric responds to different types of misspecification and argue that consistency is the right target for local goodness-of-fit assessment. This approach offers a path for neuroscientists to move from binary model rejection (is this model good or bad?) toward an iterative, diagnostic approach to building interpretable theories of neural dynamics.

Methods

State-space models

The state-space paradigm is particularly well suited for neural data analysis because many neuroscience experiments focus on internal brain processes that are not directly observable. For example, hippocampal replay of spatial trajectories has been hypothesized to be related to mental exploration of space, but the trajectories being replayed are not directly observable by experimentalists because these trajectories are different from the spatial position of the animal [8]. In such cases, state-space models are used to simultaneously estimate the unobserved internal representations and their relation to neural activity patterns.

For a discrete set of time points, $t_0, \ldots, t_K$, we define an unobserved state process x_k with initial state x_0, which influences a neural observation process y_k at each subsequent time t_k, $k = 1, \ldots, K$. In the models analyzed here, y_k comprises the spikes of each sorted unit in the kth time bin; in a clusterless model, each spike would instead be identified by its waveform features. We define a state-space model by combining a state-transition distribution $p(x_k \mid x_{k-1})$, which defines how the state evolves in time, with an observation likelihood $p(y_k \mid x_k)$, which defines the relationship between the neural activity and the state. To simplify the problem, we assume that the state-transition distribution depends only on the most recent past value of the state and that the observation likelihood depends only on the current state value. Fig. 1a shows a schematic of this state-space model structure.

This state-space model structure allows for iterative estimation of the state process at each time step based on all the neural data up to that time (Fig. 1b). If the distribution of the state at time t_{k-1} has been computed, we can integrate it against the state-transition distribution to obtain a one-step predictive distribution, $p(x_k \mid y_{1:k-1}) = \int_{x_{k-1}} p(x_k \mid x_{k-1}) \cdot p(x_{k-1} \mid y_{1:k-1})\, dx_{k-1}$. This predictive distribution combines the information from all previous observations to compute the distribution of the state at the next time step. We update this predictive distribution with the information from the most recent observation by multiplying by the observation likelihood to compute the filtering distribution, the posterior distribution of the state given all of the data up to the current time step:




Fig 1. State-space model and local goodness-of-fit measures. **(a)** The graphical representation of the state-space model includes the state-transition model, $p(x_k \mid x_{k-1})$, and the observation likelihood, $p(y_k \mid x_k)$. **(b)** These model components are sufficient to compute an iterative expression for the filtering distribution at time t_k, $p(x_k \mid y_{1:k})$, from the distribution at the previous time step. This involves first integrating the previous filtering distribution against the state-transition distribution to compute the one-step predictive distribution, $p(x_k \mid y_{1:k-1})$, and then updating the predictive distribution with information from the most recent spiking by multiplying by the observation likelihood. **(c)** For each new spike observation, we compute the local goodness-of-fit by assessing the consistency of information between the predictive distribution and the normalized likelihood of that spike. Bars beneath each pair mark the high-probability region of each distribution. We consider the distributions inconsistent when they assign high probability to mostly disjoint subsets of the state space. When the regions with high probability overlap, the distributions are considered consistent, even if the distributions differ in their central tendency or certainty.

$p(x_k \mid y_{1:k}) \propto p(y_k \mid x_k) \cdot p(x_k \mid y_{1:k-1})$.

Common approaches for assessing the goodness-of-fit of state-space models include examining cross-validated error measures in the state process when the state is observable [9], cross-validated error measures in the observation process such as the mean-squared prediction error [10], and the distribution of prediction residuals [11]. Although these approaches can be useful, they may be difficult to interpret for neural data because intentionally simplified state-space models often exhibit some detectable lack of fit even when they remain scientifically useful.

Here, we take a different approach that relies on a set of local goodness-of-fit measures. Each measure compares the one-step predictive distribution with either the normalized likelihood of a single spike as a function of state or the spike itself. These measures therefore consider the consistency between information accumulated through the state-space model over past spiking and the information from the most recent spiking activity. Critically, we do not expect these distributions to align perfectly since they likely contain different amounts of information about the state process. Instead, we use the operational notion of consistency illustrated in Fig. 1c. We consider the distributions inconsistent when their probability masses are concentrated in mostly non-overlapping regions of the state space. We consider them consistent when their high-probability regions largely overlap, even if their central tendencies differ. We also regard the distributions as consistent when a broad high-probability region of one distribution contains a substantially narrower region of the other. This situation may arise frequently because the predictive distribution contains information accumulated from many previous spikes.

In the analyses here, "local" means that each diagnostic is evaluated once per spike. The filter updates with the likelihood of everything observed in a time bin, including neurons that remained silent, whereas each diagnostic compares the predictive distribution with the normalized likelihood of a single spike; bins without spikes therefore produce no diagnostic value. "Local" does not mean that the predictive distribution is restricted to recent data: it summarizes all observations through the preceding time bin via the recursive state-space filter. More generally, the same comparisons could use a filtering or smoothing distribution defined over another chosen window, including a

window containing both past and future observations.

Local goodness-of-fit measures

In this section, we introduce three classes of metrics designed to characterize the local goodness-of-fit of the state-space model. All three are implemented in the open-source Python package `statespacecheck`, which can be applied to the output of other state-space decoders (see Discussion and Code availability).

All three metrics are evaluated at the level of individual spike events. Let C be the number of recorded neurons, let $n_{k,c}$ be the spike count of neuron c in time bin k, with $\mathbf{n}_k = (n_{k,1}, \ldots, n_{k,C})$, let $N_k = \sum_c n_{k,c}$ be the total population count, and let $y_{k,j}$ denote the mark of the jth event: the neuron identity for a spike-sorted model or the waveform features for a clusterless model. For a spike-sorted model, the observation y_k is the count vector $\mathbf{n}_k$, whose events carry the marks $y_{k,1}, \ldots, y_{k,N_k}$, so the observation likelihood $p(y_k \mid x_k)$ is $p(\mathbf{n}_k \mid x_k)$. For conditionally independent Poisson counts, it can be factored as

$$p(\mathbf{n}_k \mid x_k) = \prod_{c=1}^{C} \text{Poisson}\big(n_{k,c}; \lambda_c(x_k)\Delta t\big) = \frac{\exp[-\Lambda(x_k)\Delta t]}{\prod_{c=1}^{C} n_{k,c}!} \prod_{j=1}^{N_k} \left[\lambda_{y_{k,j}}(x_k)\Delta t\right], \tag{1}$$

where Δt is the bin width and $\lambda_c(x_k)$ is the conditional firing rate of neuron c in the bin. Its expected count is $m_c(x_k) = \lambda_c(x_k)\Delta t$. The total population rate is $\Lambda(x_k) = \sum_c \lambda_c(x_k)$, giving a total expected count of $\Lambda(x_k)\Delta t$. Equation (1) separates the exposure factor $\exp[-\Lambda(x_k)\Delta t]$, which is shared by the whole bin, from one event factor $\lambda_{y_{k,j}}(x_k)\Delta t$ for each observed event.

For the spike-sorted models analyzed here, HPD overlap and KL divergence compare the one-step predictive density

$$P_k(x_k) = p(x_k \mid y_{1:k-1})$$

with the normalized single-event likelihood obtained from that event's factor in Eq. (1):

$$Q_{k,j}(x_k) = \frac{\lambda_{y_{k,j}}(x_k)}{\int \lambda_{y_{k,j}}(u)\, du}. \tag{2}$$

The common factor Δt cancels in this normalization. $Q_{k,j}$ contains only the likelihood factor attributable to the selected event. It deliberately excludes the bin-level exposure term, silent neurons, and total spike count, which cannot be assigned to one particular event. Those aspects of fit require a complementary count- or time-rescaling diagnostic. If several spikes occur in one bin, each event is evaluated separately against the same one-step predictive density P_k. For a clusterless model, the analogous $Q_{k,j}$ is obtained by normalizing the marked event-intensity density over the state space.

Overlap between HPD regions

One way to assess the consistency between the predictive distribution and the observation likelihood is to examine the overlap between their highest probability-density (HPD) regions. We refer to the resulting measure as HPD overlap. A substantial intersection indicates that the distributions assign high density to some of the same state values. Minimal or no overlap indicates disagreement under this criterion. This metric provides an interpretable geometric summary of local consistency between the distributions.

We define the overlap between the HPD regions of the predictive distribution and the normalized single-event likelihood as

$$\mathrm{HPDOverlap}(P_k, Q_{k,j}) = \frac{\left|\mathrm{HPD}_{P_k} \cap \mathrm{HPD}_{Q_{k,j}}\right|}{\min\left\{\left|\mathrm{HPD}_{P_k}\right|, \left|\mathrm{HPD}_{Q_{k,j}}\right|\right\}}, \tag{3}$$

where HPD_{P_k} and $\mathrm{HPD}_{Q_{k,j}}$ are the highest probability-density regions of the predictive density and the normalized single-event likelihood, respectively, and $|\cdot|$ denotes the volume of the region. The numerator is the size of the overlap between these regions, and the denominator is the size of the smaller of the two HPD regions. This ratio is the Szymkiewicz–Simpson overlap coefficient applied to the two HPD regions. Unlike the Jaccard index, which divides by the size of the union

and therefore penalizes any difference in region size, the overlap coefficient equals 1 whenever one region is nested inside the other, which is exactly the nesting-tolerant behavior our consistency criterion requires. This normalization ensures that the resulting value is in the range $[0, 1]$, with 0 indicating no overlap and 1 indicating that one region is entirely contained within the other. For example, if the likelihood region is wider and therefore less informative than the predictive region but completely contains it, then the HPD overlap will be 1, suggesting that the two distributions are consistent under this criterion. Conversely, if the ratio is close to 0, it indicates little or no overlap, suggesting substantial differences between the ranges of state values inferred from the two distributions. Throughout, we compute 95% HPD regions.

Fig. 2a illustrates the computation of the HPD overlap. We compute high-density regions for the predictive distribution (top) and the normalized single-event likelihood (middle), then divide the volume of their intersection by the volume of the smaller region (bottom).

Predictive checks

The HPD overlap compares two distributions of the state: one based on the accumulated past information and the other based on the isolated information from the likelihood of the most recent spiking observation. Another approach is predictive checking, which compares the observation itself to a predictive distribution of that observation estimated from the model. This approach has been used before in other contexts [12–14] and has the advantage that it allows for the computation of p-values for individual observations, which are easy to interpret [15, 16].

Predictive checks for spiking data can be challenging to implement because, within sufficiently short intervals, a spike is typically less probable than no spike. One possible approach is to consider spike patterns over longer fixed intervals in which multiple spikes are expected. Here, we take a simpler approach of focusing only on spike times and measuring the probability that an observed spike comes from a particular neuron (for spike-sorted models) or has a particular set of waveform features (for clusterless models).

Using the event notation introduced above, the relevant observation distribution is the distribution

of the spike's mark for an event drawn from the model-implied marked point process. Because the diagnostic is evaluated once for each spike event, its predictive reference distribution corresponds to selecting an event rather than selecting a time bin that contains one or more events. Under the one-step predictive distribution P_k, the expected number of events in the bin associated with a state region dx_k is $\Lambda(x_k)\Delta t\, P_k(x_k)\, dx_k$. The latent state associated with a randomly selected predicted event therefore has the event-weighted distribution

$$P_k^{\text{event}}(x_k) = \frac{\Lambda(x_k)P_k(x_k)}{\int \Lambda(u)P_k(u)\, du}. \tag{4}$$

At states where $\Lambda(x_k) > 0$, the probability that the event came from neuron c is

$$\pi_c(x_k) = \frac{\lambda_c(x_k)}{\Lambda(x_k)}. \tag{5}$$

States where $\Lambda(x_k) = 0$ receive zero mass under P_k^{event}. Combining the event-weighted state distribution with the conditional cell-identity distribution gives the predictive probability of cell identity:

$$f_{\text{pred},k}(c) = \int \pi_c(x_k)P_k^{\text{event}}(x_k)\, dx_k = \frac{\int \lambda_c(x_k)P_k(x_k)\, dx_k}{\sum_{c'=1}^{C}\int \lambda_{c'}(x_k)P_k(x_k)\, dx_k}. \tag{6}$$

For a clusterless model, let $\lambda(y, x_k)$ be the event rate per unit mark volume at waveform mark y, so that $\Lambda(x_k) = \int \lambda(w, x_k)\, dw$ is the total event rate and $\Lambda(x_k)\Delta t$ is the total expected event count in the bin. The corresponding predictive mark density is

$$f_{\text{pred},k}(y) = \frac{\int \lambda(y, x_k)P_k(x_k)\, dx_k}{\int \Lambda(x_k)P_k(x_k)\, dx_k}. \tag{7}$$

Equation (6) is the discrete spike-sorted form of Eq. (7). Let $\widetilde{y}_{k,j}$ denote a replicated mark distributed according to $f_{\text{pred},k}$. We compute the probability that the observed spike is at least as likely as this replicate:

$$p_{k,j} = \Pr_{\widetilde{y}_{k,j}\sim f_{\text{pred},k}}\left(\log f_{\text{pred},k}(y_{k,j}) \geq \log f_{\text{pred},k}(\widetilde{y}_{k,j})\right). \tag{8}$$

For the spike-sorted models considered here, $\widetilde{y}_{k,j}$ takes one of a finite set of values—the identities of the recorded neurons. We compute Eq. (8) exactly as

$$p_{k,j} = \sum_{\substack{c \in \{1,\ldots,C\}: \\ f_{\text{pred},k}(c) \le f_{\text{pred},k}(y_{k,j})}} f_{\text{pred},k}(c), \tag{9}$$

which sums the predictive probabilities of all cell identities at least as unlikely as the observed identity. Because $p_{k,j}$ ranks the observed spike against this predictive distribution of possible spikes, we refer to it as the *rank-based predictive p-value*.

Fig. 2b shows the same probability computed by sampling, the approach one would use for a continuous or otherwise intractable mark space. States are drawn from the event-weighted predictive distribution P_k^{event} (top; in the schematic the total expected event count is constant across states, so it equals the one-step predictive distribution). Each state generates a replicated mark (second), each mark is scored by its predictive density $f_{\text{pred},k}$ (third), and p is the fraction of replicates scoring no higher than the observed mark (bottom). The spike-sorted results in this paper use the exact sum in Eq. (9). A p-value near zero indicates that the observed spike is unexpected given the past spiking and the model.

While HPD overlap explicitly assesses our definition of consistency in the state space, the predictive check probes a related notion in the observation space through the marginalization in Eq. (7). When the observation model is sufficiently informative about the state, we expect large p-values when the predictive distribution and likelihood match, but also when either distribution is narrower than the other, as long as they point to overlapping regions of the state space. This correspondence is not guaranteed: marginalization can map distinct state distributions to similar mark distributions, so a high predictive p-value does not by itself establish that the state distributions overlap. In the common case that the predictive distribution of the state is narrow relative to the likelihood, the predictive distribution of observations will be concentrated on the spikes that occur at the confidently predicted location, and the observed spike will have appreciable likelihood at that location. The observed spike is among those that the model anticipates and should therefore lead

to a high p-value. In the less common case that the likelihood is narrow relative to the predictive distribution of the state, the predictive distribution of the observations will also be broad and will assign appreciable probability to a wide range of spikes. The observed spike is likely to fall within this anticipated range, so the p-value should also be high. A low p-value tends to arise when the observed spike is specifically unlikely relative to what the model anticipates, which corresponds to the likelihood concentrating in a region the accumulated past deems improbable.

KL divergence

Finally, one of the best-known measures of discrepancy between probability distributions is the Kullback–Leibler (KL) divergence [17], defined in this case as the expected excess logarithmic loss incurred when the normalized single-event likelihood is used to approximate the predictive distribution, with the expectation taken with respect to the predictive distribution:

$$D_{\mathrm{KL}}(P_k \,\|\, Q_{k,j}) = \int P_k(x_k) \log\left(\frac{P_k(x_k)}{Q_{k,j}(x_k)}\right) dx_k, \tag{10}$$

where P_k and $Q_{k,j}$ are the distributions defined above.

Fig. 2c illustrates the computation of the KL divergence. The top panel shows the predictive distribution and normalized single-event likelihood as functions of x_k. The middle panel shows their pointwise log-density ratio, $\log\big(P_k(x_k)/Q_{k,j}(x_k)\big)$. The bottom panel shows this ratio weighted by $P_k(x_k)$, which, when integrated, gives the value of the KL divergence.

The KL divergence is the most familiar way to compare two distributions, and we include it as a natural point of reference. It is an asymmetric measure, meaning that, in general, $D_{\mathrm{KL}}(P \,\|\, Q) \neq D_{\mathrm{KL}}(Q \,\|\, P)$. We could also compute the KL divergence from the likelihood to the predictive distribution, $D_{\mathrm{KL}}(Q \,\|\, P)$, or the average of these two divergences, $\frac{1}{2}(D_{\mathrm{KL}}(P \,\|\, Q) + D_{\mathrm{KL}}(Q \,\|\, P))$, but both alternatives lead to a common issue, namely that the KL divergence can become arbitrarily large when its first argument places appreciable probability where its second argument assigns very little. Thus, $D_{\mathrm{KL}}(Q \,\|\, P)$ can become large when an uninformative spike produces a broad




Fig 2. Computation of the three local goodness-of-fit metrics. P is the one-step predictive distribution of the state and Q the normalized single-event likelihood of an observed mark y (a spike's neuron identity or waveform features). **(a)** For HPD overlap, the volume of the intersection (bottom) of the 95% high-density regions of P (top) and Q (middle), bounded by the dashed levels, is divided by that of the smaller region. **(b)** The rank-based predictive p-value by sampling, for a continuous mark equal to the state plus noise. Illustrative states are drawn from the event-weighted predictive distribution (top). Each state generates a replicated mark from $p(y \mid x_k)$, the distribution of a spike's mark given the state (second). Each mark is scored by its height on f_{pred}, the average of those distributions over P (third), and p is the fraction of many replicates scoring no higher than the observed mark (bottom). For spike-sorted data, p is evaluated exactly. **(c)** For KL divergence, P (blue) and Q (orange) are compared (top) by the difference in log densities (middle), weighted by P (bottom) and integrated.

likelihood. Choosing $D_{\mathrm{KL}}(P \,\|\, Q)$ avoids that particular behavior but raises a complementary one: the divergence will grow large whenever the predictive distribution is broad relative to the likelihood, which can occur, for example, when informative spikes are sparse. We will see in the simulation and data analysis below that this behavior flags many spikes, even when their information is consistent with the accumulated information from past spiking.

Simulation study

Validating local goodness-of-fit metrics on real neural data is fundamentally limited: when the truth is unobserved, there is no way to tell whether a flagged moment reflects a model failure or a false alarm. We therefore first evaluate the three diagnostics—HPD overlap, the rank-based predictive p-value, and KL divergence—in a simulation in which every departure from the decoder's model is known by construction. We simulate a hippocampal place-cell population on a one-dimensional track and decode it with a Bayesian filter whose model matches the simulation. Three misfit windows break that match, each by perturbing either the observation model or the state-transition model. Two control windows present activity that departs from ordinary running—a replay sweep and sparse firing during immobility—but that the decoder's observation model describes correctly. The simulation asks which of these windows make current spikes conflict with the decoder's prediction from past spikes, and whether each diagnostic flags those windows and not the others.

Simulation design

Track and observation model. The state space is a one-dimensional linear track of length $L = 100$ arbitrary units (a.u.) discretized at unit spacing, $x \in \{0, 1, \ldots, 100\}$. The simulated population consists of eleven place cells with Gaussian place fields centered at $\mu_c \in \{0, 10, \ldots, 100\}$ and shared standard deviation $\sigma_{\mathrm{pf}} = 10$ a.u. The expected spike count of cell c per 1 ms time step at position x is

$$m_c(x) = \lambda_c(x)\Delta t = \alpha\, \phi\left(x \mid \mu_c, \sigma_{\mathrm{pf}}^2\right), \tag{11}$$

where $\Delta t = 1\,\text{ms}$, $\phi(\cdot \mid \mu, \sigma^2)$ is the Gaussian density, and $\alpha = 5$ is a scale parameter for the expected count. The peak expected count is $\alpha/(\sigma_{\text{pf}}\sqrt{2\pi}) \approx 0.20$ spikes per step, corresponding to a peak rate of approximately 200 Hz. Spike counts are drawn independently across cells at each step, $n_{k,c} \sim \text{Poisson}(m_c(x_k))$. Except during the replay control described below, x_k is both the animal's physical position and the position represented by the simulated ensemble.

Position dynamics. Except where noted below, the animal's position evolves as a Gaussian random walk with step standard deviation $\sigma_{\text{pred}} = 0.5$ a.u. The trajectory is reflected at 0 and 100 a.u. throughout the session, starts at $x_0 = 0$, and is continuous across phases: the final position of each phase becomes the initial position of the next.

Decoder. The decoder is a Bayesian filter on the same grid of positions, and outside the misfit windows its model is the generative one. Its observation model treats the spike counts as independent Poisson variables with the expected counts of Eq. (11), using the true place fields; during each control, the expected counts are switched to the rates that generate that window's spikes. Its state-transition model is a Gaussian random walk with the same step standard deviation σ_{pred}, truncated at the track ends and renormalized. At each step, the decoder applies the transition to the previous filtering distribution to obtain the one-step predictive distribution P_k, and then updates P_k with the likelihood of all spike counts in the bin, including those of the cells that did not fire. The diagnostics compare P_k with the normalized single-event likelihood $Q_{k,j}$ of each spike in the bin.

Flag thresholds. A spike is flagged as a poor fit when its diagnostic crosses a threshold. The HPD-overlap and KL-divergence thresholds are set from the opening, well-specified part of the session (steps 0–6,000), with the values pooled across 100 independent realizations so that the thresholds are not dominated by the noise of a single run. Because low HPD overlap indicates disagreement, a spike is flagged when its value is at or below the 1st percentile of the pooled baseline values; because many baseline spikes are tied at that value, this rule flags 1.4% of baseline spikes rather than the nominal fraction. Because high KL divergence indicates disagreement, a spike is

flagged when its value is at or above the 99th percentile. The rank-based predictive p-value instead uses a fixed threshold: a spike is flagged when $p \leq 0.05$ (equivalently, $-\log(p) \gtrsim 3$, with log the natural logarithm).

Phase schedule. The 32-second session (32,000 steps) contains three misfit windows and two controls, described below in the order in which they appear in Fig. 3a. Each misfit window perturbs the observation model $p(y_k \mid x_k)$ or the state-transition model $p(x_k \mid x_{k-1})$, either in the generative process or in the decoder's assumptions. The two controls change the spiking in ways the decoder's observation model takes into account, so they contain no observation misfit; their movement—a deterministic sweep in one, an immobile animal in the other—is not a random walk. All other steps are well specified: the opening baseline, which sets the thresholds, and the three clean-recovery windows that follow the misfit windows (steps 10,000–14,000, 18,000–22,000, and 26,000–30,000), in which the generative process and the decoder return to the baseline configuration. Fig. 3b pools the recovery windows, without the replay steps, into a single well-specified column.

Remap: During steps 6,000–10,000, the decoder-side observation model is perturbed. Spikes are generated from the true place fields, but the decoder evaluates them against a scrambled map: the eleven place-field centers are reassigned among the cells by a fixed random permutation that moves every field by at least three place-field spacings, modeling global remapping to statistically independent locations. The diagnostics use the same scrambled map as the decoder and have no access to the true fields, so the remap is detectable only through its internal inconsistency: the scrambled map places spikes generated at neighboring positions at unrelated locations, which a smoothly moving state cannot explain.

History-dependent firing: During steps 14,000–18,000, the generative-side observation model is perturbed. Spike counts are generated with each cell's Poisson mean set to zero for 1 ms after a step in which it spiked, followed by a 2 ms–10 ms burst window with a threefold rate increase, matching the rough phenomenology of CA1 pyramidal-cell refractory and burst windows; the decoder still assumes independent Poisson firing. Because the burst window

outlasts the suppressed step, this modulation also raises each cell's mean firing rate above the Poisson rate the decoder assumes. The per-spike spatial likelihood is unchanged, so the mismatch lies in the temporal joint distribution and overall rate of the spike train, not in the spatial information each spike carries.

Replay: During steps 19,000–21,000, within the second clean-recovery window, a replay event occurs. For this control, we distinguish the animal's physical position, z_k, from the internally represented position, x_k, that drives the place-cell spiking. The animal is immobile, so z_k remains fixed, while x_k moves at constant speed from its starting point to the farther end of the track and back. During the sweep the place cells fire at an elevated rate, with $\alpha = 20$ in Eq. (11) (a peak rate of approximately 800 Hz). The decoder uses these elevated rates, so its observation model matches the replayed spikes. The replay steps are scored as their own column in Fig. 3b.

Momentum: During steps 22,000–26,000, the generative-side state-transition model is perturbed. The trajectory is generated with persistent velocity, $v_k = 0.88\, v_{k-1} + \eta_k$ and $x_k = x_{k-1} + v_k$ with $\eta_k \sim \mathcal{N}(0, \sigma^2_{\text{pred}})$; the decoder continues to assume a memoryless random walk with step standard deviation σ_{pred}.

Sparse population: During steps 30,000–32,000, the animal is immobile at $x = 30$ a.u. It reaches this position at constant speed during the last second of the third clean-recovery window, so the control begins without an abrupt position jump; these approach steps remain in the well-specified column. The eleven place cells fall silent (their expected counts are set to zero), as can occur during immobility, and the only spikes come from a sparse population of five additional cells with narrow fields clustered near $x = 30$ a.u. (centers spread over 28.5–31.5 a.u., each with standard deviation 2 a.u.). Each fires as an independent Poisson process with a peak rate of 1 Hz, so the population produces only a few spikes per second and its spikes are separated in time. Before this window the same cells fire at a peak rate of 0.01 Hz. The decoder uses these phase-specific rates and knows that the place cells are silent,

so its observation model is correctly specified.

Simulation results

The diagnostics rarely flag spikes when the model is correct. We first asked how often each metric flags spikes when the decoder's model matches the process that generated the data. In the well-specified windows, the three metrics flagged 1–3% of spikes, and the decoded position was a median of 1.8 a.u. from the animal's position, less than one-fifth of the place-field standard deviation (Fig. 3b). These windows were not used to set the thresholds, so this rate is what we would expect from the diagnostics on well-fit data. Here and below, flag percentages are medians across realizations; except in the remap window and for KL divergence in the sparse-population control, their interquartile range across realizations spans at most 2 percentage points.

All three metrics detect an incorrect place-field map. We next asked whether the diagnostics could detect an incorrect observation model when they, like the decoder, have access only to that model. When the decoder used the scrambled map, successive spikes, generated from neighboring positions, had likelihoods centered on unrelated locations, and each spike's likelihood often fell outside the region supported by the prediction (Fig. 3a). All three metrics flagged 37–43% of spikes, and the decoding error rose to 42 a.u. (Fig. 3b). The flag percentage varied widely across realizations (interquartile range 19–57%) because it depends on how much of the scrambled map the trajectory visits. The diagnostics thus identified the period in which the observation model was wrong and the decoded position unreliable.

Misfit that leaves spatial information intact is not flagged. Not every departure from the model produces conflicting information about position. When cells fired with refractory periods and bursts that the decoder did not model, the spatial tuning of each spike was unchanged, so each spike's likelihood still pointed to the animal's location. The decoder treats the spikes within a burst as independent evidence, so its predictive distribution narrowed, but it did not move away from the




Fig 3. Per-spike goodness-of-fit diagnostics for the simulation study. **(a)** Top row: the predictive distribution over time (1 ms per step) and position, with the animal's physical position in magenta; shading marks the three misfit windows and two controls. Second row: the mean normalized per-spike likelihood in each spike-containing bin (averaged for display only). Third row: spikes of all sixteen neurons (eleven place cells, five sparse-population cells), sorted by field center. Bottom rows: HPD overlap (symmetric-log axis), $-\log(p)$ of the rank-based predictive p-value, and KL divergence for each spike event, with flag thresholds. **(b)** Median percentage of spike events flagged in each phase across 100 realizations, with the clean-recovery windows (excluding the replay event) pooled into the well-specified column. HPD and KL thresholds come from the pooled opening baseline (steps 0–6,000); the predictive p-value uses a fixed threshold of 0.05. The "Distance" row gives the median absolute distance (a.u.) between the decoded position (mean of the filtering distribution) and the animal's physical position. The bottom row names the perturbed component (*Observation* or *Transition*); a dash marks well-specified and control phases.

true position. All three metrics flagged only 1–2% of spikes, at or below the well-specified rate, and the decoding error was essentially unchanged (1.6 a.u.; Fig. 3b). The diagnostics are thus sensitive to conflict between a spike and the prediction rather than to every form of misspecification.

Replay is not mistaken for model failure. In the hippocampus, the decoded position departs from the animal's location during replay [8], and a useful diagnostic should not treat these events as errors. During the simulated replay, the prediction followed the replayed trajectory far from the animal, and each spike remained consistent with it (Fig. 3a). The metrics flagged 1–3% of spikes, similar to the well-specified windows, even though the decoded position was a median of 36 a.u. from the animal (Fig. 3b). Because the diagnostics assess whether spikes are consistent with the model rather than with the animal's physical position, they leave replay unflagged.

The diagnostics also detect an incorrect movement model. When the animal moved with momentum that the decoder's random walk did not capture, the prediction lagged behind the animal. The metrics flagged 8–14% of spikes, the rank-based predictive p-value the most: several times the well-specified rate of 1–3%, though less than in the remap window. The median decoding error rose more than fourfold, to 8.0 a.u. (Fig. 3b). The flag rate is modest relative to this error because a single spike localizes the animal only coarsely: its likelihood extends well beyond the lag, so most spikes still overlap the offset prediction, and only spikes from cells whose fields lie far from the predicted position are flagged.

Only KL divergence flags consistent sparse firing. Finally, we asked whether the metrics distinguish distributions that differ from distributions that conflict. When the animal was immobile and only the sparse population fired, the prediction broadened between isolated spikes, and each spike's narrow likelihood fell within the range the prediction supported (Fig. 3a). HPD overlap and the predictive p-value flagged no spikes in the median realization, whereas KL divergence flagged 43% (interquartile range across realizations 36–57%), even though decoding remained accurate (median error 1.0 a.u.; Fig. 3b). KL divergence responds to the difference in concentration between

the two distributions, not to a conflict in the information they carry about position.

Together, these results show that HPD overlap and the rank-based predictive p-value respond to conflict between a spike and the model's prediction, whereas KL divergence responds to any difference between the two distributions. HPD overlap and the predictive p-value flagged spikes in the remap window and, less often, in the momentum window, and did not flag history-dependent firing, replay, or sparse firing, none of which create conflict. KL divergence agreed with them in every window except the sparse-population control, where it also flagged consistent spikes whose likelihood was much narrower than the prediction.

Real hippocampal data analysis

Data collection and behavioral task

We applied the local goodness-of-fit metrics to units recorded from the rat hippocampus during one recording epoch, in which the animal performed a spatial bandit task on a maze with three radially arranged Y-shaped foraging patches extending from a central point. A schematic of the maze is shown in the right inset in Fig. 4. The details of this task and the data collection methods are described by Comrie et al. [18]. Briefly, the rat was trained to run between six reward ports located in three Y-shaped "patches". Each port was assigned a reward probability of 0.2, 0.5, or 0.8, such that one patch was best on average. Reward probabilities changed periodically after a preset time or trial limit. Recordings were made with 22 tetrodes advanced to CA1; two additional tetrodes, one in each hemisphere, served as local references in the corpus callosum.

For the present analysis, we sorted the continuous 30 kHz neural signal into putative single units with MountainSort4 [19]. In the MountainSort4 pipeline, the signal was band-pass filtered and whitened during preprocessing; negative-going events were then detected on each tetrode at a threshold of 3 in whitened units, with a minimum inter-event interval of 10 samples ($\approx$0.33 ms). Units were retained from automated curation only, without manual cluster curation. Because curation was automated, some units may contain multiunit activity or represent incompletely merged

clusters; this does not affect our purpose here, which is to demonstrate the diagnostics rather than to characterize individual neurons.

For decoding, we linearized the animal's position by projecting it to the nearest point of a skeletonized track, discretized the resulting linear position into spatial bins of approximately 2 cm, and binned spikes at 2 ms resolution. We fit both decoders with `non_local_detector` version `0.6.10.dev214+g956fdccaf`. They used the same sorted-spikes kernel-density observation model, with positional bandwidth `position_std`$= \sqrt{12.5} \approx 3.5$ cm, and initialized position uniformly over the track-interior bins. The Continuous model assigned probability one to its sole dynamics mode and used a zero-mean Gaussian random-walk position transition with `movement_var`$= 6.0\,\mathrm{cm}^2$. The Continuous–Fragmented model initialized the Continuous and Fragmented modes with probabilities $(0.5, 0.5)$ and used the mode-transition matrix

$$\begin{pmatrix} 0.98 & 0.02 \\ 0.02 & 0.98 \end{pmatrix},$$

with rows and columns ordered as (Continuous, Fragmented). Its Continuous-to-Continuous position transition used the same random walk as the Continuous model; the other three mode transitions used a uniform distribution over track-interior position bins.

The Continuous–Fragmented decoder represented the joint state of discrete dynamics mode and position, with the same position-dependent observation model in both modes. For all three diagnostics, we marginalized its one-step predictive distribution over dynamics mode and compared the resulting distribution over position with one copy of the shared observation likelihood. The diagnostics for both decoders were therefore defined on the same position grid. The rank-based predictive p-value used the same fixed threshold as in the simulation, flagging $p \leq 0.05$. For HPD overlap, the recording has no designated clean baseline period from which to derive a percentile threshold, so we flagged values at or below a fixed threshold of 0.05.




Fig 4. Per-spike goodness-of-fit diagnostics applied to a hippocampal recording during navigation on a multi-arm maze (203 sorted units, 182 of which fired in this epoch; data from Comrie et al. [18]), evaluated under a Continuous and a Continuous–Fragmented state-space model. The inset shows the two-dimensional maze with the animal's trajectory in gray; colored dots mark the six reward ports, and segment colors match the bars beside rows 1–2. **(a, b)** A window containing a candidate replay event, decoded with the Continuous (a) and Continuous–Fragmented (b) models; time is relative to the start of the window. Row 1: the one-step predictive distribution over linearized position, with the animal's physical position overlaid. Row 2: the mean normalized per-spike likelihood in each spike-containing bin (averaged for display only), identical under both models. Row 3: the spike raster, with units sorted by place-field peak position. Rows 4–6: HPD overlap (symmetric-log axis), $-\log(p)$, and KL divergence for each spike event. Horizontal lines mark the flag thresholds, 0.05 for HPD overlap and $-\log(0.05) \approx 3$ for the predictive p-value; KL divergence has none. **(c)** Per-spike values across the epoch under the Continuous (horizontal) and Continuous–Fragmented (vertical) models; the dashed line is the identity. Dotted lines mark flag thresholds; outlined boxes contain spikes flagged only under the Continuous model. Color gives spike events per hexagon (shared log scale); n is their total; the $-\log(p)$ axis omits a few larger values.

Data analysis results

Fig. 4 compares decoding of these hippocampal spike data under two state-space models. The first assumes that the latent state moves continuously through space, as expected if it represents only the animal's physical location. During immobility, however, hippocampal representations can jump to distant locations and reactivate in sequences resembling past movement trajectories [20]. We therefore expect the Continuous model to exhibit local disagreement with the spiking data when the neural representation jumps. We compare this model with a Continuous–Fragmented model that permits discrete jumps in the hippocampal representation. We previously used a related model structure to capture replay and other nonlocal hippocampal representations [2].

Fig. 4a shows a brief segment decoded with the Continuous model while the animal is immobile. The rows follow the same order as in Fig. 3a. During this candidate replay event, the decoded representation transitions rapidly among maze locations while the animal remains at rest, as indicated by the magenta position trace. The Continuous model cannot track these rapid transitions, and its predictive distribution lags behind the information provided by the likelihoods of the observed spikes. The HPD overlap and rank-based predictive p-value diagnostics flag many spikes, and several spikes also have elevated KL divergence; KL divergence values are not dichotomized in this analysis.

The contrast between the Continuous and Continuous–Fragmented models is shown in panels a and b of Fig. 4. The likelihood of each spike is identical under the two models (second row), but the Continuous–Fragmented model decodes a rapidly moving state trajectory that the Continuous model cannot track. When the representation is assigned to the Fragmented mode, the predictive distribution becomes uniform or nearly uniform, allowing the likelihoods of subsequent spikes to produce a jump in the state estimate.

For HPD overlap (fourth row, blue), 38 of the 43 spikes in this window flagged under the Continuous model are no longer flagged under the Continuous–Fragmented model. Most spikes in the window (448 of 649) also have lower $-\log(p)$ values under the Continuous–Fragmented model than under the Continuous model (fifth row, pink). Under the Continuous model, the predictive distribution can concentrate at the wrong location, making the observed spike very unlikely. During

replay events, the Continuous–Fragmented model instead produces a broad predictive distribution. Although the observed spike can remain unlikely under this broad distribution, it is less unexpected than under the concentrated Continuous-model prediction. For KL divergence (bottom row, green), many spikes retain high values under the Continuous–Fragmented model. This pattern is consistent with the simulation results: predictive distributions that are broad relative to spike likelihoods produce larger KL values even when our operational criterion classifies those prediction–likelihood pairs as consistent.

Fig. 4c shows hexagonally binned density plots comparing the per-spike values of each local goodness-of-fit metric, for all 870,018 spike events in the recording epoch, under the Continuous and Continuous–Fragmented models; color indicates the number of spike events in each hexagon. The left panel shows HPD overlap in blue. Hexagons above the 45° line correspond to spikes with greater HPD overlap under the Continuous–Fragmented model. The dense vertical band at a Continuous-model value of 0 and Continuous–Fragmented values above 0.05 (within the outlined box) represents spikes for which the Continuous model's predictive distribution has no overlap with the spike likelihood, whereas the Continuous–Fragmented model's predictive distribution has nonzero overlap, so adding the Fragmented mode alleviates this disagreement for many spikes. There is comparatively little density at a Continuous–Fragmented value of 0 and Continuous-model values above 0.05, indicating that it rarely creates new disagreement. Of the 18,790 spikes flagged under the Continuous model, 17,289 (92%) are no longer flagged under the Continuous–Fragmented model (*rescued*), whereas 176 spikes are flagged only under the Continuous–Fragmented model (*newly flagged*).

The center panel of Fig. 4c shows the negative logarithm of the rank-based predictive p-value, $-\log(p)$, in pink. Hexagons below the 45° line correspond to spikes that are less unexpected under the Continuous–Fragmented model than under the Continuous model. The density band below this line extends beyond a Continuous-model value of 3 (within the outlined box), corresponding to $p \leq 0.05$ because $-\log(0.05) \approx 3$. The corresponding region above the line, where the Continuous–Fragmented value exceeds 3, is substantially less dense. Thus, the rank-based predictive p-value

identifies many spikes for which local disagreement is reduced under the Continuous–Fragmented model. Of the 33,954 spikes flagged under the Continuous model, 9,373 (28%) are rescued by the Continuous–Fragmented model, whereas 1,706 spikes are newly flagged.

The right panel of Fig. 4c shows KL divergence values in green. Hexagons below the 45° line correspond to spikes with lower KL divergence under the Continuous–Fragmented model. Most spike events (94%) lie below the line, concentrated at Continuous-model values of 2.7–3.5 (interquartile range). More strikingly, the 6% of spike events above the line have a median Continuous-model value of 1.5, whereas their Continuous–Fragmented values extend to 30. As in the simulation, these values occur when the Continuous–Fragmented model produces a broad predictive distribution after estimating the Fragmented mode. KL divergence therefore aligns less closely with the nesting-tolerant consistency criterion used for the other metrics in this setting.

Discussion

State-space modeling has become a powerful tool for describing the latent dynamics of neural systems. Validating these models is inherently difficult because latent states are unobservable and many models are purposefully simplified. To address this, we developed multiple local goodness-of-fit metrics that compare the instantaneous information received from each spike to the information carried forward from all preceding spiking activity by the state-space model. Rather than dismissing a model in its entirety, these metrics are able to assess the consistency between immediate observations and the information accumulated through the state-space structure, providing a more granular assessment of decoding reliability.

Two of the three metrics we examined, HPD overlap and the rank-based predictive p-value, behaved as a consistency measure should: they flagged spikes that conflicted with the prediction, but not spikes whose likelihood lay within a broad prediction. The HPD overlap provides a geometric measure of consistency that remains interpretable when one high-density region contains another. The rank-based predictive p-value provides a direct statistical assessment of each observation. For

spike-sorted data on a discretized state space, the p-value is exact and inexpensive, a finite sum over the recorded neurons, whatever the state-transition model; for continuous marks, as in clusterless decoding, or for other observation models whose predictive mark distribution cannot be enumerated, it must instead be estimated by Monte Carlo sampling, which is considerably more costly. The KL divergence is computationally simple but is sensitive to distribution tails and lacks a clear upper bound, making it difficult to set a threshold. More broadly, KL divergence is only one member of the larger family of f-divergences, which also includes the total variation distance and the Pearson χ^2 divergence [21]. Substituting another member of this family would emphasize different features of the prediction–likelihood mismatch, but because these measures all target distributional difference rather than the consistency we seek, KL's tendency to flag spikes that remain consistent with the model, as occurs whenever the predictive distribution is broad, would likely carry over to the family as a whole. This behavior is a liability for consistency assessment, but it could be useful in cases where the goal is to flag time points when the predictive distribution becomes uncertain relative to the information coming from individual spikes. When the goal is consistency in estimates of the state process, we recommend HPD overlap and the rank-based predictive p-value as primary diagnostic measures.

We illustrated the application of these metrics to simulated and real spike-sorted data from rat hippocampus. These same metrics naturally extend to other neural data types when incorporated into state-space models. In particular, clusterless decoding has been shown to give lower decoding error and better-calibrated uncertainty than decoding from spike-sorted units [5]. The metrics, as defined in the Methods section, naturally extend to clusterless models. In that case, a lack of fit for any particular spike suggests that a spike with that waveform was unexpected based on the accumulated information from the state-space model up to that point in time.

These metrics make it possible to identify specific periods when a state-space model is more or less consistent with the spiking data, and to turn that diagnosis into a concrete modeling decision. Consider a researcher decoding the hippocampal recording with the Continuous model alone. During the candidate replay event, the local diagnostics reveal that many observed spikes conflict with a

state representation constrained to move continuously through space. This pattern motivates the hypothesis that the continuous transition model is too restrictive. Consistent with that hypothesis, adding a Fragmented mode that permits discrete jumps eliminates the HPD-overlap flag for 92% of spikes flagged under the Continuous model across the recording epoch (Fig. 4c). A single score for the whole epoch could rank the two models, but it would not identify which individual observations drive the difference. Here, the local diagnostics, alternative-model comparison, and scientific context together support a specific refinement of the model. More broadly, this diagnose-then-refine cycle enables a feedback loop between model development and assessment that can improve the quality of state-space models.

To make these diagnostics straightforward to apply in other studies, we provide them as an open-source Python package, `statespacecheck` (https://github.com/edeno/statespacecheck). For a spike-sorted decoder, the package needs only quantities that a grid-based decoder already computes: the one-step predictive distribution in each time bin, each neuron's firing rate as a function of the state, and the time bin and neuron of each spike. From these it returns the HPD overlap, the rank-based predictive p-value (evaluated exactly over the recorded neurons), and the KL divergence for every spike, along with the building blocks (the normalized single-event likelihood and the predictive distribution over neurons) and a helper for setting thresholds from a baseline period. For clusterless decoders, the package computes the same three diagnostics from the joint mark intensity $\lambda(y, x_k)$, approximating the predictive p-value by Monte Carlo as in Fig. 2b. The package does not depend on how the decoder was fit, so it can be applied to an existing model without modification. Because the diagnostics yield one value per spike, it is often most informative to inspect them alongside the decoded state. A desktop viewer distributed with the analysis code displays a full decoded recording epoch with the per-spike diagnostics; the user can scrub through time, select an individual spike to compare its likelihood with the predictive distribution at that time, view the population likelihood against the predictive, filtered, or smoothed distribution, and, for the hippocampal recording, switch between the Continuous and Continuous–Fragmented models. We also provide a companion website (https://edeno.github.io/statespacecheck-paper/) where readers can explore how the

diagnostics are computed and inspect the simulated and hippocampal examples.

These methods could be extended in several ways. For simplicity, we focused on comparing instantaneous information in the likelihood of each spike with aggregated information from the past contained in the one-step predictive density. A natural and powerful extension of these methods is obtained by replacing the one-step predictive density with any posterior density derived from the state-space framework. In particular, replacing the one-step predictive density with a smoothing density (e.g., from a fixed-interval smoother over the observation period) would allow us to leverage both past and future data to increase statistical power in identifying model misspecification. Because filtering and smoothing densities also condition on the spike being assessed, that spike's own contribution would first need to be removed, for example by leave-one-out smoothing, so that the spike is not compared against a distribution it helped form.

These approaches also present challenges. First, the computational cost of these metrics increases as the dimensionality of the state process increases. In all of our examples, we computed the KL divergence measure and the HPD overlap by partitioning the state space into a lattice and computing the likelihoods and predictive densities at each point in that lattice. As the dimension of the state increases, the size of that lattice will grow exponentially. We also evaluated the predictive checks exactly by summing over the finite set of recorded-neuron identities. For models with continuous or otherwise high-dimensional observation spaces, the predictive check could instead be approximated by sampling from the predictive state and observation distributions, avoiding enumeration of every observation outcome; whether this is more efficient will depend on the model and the required Monte Carlo precision. Sampling-based estimators could likewise improve the tractability of KL divergence and HPD overlap in moderate dimensions, although the number of samples required for accurate estimates will still grow with dimension. Another approach for dealing with this issue may be to compute these consistency metrics in lower-dimensional subspaces of the state space. Identifying subspaces that retain the statistical power of the original space is a topic for future exploration.

Another potential challenge relates to choosing time scales for assessing lack of fit. These

methods allow us to focus on time scales as short as individual spikes, and in our place-cell decoding examples, individual spikes are sufficiently informative that we are often able to detect local model misfit at this time scale. In other neural systems, local model errors may be easier to detect over longer time scales. In this paper, we note that these goodness-of-fit measures can be extended to longer time intervals, but determining which time scales are most appropriate may require relying on prior knowledge about the system, or exploring the values of these metrics across multiple time scales.

We believe that these local goodness-of-fit tools provide an important step toward making inferences from state-space neural models more reliable and interpretable. By pinpointing specific moments when the model assumptions break down, researchers can be more confident in their inferences. Ultimately, these measures empower us to refine our models of neural dynamics and deepen our understanding of how the brain encodes and processes information.

Ethical statement

The recording analyzed here was collected for a previous study [18]. All animal procedures were approved by the Institutional Animal Care and Use Committee at the University of California, San Francisco (protocol AN174991).

Acknowledgements

This work was supported by the National Institutes of Health (RF1MH130623 to U.T.E. and L.M.F. and R01MH136875 to L.M.F.), the Simons Collaboration on the Global Brain (542971 to U.T.E. and 521921 and 542981 to L.M.F.), and the Howard Hughes Medical Institute (L.M.F.). A.E.C. was supported by the National Science Foundation Graduate Research Fellowship Program (1650113), the National Institutes of Health (F31MH124366), and the UCSF Jonas Cohler Discovery Fellowship.

The authors used Claude (Anthropic; Claude Opus 4.8, 5.0, and 5.5) to assist with writing and reviewing the simulation, analysis, and figure-generation code and with editing the manuscript text.

The authors reviewed and revised all AI-assisted material and take full responsibility for the content of this article.

The authors declare that they have no competing interests.

Data availability statement

The hippocampal recording analyzed here was originally reported by Comrie et al. [18] and is available on the Distributed Archives for Neurophysiology Data Integration (DANDI) Archive as dandiset 001942 (https://dandiarchive.org/dandiset/001942). The decoder inputs for the recording epoch analyzed in Fig. 4—the animal's position, the spike times of the sorted hippocampal units, and the track geometry—are archived on Zenodo (doi:10.5281/zenodo.23020757).

Code availability

The local goodness-of-fit diagnostics are implemented in the `statespacecheck` Python package, available at https://github.com/edeno/statespacecheck and installable from the Python Package Index (`pip install statespacecheck`); the analyses in this paper used version `0.3.1`, archived on Zenodo (doi:10.5281/zenodo.23011969). All simulation, analysis, and figure-generation code, together with the interactive viewer and the source of the project website (https://edeno.github.io/statespacecheck-paper/), is publicly available at https://github.com/edeno/statespacecheck-paper and archived on Zenodo (doi:10.5281/zenodo.23019296).

Author contributions

Conceptualization: UTE, SZ.

Methodology: UTE, SZ.

Software: SZ, ELD.

Formal analysis: SZ, ELD.

Investigation: SZ, UTE, ELD.

Data curation: AEC.

Writing – original draft: SZ, UTE, ELD.

Writing – review & editing: SZ, AEC, LMF, UTE, ELD.

Visualization: SZ, ELD.

Supervision: UTE.

Funding acquisition: UTE, LMF.

References

[1] Jones L M, Fontanini A, Sadacca B F, Miller P and Katz D B 2007 *Proc. Natl. Acad. Sci. U.S.A.* **104** 18772–18777 ISSN 0027-8424, 1091-6490

[2] Denovellis E L, Gillespie A K, Coulter M E, Sosa M, Chung J E, Eden U T and Frank L M 2021 *eLife* **10** e64505 ISSN 2050-084X

[3] Vinograd A, Nair A, Kim J H, Linderman S W and Anderson D J 2024 *Nature* **634** 910–918 ISSN 0028-0836, 1476-4687

[4] Newman K B, Buckland S T, Morgan B J T, King R, Borchers D L, Cole D J, Besbeas P, Gimenez O and Thomas L 2014 *Modelling Population Dynamics: Model Formulation, Fitting and Assessment Using State-Space Methods* Methods in Statistical Ecology (New York, NY: Springer New York) ISBN 978-1-4939-0976-6 978-1-4939-0977-3

[5] Deng X, Liu D F, Kay K, Frank L M and Eden U T 2015 *Neural Computation* **27** 1438–1460 ISSN 0899-7667, 1530-888X

[6] Tao L, Weber K E, Arai K and Eden U T 2018 *J Comput Neurosci* **45** 147–162 ISSN 0929-5313, 1573-6873

[7] Zeng S and Eden U T 2026 *IEEE Trans. Biomed. Eng.* **73** 153–167 ISSN 0018-9294, 1558-2531

[8] Eden U T, Frank L M and Tao L 2018 Characterizing complex, multi-scale neural phenomena using state-space models *Dynamic Neuroscience: Statistics, Modeling, and Control* ed Chen Z and Sarma S V (Cham: Springer International Publishing) pp 29–52

[9] Stone M 1974 *Journal of the Royal Statistical Society Series B: Statistical Methodology* **36** 111–133 ISSN 1369-7412, 1467-9868

[10] Hastie T, Tibshirani R and Friedman J H 2009 *The Elements of Statistical Learning: Data Mining, Inference, and Prediction* 2nd ed Springer Series in Statistics (New York, NY: Springer) ISBN 978-0-387-84858-7

[11] Shen X and Zhuang J 2024 *IEEE Trans. Emerg. Top. Comput. Intell.* **8** 1728–1743 ISSN 2471-285X

[12] Bayarri M J and Castellanos M E 2007 *Statist. Sci.* **22** 322–343 ISSN 0883-4237

[13] Moran G E, Blei D M and Ranganath R 2024 *Journal of the Royal Statistical Society Series B: Statistical Methodology* **86** 194–214 ISSN 1369-7412, 1467-9868

[14] Guttman I 1967 *Journal of the Royal Statistical Society: Series B (Methodological)* **29** 83–100 ISSN 0035-9246

[15] Meng X L 1994 *The annals of statistics* **22** 1142–1160 ISSN 0090-5364

[16] Gelman A, Meng X L and Stern H 1996 *Statistica Sinica* **6** 733–760 ISSN 1017-0405

[17] Kullback S and Leibler R A 1951 *The annals of mathematical statistics* **22** 79–86 ISSN 0003-4851

[18] Comrie A E, Monroe E J, Kahn A E, Denovellis E L, Joshi A, Guidera J A, Krausz T A, Berke J D, Daw N D and Frank L M 2026 *Neuron* ISSN 08966273 doi:10.1016/j.neuron.2026.08.023

[19] Chung J E, Magland J F, Barnett A H, Tolosa V M, Tooker A C, Lee K Y, Shah K G, Felix S H, Frank L M and Greengard L F 2017 *Neuron* **95** 1381–1394.e6 ISSN 08966273

[20] Karlsson M P and Frank L M 2009 *Nature Neuroscience* **12** 913–918 ISSN 1097-6256, 1546-1726

[21] Pearson K 1900 *The London, Edinburgh, and Dublin Philosophical Magazine and Journal of Science* **50** 157–175