

Sumário

1	Tabelas	2		
2	Codigos	3		
2.1	Exemplos	3	23	verifica se um grafo é bipartido 10
2.2	Teoria dos números	8	24	faz a ordenação topológica de um grafo acíclico 10
2.3	Grafos	8	25	calcula fluxo máximo 11
2.4	Geometria	11	26	ponto e poligono 11
2.5	Outros	12	27	Decide se q está sobre o segmento fechado pr. 12
			28	Decide se os segmentos fechados pq e rs têm pontos em comum. 12
			29	Calcula a distância do ponto r ao segmento pq. 12
			30	Classifica o ponto p em relação ao polígono T. Retorna 0, -1 ou 1 dependendo se p está no exterior, na fronteira ou no interior de T, respectivamente. 12
			31	josephus problem 12

Lista de Tabelas

1	Limites de representação de dados	2
2	Fatorial	2
3	scanf() - %[*][width][modifiers]type	2
4	scanf() %[*][width][modifiers]type	2
5	stdlib	2
6	math (angulos em radianos)	3

Lista de Listagens

1	Modelo	3
2	comparcao de ponto flutuante	3
3	.vimrc para a configuração do vim	4
4	printf	4
5	exemplo de map	4
6	exemplo de set e multiset	4
7	exemplo de list	5
8	exemplo de queue	5
9	exemplo de priority queue	5
10	exemplo de stack	5
11	exemplo de vector	6
12	exemplo de string	6
13	exemplo de ordenação	7
14	pesquisa binária	7
15	Arredondamento e output em outras bases	7
16	máximo divisor comum e mínimo multiplo comum	8
17	decide se um número é primo	8
18	Retorna a fatoração em números primos de abs(n).	8
19	Verifica se o grafo é aciclico.	8
20	Caminho minimo 1 para todos pesos positivos.	8
21	Floresta dijunta de arvores	9
22	Arvore geradora mínima kruskal	9

1 Tabelas

tipo	bits	min...max	precisao
char	8	0..127	2
signed char	8	-128..127	2
unsigned char	8	0..255	2
short	16	-32.768 .. 32.767	4
unsigned short	16	0 .. 65.535	4
int	32	-2x10**9 .. 2 x 10**9	9
unsigned int	32	0 .. 4x10**9	9
int64_t	64	-9 x 10**18 .. 9 x 10**18	18
uint64_t	64	0 .. 18 x 10**18	19

Tabela 1: Limites de representação de dados

0! = 1
1! = 1
2! = 2
3! = 6
4! = 24
5! = 120
6! = 720
7! = 5.040
8! = 40.320
9! = 362.880
10! = 3.628.800
11! = 39.916.800
12! = 479.001.600 [limite do (unsigned) int]
13! = 6.227.020.800
14! = 87.178.291.200
15! = 1.307.674.368.000
16! = 20.922.789.888.000
17! = 355.687.428.096.000
18! = 6.402.373.705.728.000
19! = 121.645.100.408.832.000
20! = 2.432.902.008.176.640.000 [limite do (u)int64.t]

Tabela 2: Fatorial

Tipo	%
char	c
int	d
float	e, E, f, g, G
int (octal)	o
int (hexa)	x, X
uint	u
char*	s

Tabela 3: scanf() - %[*][width][modifiers]type

modifiers	tipo
h	short int (d, i, n), or unsigned short int (o, u, x)
l	long int (d, i, n), or unsigned long int (o, u, x), or double (e, f, g)
L	long double (e, f, g)

Tabela 4: scanf() %[*][width][modifiers]type

função	descrição
atof	Convert string to double
atoi	Convert string to integer
atol	Convert string to long integer
strtod	Convert string to double
strtol	Convert string to long integer
strtoul	Convert string to unsigned long integer

Tabela 5: stdlib

função	descrição
cos	Compute cosine
sin	Compute sine
tan	Compute tangent
acos	Compute arc cosine
asin	Compute arc sine
atan	Compute arc tangent
atan2	Compute arc tangent with two parameters
cosh	Compute hyperbolic cosine
sinh	Compute hyperbolic sine
tanh	Compute hyperbolic tangent
exp	Compute exponential function
frexp	Get significand and exponent
ldexp	Generate number from significand and exponent
log	Compute natural logarithm
log10	Compute common logarithm
modf	Break into fractional and integral parts
pow	Raise to power
sqrt	Compute square root
ceil	Round up value
fabs	Compute absolute value
floor	Round down value
fmod	Compute remainder of division

Tabela 6: math (ângulos em radianos)

2 Codigos

2.1 Exemplos

```

1 #include <stdio.h>
2 #include <stdlib.h>
3 #include <string.h>
4 #include <math.h>
5
6 #include <inttypes.h>
7 #include <ctype.h>
8
9 #include <algorithm>
10 #include <utility>
11 #include <iostream>
12
13 #include <map>
14 #include <set>
15 #include <vector>
16 #include <sstream>
17
18 using namespace std;
19
20 #define abs(a) ((a) > 0 ? (a) : -(a))
21
22 int main()
23 {
24     int n;
25
26     cin >> n;
27
28     for (int i = 0; i < n; i++)
29     {
30
31     }
32
33     while (cin >> n)
34     {
35
36     }
37     return 0;
38 }

```

Código 1: Modelo

```

1 const double EPS = 1e-10;
2 /**
3  * -1 se x < y
4  * 0 se x = y
5  * 1 se x > y
6  */
7 inline int cmp (double x, double y = 0, double tol = EPS)
8 {
9     return (x <= y + tol) ? (x + tol < y) ? -1 : 0 : 1;
10 }
3

```

Código 2: comparcao de ponto flutuante

```

1 set ai noet ts=4 sw=4 bs=2
2 syn on
3 mat Keyword "<foreach>"

```

Código 3: .vimrc para a configuração do vim

```

1 /* printf example */
2 #include <stdio.h>
3
4 int main()
5 {
6     printf ("Characters: %c %c \n", 'a', 65);
7     printf ("Decimals: %d %ld\n", 1977, 650000L);
8     printf ("Preceding with blanks: %10d \n", 1977);
9     printf ("Preceding with zeros: %010d \n", 1977);
10    printf ("Some different radixes: %d %x %o %#x %#o \n", 100, 100, 100,
        100, 100);
11    printf ("floats: %4.2f %+.0e %E %4.2f\n", 3.1416, 3.1416, 3.1416, 3.1);
12    printf ("Width trick: %*d \n", 5, 10);
13    printf ("%s \n", "A string");
14    return 0;
15 }
16 /* %[flags (-, +, etc)][width][.precision][length (h,l,L)]specifier
17 Characters: a A
18 Decimals: 1977 650000
19 Preceding with blanks:          1977
20 Preceding with zeros: 0000001977
21 Some different radixes: 100 64 144 0x64 0144
22 floats: 3.14 +3e+000 3.141600E+000 3.10
23 Width trick:    10
24 A string
25 */

```

Código 4: printf

```

1 #include <iostream>
2 #include <map>
3 using namespace std;
4
5 int main ()
6 {
7     map<char,int> mymap;
8     map<char,int>::iterator it;
9     pair<map<char,int>::iterator,bool> ret;
10
11     // first insert function version (single parameter):
12     mymap.insert ( pair<char,int>('a',100) );
13     mymap.insert ( pair<char,int>('z',200) );
14
15     ret=mymap.insert (pair<char,int>('z',500) );
16     if (ret.second==false)

```

```

{
    cout << "element 'z' already existed";
    cout << " with a value of " << ret.first->second << endl;
}

// third insert function version (range insertion):
map<char,int> anothermap;
anothermap.insert(mymap.begin(),mymap.find('c'));

// showing contents:
cout << "mymap contains:\n";
for ( it=mymap.begin(); it != mymap.end(); it++ )
    cout << (*it).first << " => " << (*it).second << endl;

map<char,string> mymap;
mymap['a']="an element";
if (mymap.count('a') > 0)
    cout << mymap['a'] << " is an element of mymap.\n";

while (!mymap.empty())
{
    cout << mymap.begin()->first << " => ";
    cout << mymap.begin()->second << endl;
    map<char,int>::iterator erasedelement = mymap.erase(mymap.begin());
}

return 0;
}

```

Código 5: exemplo de map

```

1 #include <iostream>
2 #include <set>
3 using namespace std;
4
5 int main ()
6 {
7     multiset<int> mymultiset;
8     multiset<int>::iterator it;
9
10    // set some initial values:
11    for (int i=1; i<=5; i++) mymultiset.insert(i*10);    // 10 20 30 40 50
12
13    cout << "size: " << (int) mymultiset.size() << endl;
14    cout << "count: " << (int) mymultiset.count(10) << endl;
15
16    it=mymultiset.find(20);
17    mymultiset.erase (it);
18
19    if (! mymultiset.empty)
20        mymultiset.erase (mymultiset.find(40));
21
22    for (it=mymultiset.begin(); it!=mymultiset.end(); it++)
23        cout << " " << *it;
24
25    int myints[]={19,72,4,36,20,20};

```

```
26     multiset<int> first (myints,myints+3);    // 4,19,72
27     multiset<int> second (myints+3,myints+6); // 20,20,36
28
29     first.swap(second); // troca conteudo. o primeiro fica [20,20,36] e o
        segundo [4,19,72]
30
31     return 0;
32 }
```

Código 6: exemplo de set e multiset

```
1 #include <iostream>
2 #include <list>
3 using namespace std;
4
5 int main ()
6 {
7     list<int> mylist (2,100);           // two ints with a value of 100
8     mylist.push_front (200);
9     mylist.push_back (300);
10
11     it = mylist.begin();
12     mylist.insert (it,10);
13     mylist.insert (it,2,20); // two ints with a value of 20
14
15     mylist.reverse(); // Reverses the order of the elements in the list.
16
17     cout << "mylist contains:";
18     for (list<int>::iterator it=mylist.begin(); it!=mylist.end(); ++it)
19         cout << " " << *it;
20
21     cout << "Popping out the elements in mylist:";
22     while (!mylist.empty())
23     {
24         cout << " " << mylist.front();
25         mylist.pop_front();
26     }
27
28     while (!mylist.empty())
29     {
30         cout << " " << mylist.back();
31         mylist.pop_back();
32     }
33
34     cout << mylist.size() << endl;
35
36     return 0;
37 }
```

Código 7: exemplo de list

```
1 #include <iostream>
2 #include <queue>
3 using namespace std;
4
5 int main ()
```

```
6 {
7     queue<int> myqueue;
8     int sum (0);
9
10    for (int i=1;i<=10;i++) myqueue.push(i);
11
12    myqueue.back() -= myqueue.front();
13
14    cout << "size: " << (int) myqueue.size() << endl;
15
16    while (!myqueue.empty())
17    {
18        sum += myqueue.front();
19        myqueue.pop();
20    }
21
22    cout << "total: " << sum << endl;
23
24    return 0;
25 }
```

Código 8: exemplo de queue

```
1 #include <iostream>
2 #include <queue>
3 using namespace std;
4
5 int main ()
6 {
7     priority_queue<int> mypq;
8
9     mypq.push(30);
10    mypq.push(100);
11    mypq.push(25);
12    mypq.push(40);
13
14    cout << "size: " << (int) mypq.size() << endl;
15
16    cout << "Popping out elements...";
17    while (!mypq.empty())
18    {
19        cout << " " << mypq.top();
20        mypq.pop();
21    }
22    cout << endl;
23
24    return 0;
25 }
```

Código 9: exemplo de priority queue

```
1 #include <iostream>
2 #include <stack>
3 using namespace std;
4
5 int main ()
```

```

6 {
7     stack<int> mystack;
8     int sum = 0;
9
10    mystack.push(10);
11    mystack.push(20);
12
13    mystack.top() -= 5;
14
15    while (!mystack.empty())
16    {
17        sum += mystack.top();
18        mystack.pop();
19    }
20
21    cout << "size: " << (int) mystack.size() << endl;
22
23    return 0;
24 }

```

Código 10: exemplo de stack

```

1 #include <iostream>
2 #include <vector>
3 using namespace std;
4
5 int main ()
6 {
7     vector<int> myvector (3,100);
8     vector<int>::iterator it;
9
10    myvector.reserve(100);
11
12    for (i=0; i<myvector.size(); i++)
13        myvector.at(i)=i; // = myvector[i] = i
14
15    it = myvector.begin();
16    it = myvector.insert ( it , 200 );
17    myvector.insert ( it ,2,300);
18
19    vector<int> anothervector (2,400);
20    int myarray [] = { 501,502,503 };
21    myvector.insert ( it+2,anothervector.begin(),anothervector.end());
22    myvector.insert ( myvector.begin(), myarray, myarray+3);
23
24    cout << "myvector contains:";
25    for (it=myvector.begin(); it<myvector.end(); it++)
26        cout << " " << *it;
27    cout << endl;
28
29    // erase the 6th element
30    myvector.erase (myvector.begin()+5);
31    int sum;
32    while (!myvector.empty())
33    {
34        sum += myvector.back();

```

```

35        myvector.pop_back();
36    }
37
38    return 0;
39 }

```

Código 11: exemplo de vector

```

1 #include <iostream>
2 #include <string>
3 using namespace std;
4
5 int main ()
6 {
7     string str ("There are two needles in this haystack with needles.");
8     string str2 ("needle");
9     size_t found;
10
11    // different member versions of find in the same order as above:
12    found=str.find(str2);
13    if (found!=string::npos)
14        cout << "first 'needle' found at: " << int(found) << endl;
15
16    found=str.find("needles are small",found+1,6);
17    if (found!=string::npos)
18        cout << "second 'needle' found at: " << int(found) << endl;
19
20    found=str.find("haystack");
21    if (found!=string::npos)
22        cout << "'haystack' also found at: " << int(found) << endl;
23
24    found=str.find('.');
25    if (found!=string::npos)
26        cout << "Period found at: " << int(found) << endl;
27
28    // let's replace the first needle:
29    str.replace(str.find(str2),str2.length(),"preposition");
30    cout << str << endl;
31
32    string str="We think in generalities, but we live in details.";
33    // quoting Alfred N. Whitehead
34    string str2, str3;
35    size_t pos;
36
37    str2 = str.substr (12,12); // "generalities"
38
39    pos = str.find("live"); // position of "live" in str
40    str3 = str.substr (pos); // get from "live" to the end
41
42    cout << str2 << ' ' << str3 << endl;
43
44
45    return 0;
46 }
47 /*
48 first 'needle' found at: 14

```

```

49 second 'needle' found at: 44
50 'haystack' also found at: 30
51 Period found at: 51
52 There are two prepositions in this haystack with needles.
53 generalities live in details.
54 */

```

Código 12: exemplo de string

```

1 #include <iostream>
2 #include <algorithm>
3 #include <vector>
4 using namespace std;
5
6 bool myfunction (int i,int j) { return (i<j); }
7
8 struct myclass {
9     bool operator() (int i,int j) { return (i<j);}
10 } myobject;
11
12 int compare (const void * a, const void * b)
13 {
14     return ( *(int*)a - *(int*)b );
15 }
16
17
18 int main () {
19     int myints[] = {32,71,12,45,26,80,53,33};
20     vector<int> myvector (myints, myints+8);           // 32 71 12 45 26
21                                                         80 53 33
22     // using default comparison (operator <):
23     sort (myvector.begin(), myvector.end()+4);         //(12 32 45 71)26
24                                                         80 53 33
25     // using function as comp
26     sort (myvector.begin()+4, myvector.end(), myfunction); // 12 32 45 71(26
27                                                         33 53 80)
28     // using object as comp
29     sort (myvector.begin(), myvector.end(), myobject);   //(12 26 32 33 45
30                                                         53 71 80)
31
32     // if stable is need
33     stable_sort (myvector.begin(), myvector.end(), myfunction);
34
35     // Rearranges the elements in the range [first,last), in such a way that
36     // the subrange [first,middle)
37     // contains the smallest elements of the entire range sorted in ascending
38     // order, and the subrange
39     // [middle,end) contains the remaining elements without any specific order
40     partial_sort (myvector.begin(), myvector.begin()+3, myvector.end());
41
42     qsort (myints, 8, sizeof(int), compare);
43
44     return 0;
45 }

```

Código 13: exemplo de ordenação

```

1 int compareMyType (const void * a, const void * b)
2 {
3     if ( *(MyType*)a > *(MyType*)b ) return 1;
4     if ( *(MyType*)a == *(MyType*)b ) return 0;
5     if ( *(MyType*)a < *(MyType*)b ) return -1;
6 }
7
8 int key = 40;
9 item = (int*) bsearch (&key, values, n, sizeof (int), compareMyType);

```

Código 14: pesquisa binária

```

1 #include <iostream>
2 #include <iomanip> // setprecision()
3 using namespace std;
4
5 int main () {
6     double a = 3.1415926534;
7     double b = 2006.0;
8     double c = 1.0e-10;
9
10    // setprecision(1) => 1 casa decimal apos a virgula
11    cout << fixed << setprecision(1) << 9.09090901 << endl;
12    cout << fixed << setprecision(2) << 9.09090901 << endl;
13    cout << fixed << setprecision(3) << 9.09090901 << endl;
14    cout << fixed << setprecision(2) << 9.1 << endl;
15
16    // anula o efeito de setprecision
17    cout.unsetf(ios::floatfield);
18
19    // 5 digitos no maximo
20    cout.precision(5);
21
22    cout << a << '\t' << b << '\t' << c << endl;
23    cout << fixed << a << '\t' << b << '\t' << c << endl;
24    cout << scientific << a << '\t' << b << '\t' << c << endl;
25
26    // Sets the basefield format flag for the str stream to dec, hex or oct.
27    int n =70;
28    cout << dec << n << endl;
29    cout << hex << n << endl;
30    cout << oct << n << endl;
31
32    return 0;
33 }
34 /* output
35 9.1
36 9.09
37 9.091
38 9.10
39 3.1416 2006 1e-10
40 3.14159 2006.00000 0.00000
7

```

```
41 3.14159e+00      2.00600e+03      1.00000e-10
42 70
43 46
44 106
45 */
```

Código 15: Arredondamento e output em outras bases

2.2 Teoria dos números

```
1 int gcd(int x, int y)
2 {
3     return y ? gcd(y, x % y) : abs(x);
4 }
5 uint64_t lcm(int x, int y)
6 {
7     if (x && y) return abs(x) / gcd(x, y) * uint64_t(abs(y));
8     else return uint64_t(abs(x | y));
9 }
```

Código 16: máximo divisor comum e mínimo múltiplo comum

```
1 bool isPrime(int n)
2 {
3     if (n < 0) return isPrime(-n);
4     if (n == 1) return true;
5     if (n < 5 || n % 2 == 0 || n % 3 == 0) return (n == 2 || n == 3);
6
7     int maxP = sqrt(n) + 2;
8     for (int p = 5; p < maxP; p += 6)
9     {
10         if (n % p == 0 || n % (p+2) == 0) return false;
11     }
12     return true;
13 }
```

Código 17: decide se um número é primo

```
1 typedef map<int, int> prime_map;
2 void squeeze(prime_map& M, int& n, int p)
3 {
4     for (; n % p == 0; n /= p) M[p]++;
5 }
6 void factor(int n, prime_map& M)
7 {
8     if (n < 0) return n = -n;
9     if (n < 2) return;
10
11     squeeze(M, n, 2);
12     squeeze(M, n, 3);
13
14     int maxP = sqrt(n) + 2;
15     for (int p = 5; p < maxP; p += 6)
```

```
16 {
17     squeeze(M, n, p);
18     squeeze(M, n, p+2);
19 }
20 if (n > 1) M[n]++;
21 }
```

Código 18: Retorna a fatora  o em n  meros primos de abs(n).

2.3 Grafos

```
1 #define TAM 100
2 #define BRANCO 0
3 #define CINZA 1
4 #define PRETO 2
5 bool grafo[TAM][TAM];
6 int pass[TAM];
7
8 bool dfs(int v)
9 {
10     pass[v] = CINZA;
11
12     for (int i = 0; i < TAM; i++)
13     {
14         if (grafo[v][i])
15         {
16             if (pass[i] == CINZA) return false;
17             if (pass[i] == BRANCO && !dfs(i)) return false;
18         }
19     }
20
21     pass[v] = PRETO;
22     return true;
23 }
24
25 bool aciclico()
26 {
27     memset(pass, BRANCO, TAM*sizeof(int));
28
29     for (int i = 0; i < TAM; i++)
30     {
31         if (pass[i] == BRANCO)
32         {
33             if (!dfs(i)) return false;
34         }
35     }
36
37     return true;
38 }
```

C  digo 19: Verifica se o grafo    aciclico.

```
1 #include <queue>
2
3 8
```



```

3  typedef vector<map<int, int> > AdjList;
4  typedef AdjList Grafo;
5
6  int dist[MAX_VERTICES];
7  int prev[MAX_VERTICES]; // para recuperar o caminho usando um disjoint forest
8
9  void dijkstra(Grafo& grafo, int source)
10 {
11     for (int i = 0; i < grafo.size(); i++)
12     {
13         dist[i] = INF;
14         prev[i] = -1;
15     }
16
17     dist[source] = 0;
18     priority_queue<pair<int, int> > heap;
19     heap.push(make_pair(0, source));
20
21     while (!heap.empty())
22     {
23         int u = heap.top().second;
24         heap.pop();
25
26         // para cada vizinho de u
27         for (map<int, int>::iterator i = grafo[u].begin(); i != grafo[u].end(); i++)
28         {
29             int totalDist = dist[u] + (*i).second;
30             if (totalDist <= dist[(*i).first])
31             {
32                 dist[(*i).first] = totalDist;
33                 heap.push(make_pair(totalDist, (*i).first));
34                 prev[(*i).first] = u;
35             }
36         }
37     }
38 }

```

Código 20: Caminho minimo 1 para todos pesos positivos.

```

1  #define SIZE 100
2
3  struct dsf
4  {
5      int element_count;
6      int parent[SIZE];
7      int rank[SIZE];
8  };
9  typedef struct dsf * disjoint_set_forest_p;
10
11 void dsf_init(disjoint_set_forest_p forest, int element_count)
12 {
13     forest->element_count = element_count;
14     memset(forest->parent, 0, element_count*sizeof(int));
15     memset(forest->rank, 0, element_count*sizeof(int));

```

```

16
17     for (int i = 0; i < element_count; ++i)
18         forest->parent[i] = i;
19 }
20
21 int dsf_find_set(disjoint_set_forest_p forest, int i)
22 {
23     if (i != forest->parent[i])
24     {
25         forest->parent[i] = dsf_find_set(forest, forest->parent[i]);
26     }
27     return forest->parent[i];
28 }
29
30 void dsf_union(disjoint_set_forest_p forest, int i, int j)
31 {
32     int x = dsf_find_set(forest, i);
33     int y = dsf_find_set(forest, j);
34
35     if (forest->rank[x] > forest->rank[y])
36     {
37         forest->parent[y] = x;
38     }
39     else
40     {
41         forest->parent[x] = y;
42         if (forest->rank[x] == forest->rank[y])
43         {
44             forest->rank[y]++;
45         }
46     }
47 }

```

Código 21: Floresta disjunta de arvores

```

1  typedef vector<map<int, int> > AdjList;
2  struct Grafo
3  {
4      int edgeCnt;
5      AdjList adj;
6  };
7
8  struct edge
9  {
10     int u;
11     int v;
12     int weight;
13 };
14
15 int edge_compare(const void * e1, const void * e2)
16 {
17     struct edge * p1 = (struct edge *) e1;
18     struct edge * p2 = (struct edge *) e2;
19     int f = p1->weight - p2->weight;
20     if (f < 0)
21     {

```

```

22     return -1;
23 }
24 else if (f == 0)
25 {
26     return edge_compare1(e1, e2);
27 }
28 else
29 {
30     return 1;
31 }
32 }
33
34 struct edge * get_edge_list(Grafo& graph)
35 {
36     int edge_count = graph.edgeCnt;
37     struct edge *edges = (struct edge*) malloc(edge_count * sizeof(struct
        edge));
38
39     int current_edge = 0;
40
41     for (int i = 0; i < graph.adj.size(); ++i)
42     {
43         for (map<int, int>::iterator j = graph.adj[i].begin(); j != graph.
            adj[i].end(); j++)
44         {
45             struct edge e;
46             e.u = i < (*j).first ? i : (*j).first;
47             e.v = i > (*j).first ? i : (*j).first;
48             e.weight = (*j).second;
49             edges[current_edge++] = e;
50         }
51     }
52
53     return edges;
54 }
55
56 void kruskal(Grafo& graph, Grafo& mst)
57 {
58     // Obtain a list of edges and sort it by weight in  $O(E \lg E)$  time
59     int edge_count = graph.edgeCnt;
60     struct edge *edges = get_edge_list(graph);
61     qsort(edges, edge_count, sizeof(struct edge), edge_compare);
62
63     disjoint_set_forest dsf;
64     dsf_init(&dsf, edge_count);
65
66     for (int i = 0; i < edge_count; ++i)
67     {
68         struct edge e = edges[i];
69         int uset = dsf.find_set(dsf, e.u);
70         int vset = dsf.find_set(dsf, e.v);
71         if (uset != vset)
72         {
73             mst.adj[e.u][e.v] = e.weight;
74             mst.edgeCnt++;
75             dsf_union(dsf, uset, vset);

```

```

76     }
77 }
78
79 free(edges);
80 }

```

Código 22: Arvore geradora mínima kruskal

```

1 #define TAM 200
2
3 bool grafo[TAM][TAM];
4 int pass[TAM];
5 int n;
6
7 bool bipartido(int v, int color = 1)
8 {
9     pass[v] = color;
10    int thisColor = color;
11    bool ret = true;
12
13    color = color == 1 ? 2 : 1;
14
15    for (int i = 0; i < n; i++)
16    {
17        if (grafo[v][i])
18        {
19            if (!pass[i]) ret = dfs(i, color);
20            else if (pass[i] == thisColor) return false;
21
22            if (!ret) return false;
23        }
24    }
25
26    return ret;
27 }

```

Código 23: verifica se um grafo é bipartido

```

1 #define UNVISITED -1
2
3 int grafo[SIZE][SIZE];
4 int prof[SIZE];
5 int sorted[SIZE];
6 int nordem;
7
8 void dfsTopsort(int no)
9 {
10    for (int viz = 0; viz < SIZE; viz++)
11    {
12        if (grafo[no][viz])
13        {
14            if (prof[viz] == UNVISITED)
15            {
16                prof[viz] = prof[no] + 1;
17                dfsTopsort(viz);
18            }

```

```

19     }
20 }
21
22     sorted[nordem--] = no;
23 }
24
25 void topSort(int nvt)
26 {
27     memset(prof, UNVISITED, nvt*sizeof(int));
28     nordem = nvt - 1;
29
30     for (int i = 0; i < nvt; i++)
31     {
32         if (prof[i] == UNVISITED)
33         {
34             prof[i] = 0;
35             dfsTopsort(i);
36         }
37     }
38 }

```

Código 24: faz a ordenação topológica de um grafo acíclico

```

1 #define TAM 1000
2
3 int grafo[TAM][TAM];
4 int pred[TAM];
5 int f[TAM][TAM];
6 bool visitados[TAM];
7
8 bool dfs(int s, int t, int size)
9 {
10     visitados[s] = true;
11     if(s == t) return true;
12
13     for(int v = 0; v < size; v++)
14     {
15         if(grafo[s][v] - f[s][v] > 0 && !visitados[v])
16         {
17             pred[v] = s;
18             if(dfs(v, t, size)) return true;
19         }
20     }
21
22     return false;
23 }
24
25 bool findPath(int s, int t, int size)
26 {
27     memset(visitados, false, sizeof(bool)*size);
28     return dfs(s, t, size);
29 }
30
31 int maxFlow(int size, int s, int t)
32 {
33     int delta;

```

```

34
35     for(int i = 0; i < size; i++)
36     {
37         memset(f[i], 0, sizeof(int)*size);
38     }
39
40     pred[s] = s;
41
42     while(findPath(s, t, size))
43     {
44         delta = INT_MAX;
45         for(int c = t; pred[c] != c; c = pred[c])
46         {
47             delta = min(delta, grafo[pred[c]][c] - f[pred[c]][c]);
48         }
49
50         for(int c = t; pred[c] != c; c = pred[c])
51         {
52             f[pred[c]][c] += delta;
53             f[c][pred[c]] -= delta;
54         }
55     }
56
57     int soma = 0;
58
59     for(int i = 0; i < size; i++)
60     {
61         soma += f[i][t];
62     }
63
64     return soma;
65 }

```

Código 25: calcula fluxo máximo

2.4 Geometria

```

1 struct point
2 {
3     double x, y;
4     point(double x = 0, double y = 0): x(x), y(y) {}
5
6     point operator +(point q) { return point(x + q.x, y + q.y); }
7     point operator -(point q) { return point(x - q.x, y - q.y); }
8     point operator *(double t) { return point(x * t, y * t); }
9     point operator /(double t) { return point(x / t, y / t); }
10    double operator *(point q) { return x * q.x + y * q.y; }
11    double operator %(point q) { return x * q.y - y * q.x; }
12
13    int cmp(point q) const
14    {
15        if (int t = ::cmp(x, q.x)) return t;
16        return ::cmp(y, q.y);
17    }

```

```

18     bool operator==(point q) const { return cmp(q) == 0; }
19     bool operator!=(point q) const { return cmp(q) != 0; }
20     bool operator<(point q) const { return cmp(q) < 0; }
21
22     friend ostream& operator<<(ostream& o, point p) {
23         return o<< "(" << p.x << ", " << p.y << ")";
24     }
25     static point pivot;
26 };
27
28 double abs(point p) { return hypot(p.x, p.y); }
29 double arg(point p) { return atan2(p.y, p.x); }
30
31 point point::pivot;
32
33 typedef vector<point> polygon;
34
35 int ccw(point p, point q, point r)
36 {
37     return cmp((p - r) % (q - r));
38 }
39
40 double angle(point p, point q, point r)
41 {
42     point u = p - q, v = r - q;
43     return atan2(u % v, u * v);
44 }
45

```

Código 26: ponto e poligono

```

1 bool between(point p, point q, point r)
2 {
3     return ccw(p, q, r) == 0 && cmp((p - q) * (r - q)) <= 0;
4 }

```

Código 27: Decide se q está sobre o segmento fechado pr.

```

1 bool seg_intersect(point p, point q, point r, point s)
2 {
3     point A = q - p;
4     point B = s - r;
5     point C = r - p;
6     point D = s - q;
7
8     int a = cmp(A % C) + 2 * cmp(A % D);
9     int b = cmp(B % C) + 2 * cmp(B % D);
10
11     if (a == 3 || a == -3 || b == 3 || b == -3) return false;
12     if (a || b || p == r || p == s || q == r || q == s) return true;
13
14     int t = (p < r) + (p < s) + (q < r) + (q < s);
15     return t != 0 && t != 4;
16 }

```

Código 28: Decide se os segmentos fechados pq e rs têm pontos em comum.

```

1 double seg_distance(point p, point q, point r)
2 {
3     point A = r - q;
4     point B = r - p;
5     point C = q - p;
6
7     double a = A * A, b = B * B, c = C * C;
8
9     if (cmp(b, a + c) >= 0) return sqrt(a);
10    else if (cmp(a, b + c) >= 0) return sqrt(b);
11    else return fabs(A % B) / sqrt(c);
12 }

```

Código 29: Calcula a distância do ponto r ao segmento pq.

```

1 int in_poly(point p, polygon& T)
2 {
3     double a = 0;
4     int N = T.size();
5     for (int i = 0; i < N; i++)
6     {
7         if (between(T[i], p, T[(i+1) % N])) return -1;
8         a += angle(T[i], p, T[(i+1) % N]);
9     }
10    return cmp(a) != 0;
11 }

```

Código 30: Classifica o ponto p em relação ao polígono T. Retorna 0, -1 ou 1 dependendo se p está no exterior, na fronteira ou no interior de T, respectivamente.

2.5 Outros

```

1 /**
2  The Josephus problem (or Josephus permutation) is a theoretical problem
   related to a certain counting-out game. There are people standing in a
   circle waiting to be executed. After the first man is executed, certain
   number of people are skipped and one man is executed. Then again, people
   are skipped and a man is executed. The elimination proceeds around the
   circle (which is becoming smaller and smaller as the executed people are
   removed), until only the last man remains, who is given freedom. The
   task is to choose the place in the initial circle so that you are the
   last one remaining and so survive.
3  */
4
5  using namespace std;
6
7  int josephus(int n, int m)
8  {
9      int res = 0;
10     vector<int> people;
11     int loc = 0;
12
13     for (int i = 0; i < n; i++) people.push_back(i+1);
14 }

```

```

14
15     while (people.size() > 1)
16     {
17         if (loc >= people.size())
18             loc %= people.size();
19
20         people.erase(people.begin()+loc);
21         loc += (m-1);
22     }
23
24     return people[0];
25 }

```

Código 31: josephus problem