

Pump Performance Datasheet

Customer	: SERTECPET	Quote number	: 2414687
Customer reference	: Ings. Juan Guerrero/ Víctor Nole	Size	: TJ12000
Item number	: TJ12000 70stg	Stages	: 70
Service	: RYA	Based on curve number	: TJ12000
Quantity	: 1	Date last saved	: 11 Feb 2026 3:13 PM

Operating Conditions		Liquid	
Flow, rated	: 13,000.0 USbl/day	Liquid type	: User Defined
Differential head / pressure, rated (requested)	: 2,720.0 psi	Additional liquid description	: water injection
Differential head / pressure, rated (actual)	: 2,721.8 psi	Solids diameter, max	: 0.00 in
Discharge pressure (actual)	: 2,801.8 psi	Solids concentration, by volume	: 0.00 %
Suction pressure, rated / max	: 80.00 / 100.0 psi.g	Temperature, max	: 150.0 deg F
NPSH available, rated	: Ample	Fluid density, rated / max	: 1.030 / 1.040 SG
Site Supply Frequency	: 60 Hz	Viscosity, rated	: 1.00 cP
		Vapor pressure, rated	: 0.00 psi.a
Performance		Material	
Speed, rated	: 3571 rpm	Material selected	: Standard
Impeller diameter, rated	: 5.12 in	Pressure Data	
Impeller diameter, maximum	: 5.12 in	Maximum working pressure	: 3,522.3 psi.g
Impeller diameter, minimum	: 5.12 in	Maximum allowable working pressure	: N/A
Efficiency	: 79.70 %	Maximum allowable suction pressure	: N/A
NPSH required / margin required	: 24.78 / 3.00 ft	Hydrostatic test pressure	: 5,283.4 psi.g
Ns (imp. eye flow) / Nss (imp. eye flow)	: 2,394 / 6,333 US Units	Driver & Power Data (@Max density)	
MCSF	: 5,305.5 USbl/day	Driver sizing specification	: Rated power
Head, maximum, rated diameter	: 3,389.4 psi	Margin over specification	: 5.00 %
Head rise to shutoff	: 23.54 %	Service factor	: 1.00
Flow, best eff. point	: 12,748.8 USbl/day	Power, hydraulic	: 608 hp
Flow ratio, rated / BEP	: 101.97 %	Power, rated	: 763 hp
Diameter ratio (rated / max)	: 100.00 %	Power, maximum, rated diameter	: 869 hp
Head ratio (rated dia / max dia)	: 100.00 %	Minimum recommended motor rating	: 900 hp / 671 kW
Cq/Ch/Ce/Cn [ANSI/HI 9.6.7-2010]	: 1.00 / 1.00 / 1.00 / 1.00		
Selection status	: Acceptable		

