Threat Modeling Framework

First edition · release 2025.11 (RIVERBED)

…, …

Contents

Introduction 3
Worked Example 4

Introduction

Threat modeling is a discipline, not a document. The pipeline described here starts from one canonical manifest and derives every artefact from it.

Threat modeling is a discipline, not a document. The pipeline described here starts from one canonical manifest and derives every artefact from it.

The framework is described in Worked Example, which carries the worked example of a small service.

The framework is described in Worked Example, which carries the worked example of a small service.

Why one source

Why one source

Every artefact is generated from the same iteration over the chapter list, so a difference in page count is attributable to the engines' typography and not to different content.[1]

Every artefact is generated from the same iteration over the chapter list, so a difference in page count is attributable to the engines' typography and not to different content.

The threat-modeling pipeline in practice.

1 A footnote carried by the canonical manifest.

Worked Example

A worked example of the framework, from the trust boundaries of a small service to the abuse cases that follow from them.

Trust boundaries

Every trust boundary is drawn once and referenced everywhere.

Abuse cases

An abuse case is a story about a person who wants something the system should not give them.

A worked example of the framework, from the trust boundaries of a small service to the abuse cases that follow from them.

Trust boundaries

Every trust boundary is drawn once and referenced everywhere.

Abuse cases

An abuse case is a story about a person who wants something the system should not give them.