Floor Type Energy Storage Battery

KNY-P51300

- 10 year warranty
- Short circuit protection
- Ultra safe LFP material
- Flexible remote upgrade
- Wide range inverter compatibility
- Parallel up to 32 modules
- 1C rate continuous charge/discharge
- Multi protection to avoid over discharge
- Smart BMS management for longer lifespan
- Active balancing charging, low self consumption



IP20 Level
High level protection

Safer to Use
High-density LiFePO4 battery

Long Battery Life
6000 cycles life (DoD 80%)

15.36kwh Capacity
To meet more electricity needs

Stable & Reliable
Advanced BMS management

Widely Compatible
Compatible with mainstream inverters

Model	KNY-P51300

Basic Information

Nominal Voltage	51.2V DC
Voltage Range	40V-58.4V
Nominal Capacity	300Ah
Rated Capacity	15.36kWh
Communication Protocol	CAN / RS485 / RS232
Max. Number of Parallel Connections	15
Cycle Life	6000 cycles (@80% DoD)
Protection Mechanism	Temperature Protection/Over-current Protection/Short-circuit Protection Over-charge Protection/Over-discharge Protection/Low-voltage Protection

Charging Parameters

Recommended Charging Current	100A
Max. Charging Current	200A
Recommended Charging Voltage	58V
Max. Charging Voltage	58.4V

Discharging Parameters

Recommended Discharging Current	100A
Max. Discharging Current	200A
Recommended Battery Discharge Cut-off Voltage	40V
Battery Cut-off Voltage	43.2V
Battery Recovery Voltage	48V

General Parameters

Dimension	800*580*255mm
Gross/Net Weight	146kg/126kg
Shell Material	Sheet Metal
Protection Rating	IP20
Installation Method	Floor type
Cell Type	LiFePO4

Certification & Safety Standard

Safety Certification	CE
Temperature Safety Certification	UN38.3,Class9

Temperature Parameters

Discharging Temperature	-20∽60℃
Charging Temperature	0∽55℃
Storage Temperature	-20∽45℃
Work Temperature	-20°C ~ +55°C
Storage Temperature	-10°C ~ +35°C