# 1. Data Representation

## 1.1. User-defined data types

- A data type constructed by the programmer using primitive data types.
- User-defined data types are used to create new data types that help to extend the flexibility of a programming language as the programmer can create data types based on the application's requirements.
- Importance of user-defined data types:
  - Code organization- Helps structure and group related data logically, making programs easier to read and maintain.
  - Reusability- Once defined, the data type can be reused multiple times, reducing redundant code and improving efficiency.
- Examples include:
  - Record
  - Set
  - Class
  - Object

### Composite User-Defined Data Types

Composite user-defined data types have a definition referencing at least one other type.

- **Record:** A composite data type that is a collection of related items which may or may not have different data types

```
TYPE TBook // Example
  DECLARE Name : STRING
  DECLARE Isbn : INTEGER
ENDTYPE

DECLARE Book1: TBook // Creating a variable
Book1.Name = "To Kill a Mockingbird" // Accessing properties
```

- **Set:** A set stores a finite number of unique items in no particular order allowing the program to apply mathematical operations defined in set theory.

```
TYPE <set-name> = SET OF <type> //Declaration
DEFINE <var-name> (value1,value2,value3,...) : <set-name>

TYPE Numbers = SET OF INTEGERS
DEFINE EvenNumbers (2,4,6,8,10) : Numbers
```

- **Classes:** In object-oriented programming (OOP), a class is the base for creating objects. It has methods and properties.

```
// Class definition
CLASS Bird
    PRIVATE Name: STRING
    PUBLIC PROCEDURE NEW(pName: STRING)
        Name ← pName
    ENDPROCEDURE
ENDCLASS

// Implementing inheritance
CLASS FlyingBird IMPLEMENTS Bird
    // Class info...
ENDCLASS

// Creating an object
<name> ← NEW <class_name>(<parameter1>, <parameter2>, ...)
MyPet ← NEW Bird("Kiwi")
```

### Non-Composite Data Type

Data types that can be defined without referencing another type.

String and Char are both non-composite built-in types

Examples include:

- Integers
- Booleans
- Strings
- **Enumerated Data Type:** A user defined non-composite data type that contains an ordered list of all possible values.

```
TYPE <name> : (<value1>, <value2>, ...)
TYPE Days: (Sunday, Monday, Tuesday, Wednesday, Thursday, Friday, Saturday)
TYPE Numbers: (1..10) // Inclusive
DECLARE Today: Days // Declaration
Today ← Sunday
Today ← Today + 1 // Value is now Monday
```

- **Pointer Data Type:** A user defined non-composite data type that is used to reference a memory location.

```
TYPE <Name> = ^<Type>

// Declaring a pointer type
TYPE PIntPointer: ^INTEGER
// Declaring a pointer variable
DECLARE MyPointer: PIntPointer

MyPointer^ ← 3 // Sets the value at the address to
MyPointer ← 3 // Pointer points to value at the address 3
MyPointer ← @<variable_name> // Makes pointer point to value stored at
```

## 1.2. File organization and access

### File organization

- **Serial:** In serial files, records are stored one after another in chronological order. Records are appended to the next available spot. Benefits:
  - No need to sort list.
  - Data can be appended easily.
- **Sequential:** In sequential files, records are stored one after another in the order of the key field. Records are inserted into the correct position. A new version of the file has to be created to update it. Benefits:
  - Allows for batch processing.
  - Allows the data to be stored and sorted in a specific order.
- **Random:** In random files, records are stored in no particular order. Changes to file are done directly.
  - In random file organization a unique key field is passed through a hash algorithm which produces the home location for the data, if that location is empty the data is stored else it relies on an overflow method.
  - A collision can occur when two different records produce the same hash, this means that the location is already being used to store a different record. When saving a file, it searches the file linearly for an empty spot and saves the file there or search the overflow area linearly for the next empty spot and save the record there. When finding a record, search the overflow area linearly of the matching record or start from current location and search linearly and until matching record is found.
  - Benefits:
    - Fast as real time processing is used

### File access

- **Sequential:** In sequential access records are read in the order that they are stored in.
- It is read record by record until the record is found or the key field value is exceeded.
- This is used for serial and sequential file organization.
- **Direct/Random Access:** In random access you can directly access the data needed.
- This is used in both sequential and random file organisation.
- In sequential, index of all the key fields is used, while hash algorithm is used in random file organization.

## 1.3. Floating-point numbers, representation and manipulation

### Floating point representation

- **Mantissa:** Represents the numbers. If we increase the bits allocated to the mantissa, we increase accuracy.
- **Exponent:** Represents the number of times the decimal place needs to move. If we increase the bits allocated to exponent, we increase the range.

$$M \times 2^E$$

$$M = \text{Mantissa}$$

$$E = \text{Exponent}$$

### Converting from Binary Digit to Positive Float

$$\text{Mantissa} = 01101000 \text{Exponent} = 0011$$

1. Write the binary number with the decimal point

$$0 \cdot 1101$$

2. Multiply with 2 to the power of the exponent (Move the decimal point the same number of places as the exponent)

$$0 \cdot 1101 \text{ x } 2^3 \backslash 0110 \cdot 1$$

3. Convert to decimal by multiplying

$$(4 \times 1) + (2 \times 1) + (\frac{1}{2} \times 1)$$

Therefore the answer is 6.5



Copyright © 2025 ZNotes Education & Foundation. All Rights Reserved.
This document is authorised for personal use only by Sadia Ali at Enderun Colleges on 06/04/26.

### Converting from Float to Binary Digit

$$6.5$$

- Make the float into an integer by multiplying by factors of 2 tilt it becomes a whole number.

$$6.5 = \frac{13}{2}$$

- Now multiply the denominator by multiples of 2 till it is larger than the numerator.

$$\frac{13}{2} \xrightarrow{\boxed{1}} \frac{13}{4} \xrightarrow{\boxed{2}} \frac{13}{8} \xrightarrow{\boxed{3}} \frac{13}{16}$$

- So we get exponent as 3 which in binary is 0011. Now for mantissa, we slowly split $\frac{13}{16}$ into factors of $\frac{1}{2}$.

$$\frac{13}{16} = \frac{1}{16} + \frac{12}{16} = \frac{1}{16} + \frac{6}{8} = \frac{1}{16} + \frac{3}{4} = \frac{1}{16} + \frac{1}{4} + \frac{2}{4} = \frac{1}{16} + \frac{1}{4} + \frac{1}{2}$$

- Put these back into the mantissa table

  Mantissa: 01101000

  Exponent: 0011

### Converting from Binary Digit to Negative Float

By taking two's compliment on a postive binary float, converts it gets converted into the negative float.

- Do not take two's compliment of the exponent.

$$01110000 \quad 0010 \rightarrow 10010000 \quad 0010$$

+3.5 became -3.5

### Normalization

For a positive binary digit, the first two bits need to be different. (Removing extra zeros before in between the decimal and the first 1 digit).

$$0 \cdot 0110000 \quad 0011 \rightarrow \backslash 0 \cdot 1100000 \quad 0010$$

Benefits:

- Avoids two of the same number being represented differently.
- Maximizes the potential precision.
- Allows us to store the maximum range of numbers in the minimum number of bits.

Negative binary numbers

- For negative binary digit, the first bit needs to be 1.
- The mantissa are shifted until we arrive at 1.0, then the exponent must be changed to reflect the change.

  For example:

1.1101100 --> 1010

1.0110000 --> 1000

Unlike positive normalisation, the number of changes are subtracted from the exponent.

### Important values

| | |
|---|---|
| Largest positive number | 0111 1111 0111 |
| Smallest positive number | 0000 0001 1000 |
| Smallest normalized positive number | 0100 0000 1000 |
| Largest magnitude negative number | 1000 0000 0111 |

### Errors

- Rounding Error: When numbers can't be represented be represented exactly in binary, an approximate value is used which is either more or less than the needed value. When these numbers are then used in operations, the inaccuracies get added to the point where they are visible in the final answer. Like 0.1 + 0.2 = 0.3000000000004
- Underflow: Underflow occurs when a number is too close to zero to be accurately represented in binary, leading to a loss of precision.
- Overflow: Overflow happens when a number's magnitude exceeds the limit that can be represented in a given number of bits.



Copyright © 2025 ZNotes Education & Foundation. All Rights Reserved.
This document is authorised for personal use only by Sadia Ali at Enderun Colleges on 06/04/26.