1. Security, Privacy and Data Integrity

1.1. Data Security

- Data Security: ensuring data is protected against loss and unauthorized access.
- Data Integrity: making sure that data is valid and does not corrupt after transmission
- Data Privacy: ability to determine what data is shared with a third party
- Data Security and Computer System Security

Data Security	System Security
Protection of data on a computer system	Protection of the computer system
To prevent corruption of data and prevent hackers from using data	To prevent access of viruses to the system and prevent hackers from entering your computer system
E.g. encryption	E.g. ID & Password

*Threats to Computer & Data Security**

- Malware
  - software intentionally designed to damage a computer or computer network
  - Includes Virus & Spyware
  - Virus: Software that replicates itself by inserting a copy of itself into another piece of software, which may cause the computer to crash and can lead to deletion or corruption of data
  - Spyware: software that gathers information about users' online and offline activity, including accessed sites, applications, and downloaded files.
  - Risk restriction: Ensure anti-virus and anti-spyware software is installed, regularly updated and run.
- Hacking
  - illegal access to a computer system
  - Hackers can obtain user's confidential data which can cause identity theft
  - Can lead to the deletion or corruption of data
  - Risk restriction: Use strong passwords and ensure firewall
- Phishing
  - Attempt through emails to obtain user's confidential data which can cause identity theft
  - Risk restriction: Ignore suspicious mails and ensure firewall criteria include SPAM filters, blacklist, etc.
- Pharming
  - Redirects user to a fake website that appears legitimate to gain confidential data
  - Risk restriction: use a reliable ISP; check that links are genuine and ensure https is present in the URL

Computer System Security Measures

- User Accounts and Passwords
  - Usernames & passwords to deny access to unauthorized users
  - User-assigned privilege, which accesses to only the user's workplace, preventing the user to have admin rights.
  - Can assign privileges to files so users with low privileges do not have access.
- Firewalls
  - Hardware or software that filters information travelling between the computer system and the internet
  - (software) firewall can make decisions about what to allow and block by detecting illegal attempts by specific software to connect to the internet
- Authentication
  - Process of determining whether someone is who they claim to be.
  - Helps prevent unauthorized access
  - Log-on using digital signatures, passwords and biometric scans.
- Digital Signatures
  - The data is hashed using a agreed hashing algorithm, to produce a digest. The sender encrypts the digest using the sender's private key to create the digital signature. The message and the signature are sent to the receiver. The receiver uses the sender's public key to decrypt the signature to reproduce the orignal digest. The receiver then applies the same hashing algorithm on the received message to produce a second digest. The receiver compares the second digest with the one from the digital signature. If both are the same, the document is authentic and this proves the integrity of the message and the identity of the sender.
- Anti-virus software
  - Runs in the background to detect & remove viruses.
  - Checks files for known malicious patterns
- Anti-spyware software: detects & removes spyware.
- Encryption:
  - Conversion of data to code by encoding it
  - It doesn't stop illegal access but appears meaningless
  - Necessary to use decryption software to decode data
- Data Security Measures
  - Encryption
  - Access Rights to data (authorization): different users assigned different authorization levels which prevent them from accessing all data ∴ increases security

Copyright © 2025 ZNotes Education & Foundation. All Rights Reserved.
This document is authorised for personal use only by Sadia Ali at Enderun Colleges on 06/04/26.

- Data Backup
  - An exact copy of an original piece of data in case the original is lost or corrupted
  - Within the same computer system or at different site
- Disk-mirroring strategy
  - Real-time strategy that writes data to two or more disks at the same time.
  - If one fails, the other is still there to be read off of

1.2. Data Integrity

- Data validation and data verification help protect the integrity of data by checking whether the data entered is sensible and accurate, respectively.
- Data Validation: checks if data entered is valid, but not its accuracy
- Data Validation Methods
  - Range check: data must be between a set of values
  - Format check: data must follow correct pattern/order
  - Length check: data must have exact no. of characters
  - Presence check: checks if some data has been entered
  - Existence check: data entered must exist
  - Limit check: checks whether a value entered is within acceptable minimum and maximum values.
  - Check digit: A digit is used as the answer to an arithmetic operation of other digits in data. If not matched, then data entered incorrectly
- Data Verification: checks data entered is accurate during data entry and data transfer
- Data Entry Verification Methods
  - Visual Check: Person manually compares original data with that entered to check if correct
  - Double Entry: Enter data into computer twice and compares.
  - If differences found, go back to raw data to fix error

Data Transfer Verification Methods

- Errors may occur when data moved in system.
- Parity Check
  - All data transmitted as bits
  - Number of 1s in a byte must always be either an odd number or an even number
  - Parity can be set either as even or odd
  - E.g. two communicating devices decide there will always be an odd number of 1s. A byte is received that has even number of 1s so error occurred and receiving device would ask for it to be sent again
  - Used also when data sent between parts of the CPU
  - Not foolproof: if 2 bits are transposed, data accepted
- Checksum Check
  - Data sent from one place to another as block of bytes rather than individual bytes
  - Computer adds together all bytes being sent
  - Any bits lost at most-significant end as carry ignored so answer is an 8-bit number
  - Checksum calculated before and after data sent
  - If two bytes different, error occurred therefore block of bytes must be sent again

Copyright © 2025 ZNotes Education & Foundation. All Rights Reserved.
This document is authorised for personal use only by Sadia Ali at Enderun Colleges on 06/04/26.