

Contents

.....	2
Short (excluding inherited methods)	2
Class: (class Object)::(class GTK::Args)	2
Class: (class Object)::(class GTK::Runtime)	3
Class: (class Object)::(class GTK::Root)	5
Class: (class Object)::(class GTK::OpenEntity)	5
Class: (class Object)::(class FFI::MRB)	6
Class: (class Object)::(class FFI::File)	6
Class: (class Object)::(class GTK::OpenEntity)	7
Class: (class Object)::(class Module)	7
Class: (class Object)::(class GTK::Grid	9
Class: (class Object)::(class IO	10
Class: (class IO	11
Class: (class Object)::(class NilClass	11
Class: (class Object)::(class GTK::Outputs)	12
Class: (class Object)::(class Array	13
Class: (class Object)::(class GTK::Inputs)	16
Class: (class Object)::(class GTK::Controller)	16
Class: (class Object)::(class GTK::Controller)	17
Class: (class Object)::(class Array	18
Class: (class Object)::(class GTK::Keyboard)	20
Class: (class Object)::(class GTK::Mouse)	21
Full (including inherited methods)	21
Class: (class Object)::(class GTK::Args)	21
Class: (class Object)::(class GTK::Runtime)	25
Class: (class Object)::(class GTK::Root)	29
Class: (class Object)::(class GTK::OpenEntity)	32
Class: (class Object)::(class FFI::MRB)	35
Class: (class Object)::(class FFI::File)	38
Class: (class Object)::(class GTK::OpenEntity)	40
Class: (class Object)::(class Module)	44
Class: (class Object)::(class GTK::Grid	47
Class: (class Object)::(class IO	51
Class: (class IO	55
Class: (class Object)::(class NilClass	60
Class: (class Object)::(class GTK::Outputs)	63
Class: (class Object)::(class Array	67
Class: (class Object)::(class GTK::Inputs)	73
Class: (class Object)::(class GTK::Controller)	76
Class: (class Object)::(class GTK::Controller)	79
Class: (class Object)::(class Array	83
Class: (class Object)::(class GTK::Keyboard)	89
Class: (class Object)::(class GTK::Mouse)	92

Short (excluding inherited methods)

Class: (class Object)::(class GTK::Args)

args

- borders
- clear_render_targets
- click
- click_at
- controller_one
- controller_two
- destructure
- dragon
- game
- grid
- grid=
- gtk
- initialize
- inputs
- inputs=
- keyboard
- labels
- lines
- mouse
- outputs
- outputs=
- passes
- passes=
- primitives
- recording
- recording=
- render_target
- runtime
- runtime=
- serialize
- solids
- sprites
- state
- state=
- static_borders
- static_labels
- static_lines
- static_primitives

- static_solids
- static_sprites

[Top](#)

Class: (class Object)::(class GTK::Runtime)

args.dragon

- args
- args=
- argv
- argv=
- border_to_ffi
- calc_wrapper
- calcstringbox
- check_framerate
- clear_draw_passes
- clear_draw_primitives
- clear_inputs
- cli_arguments
- console
- current_framerate
- current_framerate_raw
- dequeue_sounds
- disable_console
- enable_console
- export!
- ffi_draw
- ffi_file
- ffi_misc
- ffi_mrb
- framerate_below_threshold?
- grep_source
- help
- init_args_if_needed
- initialize
- input_history
- label_to_ffi
- line_to_ffi
- load_state
- log
- next_keyboard_inputs_after_tick
- next_keyboard_inputs_before_tick

- passes
- pause!
- paused?
- pin_root_values
- primitive_to_ffi
- primitives
- queue_key_up
- quit!
- quit_requested?
- raise_conversion_for_rendering_failed
- read_file
- record_input_history
- recording
- render_height
- render_replay_mouse
- render_width
- request_quit
- require
- reserved_primitives
- reset
- reset_framerate_calculation
- root
- root=
- save_state
- set_rng
- show_console
- solid_to_ffi
- sprite_to_ffi
- stage_replay_values
- start!
- start_recording
- start_replay
- stop_recording
- stop_replay
- suppress_framerate_warning
- suppress_framerate_warning=
- suppress_print_help_when_mouse_clicked
- suppress_print_help_when_mouse_clicked=
- target
- tests
- text_font
- tick_console
- tick_core
- unpause!

[Top](#)

Class: (class Object)::(class GTK::Root)

args.dragon.root

- files_reloaded
- files_reloaded=
- hash
- hash=
- initialize
- keyboard_focus
- keyboard_focus=
- mouse_focus
- mouse_focus=
- paused
- paused=
- reloaded_files
- reloaded_files=
- take_screenshot
- take_screenshot=
- tick_count
- tick_count=
- time_per_tick
- time_per_tick=

[Top](#)

Class: (class Object)::(class GTK::OpenEntity)

args.state.new_entity Methods of an entity object

- ==
- __contains_array_indexers__
- __contains_array_indexers__=
- __get_hash_property__
- __meta__
- __reserved_keys__
- __set_hash_property__
- __touched__
- __touched__=
- attributes
- clear!
- created_at=

- created_at_elapsed
- entity_id
- entity_type=
- global_created_at=
- global_created_at_elapsed
- hash
- initialize
- inspect
- meta
- meta!
- method_missing
- new?
- new_entity
- new_entity_strict
- old?
- original_eq_eq
- set!
- to_s
- with_meta

[Top](#)

Class: (class Object)::(class FFI::MRB)

\$ffi

- eval
- parse
- reload

[Top](#)

Class: (class Object)::(class FFI::File)

FFI::File

- loadfile
- mtime
- storefile

[Top](#)

Class: (class Object)::(class GTK::OpenEntity)

args.state

- ==
- __contains_array_indexers__
- __contains_array_indexers__=
- __get_hash_property__
- __meta__
- __reserved_keys__
- __set_hash_property__
- __touched__
- __touched__=
- attributes
- clear!
- created_at_elapsed
- documenter_success
- entity_id
- global_created_at_elapsed
- hash
- initialize
- inspect
- meta
- meta!
- method_missing
- new?
- new_entity
- new_entity_strict
- old?
- original_eq_eq
- set!
- tick_count=
- to_s
- with_meta

[Top](#)

Class: (class Object)::(class Module)

GC

- ===
- alias_method
- ancestors
- append_features

- attr
- attr_accessor
- attr_reader
- attr_writer
- class_eval
- class_exec
- class_variable_defined?
- class_variable_get
- class_variable_set
- class_variables
- const_defined?
- const_get
- const_missing
- const_set
- constants
- define_method
- disable
- dup
- enable
- extend_object
- extended
- generational_mode
- generational_mode=
- include
- include?
- included
- included_modules
- initialize
- inspect
- instance_methods
- interval_ratio
- interval_ratio=
- method_defined?
- method_removed
- module_eval
- module_exec
- module_function
- name
- prepend
- prepend_features
- prepended
- private
- protected
- public
- remove_class_variable
- remove_const

- remove_method
- singleton_class?
- start
- step_ratio
- step_ratio=
- to_s
- undef_method

[Top](#)

Class: (class Object)::(class GTK::Grid

(included_modules [Serialize])) *args.grid*

- __print_origin_help
- bottom
- bottom=
- center_x
- center_x=
- center_y
- center_y=
- h
- h_half
- initialize
- left
- left=
- name
- name=
- origin_bottom_left!
- origin_center!
- origin_x
- origin_x=
- origin_y
- origin_y=
- rect
- rect=
- right
- right=
- top
- top=
- transform_angle
- transform_rect
- transform_x
- transform_y

- untransform_x
- untransform_y
- w
- w_half

[Top](#)

Class: (class Object)::(class IO

(included_modules [Enumerable])) *IO.new(IO.sysopen("/dev/tty", "w"), "w")*

- <<
- _check_readable
- _read_buf
- close
- close_on_exec=
- close_on_exec?
- close_write
- closed?
- each
- each_byte
- each_char
- each_line
- eof
- eof?
- fileno
- flush
- getc
- gets
- hash
- initialize
- initialize_copy
- isatty
- pid
- pos
- pos=
- print
- printf
- puts
- read
- readchar
- readline
- readlines
- rewind

- seek
- sync
- sync=
- sysread
- sysseek
- syswrite
- tell
- to_i
- tty?
- ungetc
- write

[Top](#)

Class: (class IO

(included_modules [Enumerable])):(class File (superclass (class IO (included_modules [Enumerable]))) (included_modules [File::Constants, Enumerable])) *File.open*

- flock
- initialize
- mtime
- path
- path=

[Top](#)

Class: (class Object):(class NilClass

(included_modules [NilClassFalseClass])) *\$layout*

- &
- ^
- __check_thrash__!
- background_color
- inspect
- method_missing
- nil?
- to_a
- to_f
- to_h
- to_i

- to_s
- |

[Top](#)

Class: (class Object)::(class GTK::Outputs)

args.outputs

- __borders=
- __labels=
- __lines=
- __primitives=
- __raise_deprecated__
- __reserved=
- __solids=
- __sprites=
- __static_borders=
- __static_labels=
- __static_lines=
- __static_primitives=
- __static_reserved=
- __static_solids=
- __static_sprites=
- all_borders
- all_labels
- all_lines
- all_primitives
- all_reserved
- all_solids
- all_sounds
- all_sprites
- borders
- borders=
- clear
- clear_non_static
- height
- height=
- initialize
- labels
- labels=
- lines
- lines=
- primitives

- primitives=
- reserved
- reserved=
- serialize
- solids
- solids=
- sounds
- sounds=
- sprites
- sprites=
- static_borders
- static_borders=
- static_labels
- static_labels=
- static_lines
- static_lines=
- static_primitives
- static_primitives=
- static_reserved
- static_reserved=
- static_solids
- static_solids=
- static_sprites
- static_sprites=
- target
- target=
- tick
- width
- width=

[Top](#)

Class: (class Object)::(class Array

(included_modules [GTK::Primitive::ConversionCapabilities, Enumerable]))

args.passes

- &
- *
- +
- -
- <<
- <=>
- ==

- []
- []=
- __ary_cmp
- __ary_eq
- __ary_index
- __original_add__
- __original_add_single__
- __sort_sub__
- __svalue
- _inspect
- any_intersects_rect?
- append
- assoc
- at
- bsearch
- bsearch_index
- clear
- collect!
- combination
- compact
- compact!
- concat
- delete
- delete_at
- delete_if
- dig
- each
- each_index
- empty?
- eql?
- fetch
- fill
- first
- flatten
- flatten!
- include_any?
- index
- initialize
- initialize_copy
- insert
- inspect
- join
- keep_if
- last
- length
- map!

- map_2d
- pack
- pairs_to_hash
- permutation
- pop
- prepend
- product
- push
- rassoc
- reject!
- reject_false
- reject_nil
- replace
- rest
- reverse
- reverse!
- reverse_each
- rindex
- rotate
- rotate!
- sample
- select!
- serialize
- shift
- shuffle
- shuffle!
- size
- slice
- slice!
- sort
- sort!
- to_a_pairs
- to_ary
- to_h
- to_s
- transpose
- uniq
- uniq!
- unshift
- values_at
- |

[Top](#)

Class: (class Object)::(class GTK::Inputs)

args.inputs

- controller_one
- controller_two
- controllers
- controllers=
- history
- history=
- initialize
- keyboard
- keyboard=
- mouse
- mouse=
- serialize
- text
- text=

[Top](#)

Class: (class Object)::(class GTK::Controller)

args.inputs.controller_one

- clear
- initialize
- key_down
- key_down=
- key_held
- key_held=
- key_up
- key_up=
- left_analog_x_perc
- left_analog_x_perc=
- left_analog_x_raw
- left_analog_x_raw=
- left_analog_y_perc
- left_analog_y_perc=
- left_analog_y_raw
- left_analog_y_raw=
- left_right
- left_right=
- right_analog_x_perc
- right_analog_x_perc=

- right_analog_x_raw
- right_analog_x_raw=
- right_analog_y_perc
- right_analog_y_perc=
- right_analog_y_raw
- right_analog_y_raw=
- serialize
- up_down
- up_down=

[Top](#)

Class: (class Object)::(class GTK::Controller)

args.inputs.controller_two

- clear
- initialize
- key_down
- key_down=
- key_held
- key_held=
- key_up
- key_up=
- left_analog_x_perc
- left_analog_x_perc=
- left_analog_x_raw
- left_analog_x_raw=
- left_analog_y_perc
- left_analog_y_perc=
- left_analog_y_raw
- left_analog_y_raw=
- left_right
- left_right=
- right_analog_x_perc
- right_analog_x_perc=
- right_analog_x_raw
- right_analog_x_raw=
- right_analog_y_perc
- right_analog_y_perc=
- right_analog_y_raw
- right_analog_y_raw=
- serialize
- up_down

- up_down=

[Top](#)

Class: (class Object)::(class Array

(included__modules [GTK::Primitive::ConversionCapabilities, Enumerable]))
args.inputs.controllers

- &
- *
- +
- -
- <<
- <=>
- ==
- []
- []=
- __ary_cmp
- __ary_eq
- __ary_index
- __original_add__
- __original_add_single__
- __sort_sub__
- __svalue
- _inspect
- any_intersects_rect?
- append
- assoc
- at
- bsearch
- bsearch_index
- clear
- collect!
- combination
- compact
- compact!
- concat
- delete
- delete_at
- delete_if
- dig
- each
- each_index

- empty?
- eql?
- fetch
- fill
- first
- flatten
- flatten!
- include_any?
- index
- initialize
- initialize_copy
- insert
- inspect
- join
- keep_if
- last
- length
- map!
- map_2d
- pack
- pairs_to_hash
- permutation
- pop
- prepend
- product
- push
- rassoc
- reject!
- reject_false
- reject_nil
- replace
- rest
- reverse
- reverse!
- reverse_each
- rindex
- rotate
- rotate!
- sample
- select!
- serialize
- shift
- shuffle
- shuffle!
- size
- slice

- slice!
- sort
- sort!
- to_a_pairs
- to_ary
- to_h
- to_s
- transpose
- uniq
- uniq!
- unshift
- values_at
- |

[Top](#)

Class: (class Object)::(class GTK::Keyboard)

args.inputs.keyboard

- clear
- down
- has_focus
- has_focus=
- initialize
- inspect
- key_down
- key_down=
- key_held
- key_held=
- key_up
- key_up=
- left
- left_right
- right
- serialize
- to_s
- up
- up_down

[Top](#)

Class: (class Object)::(class GTK::Mouse)

args.inputs.mouse

- clear
- click
- click=
- down
- has_focus
- has_focus=
- initialize
- moved
- moved=
- moved_at
- moved_at=
- moved_at_time
- moved_at_time=
- position
- previous_click
- previous_click=
- serialize
- up
- up=
- x
- x=
- y
- y=

[Top](#)

Full (including inherited methods)

Class: (class Object)::(class GTK::Args)

args

- !
- !=
- !~
- ==
- ===
- Array
- Float
- Hash
- Integer

- String
- __caller_without_noise__
- __case_eqq
- __custom_object_methods__
- __gtk_ruby_source_files__
- __gtk_ruby_string_contains_source_file_path__?
- __id__
- __method__
- __object_methods__
- __pretty_print_exception__
- __printstr__
- __send__
- __supports_ivars__?
- _inspect
- ““““
- and
- better_instance_information
- block_given?
- borders
- caller
- class
- class_defined?
- clear_render_targets
- click
- click_at
- clone
- controller_one
- controller_two
- define_singleton_method
- destructure
- dig
- dragon
- dup
- enum_for
- eql?
- equal?
- extend
- fail
- fast_rand
- format
- freeze
- frozen?
- game
- getc
- gets
- global_variables

- grid
- grid=
- gtk
- hash
- help
- here
- initialize
- initialize_copy
- inputs
- inputs=
- inspect
- instance_eval
- instance_exec
- instance_of?
- instance_variable_defined?
- instance_variable_get
- instance_variable_set
- instance_variables
- is_a?
- iterator?
- itself
- keyboard
- kind_of?
- labels
- lambda
- lines
- local_variables
- log
- log_info
- log_once
- log_once_info
- loop
- metadata_object_id
- method_missing
- methods
- mouse
- nil?
- numeric_or_default
- object_id
- open
- or
- original_puts
- outputs
- outputs=
- p
- passes

- passes=
- primitive?
- primitive_determined?
- primitives
- print
- printf
- private_methods
- proc
- protected_methods
- public_methods
- purge_class
- puts
- putsc
- raise
- raise_error_with_kind_of_okay_message
- raise_immediately
- raise_method_missing_better_error
- raise_with_caller
- rand
- recording
- recording=
- remove_instance_variable
- render_target
- require
- respond_to?
- runtime
- runtime=
- send
- serialize
- singleton_class
- singleton_methods
- solids
- sprintf
- sprites
- srand
- state
- state=
- static_borders
- static_labels
- static_lines
- static_primitives
- static_solids
- static_sprites
- tap
- then
- tick

- to_enum
- to_s
- yield_self

[Top](#)

Class: (class Object)::(class GTK::Runtime)

args.dragon

- !
- !=
- !~
- ==
- ===
- Array
- Float
- Hash
- Integer
- String
- __caller_without_noise__
- __case_eqq
- __custom_object_methods__
- __gtk_ruby_source_files__
- __gtk_ruby_string_contains_source_file_path__?
- __id__
- __method__
- __object_methods__
- __pretty_print_exception__
- __printstr__
- __send__
- __supports_ivars__?
- _inspect
- ““““
- and
- args
- args=
- argv
- argv=
- better_instance_information
- block_given?
- border_to_ffi
- calc_wrapper
- calcstringbox

- caller
- check_framerate
- class
- class_defined?
- clear_draw_passes
- clear_draw_primitives
- clear_inputs
- cli_arguments
- clone
- console
- current_framerate
- current_framerate_raw
- define_singleton_method
- dequeue_sounds
- dig
- disable_console
- dup
- enable_console
- enum_for
- eql?
- equal?
- export!
- extend
- fail
- fast_rand
- ffi_draw
- ffi_file
- ffi_misc
- ffi_mrb
- format
- framerate_below_threshold?
- freeze
- frozen?
- getc
- gets
- global_variables
- grep_source
- hash
- help
- here
- init_args_if_needed
- initialize
- initialize_copy
- input_history
- inspect
- instance_eval

- instance_exec
- instance_of?
- instance_variable_defined?
- instance_variable_get
- instance_variable_set
- instance_variables
- is_a?
- iterator?
- itself
- kind_of?
- label_to_ffi
- lambda
- line_to_ffi
- load_state
- local_variables
- log
- log_info
- log_once
- log_once_info
- loop
- metadata_object_id
- method_missing
- methods
- next_keyboard_inputs_after_tick
- next_keyboard_inputs_before_tick
- nil?
- numeric_or_default
- object_id
- open
- or
- original_puts
- p
- passes
- pause!
- paused?
- pin_root_values
- primitive?
- primitive_determined?
- primitive_to_ffi
- primitives
- print
- printf
- private_methods
- proc
- protected_methods
- public_methods

- `purge_class`
- `puts`
- `putc`
- `queue_key_up`
- `quit!`
- `quit_requested?`
- `raise`
- `raise_conversion_for_rendering_failed`
- `raise_error_with_kind_of_okay_message`
- `raise_immediately`
- `raise_method_missing_better_error`
- `raise_with_caller`
- `rand`
- `read_file`
- `record_input_history`
- `recording`
- `remove_instance_variable`
- `render_height`
- `render_replay_mouse`
- `render_width`
- `request_quit`
- `require`
- `reserved_primitives`
- `reset`
- `reset_framerate_calculation`
- `respond_to?`
- `root`
- `root=`
- `save_state`
- `send`
- `set_rng`
- `show_console`
- `singleton_class`
- `singleton_methods`
- `solid_to_ffi`
- `sprintf`
- `sprite_to_ffi`
- `srand`
- `stage_replay_values`
- `start!`
- `start_recording`
- `start_replay`
- `stop_recording`
- `stop_replay`
- `suppress_framerate_warning`
- `suppress_framerate_warning=`

- `suppress_print_help_when_mouse_clicked`
- `suppress_print_help_when_mouse_clicked=`
- `tap`
- `target`
- `tests`
- `text_font`
- `then`
- `tick`
- `tick_console`
- `tick_core`
- `to_enum`
- `to_s`
- `unpause!`
- `yield_self`

[Top](#)

Class: `(class Object)::(class GTK::Root)`

args.dragon.root

- `!`
- `!=`
- `!~`
- `==`
- `===`
- `Array`
- `Float`
- `Hash`
- `Integer`
- `String`
- `__caller_without_noise__`
- `__case_eqq`
- `__custom_object_methods__`
- `__gtk_ruby_source_files__`
- `__gtk_ruby_string_contains_source_file_path__?`
- `__id__`
- `__method__`
- `__object_methods__`
- `__pretty_print_exception__`
- `__printstr__`
- `__send__`
- `__supports_ivars__?`
- `_inspect`

- `““““`
- `and`
- `better_instance_information`
- `block_given?`
- `caller`
- `class`
- `class_defined?`
- `clone`
- `define_singleton_method`
- `dig`
- `dup`
- `enum_for`
- `eql?`
- `equal?`
- `extend`
- `fail`
- `fast_rand`
- `files_reloaded`
- `files_reloaded=`
- `format`
- `freeze`
- `frozen?`
- `getc`
- `gets`
- `global_variables`
- `hash`
- `hash=`
- `help`
- `here`
- `initialize`
- `initialize_copy`
- `inspect`
- `instance_eval`
- `instance_exec`
- `instance_of?`
- `instance_variable_defined?`
- `instance_variable_get`
- `instance_variable_set`
- `instance_variables`
- `is_a?`
- `iterator?`
- `itself`
- `keyboard_focus`
- `keyboard_focus=`
- `kind_of?`
- `lambda`

- local_variables
- log
- log_info
- log_once
- log_once_info
- loop
- metadata_object_id
- method_missing
- methods
- mouse_focus
- mouse_focus=
- nil?
- numeric_or_default
- object_id
- open
- or
- original_puts
- p
- paused
- paused=
- primitive?
- primitive_determined?
- print
- printf
- private_methods
- proc
- protected_methods
- public_methods
- purge_class
- puts
- putsc
- raise
- raise_error_with_kind_of_okay_message
- raise_immediately
- raise_method_missing_better_error
- raise_with_caller
- rand
- reloaded_files
- reloaded_files=
- remove_instance_variable
- require
- respond_to?
- send
- singleton_class
- singleton_methods
- sprintf

- srand
- take_screenshot
- take_screenshot=
- tap
- then
- tick
- tick_count
- tick_count=
- time_per_tick
- time_per_tick=
- to_enum
- to_s
- yield_self

[Top](#)

Class: (class Object)::(class GTK::OpenEntity)

args.state.new_entity Methods of an entity object

- !
- !=
- !~
- ==
- ===
- Array
- Float
- Hash
- Integer
- String
- __caller_without_noise__
- __case_eqq
- __contains_array_indexers__
- __contains_array_indexers__=
- __custom_object_methods__
- __get_hash_property__
- __gtk_ruby_source_files__
- __gtk_ruby_string_contains_source_file_path__?
- __id__
- __meta__
- __method__
- __object_methods__
- __pretty_print_exception__
- __printstr__

- `__reserved_keys__`
- `__send__`
- `__set_hash_property__`
- `__supports_ivars__?`
- `__touched__`
- `__touched__=`
- `_inspect`
- `““““`
- `and`
- `attributes`
- `better_instance_information`
- `block_given?`
- `caller`
- `class`
- `class_defined?`
- `clear!`
- `clone`
- `created_at=`
- `created_at_elapsed`
- `define_singleton_method`
- `dig`
- `dup`
- `entity_id`
- `entity_type=`
- `enum_for`
- `eql?`
- `equal?`
- `extend`
- `fail`
- `fast_rand`
- `format`
- `freeze`
- `frozen?`
- `getc`
- `gets`
- `global_created_at=`
- `global_created_at_elapsed`
- `global_variables`
- `hash`
- `help`
- `here`
- `initialize`
- `initialize_copy`
- `inspect`
- `instance_eval`
- `instance_exec`

- `instance_of?`
- `instance_variable_defined?`
- `instance_variable_get`
- `instance_variable_set`
- `instance_variables`
- `is_a?`
- `iterator?`
- `itself`
- `kind_of?`
- `lambda`
- `local_variables`
- `log`
- `log_info`
- `log_once`
- `log_once_info`
- `loop`
- `meta`
- `meta!`
- `metadata_object_id`
- `method_missing`
- `methods`
- `new?`
- `new_entity`
- `new_entity_strict`
- `nil?`
- `numeric_or_default`
- `object_id`
- `old?`
- `open`
- `or`
- `original_eq_eq`
- `original_puts`
- `p`
- `primitive?`
- `primitive_determined?`
- `print`
- `printf`
- `private_methods`
- `proc`
- `protected_methods`
- `public_methods`
- `purge_class`
- `puts`
- `putc`
- `raise`
- `raise_error_with_kind_of_okay_message`

- `raise_immediately`
- `raise_method_missing_better_error`
- `raise_with_caller`
- `rand`
- `remove_instance_variable`
- `require`
- `respond_to?`
- `send`
- `set!`
- `singleton_class`
- `singleton_methods`
- `sprintf`
- `srand`
- `tap`
- `then`
- `tick`
- `to_enum`
- `to_s`
- `with_meta`
- `yield_self`

[Top](#)

Class: (class Object)::(class FFI::MRB)

\$ffi

- `!`
- `!=`
- `!~`
- `==`
- `===`
- `Array`
- `Float`
- `Hash`
- `Integer`
- `String`
- `__caller_without_noise__`
- `__case_eqq`
- `__custom_object_methods__`
- `__gtk_ruby_source_files__`
- `__gtk_ruby_string_contains_source_file_path__?`
- `__id__`
- `__method__`

- `__object_methods__`
- `__pretty_print_exception__`
- `__printstr__`
- `__send__`
- `__supports_ivars__?`
- `_inspect`
- `““““`
- `and`
- `better_instance_information`
- `block_given?`
- `caller`
- `class`
- `class_defined?`
- `clone`
- `define_singleton_method`
- `dig`
- `dup`
- `enum_for`
- `eql?`
- `equal?`
- `eval`
- `extend`
- `fail`
- `fast_rand`
- `format`
- `freeze`
- `frozen?`
- `getc`
- `gets`
- `global_variables`
- `hash`
- `help`
- `here`
- `initialize`
- `initialize_copy`
- `inspect`
- `instance_eval`
- `instance_exec`
- `instance_of?`
- `instance_variable_defined?`
- `instance_variable_get`
- `instance_variable_set`
- `instance_variables`
- `is_a?`
- `iterator?`
- `itself`

- `kind_of?`
- `lambda`
- `local_variables`
- `log`
- `log_info`
- `log_once`
- `log_once_info`
- `loop`
- `metadata_object_id`
- `method_missing`
- `methods`
- `nil?`
- `numeric_or_default`
- `object_id`
- `open`
- `or`
- `original_puts`
- `p`
- `parse`
- `primitive?`
- `primitive_determined?`
- `print`
- `printf`
- `private_methods`
- `proc`
- `protected_methods`
- `public_methods`
- `purge_class`
- `puts`
- `putc`
- `raise`
- `raise_error_with_kind_of_okay_message`
- `raise_immediately`
- `raise_method_missing_better_error`
- `raise_with_caller`
- `rand`
- `reload`
- `remove_instance_variable`
- `require`
- `respond_to?`
- `send`
- `singleton_class`
- `singleton_methods`
- `sprintf`
- `srand`
- `tap`

- then
- tick
- to_enum
- to_s
- yield_self

[Top](#)

Class: (class Object)::(class FFI::File)

FFI::File

- !
- !=
- !~
- ==
- ===
- Array
- Float
- Hash
- Integer
- String
- __caller_without_noise__
- __case_eqq
- __custom_object_methods__
- __gtk_ruby_source_files__
- __gtk_ruby_string_contains_source_file_path__?
- __id__
- __method__
- __object_methods__
- __pretty_print_exception__
- __printstr__
- __send__
- __supports_ivars__?
- _inspect
- ““““
- and
- better_instance_information
- block_given?
- caller
- class
- class_defined?
- clone
- define_singleton_method

- dig
- dup
- enum_for
- eql?
- equal?
- extend
- fail
- fast_rand
- format
- freeze
- frozen?
- getc
- gets
- global_variables
- hash
- help
- here
- initialize
- initialize_copy
- inspect
- instance_eval
- instance_exec
- instance_of?
- instance_variable_defined?
- instance_variable_get
- instance_variable_set
- instance_variables
- is_a?
- iterator?
- itself
- kind_of?
- lambda
- loadfile
- local_variables
- log
- log_info
- log_once
- log_once_info
- loop
- metadata_object_id
- method_missing
- methods
- mtime
- nil?
- numeric_or_default
- object_id

- open
- or
- original_puts
- p
- primitive?
- primitive_determined?
- print
- printf
- private_methods
- proc
- protected_methods
- public_methods
- purge_class
- puts
- putsc
- raise
- raise_error_with_kind_of_okay_message
- raise_immediately
- raise_method_missing_better_error
- raise_with_caller
- rand
- remove_instance_variable
- require
- respond_to?
- send
- singleton_class
- singleton_methods
- sprintf
- srand
- storefile
- tap
- then
- tick
- to_enum
- to_s
- yield_self

[Top](#)

Class: (class Object)::(class GTK::OpenEntity)

args.state

- !

- !=
- !~
- ==
- ===
- Array
- Float
- Hash
- Integer
- String
- __caller_without_noise__
- __case_eqq
- __contains_array_indexers__
- __contains_array_indexers__=
- __custom_object_methods__
- __get_hash_property__
- __gtk_ruby_source_files__
- __gtk_ruby_string_contains_source_file_path__?
- __id__
- __meta__
- __method__
- __object_methods__
- __pretty_print_exception__
- __printstr__
- __reserved_keys__
- __send__
- __set_hash_property__
- __supports_ivars__?
- __touched__
- __touched__=
- _inspect
- ““““
- and
- attributes
- better_instance_information
- block_given?
- caller
- class
- class_defined?
- clear!
- clone
- created_at_elapsed
- define_singleton_method
- dig
- documenter_success
- dup
- entity_id

- enum_for
- eql?
- equal?
- extend
- fail
- fast_rand
- format
- freeze
- frozen?
- getc
- gets
- global_created_at_elapsed
- global_variables
- hash
- help
- here
- initialize
- initialize_copy
- inspect
- instance_eval
- instance_exec
- instance_of?
- instance_variable_defined?
- instance_variable_get
- instance_variable_set
- instance_variables
- is_a?
- iterator?
- itself
- kind_of?
- lambda
- local_variables
- log
- log_info
- log_once
- log_once_info
- loop
- meta
- meta!
- metadata_object_id
- method_missing
- methods
- new?
- new_entity
- new_entity_strict
- nil?

- `numeric_or_default`
- `object_id`
- `old?`
- `open`
- `or`
- `original_eq_eq`
- `original_puts`
- `p`
- `primitive?`
- `primitive_determined?`
- `print`
- `printf`
- `private_methods`
- `proc`
- `protected_methods`
- `public_methods`
- `purge_class`
- `puts`
- `putc`
- `raise`
- `raise_error_with_kind_of_okay_message`
- `raise_immediately`
- `raise_method_missing_better_error`
- `raise_with_caller`
- `rand`
- `remove_instance_variable`
- `require`
- `respond_to?`
- `send`
- `set!`
- `singleton_class`
- `singleton_methods`
- `sprintf`
- `srand`
- `tap`
- `then`
- `tick`
- `tick_count=`
- `to_enum`
- `to_s`
- `with_meta`
- `yield_self`

[Top](#)

Class: (class Object)::(class Module)

GC

- !
- !=
- !~
- ==
- ===
- Array
- Float
- Hash
- Integer
- String
- __caller_without_noise__
- __case_eqq
- __custom_object_methods__
- __gtk_ruby_source_files__
- __gtk_ruby_string_contains_source_file_path__?
- __id__
- __method__
- __object_methods__
- __pretty_print_exception__
- __printstr__
- __send__
- __supports_ivars__?
- _inspect
- ““““
- alias_method
- ancestors
- and
- append_features
- attr
- attr_accessor
- attr_reader
- attr_writer
- better_instance_information
- block_given?
- caller
- class
- class_defined?
- class_eval
- class_exec
- class_variable_defined?
- class_variable_get
- class_variable_set

- `class_variables`
- `clone`
- `const_defined?`
- `const_get`
- `const_missing`
- `const_set`
- `constants`
- `define_method`
- `define_singleton_method`
- `dig`
- `disable`
- `dup`
- `enable`
- `enum_for`
- `eql?`
- `equal?`
- `extend`
- `extend_object`
- `extended`
- `fail`
- `fast_rand`
- `format`
- `freeze`
- `frozen?`
- `generational_mode`
- `generational_mode=`
- `getc`
- `gets`
- `global_variables`
- `hash`
- `help`
- `here`
- `include`
- `include?`
- `included`
- `included_modules`
- `initialize`
- `initialize_copy`
- `inspect`
- `instance_eval`
- `instance_exec`
- `instance_methods`
- `instance_of?`
- `instance_variable_defined?`
- `instance_variable_get`
- `instance_variable_set`

- instance_variables
- interval_ratio
- interval_ratio=
- is_a?
- iterator?
- itself
- kind_of?
- lambda
- local_variables
- log
- log_info
- log_once
- log_once_info
- loop
- metadata_object_id
- method_defined?
- method_missing
- method_removed
- methods
- module_eval
- module_exec
- module_function
- name
- nil?
- numeric_or_default
- object_id
- open
- or
- original_puts
- p
- prepend
- prepend_features
- prepended
- primitive?
- primitive_determined?
- print
- printf
- private
- private_methods
- proc
- protected
- protected_methods
- public
- public_methods
- purge_class
- puts

- `putc`
- `raise`
- `raise_error_with_kind_of_okay_message`
- `raise_immediately`
- `raise_method_missing_better_error`
- `raise_with_caller`
- `rand`
- `remove_class_variable`
- `remove_const`
- `remove_instance_variable`
- `remove_method`
- `require`
- `respond_to?`
- `send`
- `singleton_class`
- `singleton_class?`
- `singleton_methods`
- `sprintf`
- `srand`
- `start`
- `step_ratio`
- `step_ratio=`
- `tap`
- `then`
- `tick`
- `to_enum`
- `to_s`
- `undef_method`
- `yield_self`

[Top](#)

Class: `(class Object)::(class GTK::Grid`

`(included_modules [Serialize]))` *args.grid*

- `!`
- `!=`
- `!~`
- `==`
- `===`
- `Array`
- `Float`
- `Hash`

- Integer
- String
- `__caller_without_noise__`
- `__case_eqq`
- `__custom_object_methods__`
- `__gtk_ruby_source_files__`
- `__gtk_ruby_string_contains_source_file_path__?`
- `__id__`
- `__method__`
- `__object_methods__`
- `__pretty_print_exception__`
- `__print_origin_help`
- `__printstr__`
- `__send__`
- `__supports_ivars__?`
- `_inspect`
- `““““`
- `and`
- `better_instance_information`
- `block_given?`
- `bottom`
- `bottom=`
- `caller`
- `center_x`
- `center_x=`
- `center_y`
- `center_y=`
- `class`
- `class_defined?`
- `clone`
- `define_singleton_method`
- `dig`
- `dup`
- `enum_for`
- `eql?`
- `equal?`
- `extend`
- `fail`
- `fast_rand`
- `format`
- `freeze`
- `frozen?`
- `getc`
- `gets`
- `global_variables`
- `h`

- h_half
- hash
- help
- here
- initialize
- initialize_copy
- inspect
- instance_eval
- instance_exec
- instance_of?
- instance_variable_defined?
- instance_variable_get
- instance_variable_set
- instance_variables
- is_a?
- iterator?
- itself
- kind_of?
- lambda
- left
- left=
- local_variables
- log
- log_info
- log_once
- log_once_info
- loop
- metadata_object_id
- method_missing
- methods
- name
- name=
- nil?
- numeric_or_default
- object_id
- open
- or
- origin_bottom_left!
- origin_center!
- origin_x
- origin_x=
- origin_y
- origin_y=
- original_puts
- p
- primitive?

- `primitive_determined?`
- `print`
- `printf`
- `private_methods`
- `proc`
- `protected_methods`
- `public_methods`
- `purge_class`
- `puts`
- `putc`
- `raise`
- `raise_error_with_kind_of_okay_message`
- `raise_immediately`
- `raise_method_missing_better_error`
- `raise_with_caller`
- `rand`
- `rect`
- `rect=`
- `remove_instance_variable`
- `require`
- `respond_to?`
- `right`
- `right=`
- `send`
- `serialize`
- `singleton_class`
- `singleton_methods`
- `sprintf`
- `srand`
- `tap`
- `then`
- `tick`
- `to_enum`
- `to_s`
- `top`
- `top=`
- `transform_angle`
- `transform_rect`
- `transform_x`
- `transform_y`
- `untransform_x`
- `untransform_y`
- `w`
- `w_half`
- `yield_self`

[Top](#)

Class: (class Object)::(class IO

(included_modules [Enumerable])) *IO.new(IO.sysopen("/dev/tty", "w"), "w")*

- !
- !=
- !~
- <<
- ==
- ===
- Array
- Float
- Hash
- Integer
- String
- __caller_without_noise__
- __case_eqq
- __custom_object_methods__
- __gtk_ruby_source_files__
- __gtk_ruby_string_contains_source_file_path__?
- __id__
- __method__
- __object_methods__
- __pretty_print_exception__
- __printstr__
- __send__
- __supports_ivars__?
- __update_hash
- _check_readable
- _inspect
- _read_buf
- ““““
- all?
- and
- any?
- better_instance_information
- block_given?
- caller
- class
- class_defined?
- clone
- close

- `close_on_exec=`
- `close_on_exec?`
- `close_write`
- `closed?`
- `collect`
- `collect_concat`
- `count`
- `cycle`
- `define_singleton_method`
- `detect`
- `dig`
- `drop`
- `drop_while`
- `dup`
- `each`
- `each_byte`
- `each_char`
- `each_cons`
- `each_line`
- `each_slice`
- `each_with_index`
- `each_with_object`
- `entries`
- `enum_for`
- `eof`
- `eof?`
- `eql?`
- `equal?`
- `extend`
- `fail`
- `fast_rand`
- `fileno`
- `find`
- `find_all`
- `find_index`
- `first`
- `flat_map`
- `flush`
- `format`
- `freeze`
- `frozen?`
- `getc`
- `gets`
- `global_variables`
- `grep`
- `group_by`

- hash
- help
- here
- include?
- initialize
- initialize_copy
- inject
- inspect
- instance_eval
- instance_exec
- instance_of?
- instance_variable_defined?
- instance_variable_get
- instance_variable_set
- instance_variables
- is_a?
- isatty
- iterator?
- itself
- kind_of?
- lambda
- lazy
- local_variables
- log
- log_info
- log_once
- log_once_info
- loop
- map
- max
- max_by
- member?
- metadata_object_id
- method_missing
- methods
- min
- min_by
- minmax
- minmax_by
- nil?
- none?
- numeric_or_default
- object_id
- one?
- open
- or

- original_puts
- p
- partition
- pid
- pos
- pos=
- primitive?
- primitive_determined?
- print
- printf
- private_methods
- proc
- protected_methods
- public_methods
- purge_class
- puts
- putsc
- raise
- raise_error_with_kind_of_okay_message
- raise_immediately
- raise_method_missing_better_error
- raise_with_caller
- rand
- read
- readchar
- readline
- readlines
- reduce
- reject
- remove_instance_variable
- require
- respond_to?
- reverse_each
- rewind
- seek
- select
- send
- singleton_class
- singleton_methods
- sort
- sort_by
- sprintf
- srand
- sync
- sync=
- sysread

- `sysseek`
- `syswrite`
- `take`
- `take_while`
- `tap`
- `tell`
- `then`
- `tick`
- `to_a`
- `to_enum`
- `to_h`
- `to_i`
- `to_s`
- `tty?`
- `ungetc`
- `uniq`
- `write`
- `yield_self`
- `zip`

[Top](#)

Class: (class IO

(included_modules [Enumerable]))::(class File (superclass (class IO (included_modules [Enumerable]))) (included_modules [File::Constants, Enumerable])) *File.open*

- `!`
- `!=`
- `!~`
- `<<`
- `==`
- `===`
- `Array`
- `Float`
- `Hash`
- `Integer`
- `String`
- `__caller_without_noise__`
- `__case_eqq`
- `__custom_object_methods__`
- `__gtk_ruby_source_files__`
- `__gtk_ruby_string_contains_source_file_path__?`

- `__id__`
- `__method__`
- `__object_methods__`
- `__pretty_print_exception__`
- `__printstr__`
- `__send__`
- `__supports_ivars__?`
- `__update_hash`
- `_check_readable`
- `_inspect`
- `_read_buf`
- `““““`
- `all?`
- `and`
- `any?`
- `better_instance_information`
- `block_given?`
- `caller`
- `class`
- `class_defined?`
- `clone`
- `close`
- `close_on_exec=`
- `close_on_exec?`
- `close_write`
- `closed?`
- `collect`
- `collect_concat`
- `count`
- `cycle`
- `define_singleton_method`
- `detect`
- `dig`
- `drop`
- `drop_while`
- `dup`
- `each`
- `each_byte`
- `each_char`
- `each_cons`
- `each_line`
- `each_slice`
- `each_with_index`
- `each_with_object`
- `entries`
- `enum_for`

- eof
- eof?
- eql?
- equal?
- extend
- fail
- fast_rand
- fileno
- find
- find_all
- find_index
- first
- flat_map
- flock
- flush
- format
- freeze
- frozen?
- getc
- gets
- global_variables
- grep
- group_by
- hash
- help
- here
- include?
- initialize
- initialize_copy
- inject
- inspect
- instance_eval
- instance_exec
- instance_of?
- instance_variable_defined?
- instance_variable_get
- instance_variable_set
- instance_variables
- is_a?
- isatty
- iterator?
- itself
- kind_of?
- lambda
- lazy
- local_variables

- log
- log_info
- log_once
- log_once_info
- loop
- map
- max
- max_by
- member?
- metadata_object_id
- method_missing
- methods
- min
- min_by
- minmax
- minmax_by
- mtime
- nil?
- none?
- numeric_or_default
- object_id
- one?
- open
- or
- original_puts
- p
- partition
- path
- path=
- pid
- pos
- pos=
- primitive?
- primitive_determined?
- print
- printf
- private_methods
- proc
- protected_methods
- public_methods
- purge_class
- puts
- putsc
- raise
- raise_error_with_kind_of_okay_message
- raise_immediately

- `raise_method_missing_better_error`
- `raise_with_caller`
- `rand`
- `read`
- `readchar`
- `readline`
- `readlines`
- `reduce`
- `reject`
- `remove_instance_variable`
- `require`
- `respond_to?`
- `reverse_each`
- `rewind`
- `seek`
- `select`
- `send`
- `singleton_class`
- `singleton_methods`
- `sort`
- `sort_by`
- `sprintf`
- `srand`
- `sync`
- `sync=`
- `sysread`
- `sysseek`
- `syswrite`
- `take`
- `take_while`
- `tap`
- `tell`
- `then`
- `tick`
- `to_a`
- `to_enum`
- `to_h`
- `to_i`
- `to_s`
- `tty?`
- `ungetc`
- `uniq`
- `write`
- `yield_self`
- `zip`

[Top](#)

Class: (class Object)::(class NilClass

(included_modules [NilClassFalseClass])) *\$layout*

- !
- !=
- !~
- &
- +
- <
- <=
- ==
- ===
- >
- >=
- Array
- Float
- Hash
- Integer
- String
- ^
- __caller_without_noise__
- __case_eqq
- __check_thrash__!
- __custom_object_methods__
- __gtk_ruby_source_files__
- __gtk_ruby_string_contains_source_file_path__?
- __id__
- __method__
- __object_methods__
- __pretty_print_exception__
- __printstr__
- __send__
- __supports_ivars__?
- _inspect
- ““““
- and
- assign_method_missing
- background_color
- better_instance_information
- block_given?
- caller

- class
- class_defined?
- clone
- define_singleton_method
- dig
- dup
- enum_for
- eql?
- equal?
- extend
- fail
- fast_rand
- feels_like_an_array?
- format
- frame_index
- freeze
- frozen?
- getc
- gets
- global_variables
- hash
- help
- here
- initialize
- initialize_copy
- inspect
- instance_eval
- instance_exec
- instance_of?
- instance_variable_defined?
- instance_variable_get
- instance_variable_set
- instance_variables
- is_a?
- iterator?
- itself
- kind_of?
- lambda
- local_variables
- log
- log_info
- log_once
- log_once_info
- loop
- metadata_object_id
- method_missing

- methods
- nil?
- numeric_or_default
- object_id
- open
- or
- original_puts
- p
- primitive?
- primitive_determined?
- print
- printf
- private_methods
- proc
- protected_methods
- public_methods
- purge_class
- puts
- putsc
- raise
- raise_error_with_kind_of_okay_message
- raise_immediately
- raise_method_missing_better_error
- raise_with_caller
- rand
- remove_instance_variable
- require
- respond_to?
- send
- serialize
- singleton_class
- singleton_methods
- sprintf
- srand
- tap
- then
- tick
- to_a
- to_enum
- to_f
- to_h
- to_i
- to_s
- unassign_method_missing
- unassign_method_missing_and_raise
- yield_self

- |

[Top](#)

Class: (class Object)::(class GTK::Outputs)

args.outputs

- !
- !=
- !~
- ==
- ===
- Array
- Float
- Hash
- Integer
- String
- __borders=
- __caller_without_noise__
- __case_eqq
- __custom_object_methods__
- __gtk_ruby_source_files__
- __gtk_ruby_string_contains_source_file_path__?
- __id__
- __labels=
- __lines=
- __method__
- __object_methods__
- __pretty_print_exception__
- __primitives=
- __printstr__
- __raise_deprecated__
- __reserved=
- __send__
- __solids=
- __sprites=
- __static_borders=
- __static_labels=
- __static_lines=
- __static_primitives=
- __static_reserved=
- __static_solids=
- __static_sprites=

- `__supports_ivars__?`
- `_inspect`
- `““““`
- `all_borders`
- `all_labels`
- `all_lines`
- `all_primitives`
- `all_reserved`
- `all_solids`
- `all_sounds`
- `all_sprites`
- `and`
- `better_instance_information`
- `block_given?`
- `borders`
- `borders=`
- `caller`
- `class`
- `class_defined?`
- `clear`
- `clear_non_static`
- `clone`
- `define_singleton_method`
- `dig`
- `dup`
- `enum_for`
- `eql?`
- `equal?`
- `extend`
- `fail`
- `fast_rand`
- `format`
- `freeze`
- `frozen?`
- `getc`
- `gets`
- `global_variables`
- `hash`
- `height`
- `height=`
- `help`
- `here`
- `initialize`
- `initialize_copy`
- `inspect`
- `instance_eval`

- `instance_exec`
- `instance_of?`
- `instance_variable_defined?`
- `instance_variable_get`
- `instance_variable_set`
- `instance_variables`
- `is_a?`
- `iterator?`
- `itself`
- `kind_of?`
- `labels`
- `labels=`
- `lambda`
- `lines`
- `lines=`
- `local_variables`
- `log`
- `log_info`
- `log_once`
- `log_once_info`
- `loop`
- `metadata_object_id`
- `method_missing`
- `methods`
- `nil?`
- `numeric_or_default`
- `object_id`
- `open`
- `or`
- `original_puts`
- `p`
- `primitive?`
- `primitive_determined?`
- `primitives`
- `primitives=`
- `print`
- `printf`
- `private_methods`
- `proc`
- `protected_methods`
- `public_methods`
- `purge_class`
- `puts`
- `putc`
- `raise`
- `raise_error_with_kind_of_okay_message`

- `raise_immediately`
- `raise_method_missing_better_error`
- `raise_with_caller`
- `rand`
- `remove_instance_variable`
- `require`
- `reserved`
- `reserved=`
- `respond_to?`
- `send`
- `serialize`
- `singleton_class`
- `singleton_methods`
- `solids`
- `solids=`
- `sounds`
- `sounds=`
- `sprintf`
- `sprites`
- `sprites=`
- `srand`
- `static_borders`
- `static_borders=`
- `static_labels`
- `static_labels=`
- `static_lines`
- `static_lines=`
- `static_primitives`
- `static_primitives=`
- `static_reserved`
- `static_reserved=`
- `static_solids`
- `static_solids=`
- `static_sprites`
- `static_sprites=`
- `tap`
- `target`
- `target=`
- `then`
- `tick`
- `to_enum`
- `to_s`
- `width`
- `width=`
- `yield_self`

[Top](#)

Class: (class Object)::(class Array

(included__modules [GTK::Primitive::ConversionCapabilities, Enumerable]))

args.passes

- !
- !=
- !~
- &
- *
- +
- -
- <<
- <=>
- ==
- ===
- Array
- Float
- Hash
- Integer
- String
- []
- []=
- __ary_cmp
- __ary_eq
- __ary_index
- __caller_without_noise__
- __case_eqq
- __custom_object_methods__
- __gtk_ruby_source_files__
- __gtk_ruby_string_contains_source_file_path__?
- __id__
- __method__
- __object_methods__
- __original_add__
- __original_add_single__
- __pretty_print_exception__
- __printstr__
- __send__
- __sort_sub__
- __supports_ivars__?
- __svalue

- `__update_hash`
- `_inspect`
- `““““`
- `a`
- `a=`
- `all?`
- `and`
- `angle`
- `angle=`
- `angle_given_point`
- `any?`
- `any_intersects_rect?`
- `append`
- `assoc`
- `at`
- `better_instance_information`
- `block_given?`
- `border`
- `bottom`
- `bsearch`
- `bsearch_index`
- `caller`
- `center_inside_rect`
- `class`
- `class_defined?`
- `clear`
- `clone`
- `collect`
- `collect!`
- `collect_concat`
- `combination`
- `compact`
- `compact!`
- `concat`
- `count`
- `cycle`
- `define_singleton_method`
- `delete`
- `delete_at`
- `delete_if`
- `detect`
- `dig`
- `drop`
- `drop_while`
- `dup`
- `each`

- each_cons
- each_index
- each_slice
- each_with_index
- each_with_object
- empty?
- entries
- enum_for
- eql?
- equal?
- extend
- fail
- fast_rand
- fetch
- fill
- find
- find_all
- find_index
- first
- flat_map
- flatten
- flatten!
- format
- freeze
- frozen?
- getc
- gets
- global_variables
- grep
- group_by
- h
- h_half
- hash
- height
- height_half
- help
- here
- include?
- include_any?
- index
- initialize
- initialize_copy
- inject
- insert
- inside_rect?
- inspect

- instance_eval
- instance_exec
- instance_of?
- instance_variable_defined?
- instance_variable_get
- instance_variable_set
- instance_variables
- intersects_rect?
- is_a?
- iterator?
- itself
- join
- keep_if
- kind_of?
- label
- lambda
- last
- lazy
- left
- length
- line
- local_variables
- log
- log_info
- log_once
- log_once_info
- loop
- map
- map!
- map_2d
- mark_as_border!
- mark_as_common!
- mark_as_label!
- mark_as_line!
- mark_as_point!
- mark_as_primitive!
- mark_as_rect!
- mark_as_solid!
- mark_as_sprite!
- max
- max_by
- member?
- metadata_object_id
- method_missing
- methods
- min

- min_by
- minmax
- minmax_by
- nil?
- none?
- numeric_or_default
- object_id
- one?
- open
- or
- original_puts
- p
- pack
- pairs_to_hash
- partition
- path
- path=
- permutation
- point
- pop
- prepend
- primitive?
- primitive_determined?
- print
- printf
- private_methods
- proc
- product
- protected_methods
- public_methods
- purge_class
- push
- puts
- putsc
- raise
- raise_error_with_kind_of_okay_message
- raise_immediately
- raise_method_missing_better_error
- raise_with_caller
- rand
- rassoc
- rect
- rect_shift
- rect_shift_down
- rect_shift_left
- rect_shift_right

- rect_shift_up
- reduce
- reject
- reject!
- reject_false
- reject_nil
- remove_instance_variable
- replace
- require
- respond_to?
- rest
- reverse
- reverse!
- reverse_each
- right
- rindex
- rotate
- rotate!
- sample
- scale_rect
- select
- select!
- send
- serialize
- shift
- shift_rect
- shuffle
- shuffle!
- singleton_class
- singleton_methods
- size
- slice
- slice!
- solid
- sort
- sort!
- sort_by
- sprintf
- sprite
- srand
- take
- take_while
- tap
- text
- text=
- then

- tick
- to_a
- to_a_pairs
- to_ary
- to_enum
- to_h
- to_s
- top
- transpose
- uniq
- uniq!
- unshift
- values_at
- w
- w_half
- width
- width_half
- x
- x2
- x=
- y
- y2
- y=
- yield_self
- zip
- |

[Top](#)

Class: (class Object)::(class GTK::Inputs)

args.inputs

- !
- !=
- !~
- ==
- ===
- Array
- Float
- Hash
- Integer
- String
- __caller_without_noise__

- `__case_eqq`
- `__custom_object_methods__`
- `__gtk_ruby_source_files__`
- `__gtk_ruby_string_contains_source_file_path__?`
- `__id__`
- `__method__`
- `__object_methods__`
- `__pretty_print_exception__`
- `__printstr__`
- `__send__`
- `__supports_ivars__?`
- `_inspect`
- `““““`
- `and`
- `better_instance_information`
- `block_given?`
- `caller`
- `class`
- `class_defined?`
- `clone`
- `controller_one`
- `controller_two`
- `controllers`
- `controllers=`
- `define_singleton_method`
- `dig`
- `dup`
- `enum_for`
- `eql?`
- `equal?`
- `extend`
- `fail`
- `fast_rand`
- `format`
- `freeze`
- `frozen?`
- `getc`
- `gets`
- `global_variables`
- `hash`
- `help`
- `here`
- `history`
- `history=`
- `initialize`
- `initialize_copy`

- inspect
- instance_eval
- instance_exec
- instance_of?
- instance_variable_defined?
- instance_variable_get
- instance_variable_set
- instance_variables
- is_a?
- iterator?
- itself
- keyboard
- keyboard=
- kind_of?
- lambda
- local_variables
- log
- log_info
- log_once
- log_once_info
- loop
- metadata_object_id
- method_missing
- methods
- mouse
- mouse=
- nil?
- numeric_or_default
- object_id
- open
- or
- original_puts
- p
- primitive?
- primitive_determined?
- print
- printf
- private_methods
- proc
- protected_methods
- public_methods
- purge_class
- puts
- putsc
- raise
- raise_error_with_kind_of_okay_message

- `raise_immediately`
- `raise_method_missing_better_error`
- `raise_with_caller`
- `rand`
- `remove_instance_variable`
- `require`
- `respond_to?`
- `send`
- `serialize`
- `singleton_class`
- `singleton_methods`
- `sprintf`
- `srand`
- `tap`
- `text`
- `text=`
- `then`
- `tick`
- `to_enum`
- `to_s`
- `yield_self`

[Top](#)

Class: (class Object)::(class GTK::Controller)

args.inputs.controller_one

- `!`
- `!=`
- `!~`
- `==`
- `===`
- `Array`
- `Float`
- `Hash`
- `Integer`
- `String`
- `__caller_without_noise__`
- `__case_eqq`
- `__custom_object_methods__`
- `__gtk_ruby_source_files__`
- `__gtk_ruby_string_contains_source_file_path__?`
- `__id__`

- `__method__`
- `__object_methods__`
- `__pretty_print_exception__`
- `__printstr__`
- `__send__`
- `__supports_ivars__?`
- `_inspect`
- `““““`
- `and`
- `better_instance_information`
- `block_given?`
- `caller`
- `class`
- `class_defined?`
- `clear`
- `clone`
- `define_singleton_method`
- `dig`
- `dup`
- `enum_for`
- `eql?`
- `equal?`
- `extend`
- `fail`
- `fast_rand`
- `format`
- `freeze`
- `frozen?`
- `getc`
- `gets`
- `global_variables`
- `hash`
- `help`
- `here`
- `initialize`
- `initialize_copy`
- `inspect`
- `instance_eval`
- `instance_exec`
- `instance_of?`
- `instance_variable_defined?`
- `instance_variable_get`
- `instance_variable_set`
- `instance_variables`
- `is_a?`
- `iterator?`

- itself
- key_down
- key_down=
- key_held
- key_held=
- key_up
- key_up=
- kind_of?
- lambda
- left_analog_x_perc
- left_analog_x_perc=
- left_analog_x_raw
- left_analog_x_raw=
- left_analog_y_perc
- left_analog_y_perc=
- left_analog_y_raw
- left_analog_y_raw=
- left_right
- left_right=
- local_variables
- log
- log_info
- log_once
- log_once_info
- loop
- metadata_object_id
- method_missing
- methods
- nil?
- numeric_or_default
- object_id
- open
- or
- original_puts
- p
- primitive?
- primitive_determined?
- print
- printf
- private_methods
- proc
- protected_methods
- public_methods
- purge_class
- puts
- putsc

- raise
- raise_error_with_kind_of_okay_message
- raise_immediately
- raise_method_missing_better_error
- raise_with_caller
- rand
- remove_instance_variable
- require
- respond_to?
- right_analog_x_perc
- right_analog_x_perc=
- right_analog_x_raw
- right_analog_x_raw=
- right_analog_y_perc
- right_analog_y_perc=
- right_analog_y_raw
- right_analog_y_raw=
- send
- serialize
- singleton_class
- singleton_methods
- sprintf
- srand
- tap
- then
- tick
- to_enum
- to_s
- up_down
- up_down=
- yield_self

[Top](#)

Class: (class Object)::(class GTK::Controller)

args.inputs.controller_two

- !
- !=
- !~
- ==
- ===
- Array

- Float
- Hash
- Integer
- String
- `__caller_without_noise__`
- `__case_eqq`
- `__custom_object_methods__`
- `__gtk_ruby_source_files__`
- `__gtk_ruby_string_contains_source_file_path__?`
- `__id__`
- `__method__`
- `__object_methods__`
- `__pretty_print_exception__`
- `__printstr__`
- `__send__`
- `__supports_ivars__?`
- `_inspect`
- `““““`
- `and`
- `better_instance_information`
- `block_given?`
- `caller`
- `class`
- `class_defined?`
- `clear`
- `clone`
- `define_singleton_method`
- `dig`
- `dup`
- `enum_for`
- `eql?`
- `equal?`
- `extend`
- `fail`
- `fast_rand`
- `format`
- `freeze`
- `frozen?`
- `getc`
- `gets`
- `global_variables`
- `hash`
- `help`
- `here`
- `initialize`
- `initialize_copy`

- inspect
- instance_eval
- instance_exec
- instance_of?
- instance_variable_defined?
- instance_variable_get
- instance_variable_set
- instance_variables
- is_a?
- iterator?
- itself
- key_down
- key_down=
- key_held
- key_held=
- key_up
- key_up=
- kind_of?
- lambda
- left_analog_x_perc
- left_analog_x_perc=
- left_analog_x_raw
- left_analog_x_raw=
- left_analog_y_perc
- left_analog_y_perc=
- left_analog_y_raw
- left_analog_y_raw=
- left_right
- left_right=
- local_variables
- log
- log_info
- log_once
- log_once_info
- loop
- metadata_object_id
- method_missing
- methods
- nil?
- numeric_or_default
- object_id
- open
- or
- original_puts
- p
- primitive?

- `primitive_determined?`
- `print`
- `printf`
- `private_methods`
- `proc`
- `protected_methods`
- `public_methods`
- `purge_class`
- `puts`
- `putc`
- `raise`
- `raise_error_with_kind_of_okay_message`
- `raise_immediately`
- `raise_method_missing_better_error`
- `raise_with_caller`
- `rand`
- `remove_instance_variable`
- `require`
- `respond_to?`
- `right_analog_x_perc`
- `right_analog_x_perc=`
- `right_analog_x_raw`
- `right_analog_x_raw=`
- `right_analog_y_perc`
- `right_analog_y_perc=`
- `right_analog_y_raw`
- `right_analog_y_raw=`
- `send`
- `serialize`
- `singleton_class`
- `singleton_methods`
- `sprintf`
- `srand`
- `tap`
- `then`
- `tick`
- `to_enum`
- `to_s`
- `up_down`
- `up_down=`
- `yield_self`

[Top](#)

Class: (class Object)::(class Array

(included_modules [GTK::Primitive::ConversionCapabilities, Enumerable]))

args.inputs.controllers

- !
- !=
- !~
- &
- *
- +
- -
- <<
- <=>
- ==
- ===
- Array
- Float
- Hash
- Integer
- String
- []
- []=
- __ary_cmp
- __ary_eq
- __ary_index
- __caller_without_noise__
- __case_eqq
- __custom_object_methods__
- __gtk_ruby_source_files__
- __gtk_ruby_string_contains_source_file_path__?
- __id__
- __method__
- __object_methods__
- __original_add__
- __original_add_single__
- __pretty_print_exception__
- __printstr__
- __send__
- __sort_sub__
- __supports_ivars__?
- __svalue
- __update_hash
- _inspect
- ““““
- a

- a=
- all?
- and
- angle
- angle=
- angle_given_point
- any?
- any_intersects_rect?
- append
- assoc
- at
- better_instance_information
- block_given?
- border
- bottom
- bsearch
- bsearch_index
- caller
- center_inside_rect
- class
- class_defined?
- clear
- clone
- collect
- collect!
- collect_concat
- combination
- compact
- compact!
- concat
- count
- cycle
- define_singleton_method
- delete
- delete_at
- delete_if
- detect
- dig
- drop
- drop_while
- dup
- each
- each_cons
- each_index
- each_slice
- each_with_index

- `each_with_object`
- `empty?`
- `entries`
- `enum_for`
- `eql?`
- `equal?`
- `extend`
- `fail`
- `fast_rand`
- `fetch`
- `fill`
- `find`
- `find_all`
- `find_index`
- `first`
- `flat_map`
- `flatten`
- `flatten!`
- `format`
- `freeze`
- `frozen?`
- `getc`
- `gets`
- `global_variables`
- `grep`
- `group_by`
- `h`
- `h_half`
- `hash`
- `height`
- `height_half`
- `help`
- `here`
- `include?`
- `include_any?`
- `index`
- `initialize`
- `initialize_copy`
- `inject`
- `insert`
- `inside_rect?`
- `inspect`
- `instance_eval`
- `instance_exec`
- `instance_of?`
- `instance_variable_defined?`

- instance_variable_get
- instance_variable_set
- instance_variables
- intersects_rect?
- is_a?
- iterator?
- itself
- join
- keep_if
- kind_of?
- label
- lambda
- last
- lazy
- left
- length
- line
- local_variables
- log
- log_info
- log_once
- log_once_info
- loop
- map
- map!
- map_2d
- mark_as_border!
- mark_as_common!
- mark_as_label!
- mark_as_line!
- mark_as_point!
- mark_as_primitive!
- mark_as_rect!
- mark_as_solid!
- mark_as_sprite!
- max
- max_by
- member?
- metadata_object_id
- method_missing
- methods
- min
- min_by
- minmax
- minmax_by
- nil?

- none?
- numeric_or_default
- object_id
- one?
- open
- or
- original_puts
- p
- pack
- pairs_to_hash
- partition
- path
- path=
- permutation
- point
- pop
- prepend
- primitive?
- primitive_determined?
- print
- printf
- private_methods
- proc
- product
- protected_methods
- public_methods
- purge_class
- push
- puts
- putsc
- raise
- raise_error_with_kind_of_okay_message
- raise_immediately
- raise_method_missing_better_error
- raise_with_caller
- rand
- rassoc
- rect
- rect_shift
- rect_shift_down
- rect_shift_left
- rect_shift_right
- rect_shift_up
- reduce
- reject
- reject!

- reject_false
- reject_nil
- remove_instance_variable
- replace
- require
- respond_to?
- rest
- reverse
- reverse!
- reverse_each
- right
- rindex
- rotate
- rotate!
- sample
- scale_rect
- select
- select!
- send
- serialize
- shift
- shift_rect
- shuffle
- shuffle!
- singleton_class
- singleton_methods
- size
- slice
- slice!
- solid
- sort
- sort!
- sort_by
- sprintf
- sprite
- srand
- take
- take_while
- tap
- text
- text=
- then
- tick
- to_a
- to_a_pairs
- to_ary

- to_enum
- to_h
- to_s
- top
- transpose
- uniq
- uniq!
- unshift
- values_at
- w
- w_half
- width
- width_half
- x
- x2
- x=
- y
- y2
- y=
- yield_self
- zip
- |

[Top](#)

Class: (class Object)::(class GTK::Keyboard)

args.inputs.keyboard

- !
- !=
- !~
- ==
- ===
- Array
- Float
- Hash
- Integer
- String
- __caller_without_noise__
- __case_eqq
- __custom_object_methods__
- __gtk_ruby_source_files__
- __gtk_ruby_string_contains_source_file_path__?

- `__id__`
- `__method__`
- `__object_methods__`
- `__pretty_print_exception__`
- `__printstr__`
- `__send__`
- `__supports_ivars__?`
- `_inspect`
- `““““`
- `and`
- `better_instance_information`
- `block_given?`
- `caller`
- `class`
- `class_defined?`
- `clear`
- `clone`
- `define_singleton_method`
- `dig`
- `down`
- `dup`
- `enum_for`
- `eql?`
- `equal?`
- `extend`
- `fail`
- `fast_rand`
- `format`
- `freeze`
- `frozen?`
- `getc`
- `gets`
- `global_variables`
- `has_focus`
- `has_focus=`
- `hash`
- `help`
- `here`
- `initialize`
- `initialize_copy`
- `inspect`
- `instance_eval`
- `instance_exec`
- `instance_of?`
- `instance_variable_defined?`
- `instance_variable_get`

- instance_variable_set
- instance_variables
- is_a?
- iterator?
- itself
- key_down
- key_down=
- key_held
- key_held=
- key_up
- key_up=
- kind_of?
- lambda
- left
- left_right
- local_variables
- log
- log_info
- log_once
- log_once_info
- loop
- metadata_object_id
- method_missing
- methods
- nil?
- numeric_or_default
- object_id
- open
- or
- original_puts
- p
- primitive?
- primitive_determined?
- print
- printf
- private_methods
- proc
- protected_methods
- public_methods
- purge_class
- puts
- putsc
- raise
- raise_error_with_kind_of_okay_message
- raise_immediately
- raise_method_missing_better_error

- `raise_with_caller`
- `rand`
- `remove_instance_variable`
- `require`
- `respond_to?`
- `right`
- `send`
- `serialize`
- `singleton_class`
- `singleton_methods`
- `sprintf`
- `srand`
- `tap`
- `then`
- `tick`
- `to_enum`
- `to_s`
- `up`
- `up_down`
- `yield_self`

[Top](#)

Class: `(class Object)::(class GTK::Mouse)`

args.inputs.mouse

- `!`
- `!=`
- `!~`
- `==`
- `===`
- `Array`
- `Float`
- `Hash`
- `Integer`
- `String`
- `__caller_without_noise__`
- `__case_eqq`
- `__custom_object_methods__`
- `__gtk_ruby_source_files__`
- `__gtk_ruby_string_contains_source_file_path__?`
- `__id__`
- `__method__`

- `__object_methods__`
- `__pretty_print_exception__`
- `__printstr__`
- `__send__`
- `__supports_ivars__?`
- `_inspect`
- `““““`
- `and`
- `better_instance_information`
- `block_given?`
- `caller`
- `class`
- `class_defined?`
- `clear`
- `click`
- `click=`
- `clone`
- `define_singleton_method`
- `dig`
- `down`
- `dup`
- `enum_for`
- `eql?`
- `equal?`
- `extend`
- `fail`
- `fast_rand`
- `format`
- `freeze`
- `frozen?`
- `getc`
- `gets`
- `global_variables`
- `has_focus`
- `has_focus=`
- `hash`
- `help`
- `here`
- `initialize`
- `initialize_copy`
- `inspect`
- `instance_eval`
- `instance_exec`
- `instance_of?`
- `instance_variable_defined?`
- `instance_variable_get`

- instance_variable_set
- instance_variables
- is_a?
- iterator?
- itself
- kind_of?
- lambda
- local_variables
- log
- log_info
- log_once
- log_once_info
- loop
- metadata_object_id
- method_missing
- methods
- moved
- moved=
- moved_at
- moved_at=
- moved_at_time
- moved_at_time=
- nil?
- numeric_or_default
- object_id
- open
- or
- original_puts
- p
- position
- previous_click
- previous_click=
- primitive?
- primitive_determined?
- print
- printf
- private_methods
- proc
- protected_methods
- public_methods
- purge_class
- puts
- puts=
- raise
- raise_error_with_kind_of_okay_message
- raise_immediately

- `raise_method_missing_better_error`
- `raise_with_caller`
- `rand`
- `remove_instance_variable`
- `require`
- `respond_to?`
- `send`
- `serialize`
- `singleton_class`
- `singleton_methods`
- `sprintf`
- `srand`
- `tap`
- `then`
- `tick`
- `to_enum`
- `to_s`
- `up`
- `up=`
- `x`
- `x=`
- `y`
- `y=`
- `yield_self`

[Top](#)
