

Timing Service

No description provided (generated by Swagger Codegen <https://github.com/swagger-api/swagger-codegen>)

More information: <https://helloeverb.com>

Contact Info: hello@helloeverb.com

Version: 0.0.1

BasePath: /

All rights reserved

<http://apache.org/licenses/LICENSE-2.0.html>

Access

1.

Methods

[[Jump to Models](#)]

Table of Contents

[Default](#)

- [POST /activities/{activityId}/records](#)
- [POST /activities/](#)
- [DELETE /activities/{activityId}](#)
- [GET /activities/](#)
- [GET /activities/{activityId}](#)
- [GET /activities/{activityId}/records](#)
- [GET /activities/stats](#)
- [GET /activities/records](#)
- [PUT /activities/{activityId}](#)

Default

POST /activities/{activityId}/records

[Up](#)

(addActivityRecord)

Triggers start or end of a record for a given activityID

Path parameters

activityId (required)

Path Parameter —

Return type

[operationResponse](#)

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

OK [operationResponse](#)

POST /activities/

[Up](#)

(createActivity)

Consumes

This API call consumes the following media types via the Content-Type request header:

- application/json

Request body

body [activity](#) (required)

Body Parameter —

Return type

[operationResponse](#)

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

OK [operationResponse](#)

DELETE /activities/{activityId}

[Up](#)

(deleteActivity)

Removes an activity with given id and all its associated records from the database.

Path parameters

activityId (required)

Path Parameter —

Return type

[operationResponse](#)

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

OK [operationResponse](#)

GET /activities/

[Up](#)

(getActivities)

Returns all activities

Return type[operationResponse](#)**Produces**

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

OK [operationResponse](#)`GET /activities/{activityId}`[Up](#)**(getActivity)**

Returns activity with given id

Path parameters**activityId (required)***Path Parameter –***Return type**[operationResponse](#)**Produces**

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

OK [operationResponse](#)`GET /activities/{activityId}/records`[Up](#)**(getActivityRecords)**

Returns all records for an activity

Path parameters**activityId (required)***Path Parameter –***Return type**[operationResponse](#)**Produces**

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

OK [operationResponse](#)

GET /activities/stats

[Up](#)

(getGlobalActivityStats)

Returns statistics for this application

Return type

[operationResponse](#)

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

OK [operationResponse](#)

GET /activities/records

[Up](#)

(getRecords)

Returns all records for a user

Query parameters

tag (optional)

Query Parameter – The tag filter for user records

activityUuid (optional)

Query Parameter – The uuid of the activity of interest

Return type

[operationResponse](#)

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

OK [operationResponse](#)

PUT /activities/{activityId}

[Up](#)

(updateActivity)

Updates the activity meta data.

Path parameters

activityId (required)

Path Parameter –

Return type

[operationResponse](#)

Produces

This API call produces the following media types according to the Accept request header; the media type will be conveyed by the Content-Type response header.

- application/json

Responses

200

OK [operationResponse](#)

Models

[[Jump to Methods](#)]

Table of Contents

1. [activity](#)
2. [activityRecord](#)
3. [operationResponse](#)

activity

[Up](#)

An activity that can be tracked

name (optional)

[String](#) The name of the activity

tag (optional)

[String](#) The tag of the activity

uuid (optional)

[String](#) The uuid of the activity

description (optional)

[String](#) The description of the activity

owneruuid (optional)

[String](#) The uuid of the user that owns this activity

activityRecord

[Up](#)

A record of an activity that a user has submitted

activityuuid (optional)

[String](#) The uuid of the activity.

activityName (optional)

[String](#) The name of the activity.

time (optional)

[Date](#) The point in time a record update was issued (e.g. the request was sent to the server) format: date-time

startTime (optional)

[Date](#) The point in time this record was created format: date-time

endTime (optional)

[Date](#) The point in time this record ended format: date-time

uuid (optional)

[String](#) The uuid of this record

duration (optional)

[*Integer*](#) The duration of the record format: int32

tag (optional)

[*String*](#) The tag of the activity

state (optional)

[*String*](#)

Enum:

STARTED

ENDED

operationResponse

[Up](#)

error (optional)

[*String*](#) Used to indicate error messages. Null if no error occurred

data (optional)

[*array\[Object\]*](#) Attached data of response