

EXERCISE 03 Named entities - INSTRUCTIONS:

TOOL (Creating a new TEI-XML File)

- Open oXygen (to open, click on “oXygen XML Editor”).
- Open new document (oXygen menu: File -> New document).
- Search or select a document type (Framework templates -> TEI -> TEI All).
- Save it and rename it.
- Tip! You can save it in the same folder as this exercise.

TRANSCRIPTION

- No need to transcribe (no time for that now), just have a look at the transcription provided “3.1.Stendhal_Memoires_1838_transcript.txt”. The text has 3 paragraphs, so we need 3 <p> elements.
- Remove the dummy text “Some text here.” between the opening <p> and the closing </p> within the <body> element. Add 2 more <p> elements (opening and closing).
- Copy and paste each paragraph from the transcription.
- There are other ways of doing all this: copy and paste the entire text within a <p> </p>, put the cursor at the beginning of each paragraph, go to Document -> Markup -> Split Element.

The document should now be well-formed (a green square is visible in the upper right-hand corner).

- Tip! To format and indent the encoding, press Cmd + Shift + P (Mac), Ctrl + Shift + P (Windows).

ENCODING

You are encoding in the <body> names of places, names of people, and dates, so you need to add these elements:

- <placeName>, <persName> and <date>.
- Tip! Remember the shortcut: Highlight the place (person or date), press Ctrl + E (Windows) or Cmd + E (Mac), start typing ‘pl.’ and press Enter after selecting your element.

Let’s add now the metadata about the named entities (places and persons) in the <teiHeader>. After this is done, you will be able to link this information to each element in the text. For now, you need to add these elements:

- <profileDesc> describes non-bibliographic aspects of a text.
 - <particDesc> persons named in the text.
 - <listPerson> list of persons.
 - <person> information about a person.
 - <settingDesc> places named in the text.
 - <listPlace> list of places.
 - <place> information about a place.
- Start adding <profileDesc> just after </fileDesc> and before </teiHeader>.
- Tip! Place the cursor right after </fileDesc> (or at the next line) and start typing < (angle bracket): oXygen suggests a list of element names available at this point.

- Add the elements `<particDesc>` and `<settingDesc>` within `<profileDesc>`.
- Add the element `<listPerson>` within `<particDesc>`.
- Add the element `<listPlace>` within `<settingDesc>`.

Don't worry about the red square, some mandatory elements are still missing. Add `<person>` within the element `<listPerson>`, and `<place>` within the element `<listPlace>`. The structure should now be well-formed and look like:

```
<profileDesc>
  <particDesc>
    <listPerson>
      <person></person>
    </listPerson>
  </particDesc>
  <settingDesc>
    <listPlace>
      <place></place>
    </listPlace>
  </settingDesc>
</profileDesc>
```

There are 4 places and 4 person names in the text. For now let's gather the information about one of each kind: Paris and Tocqueville.

Encoding places

Let's start with **Paris**. We are interested in encoding its location in terms of latitude and longitude. To obtain coordinates you can search a geographical database (gazetteer), e.g., GeoNames: <https://www.geonames.org/2988507>. You should end up collecting the following information, which you are going to encode in the element `<place>`.

<i>place name</i>	<i>coordinates</i>	<i>geonames-id</i>	<i>country</i>	<i>your own id</i>
Paris	48.85341 2.3488	2988507	France	paris

Within the element `<place>` you need to add the following elements and complete the information from the table:

- `<placeName>`
- `<country>`
- `<location>`
 - `<geo>` (latitude and longitude separated by a space, inside `<location>`)
- `<idno>` (a standardized id, in this case from GeoNames)

Unique identifier. In order to link `<place>` from the header to the element `<placeName>` in the text, we need to specify a **unique identifier** for the element you have just created. We use attributes for this:

- Add the attribute `@xml:id` to the element `<place>` and choose your own unique value, e.g., “paris”. You should have now `<place xml:id="paris">`.
- Tip! Put the cursor inside the element just before `>` (`<place↑>`), and press space; oXygen suggests a list of attributes available for this element.
- `<idno>` This element also needs an attribute and a value to supply the information, e.g.: `type="GeoNames"`.

Internal linking. Now that you have defined the place, in this case, Paris, and supplied a unique identifier, you can link this element with all place names in your text that refer to Paris:

- To do the linking, add the attribute `@ref` containing the value of the `@xml:id` (i.e., “paris”) preceded by a hash (#). You should have now `<p>À <placeName ref="#paris">Paris</placeName>, la distraction est trop [...]`.
- Tip! Put the cursor inside the element just before `>` (`<placeName↑>`), and press space; oXygen suggests a list of attributes available for this element. Choose `@ref`: automatically oXygen will suggest the identifiers you have created in the header.

Encoding persons

Let’s continue with a person name, **Tocqueville**. Wikipedia may be there always to help, but a good source for the basic information are the authority files run by national libraries, e.g., the data service of the *Bibliothèque nationale de France*, <https://data.bnf.fr>. The international authority files, like ISNI <http://www.isni.org/isni/0000000121371933> gather several of these sources.

So once you have collected the information you want to add, encode them in the element `<person>`.

<i>person name</i>	<i>birth</i>	<i>death</i>	<i>occupation</i>	<i>nationality</i>	<i>your own id</i>
Alexis de Tocqueville	29 July 1805	16 April 1859	historian	French	AT1805
<i>ISNI id</i>					
0000000121371933					

Within the element `<person>` you need to add the following elements and complete the information from the table:

- `<persName>`
- `<birth>`
- `<death>`
- `<occupation>`
- `<nationality>`
- `<idno>` (a standardized id, in this case ISNI).

Unique identifier. As we did with `<place>` we need to specify a **unique identifier** for `<person>`. It is up to you which one you want to use, e.g., the initials plus the date of birth: AT1805 (Alexis de Tocqueville 1805).

- You should have now `<person xml:id="AT1805">`.

You probably added the date of birth like `<birth>29 July 1805</birth>`. In fact you can write it as you prefer: 29 juillet 1805, 29.07.1805, etc., but in order to record the date properly, we need to use the attribute `@when` with a value in a standard form (YYYY-MM-DD): 1805-07-29. So you should have `<birth when="1805-07-29">29 July 1805</birth>`.

- Keep tagging all dates with the attribute `@when`, also in your text.

Internal linking. Now that you have defined the person, in this case, Tocqueville, and supplied a unique identifier, you can link this element with the names in your text, which refer to Tocqueville:

- Proceed in the same way you did with `<place>` and remember the tip about putting the cursor inside the element (or inside the attribute value).

Already done?

- (1 option) Search for information about Charles Louis de Montesquieu, Pierre Bayle, Lyon, Marseille, Grenoble, and keep tagging... Not your thing?
- (2 option) Could you improve the encoding of `<persName>` with forename and surname?
- (3 option) You could also add to the person list the information about the author, Stendhal, which is in fact a pseudonym; his real name was Marie-Henri Beyle. How do we encode a pseudonym? Check the TEI Guidelines for 13.2.1 Personal Names.
- (4 option) Visualize your data. Nothing fancy here, but you can easily spot the names, places and dates.

VISUALIZATION (Web browser and oXygen editor mode)

- Follow the steps as in exercise 1.

EXERCISE SOLUTION

- I provided you with a TEI-XML file already encoded, “3.4-Stendhal_Memoires_1838_done.xml”. Feel free to have a look inside or ask me for help.