










Stepreamer Ø38 Z6

A15-010

The reamer Application A15 of Quinto5 allows easily to resharpen multistep reamers. The angle and position of a chamfer or step can be defined on three points. Beside those points a additional chamfer can be added to create a smooth connection on the tool-backside from the biggest diameter to the shaft-diameter. The approach of the wheel can be adjusted to the geometry to allow acces in difficult geometries. For each chamfer 3 clearance angles can be defined.




1. Cycletime for Resharpener

Workpiece:	Ø 38 mm, Z 6, Length of cutting edge 35 mm, Helix 0°				
Material	CARBIDE				
Operations					
Feed [mm/Min]	2000	250	300	300	300
Power [kW]		1	1	1	1
Cutting speed [m/s]		24	24	24	24
Used wheels					
Grinding time [s]	25	59	33	59	59
Total cycle time	3 Min 55				

The cycle times are indicative. Material to be ground, grinding wheels, coolants can influence the cycle times considerably.

2. Used Grinding Wheels

1	12V9 Ø125 D64
---	---------------



1

3. Machine and Software Requirements

Machines:	5 axes CNC grinders : NORMA CFG	Coolant:	Synthetic Oil, pressure 6 bar
Control:	Fanuc 31i	Software:	Quinto 5
Accessories:			
Responsible engineer:	LLU 9.2.12		

www.schneeberger.ch

J. SCHNEEBERGER Maschinen AG 4914 Roggwil Switzerland

Subsidiaries in: France, Deutschland, Italia, United States, China