









Endmill Ø18 Z4

A01-010

Cylindrical endmills with radius are standard tools used in High speed milling, die molding milling and milling applications in the aircraft industry. The benefits of the corner radius are an improvement of the surface quality of milled parts, a damage reduction of the corner of the endmill, a reduction of stress intensity effects of milled parts under tensile stresses.




1. Cycletime for

Tool specifications								
Diameter 18 mm, Z 4, Length of cutting edge 35 mm, Helix angle 30°								
Material								
Operations	Probe	Flute 1	Gashing	O.D.2	O.D.1	End 2	End 1	Chamfer
Feed [mm/Min]	1500	140	100	140	120	100	120	100
Power [kW]		2	2	1	1	1	1	1
Cutting feed [m/s]		18	18	20	20	20	20	20
Used wheels								
Grinding time [s]	31	99	63	394	442	48	42	43
Total cycle time	19 Min 21							

The mentioned cycle times are indicative. The material to be ground, different grinding wheels or other coolants can influence the cycle times considerably.

2. Used Grinding Wheels

3	12V9 Ø125 D64
4	11V9 Ø75 D64



3. Machine and Software Requirements

Machines: 4 axes CNC grinders : Aries ENP4
 Control: Fanuc 35i
 Coolant: Synthetic Oil, pressure 6 bar
 Software: Menuguided ISO-programming with macroexecuter

responsible engineer: KCM, 7.01.09

www.schneeberger.ch

J. SCHNEEBERGER Maschinen AG 4914 Roggwil Switzerland

Subsidiaries in: France, Deutschland, Italia, United States, China

TECHNOLOGY
FOR TOOLING