




Top Notch Insert Ø12.4

A08-150

Roughing is done with a standard 14V1 wheel with diameter 300mm and grain D64 and standard profiling process. The finishing process is grinding with an additional oscillation. Resolution 0.01 mm and oscillation length 19 mm. The cycle time below is mentioned per side.



1. Cycletime for Production


Workpiece: 40x17.5x9.35 gageroll Ø12.4 Material CARBIDE		
Operations	 Prf Pgrd	 Prf fin
Feed [mm/Min]	10	8000
Power [kW]	1	1
Cutting speed [m/s]	22	22
Used wheels	1	2
Grinding time [s]	332	1258
Total cycle time	26 Min 30	

The cycle times are indicative. Material to be ground, grinding wheels, coolants can influence the cycle times considerably.



2. Used Grinding Wheels

1	14V1 Ø300 D64
2	14V1 Ø300 D46M



3. Machine and Software Requirements

Machines: 5 axes CNC grinders : sirius NGS

Control: Fanuc 31iB 5

Accessories: CTC for Topnotch

Responsible engineer: OP, 28.4.16

Coolant: Synthetic Oil, pressure 6 bar

Software: Quinto 5

www.schneeberger.ch

J. SCHNEEBERGER Maschinen AG 4914 Roggwil Switzerland

Subsidiaries in: France, Deutschland, Italia, United States, China