

Columns

Columns

Copy Page

▼

Learn how to create, read, update, and delete columns on monday boards using the platform API

monday.com boards are formatted as a table with columns and rows of items. Each [column](#) has specific functionality and only stores relevant data. For example, a numbers column stores numerical values, a text column stores text values, and a time tracking column stores only time-based data from log events.

Queries

Get columns

- **Required scope:** `boards:read`
- Returns an array containing metadata about one or a collection of columns
- Can only be nested within another query (e.g., `boards`); can't be queried directly at the root

GraphQL JavaScript

```
query {
  boards(ids: [1234567890]) {
    columns {
      id
      title
    }
  }
}
```

Arguments

Argument	Type	Description	Enum Values
capabilities	[ColumnCapability]	A list of column capabilities to filter by. Returns columns that have any of the specified capabilities.	CALCULATED



Need help? Ask AI!

Argument	Type	Description	Enum Values
		Use <code>null</code> in the array to retrieve columns with no capabilities (e.g., <code>[null]</code> for only columns without capabilities, <code>[null, CALCULATED]</code> for columns without capabilities or with calculated).	VISIBILITY (hidden columns)
ids	[String]	The specific columns to return. Please use quotation marks when passing this ID as a string.	
types	[ColumnType!].	The specific type of columns to return.	

Fields

Field	Type	Description
archived	Boolean!	Returns <code>true</code> if the column is archived.
capabilities	ColumnCapabilities!	Calculates and retrieves the column's rollup value.
description	String	The column's description.
id	ID!	The column's unique identifier.
revision	String!	The column's current revision. Used for optimistic concurrency control.
settings	JSON	The column's dynamic JSON settings. For multi-level boards, use this field to retrieve labels and color mappings for status rollup columns.
title	String!	The column's title.
type	ColumnType!	The column's type.
width	Int	The column's width.

Mutations

Required scope: `boards:write`

Create column

Creates a column. Returns [Column](#) .

GraphQL JavaScript

```
mutation {
  create_column(
    board_id: 1234567890
    title:"Work Status"
    description: "This is my work status column"
    column_type:status
  ) {
    id
    title
    description
  }
}
```

Arguments

Argument	Type	Description
after_column_id	ID	The unique identifier of the column after which the new column will be created.
board_id	ID!	The unique identifier of the board where the new column should be created.
capabilities	ColumnCapabilitiesInput	The new column’s capabilities configuration. If omitted, defaults apply: on multi-level boards, numeric, date, timeline, and status columns are created with the calculated capability enabled; in all other cases, no capabilities are applied. To override this default on multi-level boards, pass an empty argument to create the column without capabilities.
column_type	ColumnType!	The type of column to create. This determines which properties are valid in the defaults argument.
defaults	JSON	The new column’s defaults. Accepts a JSON object or string. Validated against the column-type schema; query get_column_type_schema to see available properties.
description	String	The new column’s description.
id	String	The column’s user-specified unique identifier. If not provided, a new ID will be auto-

Argument	Type	Description
		generated. If provided, it must meet the following requirements: • [1-20] characters in length (inclusive) • Only lowercase letters (<i>a-z</i>) and underscores (<i>_</i>) • Must be unique (no other column on the board can have the same ID) • Can't reuse column IDs, even if the column has been deleted from the board • Can't be null, blank, or an empty string
title	String!	The new column's title.

Change column value

Changes a column **with a JSON value**. Returns [Column](#) .

For multi-level boards, rollout column changes are blocked if the item has at least one subitem.

GraphQL JavaScript

```
mutation {  
  change_column_value(  
    board_id: 1234567890  
    item_id: 9876543210  
    column_id: "email9",  
    value: "{\"text\":\"test@gmail.com\",\"email\":\"test@gmail.com\"}"  
  ) {  
    id  
  }  
}
```

Arguments

Argument	Type	Description
board_id	ID!	The board's unique identifier.
column_id	String!	The column's unique identifier.
create_labels_if_missing	Boolean	Creates status/dropdown labels if they are missing. Requires permission to change the board structure.
item_id	ID	The item's unique identifier.

Argument	Type	Description
value	JSON!	The new value of the column in JSON format. See Column Types Reference for each column type and its format.

Change simple column value

Changes a column **with a string value**. Returns [Column](#) .

GraphQL JavaScript

```
mutation {
  change_simple_column_value(
    board_id: 1234567890
    item_id: 9876543210
    column_id: "status"
    value: "Working on it"
  ) {
    id
  }
}
```

Arguments

Argument	Type	Description
board_id	ID!	The board's unique identifier.
column_id	String!	The column's unique identifier.
create_labels_if_missing	Boolean	Creates status/dropdown labels if they are missing. Requires permission to change the board structure.
item_id	ID	The item's unique identifier.
value	String	The new simple value of the column.

Change multiple column values

Changes multiple columns **with a JSON value**. Returns [Column](#) .

Each column has a type, and different column types require different parameter sets to update their values. When sending data in the `column_values` argument, use a string and build it using this sample form: `{"text\": \"New text\", \"status\": {\"label\": \"Done\"}}`



You can also use **simple** (`String`) values in this mutation along with **regular** (`JSON`) values, or just simple values. Here's an example of setting a status with a simple value: `{"text\":`

```
\ "New text\ ", \ "status\ ": \ "Done\ " }
```

GraphQL JavaScript

```
mutation {
  change_multiple_column_values(
    item_id: 1234567890
    board_id: 9876543210
    column_values: "{\ "status\ ":{\ "index\ ":1},\ "date4\ ":{\ "date\ ":\"2021-01-01\"},\ "person\ ":{\ "personsAndTeams\ ":[{\ "id\ ":9603417,\ "kind\ ":\"person\ "}]}}}"
  ) {
    id
  }
}
```

Arguments

Argument	Type	Definition
board_id	ID!	The unique identifier of the board that contains the columns to change.
column_values	JSON!	The updated column values.
create_labels_if_missing	Boolean	Creates status/dropdown labels if they are missing. Requires permission to change the board structure.
item_id	ID	The unique identifier of the item to change.

Change column title

Changes the title of an existing column. Returns [Column](#) .

GraphQL JavaScript

```
mutation {
  change_column_title(
    board_id: 1234567890
    column_id: "status"
    title: "new_status"
  ) {
    id
  }
}
```

Arguments

Argument	Type	Definition
board_id	ID!	The unique identifier of the board that contains the column to change.
column_id	String!	The column's unique identifier.
title	String!	The column's new title.

Update column

Updates a column. Returns [Column](#) .

The input is validated against the column type's schema before applying changes

GraphQL

```
mutation {  
  update_column(  
    board_id: 1234567890  
    id: "status"  
    title: "Work Status"  
    description: "This is my updated work status column"  
    column_type: status  
    width: 200  
    revision: "a73d19e54f82c0b7d1e348f5ac92b6de"  
  ) {  
    id  
    title  
    description  
  }  
}
```

Arguments

Argument	Type	Description
board_id	ID!	The unique identifier of the board where the updated column is located.
capabilities	ColumnCapabilitiesInput	The new column's capabilities configuration. If omitted, defaults apply: on multi-level boards, numeric, date, timeline, and status columns are created with the calculated capability enabled; in all other cases, no capabilities are applied. To override this default on multi-level boards, pass an empty argument to create the column without capabilities.

Argument	Type	Description
column_type	ColumnType!	The updated column's type. This determines which properties are valid in the <code>defaults</code> argument.
description	String	The updated column's description.
id	String!	The updated column's user-specified unique identifier. If not provided, a new ID will be auto-generated. If provided, it must meet the following requirements: • [1-20] characters in length (inclusive) • Only lowercase letters (<i>a-z</i>) and underscores (<i>_</i>) • Must be unique (no other column on the board can have the same ID) • Can't reuse column IDs, even if the column has been deleted from the board • Can't be null, blank, or an empty string
revision	String!	The column's current revision. Used for optimistic concurrency control.
settings	JSON	The column's type-specific settings in JSON. Query get_column_type_schema to see available properties.
title	String	The updated column's title.
width	Int	The column's updated width in pixels.

Change column metadata

Updates the title or description of an existing column. Returns [Column](#) .

GraphQL JavaScript

```
mutation {  
  change_column_metadata(  
    board_id: 1234567890  
    column_id: "date4"  
    column_property: description  
    value: "This is my awesome date column"  
  ) {  
    id  
    title  
    description  
  }  
}
```

```
}  
}
```

Arguments

Argument	Type	Definition	Enum Values
board_id	ID!	The unique identifier of the board that contains the column to change.	
column_id	String!	The column's unique identifier.	
column_property	ColumnProperty	The property you want to change.	description title
value	String	The new value of that property.	

Delete column

Deletes a single column from a board. Returns [Column](#) .

GraphQL JavaScript

```
mutation {  
  delete_column(  
    board_id: 1234567890  
    column_id: "status"  
  ) {  
    id  
  }  
}
```

Arguments

Argument	Type	Description
board_id	ID!	The unique identifier of the board that contains the column to delete.
column_id	String!	The column's unique identifier.

 Updated 3 months ago

[← Other types](#)

[Column Types →](#)