

Requirements Traceability Matrix (Sample Scenario)

This matrix ensures traceability from business goal to implementation and testing for the Stets Home MVP.

BR — Business Requirement

FR — Functional Requirement

US — User Story

NFR — Non-Functional Requirement

TC — Test Case

Artifacts — Supporting design & analysis artifacts

Traceability flow: BR → US → FR → NFR → TC → Artifacts

BR ID	Business Requirement	US ID / User Story	FR ID / Functional Requirement
BR-001	Develop a smart home application with a unique energy-saving mode for Stets devices to stand out among competitors	US-018: As Mikhail, I want to enable the energy-saving mode for a smart light so that I can take care of the environment JS-019: When I am short on time, I want to disable the energy-saving mode for a smart light so that the application works faster	FR-001: The system allows the user to enable energy-saving mode FR-002: The system allows the user to disable energy-saving mode

NFR ID / Non-Functional Requirement	Test Cases	Artifacts
NFR-001: Enabled energy-saving mode is displayed in blue in the application NFR-002: Disabled energy-saving mode is displayed in white in the application NFR-003: Energy-saving mode can be enabled in ≤ 2 seconds NFR-004: Energy-saving mode can be disabled in ≤ 2 seconds NFR-005: When energy-saving mode is enabled, the system must respond to commands in ≤ 3 seconds	TC-1 6.3, TC-1 6.4	USM, DFD logical, ER, Data Dictionary, Test Report,

		Prototype s
--	--	----------------