

Pre-Lab 1

1. \$ groups
2. \$? Is used to find the return value of the last executed command
3. The command [find /foo/bar -type f -name "*.txt"] will find all the files with the suffix ".txt" in foo/bar
4. The command "uname -rn" gives us the kernel version and the "nodename"
 - a. Source: <https://www.liquidweb.com/kb/how-to-check-the-kernel-version-in-linux-ubuntu-centos/>
5. "." is the current path level, ".." goes to parent directory path, "~" is a shortcut to get back into your home directory
 - a. Source: <https://www.cs.jhu.edu/~joanne/unix.html>
6. PID is a unique number that identifies each of the running processes in operating systems. Use pidof <application name> to find the "PID" of a running process
7. Using "sort *filename* > *output*" command will sort the filename by line into another output. To show the output command "cat *output*" will show the sorted items alphabetically
 - a. Source: <https://www.computerhope.com/unix/usort.htm>
8. "su root" allows you to run a shell to become the root user account and requires the root password. "sudo" also allows you to start a program with the credentials of another user but requires a single command line that doesn't switch user accounts or requires a password
 - a. Source: <http://linux-training.be/index.php?nav=fundamentals>
9. watch -n sec <command>
 - a. Source: <https://www.tecmint.com/run-repeat-linux-command-every-x-seconds/>