

# parabolic\_\_exercice

April 6, 2022

## 1 Problem

$$\partial_t u - \nabla \cdot K(\nabla u) \nabla u = f \quad (1)$$

$f = f(x, t)$  is a time dependent forcing term and the diffusion tensor is

$$K(\nabla u) = \frac{2}{1 + \sqrt{1 + 4|\nabla u|^2}} \quad (2)$$

On the boundary we prescribe Neumann boundary conditions and require initial conditions  $u(\cdot, 0) = u_0(\cdot)$ .

We solve this problem in variational form using Implicit Euler in time

$$\int_{\Omega} \frac{u^{n+1} - u^n}{\Delta t} \varphi + K(\nabla u^{n+1}) \nabla u^{n+1} \cdot \nabla \varphi \, dx = \int_{\Omega} f(x, t^n + \Delta t) \varphi \, dx + \int_{\partial\Omega} g(x, t^n + \Delta t) \varphi \, ds .$$

on a domain  $\Omega = [0, 1]^2$ . We choose  $f, g$  so that the exact solution is

$$u(x, t) = e^{-2t} \left( \frac{1}{2}(x^2 + y^2) - \frac{1}{3}(x^3 - y^3) \right) + 1$$

Setup grid and space

```
GridParameterBlock: Parameter 'refinementedge' not specified, defaulting to 'ARBITRARY'.
```

```
WARNING (ignored): Could not open file 'alugrid.cfg', using default values 0 < [balance] < 1.2, partitioning method 'ALUGRID_SpaceFillingCurve(9)'.
```

```
You are using DUNE-ALUGrid, please don't forget to cite the paper:  
Alkaemper, Dedner, Kloefkorn, Nolte. The DUNE-ALUGrid Module, 2016.
```

```
Created parallel ALUGrid<2,2,simplex,conforming> from input stream.
```

```
Import UFL variables and define spatial coordinate, test/trial function
```

```
Define initial condition and exact solution
```

```
Define discrete functions, one for  $u^{n+1}$  and one for  $u^n$ . We also define two constants which can be used as floats in ufl expressions but can be changed at a later stage without requiring any recompilation.
```

Now setup the model and the scheme:

$$\int_{\Omega} \frac{u^{n+1} - u^n}{\Delta t} \varphi + K(\nabla u^{n+1}) \nabla u^{n+1} \cdot \nabla \varphi \, dx = \int_{\Omega} f(x, t^n + \Delta t) \varphi \, dx + \int_{\partial\Omega} g(x, t^n + \Delta t) \varphi \, ds .$$


## 1.1 Task

Implement the form **a** and right hand side **b** as described above, using terms  $K$ ,  $f$ , and  $g$ .

A Galerkin scheme is created that allows us to solve the equation  $a = b$ .

Time loop: first choose a time step and then iterate from  $t^0 = 0$  to  $t^N = N\Delta t = 0.25$ . We write vtk files every after every 0.05 time interval.

Plot result and compute error



error at final time= 0.16418668639785838