

B. Cinema Cashier

time limit per test: 1 second
memory limit per test: 256 megabytes

All cinema halls in Berland are rectangles with K rows of K seats each, and K is an odd number. Rows and seats are numbered from 1 to K . For safety reasons people, who come to the box office to buy tickets, are not allowed to choose seats themselves. Formerly the choice was made by a cashier, but now this is the responsibility of a special seating program. It was found out that the large majority of Berland's inhabitants go to the cinema in order to watch a movie, that's why they want to sit as close to the hall center as possible. Moreover, a company of M people, who come to watch a movie, want necessarily to occupy M successive seats in one row. Let's formulate the algorithm, according to which the program chooses seats and sells tickets. As the request for M seats comes, the program should determine the row number x and the segment $[y_l, y_r]$ of the seats numbers in this row, where $y_r - y_l + 1 = M$. From all such possible variants as a final result the program should choose the one with the minimum function value of total seats remoteness from the center. Say, $x_c = \lceil \frac{K}{2} \rceil$, $y_c = \lceil \frac{K}{2} \rceil$ — the row and the seat numbers of the most "central" seat. Then the function value of seats remoteness from the hall center is $\sum_{y=y_l}^{y_r} |x - x_c| + |y - y_c|$. If the amount of minimum function values is more than one, the program should choose the one that is closer to the screen (i.e. the row number x is lower). If the variants are still multiple, it should choose the one with the minimum y_l . If you did not get yet, your task is to simulate the work of this program.

Input

The first line contains two integers N and K ($1 \leq N \leq 1000$, $1 \leq K \leq 99$) — the amount of requests and the hall size respectively. The second line contains N space-separated integers M_i from the range $[1, K]$ — requests to the program.

Output

Output N lines. In the i -th line output «-1» (without quotes), if it is impossible to find M_i successive seats in one row, otherwise output three numbers x, y_l, y_r . Separate the numbers with a space.

Examples

input	Copy
2 1 1 1	
output	Copy
1 1 1 -1	

input	Copy
4 3 1 2 3 1	
output	Copy
2 2 2 1 1 2 3 1 3 2 1 1	

Codeforces Beta Round 10

Finished

Practice



→ Virtual participation

Virtual contest is a way to take part in past contest, as close as possible to participation on time. It is supported only ICPC mode for virtual contests. If you've seen these problems, a virtual contest is not for you - solve these problems in the archive. If you just want to solve some problem from a contest, a virtual contest is not for you - solve this problem in the archive. Never use someone else's code, read the tutorials or communicate with other person during a virtual contest.

[Start virtual contest](#)

→ Clone Contest to Mashup

You can clone this contest to a mashup.

[Clone Contest](#)

→ Submit?

Language: GNU G++23 14.2 (64 bit, ms)

Choose file: [Choose File](#) No file chosen

[Submit](#)

→ Last submissions

Submission	Time	Verdict
325263398	Jun/20/2025 13:30	Accepted

→ Problem tags

dp implementation *1500

No tag edit access

→ Contest materials

- Announcement (en)



The only programming contests Web 2.0 platform
Server time: Jun/20/2025 17:31:10^{UTC+7} (k1).
Desktop version, switch to [mobile version](#).
[Privacy Policy](#) | [Terms and Conditions](#)

Supported by



ITMO