

G. Eulerian Line Graph

time limit per test: 2 seconds
memory limit per test: 256 megabytes

Aryan loves graph theory more than anything. Well, no, he likes to flex his research paper on line graphs to everyone more. To start a conversation with you, he decides to give you a problem on line graphs. In the mathematical discipline of graph theory, the line graph of a simple undirected graph G is another simple undirected graph $L(G)$ that represents the adjacency between every two edges in G .

Precisely speaking, for an undirected graph G without self-loops or multiple edges, its line graph $L(G)$ is a graph such that

- Each vertex of $L(G)$ represents an edge of G .
- Two vertices of $L(G)$ are adjacent if and only if their corresponding edges share a common endpoint in G .




Figure: Generation of the Line Graph

Also, $L^0(G) = G$ and $L^k(G) = L(L^{k-1}(G))$ for $k \geq 1$.

An Euler trail is a sequence of edges that visits every edge of the graph exactly once. This trail can be either a path (starting and ending at different vertices) or a cycle (starting and ending at the same vertex). Vertices may be revisited during the trail, but each edge must be used exactly once.

Aryan gives you a simple connected graph G with n vertices and m edges and an integer k , and it is guaranteed that G has an Euler trail and it is not a path graph*. He asks you to determine if $L^k(G)$ has an Euler trail.

*A path graph is a tree where every vertex is connected to at most two other vertices.

Input

Each test contains multiple test cases. The first line contains the number of test cases t ($1 \leq t \leq 10^4$). The description of the test cases follows.

The first line of each test case contains three space-separated integers n , m , and k ($5 \leq n \leq 2 \cdot 10^5$, $n - 1 \leq m \leq \min(\frac{n \cdot (n-1)}{2}, 2 \cdot 10^5)$, $1 \leq k \leq 2 \cdot 10^5$).

The next m lines of each test case contain two space-separated integers u and v ($1 \leq u, v \leq n$, $u \neq v$), denoting that an edge connects vertices u and v .

It is guaranteed that the sum of n and m over all test cases does not exceed $2 \cdot 10^5$.

Output

For each testcase, print "YES" if $L^k(G)$ has an Euler trail; otherwise, "NO".

You can output the answer in any case (upper or lower). For example, the strings "yEs", "yes", "Yes", and "YES" will be recognized as positive responses.

Example

Codeforces Round 1033 (Div. 2) and CodeNite 2025

Finished

Practice



→ Virtual participation

Virtual contest is a way to take part in past contest, as close as possible to participation on time. It is supported only ICPC mode for virtual contests. If you've seen these problems, a virtual contest is not for you - solve these problems in the archive. If you just want to solve some problem from a contest, a virtual contest is not for you - solve this problem in the archive. Never use someone else's code, read the tutorials or communicate with other person during a virtual contest.

Start virtual contest

→ Clone Contest to Mashup

You can clone this contest to a mashup.

Clone Contest

→ Submit?

Language: GNU G++23 14.2 (64 bit, ms)

Choose file: No file chosen

Submit

→ Last submissions

Submission	Time	Verdict
325585032	Jun/22/2025 17:42	Accepted
325584013	Jun/22/2025 17:33	Wrong answer on test 2
325474946	Jun/21/2025 19:19	Wrong answer on pretest 2
325473923	Jun/21/2025 19:16	Wrong answer on pretest 2
325418924	Jun/21/2025 17:47	Wrong answer on pretest 2
325415042	Jun/21/2025 17:42	Wrong answer on pretest 2

→ Problem tags

graphs greedy math

No tag edit access


input	Copy
<pre> 4 5 5 2 1 2 2 3 3 4 4 5 5 1 5 6 1 1 2 2 3 3 4 4 5 5 1 1 3 10 11 3 1 2 2 3 3 4 4 5 4 6 4 7 5 7 6 7 7 8 8 9 9 10 7 8 2 1 3 2 3 1 4 4 5 2 5 1 6 6 7 2 7 </pre>	
output	Copy
<pre> YES NO YES NO </pre>	

→ Contest materials
<ul style="list-style-type: none"> Announcement (en) <input type="checkbox"/> Statements #1 (ru) <input type="checkbox"/> Statements #2 (en) <input type="checkbox"/> Tutorial (en) <input type="checkbox"/>

Note

For the first test case, $L^2(G)$ is isomorphic to G itself. So, since G has an Euler trail, $L^2(G)$ also has an Euler trail.

For the second test case, $L(G)$ looks as follows(Vertex $i - j$ of $L(G)$ in figure corresponds to edge between vertices i and j of G). It can be proven that this doesn't have an Euler trail.



[Codeforces](#) (c) Copyright 2010-2025 Mike Mirzayanov
The only programming contests Web 2.0 platform
Server time: Jun/22/2025 21:42:42^{UTC+7} (k1).
Desktop version, switch to [mobile version](#).
[Privacy Policy](#) | [Terms and Conditions](#)

Supported by



ITMO