

P0201R6

polymorphic_value: A Polymorphic Value Type for C++

Published Proposal, 2022-10-15

This version:

<https://wg21.link/P0201>

Issue Tracking:

[GitHub](#)

Authors:

[Jonathan B. Coe](#)

[Antony Peacock](#)

[Sean Parent](#)

Audience:

LEWG

Project:

ISO/IEC JTC1/SC22/WG21 14882: Programming Language — C++

Source:

https://github.com/jbcoe/polymorphic_value/blob/main/documentation/p0201.md

Table of Contents

1	Change history
2	TL;DR
3	Introduction
3.1	Motivation: Composite objects
3.2	Deep copies
3.3	Pointer constructor
3.4	Empty state
3.5	Lack of hashing and comparisons
3.6	Custom copiers and deleters
3.7	Allocator Support
3.8	Design changes from cloned_ptr
3.9	No implicit conversions
3.10	Impact on the standard
4	Technical specifications
4.1	Additions in [memory.syn] 20.2.2:
4.2	X.W Class template copier_traits [copier.traits]
4.3	X.X Class template default_copy [default.copy]
4.4	X.Y Class bad_polymorphic_value_construction [bad_polymorphic_value_construction]
4.5	X.Z Class template polymorphic_value [polymorphic_value]
4.5.1	X.Z.1 Class template polymorphic_value general [polymorphic_value.general]
4.5.2	X.Z.2 Class template polymorphic_value synopsis [polymorphic_value.synopsis]
4.5.3	X.Z.3 Class template polymorphic_value constructors [polymorphic_value.ctor]
4.5.4	X.Z.4 Class template polymorphic_value destructor [polymorphic_value.dtor]
4.5.5	X.Z.5 Class template polymorphic_value assignment [polymorphic_value.assignment]
4.5.6	X.Z.6 Class template polymorphic_value modifiers [polymorphic_value.modifiers]
4.5.7	X.Z.7 Class template polymorphic_value observers [polymorphic_value.observers]
4.5.8	X.Z.8 Class template polymorphic_value creation [polymorphic_value.creation]

5 Acknowledgements

5.1 References

§ 1. Change history

Changes in P0201R6

- Further clarifications to formal wording.
- Allocator support.
- Remove note suggesting that a small object optimisation is allowed.
- `constexpr` support.

Changes in P0201R5

- Make constructor of `default_copy` `noexcept` and `constexpr`.
- Clarifications to formal wording.

Changes in P0201R4

- Clarify authors' agreement with LEWG design changes.
- Add wording to clarify meaning of custom copier and deleter.
- Make constructors explicit and remove converting assignment.
- Add a second template parameter to `make_polymorphic_value` to facilitate construction of objects of derived classes.

Changes in P0201R3

- Add rationale for absence of allocator support.

Changes in P0201R2

- Change name to `polymorphic_value`.
- Remove `operator <<`.
- Add construction and assignment from values.
- Use `std::default_delete`.
- Rename `std::default_copier` to `std::default_copy`.
- Add notes on empty state and pointer constructor.
- Add `bad_polymorphic_value_construction` exception when static and dynamic type of pointee mismatch and no custom copier or deleter are supplied.
- Add clarifying note to say that a small object optimisation is allowed.

Changes in P0201R1

- Change name to `indirect`.
- Remove `static_cast`, `dynamic_cast` and `const_cast` as `polymorphic_value` is modelled on a value not a pointer.
- Add `const` accessors which return `const` references/pointers.
- Remove pointer-accessor `get`.
- Remove specialization of `propagate_const`.
- Amended authorship and acknowledgements.
- Added support for custom copiers and custom deleters.
- Removed hash and comparison operators.

§ 2. TL;DR

Add a class template, `polymorphic_value<T>`, to the standard library to support polymorphic objects with value-like semantics.

§ 3. Introduction

The class template, `polymorphic_value`, confers value-like semantics on a free-store allocated object. A `polymorphic_value<T>` may hold an object of a class publicly derived from T, and copying the `polymorphic_value<T>` will copy the object of the derived type.

§ 3.1. Motivation: Composite objects

Use of components in the design of object-oriented class hierarchies can aid modular design as components can be potentially re-used as building-blocks for other composite classes.

We can write a simple composite object formed from two components as follows:

```
// Simple composite
class CompositeObject_1 {
    Component1 c1_;
    Component2 c2_;

public:
    CompositeObject_1(const Component1& c1,
                     const Component2& c2) :
        c1_(c1), c2_(c2) {}

    void foo() { c1_.foo(); }
    void bar() { c2_.bar(); }
};
```

The composite object can be made more flexible by storing pointers to objects allowing it to take derived components in its constructor. (We store pointers to the components rather than references so that we can take ownership of them).

```
// Non-copyable composite with polymorphic components (BAD)
class CompositeObject_2 {
    IComponent1* c1_;
    IComponent2* c2_;

public:
    CompositeObject_2(IComponent1* c1,
                     IComponent2* c2) :
        c1_(c1), c2_(c2) {}

    void foo() { c1_->foo(); }
    void bar() { c2_->bar(); }

    CompositeObject_2(const CompositeObject_2&) = delete;
    CompositeObject_2& operator=(const CompositeObject_2&) = delete;

    CompositeObject_2(CompositeObject_2&& o) : c1_(o.c1_), c2_(o.c2_) {
        o.c1_ = nullptr;
        o.c2_ = nullptr;
    }

    CompositeObject_2& operator=(CompositeObject_2&& o) {
        delete c1_;
        delete c2_;
        c1_ = o.c1_;
        c2_ = o.c2_;
    }
};
```

```

    o.c1_ = nullptr;
    o.c2_ = nullptr;
}

~CompositeObject_2()
{
    delete c1_;
    delete c2_;
}
};

```

`CompositeObject_2`'s constructor API is unclear without knowing that the class takes ownership of the objects. We are forced to explicitly suppress the compiler-generated copy constructor and copy assignment operator to avoid double-deletion of the components `c1_` and `c2_`. We also need to write a move constructor and move assignment operator.

Using `unique_ptr` makes ownership clear and saves us writing or deleting compiler generated functions:

```

// Non-copyable composite with polymorphic components
class CompositeObject_3 {
    std::unique_ptr<IComponent1> c1_;
    std::unique_ptr<IComponent2> c2_;

public:
    CompositeObject_3(std::unique_ptr<IComponent1> c1,
                     std::unique_ptr<IComponent2> c2) :
        c1_(std::move(c1)), c2_(std::move(c2)) {}

    void foo() { c1_->foo(); }
    void bar() { c2_->bar(); }
};

```

The design of `CompositeObject_3` is good unless we want to copy the object.

We can avoid having to define our own copy constructor by using shared pointers. As `shared_ptr`'s copy constructor is shallow, we need to modify the component pointers to be pointers-to `const` to avoid introducing shared mutable state [S.Parent].

```

// Copyable composite with immutable polymorphic components class
class CompositeObject_4 {
    std::shared_ptr<const IComponent1> c1_;
    std::shared_ptr<const IComponent2> c2_;

public:
    CompositeObject_4(std::shared_ptr<const IComponent1> c1,
                     std::shared_ptr<const IComponent2> c2) :
        c1_(std::move(c1)), c2_(std::move(c2)) {}

    void foo() { c1_->foo(); }
    void bar() { c2_->bar(); }
};

```

`CompositeObject_4` has polymorphism and compiler-generated destructor, copy, move and assignment operators. As long as the components are not mutated, this design is good. If non-const functions of components are used then this won't compile.

Using `polymorphic_value` a copyable composite object with polymorphic components can be written as:

```

// Copyable composite with mutable polymorphic components
class CompositeObject_5 {
    std::polymorphic_value<IComponent1> c1_;
    std::polymorphic_value<IComponent2> c2_;

public:

```

```
CompositeObject_5(std::polymorphic_value<IComponent1> c1,
                  std::polymorphic_value<IComponent2> c2) :
    c1_(std::move(c1)), c2_(std::move(c2)) {}

void foo() { c1_->foo(); }
void bar() { c2_->bar(); }
};
```

The component `c1_` can be constructed from an instance of any class that inherits from `IComponent1`. Similarly, `c2_` can be constructed from an instance of any class that inherits from `IComponent2`.

`CompositeObject_5` has a compiler-generated destructor, copy constructor, move constructor, assignment operator and move assignment operator. All of these compiler-generated functions will behave correctly.

§ 3.2. Deep copies

To allow correct copying of polymorphic objects, `polymorphic_value` uses the copy constructor of the owned derived-type object when copying a base type `polymorphic_value`. Similarly, to allow correct destruction of polymorphic component objects, `polymorphic_value` uses the destructor of the owned derived-type object in the destructor of a base type `polymorphic_value`.

The requirements of deep-copying can be illustrated by some simple test code:

```
// GIVEN base and derived classes.
class Base { virtual void foo() const = 0; };
class Derived : public Base { void foo() const override {} };

// WHEN a polymorphic_value to base is formed from a derived object
polymorphic_value<Base> poly(Derived());
// AND the polymorphic_value to base is copied.
auto poly_copy = poly;

// THEN the copy owns a distinct object
assert(&*poly != &*poly_copy);
// AND the copy owns a derived type.
assert(dynamic_cast<Derived*>(&*poly_copy));
```

Note that while deep-destruction of a derived class object from a base class pointer can be performed with a virtual destructor, the same is not true for deep-copying. C++ has no concept of a virtual copy constructor and we are not proposing its addition. The class template `shared_ptr` already implements deep-destruction without needing virtual destructors; deep-destruction and deep-copying can be implemented using type-erasure [Impl].

§ 3.3. Pointer constructor

`polymorphic_value` can be constructed from a pointer and optionally a copier and/or deleter. The `polymorphic_value` constructed in this manner takes ownership of the pointer. This constructor is potentially dangerous as a mismatch in the dynamic and static type of the pointer will result in incorrectly synthesized copiers and deleters, potentially resulting in slicing when copying and incomplete deletion during destruction.

```
class Base { /* functions and members */ };
class Derived : public Base { /* functions and members */ };

Derived* d = new Derived();
Base* p = d; // static type and dynamic type differ
polymorphic_value<Base> poly(p);

// This copy will have been made using Base's copy constructor.
```

```
polymorphic_value<Base> poly_copy = poly;

// Destruction of poly and poly_copy uses Base's destructor.
```

While this is potentially error prone, we have elected to trust users with the tools they are given. `shared_ptr` and `unique_ptr` have similar constructors and issues. There are more constructors for `polymorphic_value` of a less expert-friendly nature that do not present such dangers including a factory function `make_polymorphic_value`.

Static analysis tools can be written to find cases where static and dynamic types for pointers passed in to `polymorphic_value` constructors are not provably identical.

If the user has not supplied a custom copier or deleter, an exception `bad_polymorphic_value_construction` is thrown from the pointer-constructor if the dynamic and static types of the pointer argument do not agree. In cases where the user has supplied a custom copier and deleter it is assumed that they will do so to avoid slicing and incomplete destruction: a class heirarchy with a custom `Clone` function and virtual destructor would make use of `Clone` in a user-supplied copier.

§ 3.4. Empty state

`polymorphic_value` presents an empty state as it is desirable for it to be cheaply constructed and then later assigned. In addition, it may not be possible to construct the `T` of a `polymorphic_value<T>` if it is an abstract class (a common intended use pattern). While permitting an empty state will necessitate occasional checks for `null`, `polymorphic_value` is intended to replace the uses of pointers or smart pointers where such checks are also necessary. The benefits of default constructability (use in vectors and maps) outweigh the costs of a possible empty state.

A nullable `polymorphic_value<T>` could be mimicked with `std::optional<polymorphic_value<T>>` but this is verbose and would require partial template specialization of `std::optional` to avoid the overhead that would be incurred by a nullable `polymorphic_value`. But perhaps the most unfortunate side effect of this approach is that to access the underlying `T` the `std::optional` must be dereferenced to get to the `polymorphic_value`, which then requires a second dereference to get to the underlying `T`. This access pattern is undesirable.

§ 3.5. Lack of hashing and comparisons

For a given user-defined type, `T`, there are multiple strategies to make `polymorphic_value<T>` hashable and comparable. Without requiring additional named member functions on the type, `T`, or mandating that `T` has virtual functions and RTTI, the authors do not see how `polymorphic_value` can generically support hashing or comparisons. Incurring a cost for functionality that is not required goes against the 'pay for what you use' philosophy of C++.

For a given user-defined type `T` the user is free to specialize `std::hash` and implement comparison operators for `polymorphic_value<T>`.

§ 3.6. Custom copiers and deleters

The resource management performed by `polymorphic_value` - copying and destruction of the managed object - can be customized by supplying a `_copier_` and `_deleter_`. If no copier or deleter is supplied then a default copier or deleter may be used.

A custom copier and deleter are `_not_` required, if no custom copier and deleter are provided then the copy constructor and destructor of the managed object will be used.

The default deleter is already defined by the standard library and used by `unique_ptr`.

We define the default copier in technical specifications below.

§ 3.7. Allocator Support

Previous revisions of this paper did not support allocators. However, support is desirable as it offers an opportunity to mitigate the cost of allocations. There is existing precedence for allocator support of types in the memory management library; `std::shared_ptr` supports allocators via `std::allocate_shared`, [M. Knejp] suggested the introduction of `std::allocate_unique` to support allocator use with `std::unique_ptr`.

`polymorphic_value` internally uses type-erased to create an internal control block object responsible for cloning itself and the actual type derived from `T`. It is possible to provide different types of control blocks to support allocation from multiple sources [Impl].

Memory management for `polymorphic_value` can be fully controlled via the `allocate_polymorphic_value` function which allows passing in an allocator to control the source of memory. Custom copier and deleter then use the allocator for allocations and deallocations.

§ 3.8. Design changes from `cloned_ptr`

The design of `polymorphic_value` is based upon `cloned_ptr` (from an early revision of this paper) and modified following advice from LEWG. The authors (who unreservedly agree with the design direction suggested by LEWG) would like to make explicit the cost of these design changes.

`polymorphic_value<T>` has value-like semantics: copies are deep and `const` is propagated to the owned object. The first revision of this paper presented `cloned_ptr<T>` which had mixed pointer/value semantics: copies are deep but `const` is not propagated to the owned object. `polymorphic_value` can be built from `cloned_ptr` and `propagate_const` but there is no way to remove `const` propagation from `polymorphic_value`.

As `polymorphic_value` is a value, `dynamic_pointer_cast`, `static_pointer_cast` and `const_pointer_cast` are not provided. If a `polymorphic_value` is constructed with a custom copier or deleter, then there is no way for a user to implement cast operations like those that are provided by the standard for `std::shared_ptr`.

§ 3.9. No implicit conversions

Following design feedback, `polymorphic_value`'s constructors have been made explicit so that surprising implicit conversions cannot take place. Any conversion to a `polymorphic_value` must be explicitly requested by user-code.

The converting assignment operators that were present in earlier drafts have also been removed.

For a base class, `BaseClass`, and derived class, `DerivedClass`, the converting assignment

```
polymorphic_value<DerivedClass> derived;  
polymorphic_value<Base> base = derived;
```

is no longer valid, the conversion must be made explicit:

```
polymorphic_value<DerivedClass> derived;  
auto base = polymorphic_value<Base>(derived);
```

The removal of converting assignments makes `make_polymorphic_value` slightly more verbose to use:

```
polymorphic_value<Base> base = make_polymorphic_value<DerivedClass>(args);
```

is not longer valid and must be written as

```
auto base = polymorphic_value<Base>(make_polymorphic_value<DerivedClass>(args));
```

This is somewhat cumbersome so `make_polymorphic_value` has been modified to take an optional extra template argument allowing users to write

```
polymorphic_value<Base> base = make_polymorphic_value<Base, DerivedClass>(args);
```

The change from implicit to explicit construction is deliberately conservative. One can change explicit constructors into implicit constructors without breaking code (other than SFINAE checks), the reverse is not true. Similarly, converting assignments could be added non-disruptively but not so readily removed.

§ 3.10. Impact on the standard

This proposal is a pure library extension. It requires additions to be made to the standard library header `<memory>`.

§ 4. Technical specifications

Add the following entry to [tab:support.ft]

Macro NameValue | Header(s) | |::|::|::| | `__cpp_lib_polymorphic_value` | xxxxxxL | `<memory>` |

§ 4.1. Additions in [memory.syn] 20.2.2:

```
// [indirect.value], class template indirect_value
template <class T> struct default_copy;
template <class T> struct copier_traits;

template <class T> class polymorphic_value;

template <class T, class ...Ts>
    constexpr polymorphic_value<T> make_polymorphic_value(Ts&& ...ts);

template <class T, class A = std::allocator<T>, class... Ts>
    constexpr polymorphic_value<T> allocate_polymorphic_value(A& a, Ts&&... ts);

template<class T>
    constexpr void swap(polymorphic_value<T>& p, polymorphic_value<T>& u) noexcept;
```

§ 4.2. X.W Class template `copier_traits` [copier.traits]

```
namespace std {
    template <class T>
        struct copier_traits {
            using deleter_type = *see below*;
        };
}
```

`using deleter_type = see below;`

- Type: `T::deleter_type` if the *qualified-id* `T::deleter_type` is valid and denotes a type; otherwise, `void (*) (U*)` if `T` is of the form `U* (*) (V)` for types `U` and `V`; otherwise, there is no member `deleter_type`.

§ 4.3. X.X Class template `default_copy` [default.copy]


```
namespace std {
template <class T> struct default_copy {
    using deleter_type = default_delete<T>;
    constexpr default_copy() noexcept = default;
    constexpr T* operator()(const T& t) const;
};

} // namespace std
```

The class template `default_copy` [p1950r1] serves as the default copier for the class template `polymorphic_value`.

```
constexpr T* operator()(const T& t) const;
```

- Effects: Equivalent to: `return new T(t);`

§ 4.4. X.Y Class `bad_polymorphic_value_construction` [`bad_polymorphic_value_construction`]

```
namespace std {
class bad_polymorphic_value_construction : public exception
{
public:
    bad_polymorphic_value_construction() noexcept = default;

    const char* what() const noexcept override;
};
}
```

Objects of type `bad_polymorphic_value_construction` are thrown to report invalid construction of a `polymorphic_value`.

```
const char* what() const noexcept override;
```

- Returns: An implementation-defined NTBS.

§ 4.5. X.Z Class template `polymorphic_value` [`polymorphic_value`]

§ 4.5.1. X.Z.1 Class template `polymorphic_value` general [`polymorphic_value.general`]

A `polymorphic_value` is an object that manages the lifetime of an owned object. A `polymorphic_value` object may own objects of different types at different points in its lifetime. A `polymorphic_value` object is empty if it has no owned object. `polymorphic_value` implements value semantics: the owned object (if any) is copied or destroyed when the `polymorphic_value` is copied or destroyed. Copying and destruction of the owned object can be customized by supplying a copier and a deleter, respectively.

The template parameter `T` of `polymorphic_value<T>` shall be a non-union class type; otherwise the program is ill-formed. The template parameter `T` of `polymorphic_value<T>` may be an incomplete type.

A copier and deleter are said to be `_present_` if and only if a `polymorphic_value` object is constructed from a non-null pointer, or from a `polymorphic_value` object where a copier and a deleter are present.

§ 4.5.2. X.Z.2 Class template `polymorphic_value` synopsis [`polymorphic_value.synopsis`]

```
namespace std {
template <class T> class polymorphic_value {
public:
```

```

using element_type = T;

// Constructors
constexpr polymorphic_value() noexcept;

constexpr polymorphic_value(nullptr_t) noexcept;

template <class U> constexpr explicit polymorphic_value(U&& u);

template <class U, class C=default_copy<U>,
          class D=typename copier_traits<C>::deleter_type>
    constexpr explicit polymorphic_value(U* p, C c=C(), D d=D());

constexpr polymorphic_value(const polymorphic_value& p);

template <class U>
    constexpr explicit polymorphic_value(const polymorphic_value<U>& p);

constexpr polymorphic_value(polymorphic_value&& p) noexcept;

template <class U>
    constexpr explicit polymorphic_value(polymorphic_value<U>&& p);

// Destructor
constexpr ~polymorphic_value();

// Assignment
constexpr polymorphic_value& operator=(const polymorphic_value& p);
constexpr polymorphic_value& operator=(polymorphic_value&& p) noexcept;

// Modifiers
constexpr void swap(polymorphic_value& p) noexcept;

// Observers
constexpr const T& operator*() const;
constexpr T& operator*();
constexpr const T* operator->() const;
constexpr T* operator->();
constexpr explicit operator bool() const noexcept;

// polymorphic_value specialized algorithms
friend constexpr void swap(polymorphic_value& p, polymorphic_value& u) noexcept;
};

// polymorphic_value creation
template <class T, class U=T, class... Ts>
constexpr polymorphic_value<T> make_polymorphic_value(Ts&&... ts);

template <class T, class U = T, class A = allocator<U>, class... Ts>
constexpr polymorphic_value<T> allocate_polymorphic_value(allocator_arg_t, A& a, Ts&&... ts
);

} // end namespace std

```

§ 4.5.3. X.Z.3 Class template `polymorphic_value` constructors [`polymorphic_value.ctor`]

```

constexpr polymorphic_value() noexcept;
constexpr polymorphic_value(nullptr_t) noexcept;

```

- Postconditions: `*this` is empty.

```

template <class U> constexpr explicit polymorphic_value(U&& u);

```

Let `V` be `remove_cvref_t<U>`.

- Constraints: `is_convertible_v<V*, T*>` is true. `is_constructible_v<V, U>` is true.
- Preconditions: `V` meets the `Cpp17CopyConstructible` requirements.
- Effects: Constructs a `polymorphic_value` which owns an object of type `V`, direct-non-list-initialized with `std::forward<U>(u)`.
- Throws: Any exception thrown by the selected constructor of `V` or `bad_alloc` if required storage cannot be obtained.

```
template <class U, class C=default_copy<U>,
         class D=typename copier_traits<C>::deleter_type>
constexpr explicit polymorphic_value(U* p, C c=C(), D d=D());
```

- Constraints: `is_convertible_v<U*, T*>` is true.

If the arguments `c` and/or `d` are not supplied, then `C` and/or `D` respectively are default constructible types that are not pointer types.

- Preconditions: `C` and `D` meet the `Cpp17CopyConstructible` and `Cpp17Destructible` requirements.

If `p` is non-null then invoking the expression `c(*p)` returns a non-null `U*` is as if copy constructed from `*p`. The expression `d(p)` is well formed, has well-defined behavior, and does not throw exceptions.

Where `q=c(*p)`, the expression `d(q)` is well-defined and does not throw exceptions.

- Effects: If `p` is null, creates an empty object otherwise creates an object that owns the object `*p`, with a copier of type `C` initialized from `std::move(c)` and a deleter of type `D` initialized from `std::move(d)`.
- Throws: `bad_alloc` if required storage cannot be obtained; `bad_polymorphic_value_construction` if `is_same_v<C, default_copy<U>>`, `is_same_v<D, default_delete<U>>` and `typeid(*p) != typeid(U)` are all true.
- Postconditions: If `p` is null, the empty object created has no copier and no deleter. Otherwise the object created owns the object `*p` and has a copier and a deleter present, initialized from `std::move(c)` and `std::move(d)` respectively.

```
template <class U, class A>
constexpr explicit polymorphic_value(U* u, std::allocator_arg_t, const A& alloc)
```

- Constraints: `is_convertible_v<U*, T*>` is true.
- Preconditions: `A` meets the `Cpp17Allocator` requirements.
- Effects: Constructs a `polymorphic_value` that owns the object 'u'. Construction shall use a copy of `a` to allocate memory for internal use.
- Throws: `bad_alloc` if required storage cannot be obtained;

```
polymorphic_value(const polymorphic_value& pv);
template <class U> constexpr explicit polymorphic_value(const polymorphic_value<U>& pv);
```

- Constraints: For the second constructor, `is_convertible_v<U*, T*>` is true.
- Effects: If `pv` is empty, constructs an empty object. Otherwise creates an object that owns a copy of the object managed by `pv`. If a copier and deleter are present in `pv` then the copy is created by the copier in `pv`. Otherwise the copy is created by copy construction of the owned object. If a copier and deleter are present in `pv` then the copier and deleter of the object constructed are copied from those in `pv` so that they are present and of type `C` and `D` respectively.
- Postconditions: `bool(*this) == bool(pv)`.
- Throws: Any exception thrown by invocation of the copier, copying the copier and deleter, or `bad_alloc` if required storage cannot be obtained.

```
polymorphic_value(polymorphic_value&& pv) noexcept;
template <class U> constexpr explicit polymorphic_value(polymorphic_value<U>&& pv);
```

- Constraints: For the second constructor, `is_convertible_v<U*, T*>` is true.
- Effects: If `pv` is empty, constructs an empty object. Otherwise the object owned by `pv` is transferred to the constructed object. If a copier and deleter are present in `pv` then the copier and deleter are transferred to the constructed object so that they are present and of type `C` and `D` respectively.
- Postconditions: `*this` owns the object previously owned by `pv` (if any). `pv` is empty.

4.5.4. X.Z.4 Class template `polymorphic_value` destructor [`polymorphic_value.dtor`]

```
constexpr ~polymorphic_value();
```

- Effects: If a copier `c` and a deleter `d` are present, evaluates `d(operator->())` and destroys `c` and `d`. Otherwise destroys the owned object (if any) and frees its storage.

4.5.5. X.Z.5 Class template `polymorphic_value` assignment [`polymorphic_value.assignment`]

```
constexpr polymorphic_value& operator=(const polymorphic_value& pv);
```

- Effects: Equivalent to `polymorphic_value(pv).swap(*this)`. No effects if an exception is thrown.
- Throws: Any exception thrown by the copier or `bad_alloc` if required storage cannot be obtained.
- Returns: `*this`.
- Postconditions: The state of `*this` is as if copy constructed from `pv`.

```
constexpr polymorphic_value& operator=(polymorphic_value&& pv) noexcept;
```

- Effects: Equivalent to `polymorphic_value(std::move(pv)).swap(*this)`.
- Returns: `*this`.
- Postconditions: The state `*this` is equivalent to the original state of `pv`.

4.5.6. X.Z.6 Class template `polymorphic_value` modifiers [`polymorphic_value.modifiers`]

```
constexpr void swap(polymorphic_value& p) noexcept;
```

- Constraints: `is_nothrow_swappable` is true. `is_nothrow_swappable` is true.
- Effects: Invokes swap on the stored pointers and on the stored copiers and deleters of `*this` and `p`.

4.5.7. X.Z.7 Class template `polymorphic_value` observers [`polymorphic_value.observers`]

```
constexpr const T& operator*() const;
constexpr T& operator*();
```

- Preconditions: `bool(*this)` is true.
- Returns: A reference to the owned object.

```
constexpr const T* operator->() const;
constexpr T* operator->();
```

- Preconditions: `bool(*this)` is true.
- Returns: A pointer to the owned object.

```
explicit operator bool() const noexcept;
```

- Returns: false if the `polymorphic_value` is empty, otherwise true.

§ 4.5.8. X.Z.8 Class template `polymorphic_value` creation [`polymorphic_value.creation`]

```
template <class T, class U=T, class ...Ts>
constexpr polymorphic_value<T> make_polymorphic_value(Ts&& ...ts);
```

- Constraints: `is_constructible_v<U, Ts...>` is true.
- Preconditions: `U` meets the `Cpp17CopyConstructible` requirements.
- Returns: A `polymorphic_value<T>` owning an object of type `U` direct-non-list-initialized with `std::forward<Ts>(ts)...`.

[Note: Implementations are encouraged to avoid multiple allocations. - end note]

```
template <class T, class U = T, class A = allocator<U>, class... Ts>
constexpr polymorphic_value<T> allocate_polymorphic_value(const A& a, Ts&&... ts);
```

- Constraints: `is_constructible_v<U, Ts...>` is true.
- Preconditions: `U` meets the `Cpp17CopyConstructible` requirements.
- Effects: Constructs a `polymorphic_value` that shall use a copy of `a` to allocate memory for internal use.
- Returns: A `polymorphic_value<T>` owning an object of type `U` direct-non-list-initialized with `std::forward<Ts>(ts)...`.

§ 4.5.9. X.Z.9 Class template `polymorphic_value` specialized algorithms [`polymorphic_value.spec`]

```
friend constexpr void swap(polymorphic_value& p, polymorphic_value& u) noexcept;
```

- Effects: Equivalent to `p.swap(u)`.

§ 5. Acknowledgements

The authors would like to thank Maciej Bogus, Matthew Calabrese, Casey Carter, Germán Diago, Louis Dionne, Bengt Gustafsson, Tom Hudson, Stephan T Lavavej, Tomasz Kamiński, David Krauss, Thomas Koeppe, LanguageLawyer, Nevin Liber, Nathan Myers, Roger Orr, Geoff Romer, Patrice Roy, Tony van Eerd and Ville Voutilainen for suggestions and useful discussion.

The authors would also extend thanks for contributions to the reference implementation which has driven the design, including Anthony Williams, Ed Catmur, and Marcell Kiss.

§ 5.1. References

[N3339] "A Preliminary Proposal for a Deep-Copying Smart Pointer", W.E.Brown, 2012

[p1950r1] `indirect_value`: A Free-Store-Allocated Value Type For C++

[P0302r1] "Removing Allocator support in `std::function`", Jonathan Wakely

[M. Knejp] [P0316R0: allocate_unique and allocator_delete](#)

[S.Parent] ["C++ Seasoning"](#), Sean Parent, 2013

[Impl] [Reference implementation: polymorphic_value](#), J.B.Coe

[P0302r1] ["Removing Allocator support in std::function"](#), Jonathan Wakely