

P0556R1: Integral power-of-2 operations

Introduction

This paper proposes to add simple free functions for operations related to integral powers of 2 on all unsigned integer types.

A previous proposal was in "N3864: A constexpr bitwise operations library for C++" by Matthew Fioravante.

The foundation for digital computers are binary digits (also called "bits"), and as such operating with a base-2 representation of data is often most natural or most efficient.

It is expected that the functions provided with this proposal will be, at some later time, overloaded for `std::datapar`, the nascent SIMD data type (see P0214R3: "Data-Parallel Vector Types & Operations" by Matthias Kretz).

Changes

P0556R0 was favorably reviewed by SG6 and passed to LEWG with the following changes:

- Provide wide-contract `log2p1` instead of narrow-contract `log2`.
- Rename `ceilpow2` to `ceil2` and `floorpow2` to `floor2`.

Design considerations

The functions are provided for unsigned operands only, since the domain of the proposed functions is positive.

This proposal uses readable English names for the operations, using the established abbreviations `pow` and `ceil`.

It is conceivable to add these functions to the header `<cstdliblib>` (`abs` and `div` are already there), although a new header such as `<pow2>` seems more focused. The wording below adds a new header.

Per prevailing LWG convention, only those functions are marked `noexcept` that have a wide contract, i.e. no restrictions on the values of the function arguments.

All functions are mathematically pure, i.e. do not access or modify data other than the argument values, and thus are marked `constexpr`.

Open issues

- Should the functions also be available for signed T? The proposed functions are not defined for negative values, but some programmers like to deal in signed ints.
- Should the result be unspecified instead of undefined behavior (implied by "Requires" clauses) if the argument is outside of the domain?

Wording

Add the header `<pow2>` to the table in 17.5.1.2 [headers].

Append a new subsection to clause 26 [numerics] with the following content:

29.10 Integral powers of 2 [numeric.pow.two]

29.10.1 Header `<pow2>` synopsis [pow2.syn]

```
namespace std {  
    template <class T>  
        constexpr bool ispow2(T x) noexcept;  
    template <class T>  
        constexpr T ceil2(T x);  
}
```

```
template <class T>
constexpr T floor2(T x) noexcept;
template <class T>
constexpr T log2p1(T x) noexcept;
}
```

29.10.1 Operations [numerics.pow.two.ops]

```
template <class T>
constexpr bool ispow2(T x) noexcept;
```

Returns: true if x is a power of two.

Remarks: Participates in overload resolution only if T is an unsigned integer type (3.9.1 [basic.fundamental]).

```
template <class T>
constexpr T ceil2(T x);
```

Requires: A value y representable as a value of type T exists where ispow2(y) is true and y >= x.

Returns: The minimal value y such that ispow2(y) is true and y >= x.

Throws: Nothing.

Remarks: Participates in overload resolution only if T is an unsigned integer type (3.9.1 [basic.fundamental]).

```
template <class T>
constexpr T floor2(T x) noexcept;
```

Returns: If x == 0, 0; otherwise the maximal value y such that ispow2(y) is true and y <= x.

Remarks: Participates in overload resolution only if T is an unsigned integer type (3.9.1 [basic.fundamental]).

```
template <class T>
constexpr T log2p1(T x) noexcept;
```

Returns: If x == 0, 0; otherwise one plus the base-2 logarithm of x, with any fractional part discarded.

Remarks: Participates in overload resolution only if T is an unsigned integer type (3.9.1 [basic.fundamental]).

References

- ISO/IEC JTC1 SC22 WG21 [N3864](#): "A constexpr bitwise operations library for C++" by Matthew Fioravante
- ISO/IEC JTC1 SC22 WG21 [P0214R3](#): "Data-Parallel Vector Types & Operations" by Matthias Kretz
- [ARM Compiler User Guide](#) [large PDF]
- [Intel x86 Instruction Set Reference](#) [large PDF]
- PowerPC Architecture Book, Version 2.02: [Book I: PowerPC User Instruction Set Architecture](#) [large PDF inside ZIP]