

Document Number: P1423R2
Date: 2019-06-16
Audience: Library Evolution Working Group
Library Working Group
Reply-to: Tom Honermann <tom@honermann.net>

char8_t backward compatibility remediation

- [Changes since P1423R1](#)
- [Introduction](#)
- [Examples](#)
- [Anticipated impact](#)
- [Remediation approaches](#)
 - [Disable char8_t support](#)
 - [Add overloads](#)
 - [Change u8 literals to ordinary literals with escape sequences](#)
 - [reinterpret_cast u8 literals to char](#)
 - [Emulate C++17 u8 literals](#)
 - [Substitute class types for C arrays initialized with u8 string literals](#)
 - [Use explicit conversion functions](#)
 - [Tooling](#)
- [Options considered to reduce backward compatibility impact](#)
 - 1) [Reinstate u8 literals as type char and introduce a new literal prefix for char8_t](#)
 - 2) [Allow implicit conversions from char8_t to char](#)
 - 3) [Allow initializing an array of char with a u8 string literal](#)
 - 4) [Allow initializing an array with a reference to an array](#)
 - 5) [Allow std::string to be initialized with char8_t based types](#)
 - 6) [Allow implicit conversions from std::u8string to std::string](#)
 - 7) [Add deleted ostream inserters for char8_t, char16_t, and char32_t](#)
 - 8) [Allow std::filesystem::u8path to accept ranges and iterators with char8_t value types](#)
- [Proposal](#)
- [Wording](#)
 - [Library wording](#)
 - [Annex C Compatibility wording](#)
 - [Annex D Compatibility features wording](#)
- [References](#)

Changes since [P1423R1](#)

- Addressed wording and feature feedback provided during the 2019-05-21 LWG telecon:
 - Added deleted overloads of `basic_ostream<wchar_t, ...>::operator<<` for `char8_t`, `char16_t`, and `char32_t` character and string types. This maintains consistency of deleted overloads for ordinary and wide streams.
 - Moved wording for the deleted ostream inserter overloads from [29.7.5.2.4 \[ostream.inserters.character\]](#) to the ostream synopsis in [29.7.5.1 \[ostream\]](#) and removed parameter names.
 - Updated code comments in the new paragraph added to [C.5.11 \[diff.cpp17.input.output\]](#) to avoid assumptions of which ostream inserter overload would be invoked.
- Rebased wording on N4810.

Introduction

The support for `char8_t` as adopted for C++20 via [P0482R6](#) ^[P0482R6] affects backward compatibility for existing C++17 programs in at least the following ways:

1. Introduction of a new `char8_t` keyword, new `std::u8string`, `std::u8string_view`, `std::u8streampos` type aliases and `std::mbrotoc8` and `std::c8rtomb` functions; these names may conflict with existing uses of these names.
2. Change of return type for `std::filesystem::path` member functions `u8string` and `generic_u8string`.
3. Change of type for u8 character and string literals and u8 raw string literals.

This paper does *not* further discuss case 1 above. Adding new keywords and new members to the `std` namespace is business as usual; see [SD-8](#) ^[SD-8]. It is acknowledged that these additions will affect some code bases. Code surveys have found that these names have generally been used to emulate the set of features introduced with the adoption of [P0482R6](#) ^[P0482R6]. In some cases, existing code has already been updated to adapt to the new standard features. For example, [EASTL](#) will now use the the standard provided `char8_t` type when available instead of the type alias previously used. The pull request for this change can be found at <https://github.com/electroncarts/EASTL/pull/239>.

Case 2 above is a change that does *not* fit into the set of standard library rights reserved in [SD-8](#) ^[SD-8]. This is a cause for concern, but is somewhat mitigated by the fact that `std::filesystem` is new with C++17 and therefore does not have a long history of use. Some options for dealing with this change are discussed later in this paper.

Case 3 above is the change responsible for most of the backward compatibility impact.

This paper is motivated by three goals:

- To document a set of options available to programmers to facilitate migration of existing code to C++20. Where possible, options are presented for writing code that is compatible with both C++17 and C++20.

- To ensure that WG21 members are aware of the backward compatibility issues and anticipated impact, and find the set of options available to mitigate the impact acceptable.
- To consider options available to reduce backward compatibility impact. This paper documents a number of such options, but only proposes two small standard library changes intended to remove backward compatibility impact that was not intended by the adoption of P0482R6.

Examples

The following table presents examples of well-formed C++17 code that is either ill-formed or behaves differently in C++20. The table also reflects the intended changes proposed in this paper. Note that most of these examples remain ill-formed with this proposal. This is intentional as the examples reflect problematic code that leads to mojibake in C++17 code due to use of the same type (char) for multiple encodings (execution encoding and UTF-8).

Code	C++17	C++20 with P0482R6	C++20 with this proposal
<pre>const char *p = u8"text";</pre>	Initializes p with the address of the UTF-8 encoded string.	Ill-formed.	Ill-formed.
<pre>char a[] = u8"text";</pre>	Initializes a with the UTF-8 encoded string.	Ill-formed.	Ill-formed.
<pre>int operator ""_udl(const char*, unsigned long); int v = u8"text"_udl;</pre>	Initializes v with the result of calling operator ""_udl with the UTF-8 encoded string literal.	Ill-formed.	Ill-formed.
<pre>std::string s(u8"text");</pre>	Initializes s with the UTF-8 encoded string.	Ill-formed.	Ill-formed.
<pre>std::filesystem::path p = ...; std::string s = p.u8string();</pre>	Initializes s with the UTF-8 encoded representation of the file path stored in p.	Ill-formed.	Ill-formed.
<pre>std::cout << u8'x'; std::cout << u8"text";</pre>	Writes a sequence of UTF-8 code units as characters to stdout. (mojibake if the execution character encoding is not UTF-8)	Writes an integer or pointer value to stdout. (consistent with handling of char16_t and char32_t)	Ill-formed. (for all of char8_t, char16_t, and char32_t)
<pre>std::filesystem::u8path(u8"filename");</pre>	Constructs a std::filesystem::path object from the UTF-8 encoded string.	Ill-formed.	Constructs a std::filesystem::path object from the UTF-8 encoded string.

Anticipated impact

u8 string literals were added in C++11, but support for u8 character literals was only added in C++17.

Code surveys have so far revealed little use of u8 literals. Google and Facebook have both reported less than 1000 occurrences in their code bases, approximately half of which occur in test code. Representatives of both organizations have stated that, given the actual size of their code base, this is an insignificant number of occurrences. Likewise, Firefox contains around 100 occurrences and Mozilla engineers have reviewed this paper and have no concerns regarding addressing the existing uses using the remediation approaches discussed here.

Code surveys have been attempted on github, but github search doesn't facilitate distinguishing uses of u8 as identifiers (which is quite common) vs use as a UTF-8 literal. Further, github doesn't provide a search that filters out duplicate hits for the same source code in different repositories. As a result, finding instances of u8 literals is challenging. Most cases that were identified were in tests included in clones of Clang and gcc.

Searches on Debian code search found uses in only a few packages and, with one exception discussed below, only a small number of uses (mostly single digit counts), most of which occurred in tests.

Survey results for Debian code search (<https://codesearch.debian.net>) follow. These exclude hits to gcc, clang, packages like fmt and eastl that have already been conditionalized for char8_t in C++20, and C code. Additionally, packages bundled with other packages are omitted to avoid double counting. Search hits reflect number of lines matching the search, not number of occurrences. Search results are categorized by hits in program source files vs hits in test source files.

There is one clear outlier in these search results. Chromium has two orders of magnitude more uses of u8 literals than any other package. The Chromium team was contacted to discuss this. Almost all of the existing uses appear in bulk data source files that the Chromium team has determined can be mechanically addressed.

Searched for	Debian packages (out of ~18000)
char8_t	spring (emulates its own char8_t support)
u8string	libopenmpt (defines a mpt::u8string typedef of std::basic_string with a custom char_traits) spring (defines a std::u8string class that derives from std::string)
u8string_view	<none>
u8streampos	<none>
mbrtoc8	<none>
c8rtomb	<none>
u8path(u8"text")	<none>

u8"text"	chromium (~10310, ~102 files) firefox (97 hits, 1 files, 3 test files) icu (83 hits, 1 files, 5 test files) qbs (56 hits, 1 file, 1 test file) mongodb (30 hits, 2 test files) aseba (28 hits, 1 file) monero (26 hits, 1 file, 1 test file) nlohmann-json (21 hits, 1 file, 3 test files) bambootracker (20 hits, 5 files) capnproto (18 hits, 1 file, 1 test file) lgogdownloader (11 hits, 1 file) libosmium (10 hits, 3 test files) cbmc (8 hits, 3 test files) maim (8 hits, 1 file) octave-ltfat (8 hits, 1 file) praat (8 hits, 2 files) slop (8 hits, 1 file) mame (7 hits, 3 files) nlohmann-json3 (7 hits, 3 test files) sdcc (7 hits, 1 test file) antlr4 (3 hits, 1 file) keyman-keyboardprocessor (3 hits, 2 test files) scram (3 hits, 2 test files) tesseract (3 hits, 1 test file) boost1.67 (2 hits, 1 test file) freeorion (2 hits, 1 file) supertux (2 hits, 1 file) cjs (1 hit, 1 test file) cpp-hocon (1 hit, 1 test file) efl (1 hit, 1 file) gjs (1 hit, 1 test file) kate4 (1 hit, 1 example file) kodi (1 hit, 1 test file) libtcd (1 hit, 1 test file) retroarch (1 hit, 1 file) rtags (1 hit, 1 test file)
u8R"(text)"	chromium (940, 2 files, 2 test files) kate4 (2 hits, 1 example file, 1 test file) nlohmann-json (2 hits, 1 test file) nlohmann-json3 (2 hits, 1 test file) ksyntax-highlighting (1 hit, 1 test file) ktexteditor (1 hit, 1 test file)

Remediation approaches

A single approach to addressing backward compatibility impact is unlikely to be the best approach for all projects. This section presents a number of options to address various types of backward compatibility impact. In some cases, the best solution may involve a mix of these options.

Each of these approaches assumes a requirement for continued use of UTF-8 encoded literals with char based types. For most projects, such a requirement is expected to be temporary while the project is fully migrated to C++20. However, some projects may retain a sustained need for such literals. For those projects, the [Emulate C++17 u8 literals](#) approach is able to address most cases of backward compatibility impact.

Disable char8_t support

The simplest possible solution in the short term is to simply disable the new features completely. Clang and gcc will allow disabling char8_t features in both the language and standard library, via a `-fno-char8_t` option. It is expected that Microsoft and EDG based compilers will offer a similar option.

This option should be considered a short-term solution to enable testing existing C++17 code compiled as C++20 with minimal effort. This isn't a viable long-term option as continued use would potentially complicate composition with code that depends on the new features.

Add overloads

Adding function overloads that accept char8_t based types is an effective step towards full migration to C++20. Ideally, older char based functions would eventually be removed.

Before	After
<pre>int ft(const char*); ft(u8"text");</pre>	<pre>int ft(const char*); #if defined(__cpp_char8_t) int ft(const char8_t*); #endif ft(u8"text"); // C++17 or C++20</pre>
<pre>int operator ""_udl(const char*, unsigned long);</pre>	<pre>int operator ""_udl(const char*, unsigned long); #if defined(__cpp_char8_t)</pre>

<pre>int v = u8"text"_udl;</pre>	<pre>int operator ""_udl(const char8_t*, unsigned long); #endif int v = u8"text"_udl; // C++17 or C++20</pre>
----------------------------------	--

Change u8 literals to ordinary literals with escape sequences

This approach may be a reasonable option when the execution encoding is ASCII based (but not UTF-8; otherwise just use ordinary literals) and characters outside the basic source character set are infrequently used in existing u8 literals. This approach matches how code using UTF-8 had to be written prior to C++11.

Before	After
<pre>u8"\u00E1"</pre>	<pre>"\xC3\xA1" // U+00E1</pre>
<pre>u8"á" (assuming source encoding is UTF-8)</pre>	<pre>"\xC3\xA1" // U+00E1 (works with any source encoding)</pre>

reinterpret_cast u8 literals to char

Common uses of u8 literals can be handled in a backward compatible manner through use of reinterpret_cast. Note that use of reinterpret_cast is well-formed in these situations since [values of type char may be used to access values of other types](#). Such code is valid in both C++17 and C++20.

This approach may suffice when there are just a few uses of UTF-8 literals that need to be addressed and the uses do not appear in constexpr context. In general, sprinkling reinterpret_cast all over a code base is not desirable.

Before	After
<pre>const char &r = u8'x';</pre>	<pre>const char &r = reinterpret_cast<const char &>(u8'x'); // C++17 or C++20</pre>
<pre>const char *p = u8"text";</pre>	<pre>const char *p = reinterpret_cast<const char *>(u8"text"); // C++17 or C++20</pre>

Emulate C++17 u8 literals

The techniques applied here are also applicable to the examples illustrated in the prior section regarding use of reinterpret_cast. This approach makes use of [P0732R2](#) [P0732R21](#) to enable constexpr UTF-8 encoded char based literals using a user defined literal. The example code below defines overloaded character and string UDL operators named _as_char. These UDLs can then be used in place of existing UTF-8 character and string literals.

```
#include <utility>  
  
template<std::size_t N>  
struct char8_t_string_literal {  
    static constexpr inline std::size_t size = N;  
    template<std::size_t... I>  
    constexpr char8_t_string_literal(  
        const char8_t (&r)[N],  
        std::index_sequence<I...>)  
    :  
        s{r[I]...}  
    {}  
    constexpr char8_t_string_literal(  
        const char8_t (&r)[N])  
    :  
        char8_t_string_literal(r, std::make_index_sequence<N>())  
    {}  
    auto operator <=>(const char8_t_string_literal&) = default;  
    char8_t s[N];  
};  
  
template<char8_t_string_literal L, std::size_t... I>  
constexpr inline const char as_char_buffer[ sizeof...(I) ] =  
    { static_cast<char>(L.s[I])... };  
  
template<char8_t_string_literal L, std::size_t... I>  
constexpr auto& make_as_char_buffer( std::index_sequence<I...> ) {  
    return as_char_buffer<L, I...>;  
}  
  
constexpr char operator ""_as_char(char8_t c) {  
    return c;  
}  
  
template<char8_t_string_literal L>  
constexpr auto& operator""_as_char() {  
    return make_as_char_buffer<L>(std::make_index_sequence<decltype(L)::size>());  
}
```

Before	After
--------	-------

<code>constexpr const char &r = u8'x';</code>	<code>constexpr const char &r = u8'x' as_char; // C++20 only</code>
<code>constexpr const char *p = u8"text";</code>	<code>constexpr const char *p = u8"text" as_char; // C++20 only</code>
<code>// gcc extension in C++17; standard C++ doesn't permit conversion // to arrays of unknown bound. constexpr const char (&r)[] = u8"text";</code>	<code>// Ok in C++20 with P0388R2 [P0388R2]. constexpr const char (&r)[] = u8"text" as_char; // C++20 only</code>

When wrapped in macros, the above UDL can be used to retain source compatibility across C++17 and C++20 for all known scenarios except for array initialization.

```
#if defined(__cpp_char8_t)
#define U8(x) u8##x##_as_char
#else
#define U8(x) u8##x
#endif
```

Before	After
<code>constexpr const char &r = u8'x';</code>	<code>constexpr const char &r = U8('x'); // C++17 or C++20</code>
<code>constexpr const char *p = u8"text";</code>	<code>constexpr const char *p = U8("text"); // C++17 or C++20</code>
<code>// gcc extension in C++17; standard C++ doesn't permit conversion // to arrays of unknown bound. constexpr const char (&r)[] = u8"text";</code>	<code>// Ok in C++20 with P0388R2 [P0388R2]. constexpr const char (&r)[] = U8("text"); // C++17 or C++20</code>

Substitute class types for C arrays initialized with u8 string literals

In C++17, arrays of char may be initialized with u8 string literals, but such initialization is ill-formed in C++20. C++17 behavior can be emulated by substituting a class type with appropriate class template argument deduction guides.

```
#include <utility>

template<std::size_t N>
struct char_array {
    template<std::size_t P, std::size_t... I>
    constexpr char_array(
        const char (&r)[P],
        std::index_sequence<I...>)
    :
        data{(I<P?r[I]:'\0')...}
    {}
    template<std::size_t P, typename = std::enable_if_t<(P<=N)>>
    constexpr char_array(const char(&r)[P])
        : char_array(r, std::make_index_sequence<N>())
    {}
};

#if defined(__cpp_char8_t)
template<std::size_t P, std::size_t... I>
constexpr char_array(
    const char8_t (&r)[P],
    std::index_sequence<I...>)
:
    data{(I<P?static_cast<char>(r[I]):'\0')...}
{}
template<std::size_t P, typename = std::enable_if_t<(P<=N)>>
constexpr char_array(const char8_t(&r)[P])
    : char_array(r, std::make_index_sequence<N>())
{}
#endif

constexpr (operator const char() const)[N] {
    return data;
}
constexpr (operator char())[N] {
    return data;
}

char data[N];
};

template<std::size_t N>
char_array(const char(&)[N]) -> char_array<N>;
#if defined(__cpp_char8_t)
template<std::size_t N>
char_array(const char8_t(&)[N]) -> char_array<N>;
#endif
```

Before	After
<code>char a[] = u8"text";</code>	<code>char_array a = u8"text";</code> // Ok, initialized with "text\0"
<code>constexpr char a[] = u8"text";</code>	<code>constexpr char_array a = u8"text";</code> // Ok, initialized with "text\0"
<code>constexpr char a[3] = u8"text";</code> // ill-formed	<code>constexpr char_array<3> a = u8"text";</code> // ill-formed (too many initializers)
<code>constexpr char a[6] = u8"text";</code>	<code>constexpr char_array<6> a = u8"text";</code> // Ok, initialized with "text\0\0"

Use explicit conversion functions

Explicit conversion functions can be used, in a C++17 compatible manner, to cope with the change of return type to the `std::filesystem::path` member functions when a UTF-8 encoded path is desired in an object of type `std::string`. For example:

```
std::string from_u8string(const std::string &s) {
    return s;
}
std::string from_u8string(std::string &&s) {
    return std::move(s);
}
#ifdef __cpp_lib_char8_t
std::string from_u8string(const std::u8string &s) {
    return std::string(s.begin(), s.end());
}
#endif

std::filesystem::path p = ...;
std::string s = from_u8string(p.u8string()); // C++17 or C++20
```

This naturally incurs a cost when building with `char8_t` support enabled due to the need to copy the path contents.

Tooling

Tooling could potentially assist programmers in migrating code. Several of the approaches discussed above could be applied mechanically to an existing code base. For example, re-writing existing `u8` literals to ordinary literals with escape sequences, or adding an `_as_char` UDL suffix to existing literals (inserting include directives as needed).

Options considered to reduce backward compatibility impact

The following sections summarize options that have been considered to reduce backward compatibility impact. Most of these options are *not* proposed in this paper because they would actively interfere with goals of the `char8_t` proposal; to enable the type system to protect against inadvertent mixing of UTF-8 data and the execution encoding. However, some of these options may be useful for some code bases and could be provided by implementations as opt-in extensions.

Only two of these options (7 and 8) are proposed for inclusion in the standard. In both of these cases, the concern that is addressed was not specifically intended by the changes adopted in P0482R6. These are effectively bug fixes.

1) Reinstate u8 literals as type char and introduce a new literal prefix for char8_t

Not proposed

Many of the backward compatibility concerns could be avoided by reinstating `u8` literals as having type `char` and introducing a new prefix, for example `u8`, to specify UTF-8 literals with type `char8_t`.

The visible difference between `u8` and `u8` is subtle. Some coding compliance standards, such as MISRA, forbid use of identifiers that differ only in case. It has been suggested that C++11's use of `u` and `U` to denote UTF-16 and UTF-32 literals was a mistake because the visual distinction is too subtle. To avoid these subtle visual differences, new literal prefixes such as `utf8`, `utf16`, and `utf32` could be introduced and the old ones deprecated. The downside of these prefixes is, of course, that they are longer.

Implementing this option would continue enabling problems with encoding confusion that we see today. The execution encoding is not UTF-8 on some popular platforms and continuing to use `char` based types for execution encoding and UTF-8 (and other untrusted input or encodings) is a recipe for continued occurrences of mojibake in applications. For platforms that use UTF-8 as the execution encoding, ordinary literals are already UTF-8 encoded. This option would introduce three distinct ways of writing UTF-8 literals on such platforms; having two ways to do (almost) the same thing is usually one too many already.

2) Allow implicit conversions from char8_t to char

Not proposed

Allowing implicit conversions from `char8_t` to `char` was considered with the original P0482 proposal. The concerns with this approach are the same as in option 1; this enables continued, potentially unintended, mixing of UTF-8 data with non-UTF-8 data resulting in mojibake.

Additionally, allowing implicit conversions would not address all compatibility concerns. For example:

```
template<typename T> void f(T); // #1
void f(char); // #2
f(u8'x'); // Calls #2 in C++17, would still call #1 in C++20.
```

However, such implicit conversions could still be useful for some existing code. Implementations could offer extensions to enable such conversions.

3) Allow initializing an array of char with a u8 string literal

Not proposed

This option would allow the following code to remain well-formed in C++20.

```
char a[] = u8"text";
```

Array initialization is the one context in which the previously discussed uses of `reinterpret_cast` or the `_as_char` UDL isn't an option. This option would allow array initializations to remain well-formed and avoid the need for workarounds like the previously discussed `char_array` template. However, this option would continue to promote mixing of UTF-8 data with non-UTF-8 data potentially resulting in mojibake.

Implementations could allow these initializations as a conforming extension.

4) Allow initializing an array with a reference to an array

Not proposed

This option would enable use of the previously discussed `_as_char` UDL to initialize an array without the need for workarounds like the previously discussed `char_array` template. However, this option would continue to promote mixing of UTF-8 data with non-UTF-8 data potentially resulting in mojibake.

```
char a[] = u8"text"_as_char;
```

Implementations could allow these initializations as a conforming extension.

5) Allow `std::string` to be initialized with `char8_t` based types

Not proposed

This option has been suggested as a way to allow some existing uses of `std::string` to hold UTF-8 data to remain valid in C++20. For example:

```
std::string s1 = u8"text";
std::string s2 = s1 + u8"text";
```

This option constitutes a narrow fix for a few specific use cases within a considerably larger problem space. Further, it would require changes to `std::basic_string` specifically for its `char`-based specializations. As with previously discussed options, this would again continue to promote mixing of UTF-8 data with non-UTF-8 data potentially resulting in mojibake.

6) Allow implicit conversions from `std::u8string` to `std::string`

Not proposed

This option has been suggested as a means to address the backward compatibility impact due to the changes to the `std::filesystem::path` `u8string` and `generic_u8string` member functions. It would allow code like the following to continue to work as expected:

```
std::filesystem::path p = ...;
std::string s1 = p.u8string();
```

This option is, again, not proposed because it would allow unintended mixing of UTF-8 encoded data and the execution character encoding.

7) Add deleted ostream inserters for `char8_t`, `char16_t`, and `char32_t`

Proposed

An unintended and silent behavioral change was introduced with the adoption of P0482R6. In C++17, the following code wrote the code units of the literals to `stdout`. In C++20, this code now writes the character literal as a number, and the address of the string literal, to `stdout`.

```
std::cout << u8'x'; // In C++20, writes the number 120.
std::cout << u8"text"; // In C++20, writes a memory address.
```

This is a surprising change that provides no benefit to programmers. Adding deleted ostream inserters would avoid this surprising behavioral change while reserving the possibility to specify behavior for these operations in the future (for example, to specify implicit transcoding to the execution encoding).

8) Allow std::filesystem::u8path to accept ranges and iterators with char8_t value types

Proposed

Another unintended behavioral change introduced with the adoption of P0482R6 is that the following code is now ill-formed because std::filesystem::u8path requires a range or pair of iterators specifically with a value type of char.

```
std::filesystem::u8path(u8"text");
```

std::filesystem::u8path is now deprecated, but since it previously required UTF-8 data, there is no risk of encoding confusion (unlike with many of the other options discussed in this paper). Allowing it to continue to be called with u8 literals (or other char8_t based ranges and iterators) causes no harm other than potentially encouraging continued use of a deprecated interface.

Proposal

This paper proposes implementing only options 7 and 8.

- Add deleted overloads of basic_ostream<char, ...>::operator<< and basic_ostream<wchar_t, ...>::operator<< for char8_t character and string types. This avoids the silent and surprising behavior change introduced by P0482R6 [P0482R6] that resulted in UTF-8 characters being formatted as numeric values and UTF-8 strings being formatted as pointers.
- Add deleted overloads of basic_ostream<char, ...>::operator<< for wchar_t, char16_t and char32_t character and string types and deleted overloads of basic_ostream<wchar_t, ...>::operator<< for char16_t and char32_t character and string types. This removes surprising behavior that has been present since C++11; that characters are formatted as numeric values and that strings are formatted as pointers.
- Modify std::filesystem::u8path to accept ranges and iterators with char8_t value types. This allows existing code that passes UTF-8 string literals to remain well-formed.
u8path(u8"filename"); // Ok; ill-formed following P0482R6 [P0482R6].
- Update the __cpp_lib_char8_t feature test macro to reflect proposed changes in library behavior.

Wording

☐ Hide deleted text

These changes are relative to N4810 [N4810]

Library wording

Change in table 35 of 17.3.1 [support.limits.general].paragraph 3:

Table 35 — Standard library feature-test macros		
Macro name	Value	Header(s)
[...]	[...]	[...]
__cpp_lib_char8_t	201811201907L ** placeholder **	<atomic> <filesystem> <istream> <limits> <locale> <ostream> <string> <string_view>
[...]	[...]	[...]

Drafting note: the final value for the __cpp_lib_char8_t feature test macro will be selected by the project editor to reflect the date of approval.

Change in 29.7.5.1 [ostream]:

```
namespace std {  
  
    [...]  
  
    // [ostream.inserters.character], character inserters  
    template<class charT, class traits>  
        basic_ostream<charT, traits>& operator<< (basic_ostream<charT, traits>&, charT);  
    template<class charT, class traits>  
        basic_ostream<charT, traits>& operator<< (basic_ostream<charT, traits>&, char);  
    template<class traits>  
        basic_ostream<char, traits>& operator<< (basic_ostream<char, traits>&, char);  
  
    template<class traits>  
        basic_ostream<char, traits>& operator<< (basic_ostream<char, traits>&, signed char);  
    template<class traits>  
        basic_ostream<char, traits>& operator<< (basic_ostream<char, traits>&, unsigned char);  
  
    // The following deleted overloads prevent formatting character values as numeric values.  
    template<class traits>  
        basic_ostream<char, traits>& operator<< (basic_ostream<char, traits>&, wchar_t) = delete;  
    template<class traits>  
        basic_ostream<char, traits>& operator<< (basic_ostream<char, traits>&, char8_t) = delete;  
    template<class traits>  
        basic_ostream<char, traits>& operator<< (basic_ostream<char, traits>&, char16_t) = delete;
```

```

template<class traits>
basic_ostream<char, traits>& operator<<(basic_ostream<char, traits>&, char32_t) = delete;
template<class traits>
basic_ostream<wchar_t, traits>& operator<<(basic_ostream<wchar_t, traits>&, char8_t) = delete;
template<class traits>
basic_ostream<wchar_t, traits>& operator<<(basic_ostream<wchar_t, traits>&, char16_t) = delete;
template<class traits>
basic_ostream<wchar_t, traits>& operator<<(basic_ostream<wchar_t, traits>&, char32_t) = delete;

template<class charT, class traits>
basic_ostream<charT, traits>& operator<<(basic_ostream<charT, traits>&, const charT*);
template<class charT, class traits>
basic_ostream<charT, traits>& operator<<(basic_ostream<charT, traits>&, const char*);
template<class traits>
basic_ostream<char, traits>& operator<<(basic_ostream<char, traits>&, const char*);

template<class traits>
basic_ostream<char, traits>& operator<<(basic_ostream<char, traits>&, const signed char*);
template<class traits>
basic_ostream<char, traits>& operator<<(basic_ostream<char, traits>&, const unsigned char*);

// The following deleted overloads prevent formatting strings as pointer values.
template<class traits>
basic_ostream<char, traits>& operator<<(basic_ostream<char, traits>&, const wchar_t*) = delete;
template<class traits>
basic_ostream<char, traits>& operator<<(basic_ostream<char, traits>&, const char8_t*) = delete;
template<class traits>
basic_ostream<char, traits>& operator<<(basic_ostream<char, traits>&, const char16_t*) = delete;
template<class traits>
basic_ostream<char, traits>& operator<<(basic_ostream<char, traits>&, const char32_t*) = delete;
template<class traits>
basic_ostream<wchar_t, traits>& operator<<(basic_ostream<wchar_t, traits>&, const char8_t*) = delete;
template<class traits>
basic_ostream<wchar_t, traits>& operator<<(basic_ostream<wchar_t, traits>&, const char16_t*) = delete;
template<class traits>
basic_ostream<wchar_t, traits>& operator<<(basic_ostream<wchar_t, traits>&, const char32_t*) = delete;
}

```

Annex C Compatibility wording

Change in [C.5.11 \[diff.cpp17.input.output\].paragraph 2](#):

Affected subclause: [29.7.5.2.4](#)

Change: Overload resolution for ostream inserters used with UTF-8 literals.

Rationale: Required for new features.

Effect on original feature: Valid ISO C++ 2017 code that passes UTF-8 literals to `basic_ostream<char, ...>::operator<<` **or** `basic_ostream<wchar_t, ...>::operator<<` **no longer calls character-related overloads** **is now ill-formed.**

```

std::cout << u"text";           // Previously called operator<<(const char*) and printed a string.
                                // Now calls operator<<(const void*) and prints a pointer value ill-formed.
std::cout << u'X';              // Previously called operator<<(char) and printed a character.
                                // Now calls operator<<(int) and prints an integer value ill-formed.

```

Add a new paragraph after [C.5.11 \[diff.cpp17.input.output\].paragraph 2](#):

Affected subclause: [29.7.5.2.4](#)

Change: Overload resolution for ostream inserters used with `wchar_t`, `char16_t`, or `char32_t` types.

Rationale: Removal of surprising behavior.

Effect on original feature: Valid ISO C++ 2017 code that passes `wchar_t`, `char16_t`, or `char32_t` characters or strings to `basic_ostream<char, ...>::operator<<`, or that passes `char16_t`, or `char32_t` characters or strings to `basic_ostream<wchar_t, ...>::operator<<` **is now ill-formed.**

```

std::cout << u"text";           // Previously formatted the string as a pointer value.
                                // Now ill-formed.
std::cout << u'X';              // Previously formatted the character as an integer value.
                                // Now ill-formed.

```

Annex D Compatibility features wording

Change in [D.17 \[depr.fs.path.factory\].paragraph 1](#):

Requires: The source and `[first, last)` sequences are UTF-8 encoded. The value type of Source and InputIterator is `char` **or** `char8_t`. Source meets the requirements specified in [29.11.7.3](#).

References

- [N4810] "Working Draft, Standard for Programming Language C++", N4810, 2019.
<http://www.open-std.org/jtc1/sc22/wg21/docs/papers/2019/n4810.pdf>

- [P0388R2] Robert Haberlach, "Permit conversions to arrays of unknown bound", P0388R2, 2018.
<http://www.open-std.org/jtc1/sc22/wg21/docs/papers/2018/p0388r2.html>
- [P0482R6] Tom Honermann, "char8_t: A type for UTF-8 characters and strings (Revision 6)", P0482R6, 2018.
<http://www.open-std.org/jtc1/sc22/wg21/docs/papers/2018/p0482r6.html>
- [P0732R2] Jeff Snyder and Louis Dionne, "Class Types in Non-Type Template Parameters", P0732R2, 2018.
<http://www.open-std.org/jtc1/sc22/wg21/docs/papers/2018/p0732r2.pdf>
- [SD-8] Titus Winters, "SD-8: Standard Library Compatibility", SD-8, 2018.
<https://isocpp.org/std/standing-documents/sd-8-standard-library-compatibility>