

An allocator-aware optional type

Abstract

Library types that can potentially hold *allocator-aware* (AA) objects should, themselves, be allocator-aware. A PMR container, for example, depends on AA types following a known AA protocol so that it (the container) can uniformly manage its memory. Even types that don't manage their own memory, such as tuple, follow the AA rules when they hold one more more AA elements. (A special case is pair, which is not actually AA but effectively follows the rules through special handling in *uses-allocator construction*.)

The current definition of `std::optional` does not follow the rules for an AA type, even when holding an AA value. This limitation makes `std::optional` unsuitable for storage in an AA container when memory allocation customization is needed.

In this paper, we propose a new, allocator-aware `std::pmr::optional` usable as a container element type and in any other context where allocator propagation is expected. This new type would not replace the current `std::optional`, but would resolve to `std::optional` when the value type is not AA. By automatically handling the distinction between AA and non-AA value types, `std::pmr::optional` can easily be used in generic code where it is not known in advance if it would be storing an AA type or not.

This is a complete proposal with formal wording. It has not yet been discussed in LEWGI or LEWG.

change history :

- replaced `alloc_optional` with additional overloads of `make_optional` that take an `allocator_arg_t` : it was observed that `alloc_optional` doesn't actually do any allocation, and that the name is not appropriate
- fixed the order of arguments in the *Returns* clause of what used to be `alloc_optional`
- adjusted for LWG 2833
- added discussion on deduction guides
- removed mentions of using a type alias since the type alias approach has proven to be problematic
- modified the specification of `std::pmr::optional` to cover both AA and non AA types
- added CTAD specification
- modified the specification of `std::pmr::optional` to be expressed in terms of `std::pmr::polymorphic_allocator<>`, as opposed to `std::pmr::memory_resource` gt;
- moved `std::pmr::optional` to `optional` header as discussed in the reflector discussion
- added request for discussion on making `std::pmr::optional` a more allocator generic type.
- added free swap function to be in line with P0178

Motivation and Proposal Summary

C++ has been moving towards a consistent PMR allocator model whereby *allocator-aware* (AA) types adhere to a few rules:

1. Once constructed, an object's allocator never changes.
2. The object's constructors all follow one of two argument protocols so that they work with *uses-allocator construction* and thus can be inserted as container elements using the container's allocator.
3. An object that can contain an AA element of user-specified type should itself be AA and use its allocator to initialize its AA subobjects.

The current `std::optional` does not follow the above rules. When disengaged, it forgets its allocator, violating the first rule; its constructors don't follow the AA protocols, so containers cannot pass their allocators to optional elements; and it does not hold on an allocator by which it can initialize its contained object. As a result, `std::optional` is not a good fit for situations where allocators are used. A `std::pmr::vector<optional<std::pmr::string>>`, for example, cannot ensure that all of strings within it use the same allocator, violating a key invariant of PMR containers. If one of the elements of the vector became disengaged and re-engaged, for example, the allocator for that one element could change. /p>

The `std::pmr::optional` class template proposed here properly adheres to the rules of an AA type when instantiated with an AA value type. It holds a copy of the allocator used to construct it, even when disengaged, and uses that allocator to construct its element when re-engaged. Containers of `std::pmr::optional` objects can correctly manage their memory.

The basic design of an AA optional is straight-forward: Add an allocator to all of its constructors and use that allocator to construct the value object each type the optional is engaged. However, when holding a non-AA type, there is no reason to pay the overhead of storing an allocator, nor to support the AA constructor interface. For this reason, `std::pmr::optional`

has a different specialisation for AA and non-AA type.

Design decisions:

Rather than support the entire C++11-style set allocators, `std::pmr::optional` works only with `std::pmr::polymorphic_allocator`. The design keeps the allocator from infecting the optional's type, in the sense that it's not a template parameter. The modern PMR-style allocator model simplifies specification, implementation, and use of `std::pmr::optional`. Allocator-aware optionals are interoperable even if they use different concrete allocators, because the concrete allocator doesn't change the type, nor does it change the size of the type.

When prototyping this proposal, we realized that an allocator-aware optional is never trivially copyable. Copy constructor and copy assignment always potentially invoke the allocator; these operations are never bitwise copies. Move operations aren't trivial either, because they may also end up doing uses-allocator construction.

This was an implementation-based reason for having an allocator-aware type separate from the usual optional. All the complexity of conditional triviality is in `std::optional`, and `std::pmr::optional`'s allocator-aware alias target has none of that.

The first proposal suggested using a type alias where a non-AA `std::pmr::optional` aliases `std::optional`, and AA `std::pmr::optional` aliases a new unnamed type. However, this causes usability issues. Type deduction in cases like :

```
template <typename T>
void foo(std::pmr::optional<T>);
```

did not work. The above was equivalent to

```
template <typename T>
void foo(std::conditional<std::uses_allocator<T, std::pmr::polymorphic_allocator<>>::value ,
    alloc_optional<T>,
    std::optional<T>>::type);
```

and using the nested type of the `std::conditional` as the function template parameter made for an undeduced context.

The free swap function has been made to have a wide contract and work with different allocators, as discussed in P0178 (<http://www.open-std.org/jtc1/sc22/wg21/docs/papers/2016/p0178r0.html>)

Feedback items for LEWG:

Should `std::pmr::optional` be placed in the `<optional>` header?

This proposal puts `std::pmr::optional` in a `optional` header. Historically, `pmr` containers didn't have their own header files. However, `std::pmr::optional` is a more complex type than, for example, `std::pmr::vector`.

Should the deduction guide for mixed optional unpack or not?

Consider

```
std::optional x1 = value_type();
std::pmr::optional copy1 = x1; // #1

std::optional x2 = value_type_aa();
std::pmr::optional copy2 = x2; // #2

std::pmr::optional x3 = value_type();
std::optional copy3 = x3; // #3

std::pmr::optional x4 = value_type_aa();
std::optional copy4 = x4; // #4
```

What should the types of `x1`, `x2`, `x3`, and `x4` in the above example be ?

The current proposal favours unpacking, and the types are `std::pmr::optional<value_type>` , `std::pmr::optional<value_type_aa>`, `std::optional<value_type>` and `std::optional<value_type_aa>`. This seems to fit with the idea that `std::pmr::optional` and `std::optional` are types that are close enough that they deserve to be treated equally wherever they can. However, it does mean that they are somehow blessed by the standard to work together in a way a user defined type which inherits from `std::optional` wouldn't be.

Which allocator should be used in `value_or` ?

It is not all that obvious which allocator should be used for the object returned by `value_or`. Should the decision be left to the type or should it be mandated by the `optional` ? That is, should the object be constructed by plain copy/move construction or with `uses-allocator` construction?

Should assignments use `is_constructible` trait ?

It's not construct from U we need, it's construct from U using the allocator. Do we need a new trait ?

Do we need an “allocator_aware” concept?

We might consider an “allocator aware” (AA) concept that requires a `get_allocator()` method that returns something convertible to `std::pmr::polymorphic_allocator<>`. If we used this concept instead of the `std::uses_allocator` trait, the allocator would require zero extra space in most (but not all) cases. (The exception would be a type that stores its allocator outside of its footprint and whose footprint is smaller than `polymorphic_allocator<>`.)

Should `std::pmr::optional` be a more allocator generic type

In the reflector discussion, Ville Voutilainen and Tomasz Kamiński made the following request : ": The C++ standard library should provide building blocks that allow multiple semantics to be expressed, as opposed to deciding on a narrow subset, and making an allocator-aware optional obey the static properties, namely the propagation traits, of an allocator is a fundamental piece of such genericity. See P2080 <https://wg21.link/P2080>"

Proposed wording

Add new paragraphs after 20.6.1/p1 [optional.general]

[2] `std::pmr::optional` is a class template such that for a type `T`, where `uses_allocator<T, pmr::polymorphic_allocator<>>` is true, an optional object of type `std::pmr::optional<T>` will construct the contained object, if any, with an allocator of type `pmr::polymorphic_allocator<>`.

Modify 20.6.2 Header synopsis1 [optional.syn]

```
namespace std {  
    // [optional.optional], class template optional  
    template<class T>  
        class optional;  
namespace pmr {  
    // [pmr.optional.optional], class template optional  
    template<class T>  
        class optional;  
}  
...
```

Modify 20.6.3 Class template optional [optional.optional]

```
// [optional.ctor], constructors  
...  
    template<class U>  
        explicit(see below) optional(const pmr::optional<U>&);  
    template<class U>  
        explicit(see below) optional(pmr::optional<U>&&);  
...  
// [optional.assign], assignment  
...  
    template<class U> optional& operator=(const pmr::optional&);  
    template<class U> optional& operator=(pmr::optional&&) noexcept(see  
below);  
...  
    template<class T>  
        optional(T) -> optional<T>;  
    template<class T>  
        optional(const pmr::optional<T>&) -> optional<T>;
```

```
template<class T>
optional(pmr::optional<T>&&) -> optional<T>;
```

Modify 20.6.3.1 Constructors [optional.ctor]

```
template<class U> explicit(see below) optional(const optional<U>& v);...
```

Mandates:

- is constructible v<T, optional<U>&> is false,
- is constructible v<T, pmr::optional<U>&> is false,
- is constructible v<T, optional<U>&&> is false,
- is constructible v<T, pmr::optional<U>&&> is false,
- is constructible v<T, const optional<U>&> is false,
- is constructible v<T, const pmr::optional<U>&> is false,
- is constructible v<T, const optional<U>&&> is false,
- is constructible v<T, const pmr::optional<U>&&> is false,
- is convertible v<optional<U>&, T> is false,
- is convertible v<pmr::optional<U>&, T> is false,
- is convertible v<optional<U>&&, T> is false,
- is convertible v<pmr::optional<U>&&, T> is false,
- is convertible v<const optional<U>&, T> is false, and
- is convertible v<const pmr::optional<U>&, T> is false,
- is convertible v<const optional<U>&&, T> is false, and
- is convertible v<const pmr::optional<U>&&, T> is false ...

```
template<class U> explicit(see below) optional(optional<U>&& v);...
```

Mandates:

- is constructible v<T, optional<U>&> is false,
- is constructible v<T, pmr::optional<U>&> is false,
- is constructible v<T, optional<U>&&> is false,
- is constructible v<T, pmr::optional<U>&&> is false,
- is constructible v<T, const optional<U>&> is false,
- is constructible v<T, const pmr::optional<U>&> is false,
- is constructible v<T, const optional<U>&&> is false,
- is constructible v<T, const pmr::optional<U>&&> is false,
- is convertible v<optional<U>&, T> is false,
- is convertible v<pmr::optional<U>&, T> is false,
- is convertible v<optional<U>&&, T> is false,
- is convertible v<pmr::optional<U>&&, T> is false,
- is convertible v<const optional<U>&, T> is false, and
- is convertible v<const pmr::optional<U>&, T> is false,
- is convertible v<const optional<U>&&, T> is false, and
- is convertible v<const pmr::optional<U>&&, T> is false ...

...

```
template<class U> explicit(see below) optional(const pmr::optional<U>&
rhs);
```

Effects: If rhs contains a value, initializes the contained value as if direct-non-list-initializing an object of type T with the expression *rhs.

Ensures: bool(rhs) == bool(*this).

Throws: Any exception thrown by the selected constructor of T.

Remarks:

The expression inside explicit is equivalent to:

!is_convertible v<const U&, T>

Mandates:

- is_constructible v<T, const U&> is true,
- is_same<T,U> is false,
- is_constructible v<T, optional<U>&> is false,
- is_constructible v<T, pmr::optional<U>&> is false,
- is_constructible v<T, optional<U>&&> is false,
- is_constructible v<T, pmr::optional<U>&&> is false,
- is_constructible v<T, const optional<U>&> is false,
- is_constructible v<T, const pmr::optional<U>&> is false,
- is_constructible v<T, const optional<U>&&> is false,
- is_constructible v<T, const pmr::optional<U>&&> is false,
- is_convertible v<optional<U>&, T> is false,
- is_convertible v<pmr::optional<U>&, T> is false,
- is_convertible v<optional<U>&&, T> is false,
- is_convertible v<pmr::optional<U>&&, T> is false,
- is_convertible v<const optional<U>&, T> is false,
- is_convertible v<const pmr::optional<U>&, T> is false,
- is_convertible v<const optional<U>&&, T> is false, and
- is_convertible v<const pmr::optional<U>&&, T> is false

template<class U> explicit(see below) optional(pmr::optional<U>&& rhs);

Effects: If rhs contains a value, initializes the contained value as if direct-non-list-initializing an object of type T with the expression `std::move(*rhs)`. `std::move(*rhs)` as the constructor argument. `bool(rhs)` is unchanged.

Ensures: `bool(rhs) == bool(*this)`.

Throws: Any exception thrown by the selected constructor of T.

Remarks: The expression inside explicit is equivalent to:

!is_convertible v<U, T>

Mandates:

- is_constructible v<T,U&&> is true,
- is_same<T,U> is false,
- is_constructible v<T, optional<U>&> is false,
- is_constructible v<T, pmr::optional<U>&> is false,
- is_constructible v<T, optional<U>&&> is false,
- is_constructible v<T, pmr::optional<U>&&> is false,
- is_constructible v<T, const optional<U>&> is false,
- is_constructible v<T, const pmr::optional<U>&> is false,
- is_constructible v<T, const optional<U>&&> is false,
- is_constructible v<T, const pmr::optional<U>&&> is false,
- is_convertible v<optional<U>&, T> is false,
- is_convertible v<pmr::optional<U>&, T> is false,
- is_convertible v<optional<U>&&, T> is false,
- is_convertible v<pmr::optional<U>&&, T> is false,
- is_convertible v<const optional<U>&, T> is false,
- is_convertible v<const pmr::optional<U>&, T> is false,
- is_convertible v<const optional<U>&&, T> is false, and
- is_convertible v<const pmr::optional<U>&&, T> is false

...

template<class U> optional& operator=(const optional<U>& rhs);...

Remarks: ... This operator shall not participate in overload resolution unless

- is constructible v<T, const U> is true,
- is assignable<T&, const U> is true,
- is constructible v<T, optional<U>&> is false,
- is constructible v<T, pmr::optional<U>&> is false,
- is constructible v<T, optional<U>&&> is false,
- is constructible v<T, pmr::optional<U>&&> is false,
- is constructible v<T, const optional<U>&> is false,
- is constructible v<T, const pmr::optional<U>&> is false,
- is constructible v<T, const optional<U>&&> is false,
- is constructible v<T, const pmr::optional<U>&&> is false,
- is convertible v<optional<U>&, T> is false,
- is convertible v<pmr::optional<U>&, T> is false,
- is convertible v<optional<U>&&, T> is false,
- is convertible v<pmr::optional<U>&&, T> is false,
- is convertible v<const optional<U>&, T> is false,
- is convertible v<const pmr::optional<U>&, T> is false,
- is convertible v<const optional<U>&&, T> is false,
- is convertible v<const pmr::optional<U>&&, T> is false,
- is assignable v<T&, optional<U>&> is false,
- is assignable v<T&, pmr::optional<U>&> is false,
- is assignable v<T&, optional<U>&&> is false,
- is assignable v<T&, pmr::optional<U>&&> is false,
- is assignable v<T&, const optional<U>&> is false, and
- is assignable v<T&, const pmr::optional<U>&> is false,
- is assignable v<T&, const optional<U>&&> is false, and
- is assignable v<T&, const pmr::optional<U>&&> is false

template<class U> optional& operator=(optional<U>&& rhs);...

Remarks: ... This operator shall not participate in overload resolution unless

- is constructible v<T, const U> is true,
- is assignable<T&, const U> is true,
- is constructible v<T, optional<U>&> is false,
- is constructible v<T, pmr::optional<U>&> is false,
- is constructible v<T, optional<U>&&> is false,
- is constructible v<T, pmr::optional<U>&&> is false,
- is constructible v<T, const optional<U>&> is false,
- is constructible v<T, const pmr::optional<U>&> is false,
- is constructible v<T, const optional<U>&&> is false,
- is constructible v<T, const pmr::optional<U>&&> is false,
- is convertible v<optional<U>&, T> is false,
- is convertible v<pmr::optional<U>&, T> is false,
- is convertible v<optional<U>&&, T> is false,
- is convertible v<pmr::optional<U>&&, T> is false,
- is convertible v<const optional<U>&, T> is false,
- is convertible v<const pmr::optional<U>&, T> is false,
- is convertible v<const optional<U>&&, T> is false,
- is convertible v<const pmr::optional<U>&&, T> is false,
- is assignable v<T&, optional<U>&> is false,
- is assignable v<T&, pmr::optional<U>&> is false,
- is assignable v<T&, optional<U>&&> is false,

- is assignable `v<T&, _pmr::optional<U>&&>` is false,
- is assignable `v<T&, const optional<U>&>` is false, and
- is assignable `v<T&, const _pmr::optional<U>&>` is false,
- is assignable `v<T&, const optional<U>&&>` is false, and
- is assignable `v<T&, const _pmr::optional<U>&&>` is false

```
template<class U> optional& operator=(const _pmr::optional<U>& rhs);
```

Effects: See Table

Table — `optional operator=(const _pmr::optional<U>&)` effects

	*this contains a value	*this does not contain a value
rhs contains a value	assigns <code>*rhs</code> to the contained value	initializes the contained value as if <u>direct-non-list-initializing an object of type T with <code>*rhs</code>.</u>
rhs does not contain a value	destroys the contained value by calling <code>val->T::~~T()</code> .	no effect

Returns: `*this`.

Ensures: `bool(rhs) == bool(*this)`.

Remarks: If any exception is thrown, the result of the expression `bool(*this)` remains unchanged. If an exception is thrown during the call to T's constructor, the state of `*rhs.val` is determined by the exception safety guarantee of T's constructor. If an exception is thrown during the call to T's assignment, the state of `*val` and `*rhs.val` is determined by the exception safety guarantee of T's assignment.

Mandates:

- is `same<T,U>` is false,
- is constructible `v<T, const U&>` is true,
- is assignable `<T&, const U&>` is true,
- is constructible `v<T, optional<U>&>` is false,
- is constructible `v<T, _pmr::optional<U>&>` is false,
- is constructible `v<T, optional<U>&&>` is false,
- is constructible `v<T, _pmr::optional<U>&&>` is false,
- is constructible `v<T, const optional<U>&>` is false,
- is constructible `v<T, const _pmr::optional<U>&>` is false,
- is constructible `v<T, const optional<U>&&>` is false,
- is constructible `v<T, const _pmr::optional<U>&&>` is false,
- is convertible `v<const U&, T>` is true,
- is convertible `v<optional<U>&, T>` is false,
- is convertible `v<_pmr::optional<U>&, T>` is false,
- is convertible `v<optional<U>&&, T>` is false,
- is convertible `v<_pmr::optional<U>&&, T>` is false,
- is convertible `v<const optional<U>&, T>` is false,
- is convertible `v<const _pmr::optional<U>&, T>` is false,
- is convertible `v<const optional<U>&&, T>` is false,
- is convertible `v<const _pmr::optional<U>&&, T>` is false,
- is assignable `v<T&, optional<U>&>` is false,
- is assignable `v<T&, _pmr::optional<U>&>` is false,
- is assignable `v<T&, optional<U>&&>` is false,

- is assignable `v<T&, pmr::optional<U>&&>` is false,
- is assignable `v<T&, const optional<U>&>` is false,
- is assignable `v<T&, const pmr::optional<U>&>` is false,
- is assignable `v<T&, const optional<U>&&>` is false, and
- is assignable `v<T&, const pmr::optional<U>&&>` is false

`template<class U> optional& operator=(pmr::optional<U>&& rhs);`

Effects: See Table

Table — `optional operator=(pmr::optional<U>&&) effects`

	*this contains a value	*this does not contain a value
rhs contains a value	assigns *rhs to the contained value	initializes the contained value as if direct-non-list-initializing an object of type T with <code>std::move(*rhs)</code> .
rhs does not contain a value	destroys the contained value by calling <code>val->T::~T()</code> .	no effect

Returns: *this.

Ensures: `bool(rhs) == bool(*this)`.

Remarks: If any exception is thrown, the result of the expression `bool(*this)` remains unchanged. If an exception is thrown during the call to T's constructor, the state of `*rhs.val` is determined by the exception safety guarantee of T's constructor. If an exception is thrown during the call to T's assignment, the state of `*val` and `*rhs.val` is determined by the exception safety guarantee of T's assignment.

Mandates:

- is constructible `v<T, const U&>` is true,
- is assignable `<T&, const U&>` is true,
- is constructible `v<T, std::optional<U>&>` is false,
- is constructible `v<T, pmr::optional<U>&>` is false,
- is constructible `v<T, std::optional<U>&&>` is false,
- is constructible `v<T, pmr::optional<U>&&>` is false,
- is constructible `v<T, const std::optional<U>&>` is false,
- is constructible `v<T, const pmr::optional<U>&>` is false,
- is constructible `v<T, const std::optional<U>&&>` is false,
- is constructible `v<T, const pmr::optional<U>&&>` is false,
- is convertible `v<const U&, T>` is true,
- is convertible `v<std::optional<U>&, T>` is false,
- is convertible `v<pmr::optional<U>&, T>` is false,
- is convertible `v<std::optional<U>&&, T>` is false,
- is convertible `v<pmr::optional<U>&&, T>` is false,
- is convertible `v<const std::optional<U>&, T>` is false,
- is convertible `v<const pmr::optional<U>&, T>` is false,
- is convertible `v<const std::optional<U>&&, T>` is false,
- is convertible `v<const pmr::optional<U>&&, T>` is false,
- is assignable `v<T&, std::optional<U>&>` is false,
- is assignable `v<T&, pmr::optional<U>&>` is false,
- is assignable `v<T&, std::optional<U>&&>` is false,
- is assignable `v<T&, pmr::optional<U>&&>` is false,
- is assignable `v<T&, const std::optional<U>&>` is false,

- is assignable v<T&, const pmr::optional<U>&> is false,
- is assignable v<T&, const std::optional<U>&&> is false, and
- is assignable v<T&, const pmr::optional<U>&&> is false

Insert new sections after 20.6.3 Class template optional [optional.optional]

Header <optional> synopsis [pmroptional.sys]

```
namespace std::pmr {  
    // [pmroptional.optional]  
    template<class T>  
        class optional;  
  
    // [pmroptional.traits], allocator-related traits  
    template<class T>  
        struct uses_allocator<T, polymorphic_allocator<>>;  
  
    // [pmroptional.relops], relational operators  
    template<class T, class U>  
        bool operator==(const optional<T>&, const optional<U>&);  
    template<class T, class U>  
        bool operator==(const optional<T>&, const std::optional<U>&);  
    template<class T, class U>  
        bool operator==(const std::optional<T>&, const optional<U>&);  
    template<class T, class U>  
        bool operator!=(const optional<T>&, const optional<U>&);  
    template<class T, class U>  
        bool operator!=(const optional<T>&, const std::optional<U>&);  
    template<class T, class U>  
        bool operator!=(const std::optional<T>&, const optional<U>&);  
    template<class T, class U>  
        bool operator<(const optional<T>&, const optional<U>&);  
    template<class T, class U>  
        bool operator<(const optional<T>&, const std::optional<U>&);  
    template<class T, class U>  
        bool operator<(const std::optional<T>&, const optional<U>&);  
    template<class T, class U>  
        bool operator>(const optional<T>&, const optional<U>&);  
    template<class T, class U>  
        bool operator>(const optional<T>&, const std::optional<U>&);  
    template<class T, class U>  
        bool operator>(const std::optional<T>&, const optional<U>&);  
    template<class T, class U>  
        bool operator<=(const optional<T>&, const optional<U>&);  
    template<class T, class U>  
        bool operator<=(const optional<T>&, const std::optional<U>&);  
    template<class T, class U>  
        bool operator<=(const std::optional<T>&, const optional<U>&);  
    template<class T, class U>  
        bool operator>=(const optional<T>&, const optional<U>&);  
    template<class T, class U>  
        bool operator>=(const optional<T>&, const std::optional<U>&);  
    template<class T, class U>  
        bool operator>=(const std::optional<T>&, const optional<U>&);  
    template<class T, three_way_comparable_with<T> U>  
        compare_three_way_result_t<T,U>  
            operator<=>(const optional<T>&, const optional<U>&);  
    template<class T, three_way_comparable_with<T> U>  
        compare_three_way_result_t<T,U>  
            operator<=>(const optional<T>&, const std::optional<U>&);  
    template<class T, three_way_comparable_with<T> U>  
        compare_three_way_result_t<T,U>  
            operator<=>(const std::optional<T>&, const optional<U>&);
```

```

    // [pmroptional.nullops], comparison with nullopt
    template<class T> bool operator==(const optional<T>&, nullopt t)
noexcept;
    template<class T>
        strong_ordering operator<=>(const optional<T>&, nullopt t)
noexcept;

    // [pmroptional.comp.with.t], comparison with T
    template<class T, class U> bool operator==(const optional<T>&, const
U&);
    template<class T, class U> bool operator==(const T&, const
optional<U>&);
    template<class T, class U> bool operator!=(const optional<T>&, const
U&);
    template<class T, class U> bool operator!=(const T&, const
optional<U>&);
    template<class T, class U> bool operator<(const optional<T>&, const
U&);
    template<class T, class U> bool operator<(const T&, const
optional<U>&);
    template<class T, class U> bool operator>(const optional<T>&, const
U&);
    template<class T, class U> bool operator>(const T&, const
optional<U>&);
    template<class T, class U> bool operator<=(const optional<T>&, const
U&);
    template<class T, class U> bool operator<=(const T&, const
optional<U>&);
    template<class T, class U> bool operator>=(const optional<T>&, const
U&);
    template<class T, class U> bool operator>=(const T&, const
optional<U>&);
    template<class T, three way comparable with<T> U>
        compare_three_way_result t<T,U>
        operator<=>(const optional<T>&, const U&);

    // [pmroptional.specalg], specialized algorithms
    template<class T>
        void swap(optional<T>&, optional<T>&);

    template<class T>
        constexpr optional<see below> make_optional(T&&);
    template<class T>
        constexpr optional<T> make_optional();
    template<class T, class Arg0, class... Args>
        constexpr optional<T> make_optional(Arg0 arg0&&, Args&&... args);
    template<class T, class U, class... Args>
        constexpr optional<T> make_optional(initializer_list<U> il,
Args&&... args);

    template<class T>
        constexpr optional<see below> make_optional(allocator_arg t,
const polymorphic_allocator<>& a, T&&);
    template<class T, class... Args>
        constexpr optional<T> make_optional(allocator_arg t, const
polymorphic_allocator<>& a, Args&&... args);
    template<class T, class U, class... Args>
        constexpr optional<T> make_optional(allocator_arg t, const
polymorphic_allocator<>& a, initializer_list<U> il, Args&&... args);

    // [pmroptional.hash], hash support
    template<class T> struct hash<optional<T>>;
}

```

Class template optional [optional.pmroptional]

```
namespace std::pmr {
    template<class T>
    class optional see below{
    public:
        using value_type = T;
        using allocator_type = polymorphic_allocator<>; // not always defined, see below

        // [pmroptional.ctor], constructors
        optional() noexcept;
        optional(nullopt_t) noexcept;
        optional(const optional&);
        optional(optional&&) noexcept(see below);
        optional(const std::optional&);
        optional(std::optional&&);
        template<class... Args>
            explicit optional(in_place_t, Args&&...);
        template<class U, class... Args>
            explicit optional(in_place_t, initializer_list<U>, Args&&...);
        template<class U = T>
            explicit(see below) optional(U&&);
        template<class U>
            explicit(see below) optional(const optional<U>&);
        template<class U>
            explicit(see below) optional(optional<U>&&);
        template<class U>
            explicit(see below) optional(const std::optional<U>&);
        template<class U>
            explicit(see below) optional(std::optional<U>&&);

        // allocator-extended constructors
        optional(allocator_arg_t, const polymorphic_allocator<>&).
noexcept; // not always provided, see below
        optional(allocator_arg_t, const polymorphic_allocator<>&,
nullopt_t) noexcept; // not always provided, see below
        optional(allocator_arg_t, const polymorphic_allocator<>&, const
optional&); // not always provided, see below
        optional(allocator_arg_t, const polymorphic_allocator<>&,
optional&&) noexcept(see below); // not always provided, see below
        optional(allocator_arg_t, const polymorphic_allocator<>&, const
std::optional&); // not always provided, see below
        optional(allocator_arg_t, const polymorphic_allocator<>&,
std::optional&&); // not always provided, see below
        template<class... Args>
            explicit optional(allocator_arg_t, const
polymorphic_allocator<>&, in_place_t, Args&&...); // not always provided, see below
        template<class U, class... Args>
            explicit optional(allocator_arg_t, const
polymorphic_allocator<>&, in_place_t, initializer_list<U>, Args&&...);
// not always provided, see below
        template<class U = T>
            explicit(see below) optional(allocator_arg_t, const
polymorphic_allocator<>&, U&&); // not always provided, see below
        template<class U>
            explicit(see below) optional(allocator_arg_t, const
polymorphic_allocator<>&, const optional<U>&); // not always provided, see below
        template<class U>
            explicit(see below) optional(allocator_arg_t, const
polymorphic_allocator<>&, optional<U>&&); // not always provided, see below
```

```

    template<class U>
        explicit(see below) optional(allocator_arg_t, const
polymorphic_allocator<>&, const std::optional<U>&); // not always
provided, see below
    template<class U>
        explicit(see below) optional(allocator_arg_t, const
polymorphic_allocator<>&, std::optional<U>&&); // not always provided,
see below

```

```

// [pmroptional.dtor], destructor
~optional();

```

```

// [pmroptional.assign], assignment
optional& operator=(nullopt_t) noexcept;
optional& operator=(const optional&);
optional& operator=(optional&&) noexcept(see below);
template<class U = T> optional& operator=(U&&);
template<class U> optional& operator=(const optional<U>&);
template<class U> optional& operator=(optional<U>&&);
template<class U> optional& operator=(const std::optional<U>&);
template<class U> optional& operator=(std::optional<U>&&);
template<class... Args>> T& emplace(Args&&...);
template<class U, class... Args> T& emplace(initializer_list<U>,
Args&&...);

```

```

// [pmroptional.swap], swap
void swap(optional&) noexcept(see below);

```

```

// [pmroptional.observe], observers
const T* operator->() const;
T* operator->();
const T& operator*() const&
T& operator*() &;
T&& operator*() &&;
const T&& operator*() const&&;
explicit operator bool() const noexcept;
bool has_value() const noexcept;
const T& value() const&;
T& value() &;
T&& value() &&;
const T&& value() const&&;
template<class U> T value_or(U&&) const&;
template<class U> T value_or(U&&) &&;
template<class U> T value_or(allocator_arg_t, const
polymorphic_allocator<>&, U&&) const&; // not always provided, see below
template<class U> T value_or(allocator_arg_t, const
polymorphic_allocator<>&, U&&) &&; // not always provided, see below
allocator_type get_allocator() const noexcept;

```

```

// [pmroptional.mod], modifiers
void reset() noexcept;

```

```

private:
    T* val; // exposition only
    const polymorphic_allocator<> M alloc; // exposition only; not
always provided, see below
};

```

```

template<class T>
optional(T) -> optional<T>;
template<class T>
optional(const std::optional<T>&) -> optional<T>;
template<class T>
optional(std::optional<T>&&) -> optional<T>;

```

}

Any instance of `optional<T>` at any given time either contains a value or does not contain a value. When an instance of `optional<T>` contains a value, it means that an object of type `T` is allocated within the storage of the `optional` object. Implementations are not permitted to use additional storage, such as dynamic memory, to allocate its contained value. The contained value shall be allocated in a region of the `optional<T>` storage suitably aligned for the type `T` and, if uses `allocator<T>`, `polymorphic_allocator<>>` is true, constructed by `uses-allocator` construction with `allocator M_alloc`. When an object of type `optional<T>` is contextually converted to `bool`, the conversion returns true if the object contains a value; otherwise the conversion returns false.

Member `val` is provided for exposition only. When an `optional<T>` object contains a value, `val` points to the contained value.

If and only if uses `allocator<T>`, `polymorphic_allocator<>>` is false, `optional<T>` publicly inherits from `std::optional<T>`

If and only if uses `allocator<T>`, `polymorphic_allocator<>>` is true, the following applies :

- `allocator` type will be defined,
- exposition only member `M_alloc` will be provided and will be used to create the contained value, if any, and
- if `<T>` provides `get_allocator()` member function whose return type is convertible to `polymorphic_allocator<>`, the implementation is allowed to assume that the allocator used for constructing the element is the same allocator as returned by `T::get_allocator()`. [Note: In such an implementation, `pmr::optional<pmr::string>` will be zero-overhead compared to `optional<pmr::string>`. -- end note]

`T` shall be a type other than `cv in_place_t`, `cv_allocator_arg`, `t`, or `cv_nullopt_t` that meets the *Cpp17Destructible* requirements (Table 30).

Constructors [pmroptional.ctor]

```
optional() noexcept;
```

```
optional(nullopt_t) noexcept;
```

Effects: If uses `allocator<T>`, `polymorphic_allocator<>>` is true, `M_alloc` is default initialized

Ensures: `*this` does not contain a value.

Remarks: No contained value is initialized.

```
optional(const optional&);
```

Effects: If uses `allocator<T>`, `polymorphic_allocator<>>` is true, `M_alloc` is default initialized. If `rhs` contains a value, initializes the contained value with the expression `*rhs`.

Ensures: `bool(rhs) == bool(*this)`.

Throws: Any exception thrown by the selected constructor of `T`.

Mandates: is copyconstructible `v<T>` is true.

```
optional(optional&& rhs) noexcept(see below).
```

Effects: If uses `allocator<T>`, `polymorphic_allocator<>>` is true, `M_alloc` is

initialized with `rhs.M_alloc`. If `rhs` contains a value, initializes the contained value with the expression `std::move(*rhs)`. `bool(rhs)` is unchanged.

Ensures: `bool(rhs) == bool(*this)`.

Throws: Any exception thrown by the selected constructor of `T`.

Remarks: The expression inside `noexcept` is equivalent to `is_nothrow_move_constructible v<T>`.

Mandates: `is_move_constructible v<T>` is true.

`optional(const std::optional&);`

Effects: If `uses_allocator<T, polymorphic_allocator<>>` is true, `M_alloc` is default initialized. If `rhs` contains a value, initializes the contained value with the expression `*rhs`.

Ensures: `bool(rhs) == bool(*this)`.

Throws: Any exception thrown by the selected constructor of `T`.

Mandates: `is_copy_constructible v<T>` is true.

`optional(std::optional&& rhs);`

Effects: If `uses_allocator<T, polymorphic_allocator<>>` is true, `M_alloc` is initialized with `rhs.M_alloc`. If `rhs` contains a value, initializes the contained value with the expression `std::move(*rhs)`. `bool(rhs)` is unchanged.

Ensures: `bool(rhs) == bool(*this)`.

Throws: Any exception thrown by the selected constructor of `T`.

Mandates: `is_move_constructible v<T>` is true.

`template<class... Args> explicit optional(in_place_t, Args&&... args);`

Effects: If `uses_allocator<T, polymorphic_allocator<>>` is true, `M_alloc` is default initialized. Initializes the contained value with `std::forward<Args>(args).....`

Ensures: `*this` contains a value..

Throws: Any exception thrown by the selected constructor of `T`.

Mandates: `is_copy_constructible v<T>` is true.

`template<class... Args> explicit optional(in_place_t, initializer_list<U> il, Args&&... args);`

Effects: If `uses_allocator<T, polymorphic_allocator<>>` is true, `M_alloc` is default initialized. Initializes the contained value with `il` and `std::forward<Args>(args).....`

Ensures: `*this` contains a value..

Throws: Any exception thrown by the selected constructor of `T`.

Mandates: `is_constructible v<T, initializer_list<U>&, Args&&...>` is true.

`template<class U = T> explicit(see below) optional(U&& rhs);`

Effects: If `uses_allocator<T, polymorphic_allocator<>>` is true, `M_alloc` is default initialized. Initializes the contained value with `std::forward<U>(rhs)`.

Ensures: `*this` contains a value.

Throws: Any exception thrown by the selected constructor of `T`.

Remarks: The expression inside `explicit` is equivalent to:

`!is_convertible v<U, T>`

Mandates:

- `is_constructible v<T, U&&>` is true,

- `is_same v<remove_cvref t<U>, in_place t>` is false, and

- `is_same v<remove_cvref t<U>, optional>` is false.

`template<class U> explicit(see below) optional(const optional<U>& rhs);`

Effects: If uses_allocator<T, polymorphic_allocator<>> is true, M_alloc is default initialized. If rhs contains a value, initializes the contained value with *rhs.

Ensures: bool(rhs) == bool(*this).

Throws: Any exception thrown by the selected constructor of T.

Remarks: The expression inside explicit is equivalent to:

!is_convertible_v<const U&, T>

Mandates:

- is_constructible_v<T, const U&> is true,
- is_constructible_v<T, std::optional<U>&> is false,
- is_constructible_v<T, optional<U>&> is false,
- is_constructible_v<T, std::optional<U>&&> is false,
- is_constructible_v<T, optional<U>&&> is false,
- is_constructible_v<T, const std::optional<U>&> is false,
- is_constructible_v<T, const optional<U>&> is false,
- is_constructible_v<T, const std::optional<U>&&> is false,
- is_constructible_v<T, const optional<U>&&> is false,
- is_convertible_v<std::optional<U>&, T> is false,
- is_convertible_v<optional<U>&, T> is false,
- is_convertible_v<std::optional<U>&&, T> is false,
- is_convertible_v<optional<U>&&, T> is false,
- is_convertible_v<const std::optional<U>&, T> is false,
- is_convertible_v<const optional<U>&, T> is false,
- is_convertible_v<const std::optional<U>&&, T> is false, and
- is_convertible_v<const optional<U>&&, T> is false

template<class U> explicit(see below) optional(optional<U>&& rhs);

Effects: If uses_allocator<T, polymorphic_allocator<>> is true, M_alloc is default initialized. If rhs contains a value, initializes the contained value with std::move(*rhs). bool(rhs) is unchanged.

Ensures: bool(rhs) == bool(*this).

Throws: Any exception thrown by the selected constructor of T.

Remarks: The expression inside explicit is equivalent to:

!is_convertible_v<U, T> Mandates:

- is_constructible_v<T, U&&> is true,
- is_constructible_v<T, std::optional<U>&> is false,
- is_constructible_v<T, optional<U>&> is false,
- is_constructible_v<T, std::optional<U>&&> is false,
- is_constructible_v<T, optional<U>&&> is false,
- is_constructible_v<T, const std::optional<U>&> is false,
- is_constructible_v<T, const optional<U>&> is false,
- is_constructible_v<T, const std::optional<U>&&> is false,
- is_constructible_v<T, const optional<U>&&> is false,
- is_convertible_v<std::optional<U>&, T> is false,
- is_convertible_v<optional<U>&, T> is false,
- is_convertible_v<std::optional<U>&&, T> is false,
- is_convertible_v<optional<U>&&, T> is false,
- is_convertible_v<const std::optional<U>&, T> is false,
- is_convertible_v<const optional<U>&, T> is false,
- is_convertible_v<const std::optional<U>&&, T> is false, and
- is_convertible_v<const optional<U>&&, T> is false

template<class U> explicit(see below) optional(const std::optional<U>& rhs);

Effects: If uses_allocator<T, polymorphic_allocator<>> is true, M_alloc is default initialized. If rhs contains a value, initializes the contained value with *rhs.

Ensures: bool(rhs) == bool(*this).

Throws: Any exception thrown by the selected constructor of T.

Remarks: The expression inside explicit is equivalent to:

!is_convertible_v<const U&, T>

Mandates:

- is_constructible_v<T, const U&> is true,
- is_constructible_v<T, std::optional<U>&> is false,
- is_constructible_v<T, optional<U>&> is false,
- is_constructible_v<T, std::optional<U>&&> is false,
- is_constructible_v<T, optional<U>&&> is false,
- is_constructible_v<T, const std::optional<U>&> is false,
- is_constructible_v<T, const optional<U>&> is false,
- is_constructible_v<T, const std::optional<U>&&> is false,
- is_constructible_v<T, const optional<U>&&> is false,
- is_convertible_v<std::optional<U>&, T> is false,
- is_convertible_v<optional<U>&, T> is false,
- is_convertible_v<std::optional<U>&&, T> is false,
- is_convertible_v<optional<U>&&, T> is false,
- is_convertible_v<const std::optional<U>&, T> is false,
- is_convertible_v<const optional<U>&, T> is false,
- is_convertible_v<const std::optional<U>&&, T> is false, and
- is_convertible_v<const optional<U>&&, T> is false

template<class U> explicit(see below) optional(std::optional<U>&& rhs);

Effects: If uses_allocator<T, polymorphic_allocator<>> is true, M_alloc is default initialized. If rhs contains a value, initializes the contained value with std::move(*rhs). bool(rhs) is unchanged.

Ensures: bool(rhs) == bool(*this).

Throws: Any exception thrown by the selected constructor of T.

Remarks:

The expression inside explicit is equivalent to:

!is_convertible_v<U, T>

Mandates:

- is_constructible_v<T, U&&> is true,
- is_constructible_v<T, std::optional<U>&> is false,
- is_constructible_v<T, optional<U>&> is false,
- is_constructible_v<T, std::optional<U>&&> is false,
- is_constructible_v<T, optional<U>&&> is false,
- is_constructible_v<T, const std::optional<U>&> is false,
- is_constructible_v<T, const optional<U>&> is false,
- is_constructible_v<T, const std::optional<U>&&> is false,
- is_constructible_v<T, const optional<U>&&> is false,
- is_convertible_v<std::optional<U>&, T> is false,
- is_convertible_v<optional<U>&, T> is false,
- is_convertible_v<std::optional<U>&&, T> is false,
- is_convertible_v<optional<U>&&, T> is false,
- is_convertible_v<const std::optional<U>&, T> is false,
- is_convertible_v<const optional<U>&, T> is false,
- is_convertible_v<const std::optional<U>&&, T> is false, and
- is_convertible_v<const optional<U>&&, T> is false

```

optional(allocator_arg_t, const polymorphic_allocator<>&) noexcept;
optional(allocator_arg_t, const polymorphic_allocator<>&, nullopt_t)
noexcept;
optional(allocator_arg_t, const polymorphic_allocator<>&, const
optional&);
optional(allocator_arg_t, const polymorphic_allocator<>&, optional&&)
noexcept(see below);
optional(allocator_arg_t, const polymorphic_allocator<>&, const
std::optional&);
optional(allocator_arg_t, const polymorphic_allocator<>&,
std::optional&&);
template<class... Args>
    explicit optional(allocator_arg_t, const polymorphic_allocator<>&,
in_place_t, Args&&...);
template<class U, class... Args>
    explicit optional(allocator_arg_t, const polymorphic_allocator<>&,
in_place_t, initializer_list<U>, Args&&...);
template<class U = T>
    explicit(see below) optional(allocator_arg_t, const
polymorphic_allocator<>&, U&&);
template<class U>
    explicit(see below) optional(allocator_arg_t, const
polymorphic_allocator<>&, const optional<U>&);
template<class U>
    explicit(see below) optional(allocator_arg_t, const
polymorphic_allocator<>&, optional<U>&&);
template<class U>
    explicit(see below) optional(allocator_arg_t, const
polymorphic_allocator<>&, const std::optional<U>&);
template<class U>
    explicit(see below) optional(allocator_arg_t, const
polymorphic_allocator<>&, std::optional<U>&&);
    Constraints: uses_allocator<T, polymorphic_allocator<>> is true;
    Effects: Equivalent to the preceding constructors except that M alloc is initialized
with a.

```

Destructor [pmroptional.dtor]

```

~optional();
    Effects: If is_trivially_destructible v<T> != true and *this contains a
value, calls val->T::~~T().
    Remarks: If is_trivially_destructible v<T> is true, then this destructor is
trivial.

```

Assignment [pmroptional.assign]

```

optional<T>& operator=(nullopt_t) noexcept;
    Effects: If *this contains a value, calls val->T::~~T() to destroy the contained
value; otherwise no effect.
    Remarks: *this
    Ensures: *this does not contain a value.

optional<T>& operator=(const optional& rhs);
    Effects: See Table

```

Table — optional operator=(const optional& rhs) effects

	<u>*this contains a value</u>	<u>*this does not contain a value</u>
<u>rhs contains a value</u>	<u>assigns *rhs to the contained value</u>	<u>initializes the contained value with *rhs. If uses_allocator<T, polymorphic_allocator<>> is true, initialization is done by uses-allocator construction with allocator M alloc</u>
<u>rhs does not contain a value</u>	<u>destroys the contained value by calling val->T::~~T().</u>	<u>no effect</u>

Returns: *this.

Ensures: bool(rhs) == bool(*this).

Remarks: If any exception is thrown, the result of the expression bool(*this) remains unchanged. If an exception is thrown during the call to T's copy constructor, no effect. If an exception is thrown during the call to T's copy assignment, the state of its contained value is as defined by the exception safety guarantee of is determined by the exception safety guarantee of T's copy assignment. This operator shall be defined as deleted unless is_copy_constructible v<T> is true and is_copy_assignable v<T> is true.

optional<T>& operator=(optional&& rhs) noexcept(see below);

Effects: See Table

Table — optional operator=(optional&& rhs) effects

	<u>*this contains a value</u>	<u>*this does not contain a value</u>
<u>rhs contains a value</u>	<u>assigns std::move(*rhs) to the contained value</u>	<u>initializes the contained value with std::move(*rhs). If uses_allocator<T, polymorphic_allocator<>> is true, initialization is done by uses-allocator construction with allocator M alloc</u>
<u>rhs does not contain a value</u>	<u>destroys the contained value by calling val->T::~~T().</u>	<u>no effect</u>

Returns: *this.

Ensures: bool(rhs) == bool(*this).

Remarks: The expression inside noexcept is equivalent to:

**is_nothrow_move_assignable v<T> &&
is_nothrow_move_constructible v<T>**

If any exception is thrown, the result of the expression bool(*this) remains unchanged. If an exception is thrown during the call to T's move constructor, the state of *rhs.val is determined by the exception safety guarantee of T's move constructor. If an exception is thrown during the call to T's move assignment, the state of *val and *rhs.val is determined by the exception safety guarantee of T's move assignment.

Mandates: is_move_constructible v<T> is true and is_move_assignable v<T> is true.

```
template<class U = T> optional& operator=(U&& v);
```

Effects: If `*this` contains a value, assigns `std::forward<U>(v)` to the contained value; otherwise initializes the contained value with `std::forward<U>(v)`. If `uses_allocator<T, polymorphic_allocator<>>` is true, initialization is done by uses-allocator construction with allocator `M alloc`

Returns: `*this`.

Ensures: `*this` contains a value.

Remarks: If any exception is thrown, the result of the expression `bool(*this)` remains unchanged. If an exception is thrown during the call to `T`'s constructor, the state of `v` is determined by the exception safety guarantee of `T`'s constructor. If an exception is thrown during the call to `T`'s assignment, the state of `*val` and `v` is determined by the exception safety guarantee of `T`'s assignment.

Mandates:

- is same `v<remove_cvref t<U>, alloc-optional>` is false,
- conjunction `v<is scalar<T>, is same<T, decay t<U>>>` is false,
- is constructible `v<T,U>` is true, and
- is assignable `v<T&,U>` is true

```
template<class U> optional& operator=(const optional<U>& rhs);
```

Effects: See Table

Table — `optional operator=(const optional<U>&)` effects

	<code>*this</code> contains a value	<code>*this</code> does not contain a value
<code>rhs</code> contains a value	<code>assigns *rhs</code> to the contained value	<code>initializes the contained value with *rhs. If</code> <code>uses_allocator<T,</code> <code>polymorphic_allocator<>></code> is true, <code>initialization is done by uses-allocator</code> <code>construction with allocator M alloc</code>
<code>rhs</code> does not contain a value	<code>destroys the</code> <code>contained</code> <code>value by</code> <code>calling val-</code> <code>>T::~T(.</code>	<code>no effect</code>

Returns: `*this`.

Ensures: `bool(rhs) == bool(*this)`.

Remarks: If any exception is thrown, the result of the expression `bool(*this)` remains unchanged. If an exception is thrown during the call to `T`'s constructor, no effect. If an exception is thrown during the call to `T`'s assignment, the state of `*val` is determined by the exception safety guarantee of `T`'s assignment.

Mandates:

- is same `<T,U>` is false,
- is constructible `v<T, const U&>` is true,
- is assignable `<T&, const U&>` is true,
- is constructible `v<T, std::optional<U>&>` is false,
- is constructible `v<T, optional<U>&>` is false,
- is constructible `v<T, std::optional<U>&&>` is false,
- is constructible `v<T, optional<U>&&>` is false,
- is constructible `v<T, const std::optional<U>&>` is false,
- is constructible `v<T, const optional<U>&>` is false,

- is constructible `v<T, const std::optional<U>&&>` is false,
- is constructible `v<T, const optional<U>&&>` is false,
- is convertible `v<std::optional<U>&, T>` is false,
- is convertible `v<optional<U>&, T>` is false,
- is convertible `v<std::optional<U>&&, T>` is false,
- is convertible `v<optional<U>&&, T>` is false,
- is convertible `v<const std::optional<U>&, T>` is false,
- is convertible `v<const optional<U>&, T>` is false,
- is convertible `v<const std::optional<U>&&, T>` is false,
- is convertible `v<const optional<U>&&, T>` is false,
- is assignable `v<T&, std::optional<U>&>` is false,
- is assignable `v<T&, optional<U>&>` is false,
- is assignable `v<T&, std::optional<U>&&>` is false,
- is assignable `v<T&, optional<U>&&>` is false,
- is assignable `v<T&, const std::optional<U>&>` is false,
- is assignable `v<T&, const optional<U>&>` is false,
- is assignable `v<T&, const std::optional<U>&&>` is false, and
- is assignable `v<T&, const optional<U>&&>` is false

`template<class U> optional& operator=(const std::optional<U>& rhs);`
Effects: The result of the expression `bool(rhs)` remains unchanged. See Table

Table — `optional operator=(const std::optional<U>&)` effects

	<i>*this contains a value</i>	<i>*this does not contain a value</i>
<i>rhs contains a value</i>	<i>assigns <code>std::move(*rhs)</code> to the contained value</i>	<i>initializes the contained value with <code>std::move(*rhs)</code>. If <code>uses_allocator<T, polymorphic_allocator<>></code> is true, initialization is done by <code>uses_allocator</code> construction with <code>allocator M alloc</code>.</i>
<i>rhs does not contain a value</i>	<i>destroys the contained value by calling <code>val->T::~T()</code></i>	<i>no effect</i>

*Returns: *this.*

Ensures: `bool(rhs) == bool(*this)`.

Remarks: If any exception is thrown, the result of the expression `bool(*this)` remains unchanged. If an exception is thrown during the call to `T`'s constructor, no effect. If an exception is thrown during the call to `T`'s assignment, the state of `*val` is determined by the exception safety guarantee of `T`'s assignment.

Mandates:

- is constructible `v<T, U>` is true,
- is assignable `v<T&, U>` is true,
- is constructible `v<T, std::optional<U>&>` is false,
- is constructible `v<T, optional<U>&>` is false,
- is constructible `v<T, std::optional<U>&&>` is false,
- is constructible `v<T, optional<U>&&>` is false,
- is constructible `v<T, const std::optional<U>&>` is false,
- is constructible `v<T, const optional<U>&>` is false,
- is constructible `v<T, const std::optional<U>&&>` is false,
- is constructible `v<T, const optional<U>&&>` is false,

- is convertible `v<std::optional<U>&, T>` is false,
- is convertible `v<optional<U>&, T>` is false,
- is convertible `v<std::optional<U>&&, T>` is false,
- is convertible `v<optional<U>&&, T>` is false,
- is convertible `v<const std::optional<U>&, T>` is false,
- is convertible `v<const optional<U>&, T>` is false,
- is convertible `v<const std::optional<U>&&, T>` is false,
- is convertible `v<const optional<U>&&, T>` is false,
- is assignable `v<T&, std::optional<U>&>` is false,
- is assignable `v<T&, optional<U>&>` is false,
- is assignable `v<T&, std::optional<U>&&>` is false,
- is assignable `v<T&, optional<U>&&>` is false,
- is assignable `v<T&, const std::optional<U>&>` is false,
- is assignable `v<T&, const optional<U>&>` is false,
- is assignable `v<T&, const std::optional<U>&&>` is false, and
- is assignable `v<T&, const optional<U>&&>` is false

`template<class U> optional& operator=(optional<U>&& rhs);`

Effects: See Table

Table — `optional operator=(optional<U>&&) effects`

	<code>*this</code> contains a value	<code>*this</code> does not contain a value
<code>rhs</code> contains a value	<code>assigns *rhs</code> to the contained value	initializes the contained value with <code>*rhs</code>. If uses <code>allocator<T,</code> <code>polymorphic allocator<>></code> is true, initialization is done by uses-allocator construction with allocator <code>M alloc</code>.
<code>rhs</code> does not contain a value	<code>destroys the</code> <code>contained</code> <code>value by</code> <code>calling <code>val->T::~T(.)</code></code>	<code>no effect</code>

Returns: `*this`.

Ensures: `bool(rhs) == bool(*this)`.

Remarks: If any exception is thrown, the result of the expression `bool(*this)` remains unchanged. If an exception is thrown during the call to `T`'s move constructor, the state of `*rhs.val` is determined by the exception safety guarantee of `T`'s move constructor. If an exception is thrown during the call to `T`'s move assignment, the state of `*val` and `*rhs.val` is determined by the exception safety guarantee of `T`'s move assignment.

Mandates:

- is same`<T,U>` is false,
- is constructible `v<T, const U&>` is true,
- is assignable`<T&, const U&>` is true,
- is constructible `v<T, std::optional<U>&>` is false,
- is constructible `v<T, optional<U>&>` is false,
- is constructible `v<T, std::optional<U>&&>` is false,
- is constructible `v<T, optional<U>&&>` is false,
- is constructible `v<T, const std::optional<U>&>` is false,
- is constructible `v<T, const optional<U>&>` is false,

- is constructible `v<T, const std::optional<U>&&>` is false,
- is constructible `v<T, const optional<U>&&>` is false,
- is convertible `v<const U&, T>` is true,
- is convertible `v<std::optional<U>&, T>` is false,
- is convertible `v<optional<U>&, T>` is false,
- is convertible `v<std::optional<U>&&, T>` is false,
- is convertible `v<optional<U>&&, T>` is false,
- is convertible `v<const std::optional<U>&, T>` is false,
- is convertible `v<const optional<U>&, T>` is false,
- is convertible `v<const std::optional<U>&&, T>` is false,
- is convertible `v<const optional<U>&&, T>` is false,
- is assignable `v<T&, std::optional<U>&>` is false,
- is assignable `v<T&, optional<U>&>` is false,
- is assignable `v<T&, std::optional<U>&&>` is false,
- is assignable `v<T&, optional<U>&&>` is false,
- is assignable `v<T&, const std::optional<U>&>` is false,
- is assignable `v<T&, const optional<U>&>` is false,
- is assignable `v<T&, const std::optional<U>&&>` is false, and
- is assignable `v<T&, const optional<U>&&>` is false

`template<class U> optional& operator=(std::optional<U>&& rhs);`

Effects: See Table

Table — optional operator=(std::optional<U>&&) effects

	<u>*this</u> <u>contains a</u> <u>value</u>	<u>*this does not contain a value</u>
<u>rhs</u> <u>contains a</u> <u>value</u>	<u>assigns *rhs</u> <u>to the</u> <u>contained</u> <u>value</u>	<u>initializes the contained value with *rhs. If</u> <u>uses allocator<T,</u> <u>polymorphic allocator<>> is true,</u> <u>initialization is done by uses-allocator</u> <u>construction with allocator M alloc</u>
<u>rhs does</u> <u>not</u> <u>contain a</u> <u>value</u>	<u>destroys the</u> <u>contained</u> <u>value by</u> <u>calling val-</u> <u>>T::~~T(.)</u>	<u>no effect</u>

Returns: *this.

Ensures: bool(rhs) == bool(*this).

Remarks: If any exception is thrown, the result of the expression bool(*this) remains unchanged. If an exception is thrown during the call to T's constructor, the state of *rhs.val is determined by the exception safety guarantee of T's constructor. If an exception is thrown during the call to T's assignment, the state of *val and *rhs.val is determined by the exception safety guarantee of T's assignment.

Mandates:

- is constructible `v<T, const U&>` is true,
- is assignable `<T&, const U&>` is true,
- is constructible `v<T, std::optional<U>&>` is false,
- is constructible `v<T, optional<U>&>` is false,
- is constructible `v<T, std::optional<U>&&>` is false,
- is constructible `v<T, optional<U>&&>` is false,
- is constructible `v<T, const std::optional<U>&>` is false,

- is constructible `v<T, const optional<U>&>` is false,
- is constructible `v<T, const std::optional<U>&&>` is false,
- is constructible `v<T, const optional<U>&&>` is false,
- is convertible `v<const U&, T>` is true,
- is convertible `v<std::optional<U>&, T>` is false,
- is convertible `v<optional<U>&, T>` is false,
- is convertible `v<std::optional<U>&&, T>` is false,
- is convertible `v<optional<U>&&, T>` is false,
- is convertible `v<const std::optional<U>&, T>` is false,
- is convertible `v<const optional<U>&, T>` is false,
- is convertible `v<const std::optional<U>&&, T>` is false,
- is convertible `v<const optional<U>&&, T>` is false,
- is assignable `v<T&, std::optional<U>&>` is false,
- is assignable `v<T&, optional<U>&>` is false,
- is assignable `v<T&, std::optional<U>&&>` is false,
- is assignable `v<T&, optional<U>&&>` is false,
- is assignable `v<T&, const std::optional<U>&>` is false,
- is assignable `v<T&, const optional<U>&>` is false,
- is assignable `v<T&, const std::optional<U>&&>` is false, and
- is assignable `v<T&, const optional<U>&&>` is false

`template<class... Args>> T& emplace(Args&&...);`

Constraints: is constructible `v<T, Args&&...>` is true.

Effects: Calls `*this = nullopt`. Then initializes the contained value with `std::forward<Args>(args).....` If uses allocator `<T, polymorphic allocator<>>` is true, initialization is done by uses-allocator construction with allocator `M alloc`.

Ensures: `*this` contains a value.

Returns: A reference to the new contained value.

Throws: Any exception thrown by the selected constructor of `T`.

Remarks: If an exception is thrown during the call to `T`'s constructor, `*this` does not contain a value, and the previous `*val` (if any) has been destroyed.

`template<class U, class... Args> T& emplace(initializer_list<U>, Args&&...);`

Constraints: is constructible `v<T, initializer_list<U>&, Args&&...>` is true.

Effects: Calls `*this = nullopt`. Then initializes the contained value with `il` and `std::forward<Args>(args).....` If uses allocator `<T, polymorphic allocator<>>` is true, initialization is done by uses-allocator construction with allocator `M alloc`.

Ensures: `*this` contains a value.

Returns: A reference to the new contained value.

Throws: Any exception thrown by the selected constructor of `T`.

Remarks: If an exception is thrown during the call to `T`'s constructor, `*this` does not contain a value, and the previous `*val` (if any) has been destroyed.

Swap [pmroptional.swap]

`void swap(optional& rhs) noexcept(see below);`

Constraints: Lvalues of type `T` shall be swappable and is move constructible - `v<T>` is true.

Expects: If uses allocator `<T, polymorphic allocator<>>` is true, `a.get_allocator() == b.get_allocator()`.

Effects: See Table x

Throws: Any exceptions thrown by the operations in the relevant part of Table x.

Remarks: The expression inside noexcept is equivalent to:

is nothrow move constructible $v < T > \wedge \wedge$ is nothrow swappable $v < T >$ If any exception is thrown, the results of the expressions $\text{bool}(*\text{this})$ and $\text{bool}(\text{rhs})$ remain unchanged. If an exception is thrown during the call to function swap, the state of $*\text{val}$ and $*\text{rhs}.val$ is determined by the exception safety guarantee of swap for lvalues of T . If an exception is thrown during the call to T 's move constructor, the state of $\text{tt} > *\text{val}$ and $*\text{rhs}.val$ is determined by the exception safety guarantee of T 's move constructor.

Table x — swap(optional&) effects

	<u>*this contains a value</u>	<u>*this does not contain a value</u>
<u>rhs contains a value</u>	<u>calls swap(*(*this), rhs).</u>	<u>initializes the contained value with $\text{std}::\text{move}(*\text{rhs})$ as the constructor argument, followed by $\text{rhs}.val \rightarrow T::\sim T()$; If $\text{uses_allocator} < T$, $\text{polymorphic_allocator} < >$ is true, initialization is done by uses-allocator construction with allocator M alloc. Postcondition is that *this contains a value and rhs does not contain a value</u>
<u>rhs does not contain a value</u>	<u>initializes the contained value with $\text{std}::\text{move}(*(*this))$ as the constructor argument, followed by $\text{val} \rightarrow T::\sim T()$; If $\text{uses_allocator} < T$, $\text{polymorphic_allocator} < >$ is true, initialization is done by uses-allocator construction with allocator M alloc. Postcondition is that *this does not contain a value and rhs contains a value</u>	<u>no effect</u>

Throws: Any exceptions thrown by the operations in the relevant part of Table x.

Observers [pmroptional.observe]

```
const T* operator->() const;  
T* operator->();
```

Expects: *this contains a value.

Returns: val.

Throws: Nothing.

```
const T& operator*() const&;  
T& operator*() &;();
```

Expects: *this contains a value.

Returns: *val.

Throws: Nothing.

T&& operator*() &&;
const T&& operator*() const&&; &;().;

Expects: *this contains a value.

Effects: Equivalent to: return std::move(*val);

explicit operator bool() const noexcept;

Returns: true if and only if contains a value.

bool has_value() const noexcept;

Returns: true if and only if contains a value.

const T& value() const&;

T& value() &;

Effects: Equivalent to:

return bool(*this) ? *val : throw bad optional access();

T&& value() &&;

const T&& value() const&&;

Effects: Equivalent to:

return bool(*this) ? std::move(*val) : throw
bad optional access();

template<class U> T value_or(U&& v) const&;

Effects: Equivalent to:

return bool(*this) ? **this : static cast<T>(std::forward<U>
(v)).;

Remarks: If is copy constructible v<T> && is convertible v<U&&, T> is
false, the program is ill-formed.

template<class U> T value_or(U&& v) &&;

Effects: Equivalent to:

return bool(*this) ? std::move(**this) : static cast<T>
(std::forward<U>(v)).;

Remarks: If is move constructible v<T> && is convertible v<U&&, T> is
false, the program is ill-formed.

template<class U> T value_or(allocator arg_t, const

polymorphic allocator<>& a, U&& v) const&;tt>

Constraints: uses allocator<T, polymorphic allocator<>> is true;

Effects: if *this contains a value, returns an object of type T initialized by uses-
allocator construction with allocator a and **this as the constructor argument.
Otherwise, returns an object of type T initialized by uses-allocator construction with
allocator a and std::forward<U>(v) as the constructor argument.

Remarks: If is copy constructible v<T> && is convertible v<U&&, T> is
false, the program is ill-formed.

template<class U> T value_or(allocator arg_t, const

polymorphic allocator<>& a, U&& v) &&;

Constraints: uses allocator<T, polymorphic allocator<>> is true;

Effects: if *this contains a value, returns an object of type T initialized by uses-
allocator construction with allocator a and std::move(**this) as the constructor
argument. Otherwise, returns an object of type T initialized by uses-allocator
construction with allocator a and std::forward<U>(v) as the constructor argument.

Remarks: If is copy constructible v<T> && is convertible v<U&&, T> is
false, the program is ill-formed.

allocator type `get_allocator() const noexcept;`
Constraints: `uses_allocator<T, polymorphic_allocator<>> is true;`
Returns: `M alloc.`
Throws: `nothing.`

Modifiers [pmroptional.mod]

`void reset() noexcept;`
Effects: `If *this contains a value, calls val->T::~T(.) to destroy the contained value; otherwise no effect.`
Ensures: `*this does not contain a value.`

Allocator-related traits [pmroptional.traits]

```
template<class T>
struct uses_allocator<T, polymorphic_allocator<>> :
    uses_allocator<T, polymorphic_allocator<>> {_};
```

Relational operators [pmroptional.relops]

```
template<class T, class U> bool operator==(const optional<T>&, const
optional<U>&);
template<class T, class U> bool operator==(const optional<T>&, const
std::optional<U>&);
template<class T, class U> bool operator==(const std::optional<T>&,
const optional<U>&);
Mandates: The expression *x == *y shall be well-formed and its result shall be convertible to bool. [ Note: T need not be Cpp17EqualityComparable. – end note ]  
Returns: If bool(x) != bool(y), false; otherwise if bool(x) == false, true; otherwise *x == *y.
```

```
template<class T, class U> bool operator!=(const optional<T>&, const
optional<U>&);
template<class T, class U> bool operator!=(const optional<T>&, const
std::optional<U>&);
template<class T, class U> bool operator!=(const std::optional<T>&,
const optional<U>&);
Mandates: The expression *x != *y shall be well-formed and its result shall be convertible to bool.  
Returns: If bool(x) != bool(y), true; otherwise if bool(x) == false, false; otherwise *x != *y.
```

```
template<class T, class U> bool operator<(const optional<T>&, const
optional<U>&);
template<class T, class U> bool operator<(const optional<T>&, const
std::optional<U>&);
template<class T, class U> bool operator<(const std::optional<T>&,
const optional<U>&);
Mandates: The expression *x < *y shall be well-formed and its result shall be convertible to bool.  
Returns: If !y, false; otherwise if !x, true; otherwise *x < *y.
```

```
template<class T, class U> bool operator>(const optional<T>&, const
optional<U>&);
template<class T, class U> bool operator>(const optional<T>&, const
std::optional<U>&);
template<class T, class U> bool operator>(const std::optional<T>&,
```

const optional<U>&);

Mandates: The expression $*x > *y$ shall be well-formed and its result shall be convertible to bool.

Returns: If $!x$, false; otherwise if $!y$, true; otherwise $*x > *y$.

template<class T, class U> bool operator<=(const optional<T>&, const optional<U>&);

template<class T, class U> bool operator<=(const optional<T>&, const std::optional<U>&);

template<class T, class U> bool operator<=(const std::optional<T>&, const optional<U>&);

Mandates: The expression $*x <= *y$ shall be well-formed and its result shall be convertible to bool.

Returns: If $!x$, true; otherwise if $!y$, false; otherwise $*x <= *y$.

template<class T, class U> bool operator>=(const optional<T>&, const optional<U>&);

template<class T, class U> bool operator>=(const optional<T>&, const std::optional<U>&);

template<class T, class U> bool operator>=(const std::optional<T>&, const optional<U>&);

Mandates: The expression $*x >= *y$ shall be well-formed and its result shall be convertible to bool.

Returns: If $!y$, true; otherwise if $!x$, false; otherwise $*x >= *y$.

template<class T, three way comparable with<T> U>

compare three way result t<T,U>

operator<=>(const optional<T>&, const optional<U>&);

template<class T, three way comparable with<T> U>

compare three way result t<T,U>

operator<=>(const optional<T>&, const std::optional<U>&);

template<class T, three way comparable with<T> U>

compare three way result t<T,U>

operator<=>(const std::optional<T>&, const optional<U>&);

Returns: If $x \&\& y$, $*x <=> *y$; otherwise $\text{bool}(x) <=> \text{bool}(y)$.

Comparison with nullopt [pmroptional.nullopts]

template<class T> bool operator==(const optional<T>&, nullopt t) noexcept;

Returns: $!x$.

template<class T> strong_ordering operator<=>(const optional<T>&, nullopt t) noexcept;

Returns: $\text{bool}(x) <=> \text{false}$.

Comparison with T [pmroptional.comp.with.t]

template<class T, class U> bool operator==(const optional<T>& x, const U& v);

Mandates: The expression $*x == v$ shall be well-formed and its result shall be convertible to bool. [Note: T need not be Cpp17EqualityComparable. – end note]

Effects: Equivalent to: $\text{return } \text{bool}(x) ? *x == v : \text{false};$

template<class T, class U> bool operator==(const T& t, const optional<U>& v);

Mandates: The expression $x == *v$ shall be well-formed and its result shall be convertible to bool.

Effects: Equivalent to: $\text{return } \text{bool}(v) ? x == *v : \text{false};$

template<class T, class U> bool operator!=(const optional<T>& u, const U& v);

Mandates: The expression $*x \neq v$ shall be well-formed and its result shall be convertible to bool.

Effects: Equivalent to: $\text{return bool}(x) ? *x \neq v : \text{true};$

$\text{template}<\text{class } T, \text{ class } U> \text{ bool operator}\neq(\text{const } T\& t, \text{ const optional}<U>\& v);$

Mandates: The expression $x \neq *v$ shall be well-formed and its result shall be convertible to bool.

Effects: Equivalent to: $\text{return bool}(v) ? x \neq *v : \text{true};$

$\text{template}<\text{class } T, \text{ class } U> \text{ bool operator}<(\text{const optional}<T>\&, \text{ const } U\&);$

Mandates: The expression $*x < v$ shall be well-formed and its result shall be convertible to bool.

Effects: Equivalent to: $\text{return bool}(x) ? *x < v : \text{true};$

$\text{template}<\text{class } T, \text{ class } U> \text{ bool operator}<(\text{const } T\& t, \text{ const optional}<U>\& v);$

Mandates: The expression $x < *v$ shall be well-formed and its result shall be convertible to bool.

Effects: Equivalent to: $\text{return bool}(v) ? x < *v : \text{false};$

$\text{template}<\text{class } T, \text{ class } U> \text{ bool operator}>(\text{const optional}<T>\&, \text{ const } U\&);$

Mandates: The expression $*x > v$ shall be well-formed and its result shall be convertible to bool.

Effects: Equivalent to: $\text{return bool}(x) ? *x > v : \text{false};$

$\text{template}<\text{class } T, \text{ class } U> \text{ bool operator}>(\text{const } T\& t, \text{ const optional}<U>\& v);$

Mandates: The expression $x > *v$ shall be well-formed and its result shall be convertible to bool.

Effects: Equivalent to: $\text{return bool}(v) ? x > *v : \text{true};$

$\text{template}<\text{class } T, \text{ class } U> \text{ bool operator}<=(\text{const optional}<T>\&, \text{ const } U\&);$

Mandates: The expression $*x \leq v$ shall be well-formed and its result shall be convertible to bool.

Effects: Equivalent to: $\text{return bool}(x) ? *x \leq v : \text{true};$

$\text{template}<\text{class } T, \text{ class } U> \text{ bool operator}<=(\text{const } T\& t, \text{ const optional}<U>\& v);$

Mandates: The expression $x \leq *v$ shall be well-formed and its result shall be convertible to bool.

Effects: Equivalent to: $\text{return bool}(v) ? x \leq *v : \text{false};$

$\text{template}<\text{class } T, \text{ class } U> \text{ bool operator}>=(\text{const optional}<T>\&, \text{ const } U\&);$

Mandates: The expression $*x \geq v$ shall be well-formed and its result shall be convertible to bool.

Effects: Equivalent to: $\text{return bool}(x) ? *x \geq v : \text{false};$

$\text{template}<\text{class } T, \text{ class } U> \text{ bool operator}>=(\text{const } T\& t, \text{ const optional}<U>\& v);$

Mandates: The expression $x \geq *v$ shall be well-formed and its result shall be convertible to bool.

Effects: Equivalent to: $\text{return bool}(v) ? x \geq *v : \text{true};$

$\text{template}<\text{class } T, \text{ three way comparable with}<T> U>$

$\text{compare three way result } t<T,U>$

$\text{operator}<=>(\text{const optional}<T>\& x, \text{ const } U\&v);$

Effects: Equivalent to: $\text{return bool}(x) ? *x \geq v : \text{strong_ordering}::\text{less};$

Specialized algorithms [pmroptional.specalg]

template<class T> void swap(optional<T>& x, optional<T>& y);
Effects: if x.get_allocator() == y.get_allocator(), calls x.swap(y).
Otherwise equivalent to
std::pmr::optional futureX(allocator arg t, x.get_allocator(), y);
std::pmr::optional futureY(allocator arg t, y.get_allocator(), x);
futureX.swap(x);
futureY.swap(y);

template<class T> constexpr optional<decay_t<T>> make_optional(T&&);
Returns: optional<decay_t<T>>(std::forward<T>(v)).
Remarks: Specialization of this function template shall be a
constexpr function if uses allocator<T, polymorphic allocator<>>::value
is false.

template<class T> constexpr optional<T> make_optional();
Effects: Equivalent to: return optional<T>(in place).
Remarks: Specialization of this function template shall be a
constexpr function if uses allocator<T, polymorphic allocator<>>::value
is false.

template<class T, class Arg0, class... Args> constexpr optional<T>
make_optional(Arg0&& arg0, Args&&... args);
Effects: Equivalent to: return optional<T>(in place, std::
forward<Arg0>(arg0), std::forward<Args>(args)...).
Constraints: !is same< typename remove cvref t<ARG0>,
allocator arg t>
Remarks: Specialization of this function template shall be a
constexpr function if uses allocator<T, polymorphic allocator<>>::value
is false.

template<class T, class... Args> constexpr optional<T>
make_optional(Args&&... args);
Effects: Equivalent to: return optional<T>(in place, std::
forward<Args>(args)...).
Remarks: Specialization of this function template shall be a
constexpr function if uses allocator<T, polymorphic allocator<>>::value
is false.

template<class T, class U, class... Args> optional<T>
constexpr make_optional(initializer_list<U> il, Args&&... args);
Effects: Equivalent to: return optional<T>(in place, il, std::
forward<Args>(args)...).
Remarks: Specialization of this function template shall be a
constexpr function if uses allocator<T, polymorphic allocator<>>::value
is false.

template<class T, optional<decay_t<T>>
make_optional(allocator arg t, const polymorphic allocator<>& a,
T&&);
Mandates: uses allocator<T, polymorphic allocator<>> is true;
Returns: optional<decay_t<T>>(allocator arg, a, in place, std::
forward<T>(v)).

template<class T, class... Args> optional<T>
make_optional(allocator arg t, const polymorphic allocator<>& a,
Args&&... args);
Mandates: uses allocator<T, polymorphic allocator<>> is true;
Effects: Equivalent to: return optional<T>(allocator arg, a,
in place, std::forward<Args>(args)...).

template<class T, class U, class... Args> optional<T>
make_optional(allocator arg t, const polymorphic allocator<>& a,
initializer_list<U> il, Args&&... args);
Mandates: uses allocator<T, polymorphic allocator<>> is true;

Effects: Equivalent to: return optional<T>(allocator arg, a, in_place, il, std::forward<Args>(args)...).

Hash support [pmroptional.hash]

template<class T> struct hash<optional<T>>;

The specialization hash<optional<T>> is enabled ([unord.hash]) if and only if hash<remove const t<T>> is enabled. When enabled, for an object o of type optional<T>, if bool(o) == true, then hash<optional<T>>().(o) shall evaluate to the same value as hash<remove const t<T>>().(*o); otherwise it evaluates to an unspecified value. The member functions are not guaranteed to be noexcept.