

Freestanding Library: Character primitives and the C library

Document number: P2338R0

Date: 2021-03-13

Reply-to: Ben Craig <ben dot craig at gmail dot com>

Audience: SG14 (Low Latency), SG22 (C Liaison), Library Evolution Working Group

Abstract

Add everything to the shared C and C++ freestanding library that can be implemented without OS calls and space overhead. Also add primitive character operations (<charconv> and `char_traits`) to the C++ freestanding library.

Introduction

The current definition of the freestanding implementation is not very useful. Here is the current high level definition from WG21's [intro.compliance]:

- 7 Two kinds of implementations are defined: a *hosted implementation* and a *freestanding implementation*. For a hosted implementation, this document defines the set of available libraries. A freestanding implementation is one in which execution may take place without the benefit of an operating system, and has an implementation-defined set of libraries that includes certain language-support libraries ([compliance]).

Similar wording is present in 5.1.2.1 "Freestanding Environment" in WG14 N2454.

In a freestanding environment (in which C program execution may take place without any benefit of an operating system)[...]

The main people served by the current C++ freestanding definition are people writing their own hosted C++ standard library to sit atop the compiler author's freestanding implementation (i.e. the STLport use case). The C++ freestanding portions contain most of the functions and types known to the compiler that can't easily be authored in a cross-compiler manner.

The current set of freestanding libraries provides too little to kernel, micro-controller, and GPU programmers. Why should a systems programmer need to rewrite `std::from_chars` or `memcpy()`?

I propose we provide the (nearly) maximal subset of the library that does not require an OS or space overhead. In order to continue supporting the "layered" C++ standard library users, we will continue to provide the (nearly) minimal subset of the library needed to support all the language features, even if these features have space overhead. Language features requiring space overhead or OS support will remain intact.

Motivation

The C and C++ standard libraries have many generally useful facilities that systems programmers could benefit from. By requiring those functions to be present in freestanding implementations, we make it possible to make higher level programs both easier to write, and portable. Currently, programs that would like to be portable are required to either rely on implementation defined extensions, or provide look-alike implementations.

Current State

The requirements on freestanding implementations have diverged over time between C and C++.

A freestanding C implementation is required to provide the entirety of the following headers:

- `<float.h>`
- `<iso646.h>`
- `<limits.h>`
- `<stdalign.h>`
- `<stdarg.h>`
- `<stdbool.h>`
- `<stddef.h>`
- `<stdint.h>`
- `<stdnoreturn.h>`

Some additional features are required if the implementation defines the `__STDC_IEC_60559_BFP__` (binary floating point) macro or the `__STDC_IEC_60559_DFP__` (decimal floating point) macro. This includes `<fenv.h>`, `<math.h>`, and parts of `<stdlib.h>`. Such implementations indirectly require locale support, as the `<stdlib.h>` numeric conversion functions are implemented in terms of `isspace`.

The entire core language is required. This includes `_Thread_local`, which requires operating system interaction on multi-threaded systems.

C++

A freestanding C++ implementation is required to provide the entirety of the following headers:

- `<cstddef>`
- `<cfloat>`
- `<climits>`
- `<limits>`
- `<version>`
- `<cstdint>`
- `<new>`
- `<typeinfo>`
- `<source_location>`
- `<exception>`
- `<initializer_list>`
- `<compare>`
- `<coroutine>`
- `<cstdarg>`
- `<concepts>`
- `<type_traits>`
- `<bit>`

Almost all of `<atomic>` is required (C does not require `<stdatomic.h>` in freestanding implementations). `<cstdlib>` must provide `abort`, `atexit`, `at_quick_exit`, `exit`, and `quick_exit`.

The entire core language is required. For C++, this is much more onerous than for C, as the C++ core language includes exceptions, RTTI, thread-safe static initialization, and heap allocations.

The in-flight paper [P2013](#) makes it such that the allocating forms of `::operator new` are no longer required. This requirement often meant that the underlying C implementation of a freestanding C++ library needed to have `malloc` and `free` implementations.

The in-flight paper [P1642](#) adds many C++ specific facilities, but it also adds `_Exit`. The specification for `quick_exit` specifically calls out `_Exit`, so this omission is a specification bug.

A freestanding C++ implementation is mostly a superset of a freestanding C implementation, even in the "C" parts of C++. This means that a freestanding C++ implementation can not generally be built on top of a minimal freestanding C implementation. Either the C++ implementation must provide some of the C parts, or the C++ implementation will require a C implementation that provides more than the minimum.

Scope

The current scope of this proposal is limited to the freestanding standard library available to micro-controller, kernel, and GPU development.

This paper is currently concerned with the divisions of headers and library functions as they were in C++17. "[Standard Library Modules](#)" (P0581) discusses how the library will be split up in a post-modules world. This paper may influence the direction of P0581, but this paper won't make any modules recommendations.

Impact on the standards

In the C standard library, a new editorial strategy will be used to mark facilities as freestanding. Prose in the standard will declare various facilities as *freestanding library facilities*. Only the primary definition will be declared this way, so we won't be duplicating this prose multiple times for the same facility (e.g. `NULL`, `size_t`, `wchar_t`, etc...).

Prior to this paper, the required contents of the C freestanding library were called out by header, and (conditionally) by clause in the case of `<stdlib.h>` numeric conversion functions in 7.22.1. This editorial strategy is cumbersome for partially required headers.

In the C++ standard library, the editorial strategy described in WG21 [P1642](#) will be used to annotate which facilities are required in freestanding implementations.

Impact on implementations

C freestanding libraries would be required to provide more facilities than they are currently required to provide. Implementations likely already provide many of these functions due to user demand.

In theory, providing additional headers could silently break customer code that was already providing those headers. Those uses were undefined behavior according to WG14 N2454, 7.1.2 Standard Headers#4.

If a file with the same name as one of the above `<` and `>` delimited sequences, not provided as part of the implementation, is placed in any of the standard places that are searched for included source files, the behavior is undefined.

A C program could be using its own definition of, say, `memcpy`, so long as it does not include `string.h`. Implementations that are worried about such cases will need to take care to use macro definitions for most functions that forward to reserved identifier functions, so as to avoid multiple definitions.

C++ standard library headers will likely need to add preprocessor feature toggles to portions of headers that would emit warnings or errors in freestanding mode. The timeliness (compile time vs. link time) of errors remains a quality-of-implementation detail.

A minimal freestanding C17 standard library will not be sufficient to provide the C portions of the C++ standard library. `std::char_traits` and many of the function specializations in `<algorithm>` are implemented in terms of non-freestanding C functions. In practice, most C libraries are not minimal freestanding C17 libraries. The optimized versions of the `<cstring>` and `<wchar>` functions will often be the same for both hosted and freestanding environments. The main way in which a hosted implementation of (for example) `memcpy` could differ between hosted and freestanding is that some freestanding implementations (e.g. kernel implementations) would not want `memcpy` to use vector / floating point registers.

My expectation is that no new C++ freestanding library will be authored as a result of this paper. Instead hosted libraries will be stripped down through some feature toggle mechanism to become freestanding.

Design decisions

Even more so than for a hosted implementation; kernel, micro-controller, and GPU programmers do not want to pay for what they don't use. As a consequence, I am not adding features that require global data storage, even if that storage is immutable.

Note that the following concerns are not revolving around execution time performance. These are generally concerns about space overhead and correctness.

This proposal doesn't remove problematic features from the language, but it does make it so that the bulk of the freestanding standard library doesn't require those features. Users that disable the problematic features (as is existing practice) will still have

portable portions of the standard library at their disposal.

Note that we cannot just take the list of C++ constexpr functions and make those functions the freestanding subset. We also can't do the reverse, and make everything freestanding constexpr or conditionally noexcept. memcpy cannot currently be made constexpr because it must convert from `cv void*` to `unsigned char[]`. Several floating point functions could be made constexpr, but would not be permitted in freestanding. constexpr also allows allocations, which freestanding avoids.

We also cannot just take the list of everything that is conditionally noexcept and make those functions freestanding. The "Lakos Rule"[Meredith11] prohibits most standard library functions from being conditionally noexcept, unless they have a wide contract.

Regardless, if a function or class is constexpr or noexcept, and it doesn't involve floating point, then that function or class is a strong candidate to be put into freestanding mode.

In the future, it may make sense to allow all constexpr functions into freestanding, so long as they are used in a constexpr context and not invoked at runtime.

Split overload sets

In C++, `to_chars`, `from_chars`, and `abs` are overloaded on floating point and integral types. This paper is making the integral overloads required in freestanding implementations.

It would be undesirable for the behavior of a library or program to silently change when porting it from a freestanding implementation to a hosted implementation though. That could easily happen with this overload set if a user called `abs(0.5)`. If the floating point overloads were merely omitted, then `abs(0.5)` would call one of the integral overloads on a freestanding implementation.

To avoid this trap, the floating point overloads will be marked as *//freestanding delete*. Freestanding implementations can either `=delete` the function, or provide an implementation of the function that meets the hosted requirements. This will cause accidental uses of these functions to fail to compile, as `=delete` functions participate in overload resolution.

Note that split overload set problems already exist in the C++ standard. A translation unit that includes `<inttypes>` and calls `abs(0.5)` may end up resolving the overload to `abs(intmax_t)`.

Exceptions

Exceptions either require external jump tables or extra bookkeeping instructions. This consumes program storage space.

In the Itanium ABI, throwing an exception requires a heap allocation. In the Microsoft ABI, re-throwing an exception will consume surprisingly large amounts of stack space (2,100 bytes for a re-throw in 32-bit environments, 9,700 bytes in a 64-bit environment). Program storage space, heap space, and stack space are typically scarce resources in micro-controller development.

In environments with threads, exception handling requires the use of thread-local storage.

RTTI

RTTI requires extra data in vtables and extra classes that are difficult to optimize away, consuming program storage space.

Thread-local storage

Thread-local storage requires extra code in the operating system for support. In addition, if one thread uses thread-local storage, that cost is imposed on other threads. Note that there are common environments (e.g. the kernels of all major desktop operating systems) that support multiple threads, but do not support arbitrary thread local variables.

The heap

The heap is a big set of global state. In addition, C++ heap exhaustion is typically expressed via exception. Some micro-controller systems don't have a heap. In kernel environments, there is typically a heap, but there isn't a reasonable choice of *which* heap to use as the default. In the Windows kernel, the two best candidates for a default heap are the paged pool (plentiful available memory, but unsafe to use in many contexts), and the non-paged pool (safe to use, but limited capacity). The C++ implementation in the Windows kernel forces users to implement their own global operator `new` to make this decision.

P2013 allows freestanding C++ implementations to omit the global allocating `::operator new` implementations by default.

Floating point

Many micro-controller systems don't have floating point hardware. Software emulated floating point can drag in large runtimes that are difficult to optimize away.

Most operating systems speed up system calls by not saving and restoring floating point state. That means that kernel uses of floating point operations require extra care to avoid corrupting user state.

In C, the dynamic floating-point environment has thread storage duration. This drags in the same set of problems that Thread-local storage has.

Functions requiring global or thread-local storage

These functions are not being added to the freestanding library. Examples are the locale aware functions, the C random number functions, and functions relying on `errno`.

Experience

The musl, newlib, and uclibc-ng C libraries are all marketed towards embedded use cases, and are all frequently used in embedded environments. All of the C facilities that this paper adds to the freestanding requirements are already present in musl, newlib, and uclibc-ng. This includes `memcpy`.

The Linux kernel uses a custom C library, though that library is more minimal, and in non-standard locations. The Linux kernel has implementations of `bsearch` (in `<linux/bsearch.h>`) and all of the `<string.h>` functions except for `memcpy`, though the `<string.h>` functions are in `<linux/string.h>`. The `<wchar.h>`, `<inttypes.h>`, and most of the `<stdlib.h>` functions were not present.

The Microsoft Windows kernel also has a C implementation that is distinct from the one that ships from Microsoft Visual Studio. That C implementation contains all of the new freestanding requirements with the exception of `imaxabs`, `imaxdiv`, `llabs`, and `lldiv`.

On the C++ front, I have successfully tested Visual Studio's `char_traits` implementation with a C++14 era set of `libc++` tests, all in the Windows kernel. The integral `<charconv>` functions have not been tested, but I do not foresee any issues there.

Technical Specifications

Partial headers newly required for freestanding implementations

Portions of `<cstdlib>`

- `size_t`
- `div_t`
- `ldiv_t`
- `lldiv_t`
- `NULL`
- `bsearch`
- `qsort`
- `abs(int)`
- `abs(long int)`
- `abs(long long int)`
- `labs`
- `llabs`
- `div`
- `ldiv`
- `lldiv`

All the error `#defines` in `<cerrno>`, but not `errno`.

The `errc` enum from `<system_error>`.

Portions of <charconv>.

- to_chars_result
- from_chars_result
- to_chars(integral)
- from_chars(integral)

The char_traits class from <string>.

Portions of <cstring>.

- memcpy
- memmove
- strcpy
- strncpy
- strcat
- strncat
- memcmp
- strcmp
- strncmp
- memchr
- strchr
- strcspn
- strpbrk
- strrchr
- strspn
- strstr
- memset
- strlen

On C, include memcpy in <string.h>, in addition to what is mentioned above for <cstring>.

Portions of <wchar>.

- wcsncpy
- wcsncat
- wmemcpy
- wmemmove
- wcscat
- wcsncat
- wcscmp
- wcsncmp
- wmemcmp
- wcschr
- wcscspn
- wcpbrk
- wcsrchr
- wcssp
- wcsstr
- wcstok
- wmemchr
- wcslen
- wmemset

A small portion of <cmath> will be present.

- abs(int)
- abs(long int)
- abs(long long int)

A portion of <inttypes> will be present.

- imaxabs
- imaxdiv
- abs(intmax_t)
- div(intmax_t, intmax_t)

Notable omissions

errno is not included as it is global state. In addition, errno is best implemented as a thread-local variable.

`error_code`, `error_condition`, and `error_category` all have `string` in the interface.

Many string functions (`strtol` and family) rely on `errno`.

`strtok` and `rand` aren't required to use thread-local storage, but good implementations do. I don't want to encourage bad implementations.

`assert` is not included as it requires a `stderr` stream.

`_Exit` is not included as I do not wish to add more termination functions. I hope to remove most of them in the future. Program termination requires involvement from the operating system / environment.

`<cctype>` and `<cwctype>` rely heavily on global locale data.

Potential removals

Here are some things that I am currently requiring, but could be convinced to remove.

- `<wchar>`

The `<wchar>` functions are implementable for freestanding environments. The Microsoft and EFI ecosystems (EFI was the successor to BIOS and the predecessor to UEFI) use `wchar_t` extensively.

Potential additions

Here are some things that I am not currently requiring, but could be convinced to add.

- Floating point support

Perhaps we don't worry about library portability in all cases. Just because kernel modes can't easily use floating point doesn't mean that we should deny floating point to the micro-controller space. Do note that most of `<cmath>` has a dependency on `errno`.

- `errno` and string functions like `strtol`

While `errno` is global data, it isn't much global data. Thread safety is a concern for those platforms that have threading, but don't have thread-local storage. Environments that don't support arbitrary thread local data could special case `errno`.

- C `<stdatomic.h>`

C doesn't currently require `<stdatomic.h>` in freestanding implementations, but C++ requires `std::atomic`. I don't currently recommend adding `<stdatomic.h>` to freestanding C implementations, as that would also require dealing with non-lock-free atomics. If others feel strongly about unifying this aspect of C and C++ freestanding implementations, then the facilities could be added.

Feature Test Macros

A freestanding implementation that provides support for this paper shall define the following feature test macros:

Name	Header	Notes
<code>__cpp_lib_freestanding_char_traits</code>	<code><string></code>	
<code>__cpp_lib_freestanding_charconv</code>	<code><charconv></code>	
<code>__cpp_lib_freestanding_cinttypes</code>	<code><cinttypes></code>	
<code>__cpp_lib_freestanding_cstdlib</code>	<code><cstdlib></code> and <code><cmath></code>	The only freestanding parts of <code><cmath></code> are abs overloads that are also covered in <code><cstdlib></code>
<code>__cpp_lib_freestanding_cstring</code>	<code><cstring></code>	
<code>__cpp_lib_freestanding_cwchar</code>	<code><cwchar></code>	
<code>__cpp_lib_freestanding_errc</code>	<code><cerrno></code> and <code><system_error></code>	Covers <code>errc</code> and <code><cerrno></code> #defines

The above macros are useful for detecting the presence of various facilities. The user can provide a hand-rolled replacement on old or non-conforming implementations, while using the toolchain's facilities when available. These macros follow the policies

proposed in [P2198: Freestanding Feature-Test Macros and Implementation-Defined Extensions](#).

C Wording

Wording is based off of WG14's N2596.

Change in 4. Conformance

Change paragraph 6 as follows:

The two forms of conforming implementation are hosted and freestanding. A conforming hosted implementation shall accept any strictly conforming program. A conforming freestanding implementation shall accept any strictly conforming program in which the use of the features specified in the library clause (Clause 7) is confined to ~~the contents of the standard headers `<float.h>`, `<iso646.h>`, `<limits.h>`, `<stdalign.h>`, `<stdarg.h>`, `<stdbool.h>`, `<stddef.h>`, `<stdint.h>`, and `<stdnoreturn.h>`.~~ **freestanding library facilities. The strictly conforming programs that shall be accepted by a conforming freestanding implementation may include any standard library header that contains freestanding library facilities.** A conforming implementation may have extensions (including additional library functions), provided they do not alter the behavior of any strictly conforming program. **All identifiers that are reserved when a standard header is included in a hosted implementation are reserved when it is included in a freestanding implementation.**

Change paragraph 7 as follows:

The strictly conforming programs that shall be accepted by a conforming freestanding implementation that defines `__STDC_IEC_60559_BFP__` or `__STDC_IEC_60559_DFP__` may also use features in the contents of the standard headers `<fenv.h>` and `<math.h>` and the numeric conversion functions (7.22.1) of the standard header `<stdlib.h>`. ~~All identifiers that are reserved when `<stdlib.h>` is included in a hosted implementation are reserved when it is included in a freestanding implementation.~~

Change in 7.5 Errors `<errno.h>`

Add a sentence to paragraph 2:

[...]or a program defines an identifier with the name `errno`, the behavior is undefined. **EDOM, EILSEQ, and ERANGE are freestanding library facilities.**

Change in 7.7 Characteristics of floating types `<float.h>`

Add a new paragraph:

The macros in `<float.h>` are freestanding library facilities.

Change in 7.8.2.1 The `imaxabs` function

Add a paragraph to the synopsis:

The `imaxabs` function is a freestanding library facility.

Change in 7.8.2.2 The `imaxdiv` function

Add a paragraph to the synopsis:

The `imaxdiv` function is a freestanding library facility.

Change in 7.9 Alternative spellings <iso646.h>

Add a new paragraph:

The macros in <iso646.h> are freestanding library facilities.

Change in 7.10 Sizes of integer types <limits.h>

Add a new paragraph:

The macros in <limits.h> are freestanding library facilities.

Change in 7.15 Alignment <stdalign.h>

Add a new paragraph:

The macros in <stdalign.h> are freestanding library facilities.

Change in 7.16 Variable arguments <stdarg.h>

Add a new paragraph:

The types and macros in <stdarg.h> are freestanding library facilities.

Change in 7.18 Boolean type and values <stdbool.h>

Add a new paragraph:

The macros in <stdbool.h> are freestanding library facilities.

Change in 7.19 Common definitions <stddef.h>

Add a new paragraph:

The types and macros in <stddef.h> are freestanding library facilities.

Change in 7.20 Integer types <stdint.h>

Add a new paragraph:

The types and macros in <stdint.h> are freestanding library facilities.

Change in 7.22 General utilities <stdlib.h>

Add a sentence to paragraph 3:

[...]which is a structure type that is the type of the value returned by the `lldiv` function. `div_t`, `ldiv_t`, and `lldiv_t` are freestanding library facilities.

Change in 7.22.5.1 The `bsearch` function

Add a paragraph to the synopsis:

The `bsearch` function is a freestanding library facility.

Change in 7.22.5.2 The `qsort` function

Add a paragraph to the synopsis:

The `qsort` function is a freestanding library facility.

Change in 7.22.6.1 The `abs`, `labs`, and `llabs` functions

Add a paragraph to the synopsis:

The `abs`, `labs`, and `llabs` functions are freestanding library facilities.

Change in 7.22.6.2 The `div`, `ldiv`, and `lldiv` functions

Add a paragraph to the synopsis:

The `div`, `ldiv`, and `lldiv` functions are freestanding library facilities.

Change in 7.23 `_Noreturn` `<stdnoreturn.h>`

Add a new paragraph:

The macros in `<stdnoreturn.h>` are freestanding library facilities.

Change in 7.24 String handling `<string.h>`

For each of the following synopses...

- 7.24.2.1 The `memcpy` function
- 7.24.2.2 The `memccpy` function
- 7.24.2.3 The `memmove` function
- 7.24.2.4 The `strcpy` function
- 7.24.2.5 The `strncpy` function
- 7.24.3.1 The `strcat` function
- 7.24.3.2 The `strncat` function
- 7.24.4.1 The `memcmp` function
- 7.24.4.2 The `strcmp` function
- 7.24.4.4 The `strncmp` function
- 7.24.5.1 The `memchr` function
- 7.24.5.2 The `strchr` function
- 7.24.5.3 The `strcspn` function
- 7.24.5.4 The `strpbrk` function
- 7.24.5.5 The `strrchr` function
- 7.24.5.6 The `strspn` function
- 7.24.5.7 The `strstr` function
- 7.24.6.1 The `memset` function
- 7.24.6.3 The `strlen` function

...add the following new paragraph to the synopsis, with `__placeholder__` replaced with the corresponding function name:

The `__placeholder__` function is a freestanding library facility.

Change in 7.29 Extended multibyte and wide character utilities <wchar.h>

Add a sentence to paragraph 2:

[...] which is declared as an incomplete structure type (the contents are described in 7.27.1). **mbstate_t and wint_t are freestanding library facilities.**

Add a sentence to paragraph 3:

[...] It is also used as a wide character value that does not correspond to any member of the extended character set. **WEOF is a freestanding library facility.**

For each of the following synopses...

- 7.29.4.2.1 The wcsncpy function
- 7.29.4.2.2 The wcsncpy function
- 7.29.4.2.3 The wmemcpy function
- 7.29.4.2.4 The wmemmove function
- 7.29.4.3.1 The wscat function
- 7.29.4.3.2 The wcsncat function
- 7.29.4.4.1 The wscmp function
- 7.29.4.4.3 The wcsncmp function
- 7.29.4.4.5 The wmemcmp function
- 7.29.4.5.1 The wcschr function
- 7.29.4.5.2 The wcsnspn function
- 7.29.4.5.3 The wcpbrk function
- 7.29.4.5.4 The wcsrchr function
- 7.29.4.5.5 The wcsspn function
- 7.29.4.5.6 The wcsstr function
- 7.29.4.5.7 The wcstok function
- 7.29.4.5.8 The wmemchr function
- 7.29.4.6.1 The wcslen function
- 7.29.4.6.2 The wmemset function

...add the following new paragraph to the synopsis, with `__placeholder__` replaced with the corresponding function name:

The `__placeholder__` function is a freestanding library facility.

C++ Wording

Wording is based off [WG21 N4878](#) from 2020-12-15. This paper also assumes that [P1642](#) and [P2198](#) have been accepted and applied.

Change in [\[conventions\]](#)

Add a new paragraph to `[freestanding.membership]` (added in [P1642](#)).

? On a freestanding implementation, a *freestanding deleted function* is a function that has either a deleted definition or a definition meeting the corresponding requirements in a hosted implementation. In the associated header synopsis for such freestanding deleted functions, the items are followed with a comment that includes *freestanding deleted*.
[Example:

`double abs(double j); // freestanding deleted`

-end example]

Change in [compliance]

Change [tab:headers.cpp.fs]:

	Subclause	Header(s)
[...]	[...]	[...]
?? [support.start.term]?? [cstdlib.syn]	Start and termination	C standard library
[...]	[...]	[...]
?? [errno]	Error numbers	<cerrno>
?? [syserr]	System error support	<system_error>
?? [charconv]	Primitive numeric conversions	<charconv>
?? [string.classes]	String classes	<string>
?? [ratio]	Compile-time rational arithmetic	<ratio>
?? [c.strings]	Null-terminated sequence utilities	<cstring>, <cwchar>
?? [c.math]	Mathematical functions for floating-point types	<cmath>
?? [c.files]	C library files	<cinttypes>
[...]	[...]	[...]

Change in [cstdlib.syn]

Instructions to the editor:
Please append a // *freestanding* comment to the following entities:

- div_t
- ldiv_t
- lldiv_t
- bsearch
- qsort
- abs(int)
- abs(long int)
- abs(long longint)
- labs
- llabs
- div
- ldiv
- lldiv

Please append a // *freestanding deleted* comment to the following entities:

- abs(float)
- abs(double)
- abs(long double)

Change in [version.syn]

Please add the following feature test macros to [version.syn]:

```
#define cpp_lib freestanding_char_traits new-val // freestanding, also in <string>
#define cpp_lib freestanding_charconv new-val // freestanding, also in <charconv>
#define cpp_lib freestanding_cinttypes new-val // freestanding, also in <cinttypes>
#define cpp_lib freestanding_cstdlib new-val // freestanding, also in <cstdlib>, <cmath>
#define cpp_lib freestanding_cstring new-val // freestanding, also in <cstring>
#define cpp_lib freestanding_cwchar new-val // freestanding, also in <cwchar>
#define cpp_lib freestanding_errc new-val // freestanding, also in <cerrno>, <system_error>
```

Change in [cerrno.syn]

Instructions to the editor:
Please append a // *freestanding* comment to the following entities:

- E2BIG
- EACCES
- EADDRINUSE
- EADDRNOTAVAIL
- EAFNOSUPPORT
- EAGAIN
- EALREADY
- EBADF
- EBADMSG
- EBUSY
- ECANCELED
- ECHILD
- ECONNABORTED
- ECONNREFUSED
- ECONNRESET
- EDEADLK
- EDESTADDRREQ
- EDOM
- EEXIST
- EFAULT
- EFBIG
- EHOSTUNREACH
- EIDRM
- EILSEQ
- EINPROGRESS
- EINTR
- EINVAL
- EIO
- EISCONN
- EISDIR
- ELOOP
- EMFILE
- EMLINK
- EMSGSIZE
- ENAMETOOLONG
- ENETDOWN
- ENETRESET
- ENETUNREACH
- ENFILE
- ENOBUFS
- ENODATA
- ENODEV
- ENOENT
- ENOEXEC
- ENOLCK
- ENOLINK
- ENOMEM
- ENOMSG
- ENOPROTOOPT
- ENOSPC
- ENOSR
- ENOSTR
- ENOSYS
- ENOTCONN
- ENOTDIR
- ENOTEMPTY
- ENOTRECOVERABLE
- ENOTSOCK
- ENOTSUP
- ENOTTY
- ENXIO
- EOPNOTSUPP
- EOVERFLOW

- EOWNERDEAD
- EPERM
- EPIPE
- EPROTO
- EPROTONOSUPPORT
- EPROTOTYPE
- ERANGE
- EROFS
- ESPIPE
- ESRCH
- ETIME
- ETIMEDOUT
- ETXTBSY
- EWOULDBLOCK
- EXDEV

Change in [\[system_error.syn\]](#)

Instructions to the editor:

Please append a *// freestanding* comment to the `errc` entity.

Change in [\[charconv.syn\]](#)

Instructions to the editor:

Please append a *// freestanding* comment to the following entities:

- `to_chars_result`
- `from_chars_result`
- `to_chars_result to_chars(char* first, char* last, see below value, int base = 10);`
- `from_chars_result from_chars(const char* first, const char* last, see below& value, int base = 10);`

Please append a *// freestanding deleted* comment to the following entities:

- `to_chars(char* first, char* last, float value)`
- `to_chars(char* first, char* last, double value)`
- `to_chars(char* first, char* last, long double value)`
- `from_chars(const char *first, const char *last, float& value, chars_format fmt = chars_format::general)`
- `from_chars(const char *first, const char *last, double& value, chars_format fmt = chars_format::general)`
- `from_chars(const char *first, const char *last, long double& value, chars_format fmt = chars_format::general)`

Change in [\[string.syn\]](#)

Instructions to the editor:

Please append a *// freestanding* comment to the following entities:

- `template<class charT> struct char_traits`
- `template<> struct char_traits<char>`
- `template<> struct char_traits<char8_t>`
- `template<> struct char_traits<char16_t>`
- `template<> struct char_traits<char32_t>`
- `template<> struct char_traits<wchar_t>`

Change in [\[cstring.syn\]](#)

Instructions to the editor:

Please append a *// freestanding* comment to the following entities:

- `memcpy`
- `memmove`

- strcpy
- strncpy
- strcat
- strncat
- memcmp
- strcmp
- strncmp
- memchr
- strchr
- strcspn
- strpbrk
- strrchr
- strspn
- strstr
- memset
- strlen
- NULL

The following entities should **NOT** have freestanding comments appended to them:

- strcoll
- strxfrm
- strtok
- strerror

Change in [\[cwchar.syn\]](#)

Instructions to the editor:

Please append a *// freestanding* comment to the following entities:

- size_t
- mbstate_t
- wint_t
- wcscpy
- wcsncpy
- wmemcpy
- wmemmove
- wcscat
- wcsncat
- wcscmp
- wcsncmp
- wmemcmp
- wcschr
- wcscspn
- wcpbrk
- wcsrchr
- wcssp
- wcsstr
- wcstok
- wmemchr
- wcslen
- wmemset
- NULL
- WCHAR_MAX
- WCHAR_MIN
- WEOF

The following entities should **NOT** have freestanding comments appended to them:

- struct tm
- fwprintf
- fwscanf
- swprintf

- swscanf
- vfwprintf
- vfwscanf
- vswprintf
- vswscanf
- vwprintf
- vwscanf
- wprintf
- wscanf
- fgetwc
- fgetws
- fputwc
- fputws
- fwide
- getwc
- getwchar
- putwc
- putwchar
- ungetwc
- wcstod
- wcstof
- wcstold
- wcstol
- wcstoll
- wcstoul
- wcstoull
- wcscoll
- wcsxfrm
- wcsftime
- btowc
- wctob
- mbsinit
- mbrlen
- mbrtowc
- wcrctomb
- mbsrtowcs
- wcsrtombs

Change in [\[cmath.syn\]](#)

Instructions to the editor:

Please append a *// freestanding* comment to the following entities:

- abs(int)
- abs(long int)
- abs(long long int)

Please append a *// freestanding deleted* comment to the following entities:

- abs(float)
- abs(double)
- abs(long double)

Change in [\[cinttypes.syn\]](#)

Instructions to the editor:

Please append a *// freestanding* comment to the following entities:

- imaxabs
- imaxdiv
- abs(intmax_t)
- div(intmax_t, intmax_t)