

Relaxing some `constexpr` restrictions

Document #: P2448R2
Date: 2022-01-27
Project: Programming Language C++
Audience: CWG
Reply-to: Barry Revzin
<barry.revzin@gmail.com>

Contents

- [1 Abstract](#)
- [2 Revision History](#)
- [3 Maybe Not Now, But Soon](#)
- [4 Sometimes Maybe, Sometimes Always](#)
- [5 Onwards to `constexpr` classes](#)
- [6 Getting rid of `constexpr-compatible`](#)
 - [6.1 Going Deeper](#)
 - [6.2 Going Deeper](#)
- [7 Proposal](#)
 - [7.1 Feature-test Macro](#)
- [8 References](#)

§ 1 Abstract

There are two rules about `constexpr` programming that make code ill-formed or ill-formed (no diagnostic required) when functions or function templates are marked `constexpr` that might never evaluate to a constant expression. But... so what if they don't? The goal of this paper is to stop diagnosing problems that don't exist.

§ 2 Revision History

Since [[P2448R1](#)], updated wording.

Since [[P2448R0](#)], CWG telecon pointed out that there were several other rules that could be stricken in the same theme. Updated wording.

A draft of the first revision of this paper was discussed in an [EWG telecon](#), where the following poll was taken:

send P2448 to electronic polling, targeting CWG for C++23.

SF	F	N	A	SA
10	8	1	0	0

This first published revision thus targets CWG.

§ 3 Maybe Not Now, But Soon

`constexpr` functions and function templates in C++ generally speaking mean *maybe constexpr*. Not all instantiations or evaluations must be invocable at compile time, it's just that there must be at least one set of function arguments in at least one instantiation that works.

And this isn't just generally speaking, this is enshrined as a rule: 9.2.6 [\[dcl.constexpr\]](#)/6:

For a constexpr function or constexpr constructor that is neither defaulted nor a template, if no argument values exist such that an invocation of the function or constructor could be an evaluated subexpression of a core constant expression, or, for a constructor, an evaluated subexpression of the initialization full-expression of some constant-initialized object ([basic.start.static]), the program is ill-formed, no diagnostic required.

Here is an example of a program that violates this rule:

```
void f(int& i) {
    i = 0;
}

constexpr void g(int& i) {
    f(i);
}
```

`g` unconditionally calls `f`, which is not a `constexpr` function, so there does not exist any invocation that would be a constant expression. Ill-formed, no diagnostic required. gcc and msvc both diagnose this.

Now, one could argue that this diagnosis is a good thing: that `constexpr` annotation on `g` makes no sense! It can't be a constant expression, so having that specifier on the function is misleading. Diagnosing this error helps the programmer realize that they were mistaken and they can take steps to change this. That seems compelling enough.

Consider instead this example:

```
#include <optional>

constexpr void h(std::optional<int>& o) {
    o.reset();
}
```

Here, `h` is the exact same kind of function as `g`: we have a function unconditionally calling another non-`constexpr` function. At least, that's true for C++17. It won't be true in C++23, and the answer for

C++20 depends on how vendors choose to implement [\[P2231R1\]](#). Here the answer depends: some functions can easily be `constexpr` in one standard but not in earlier ones.

Now, the sanctioned way to fix this code is to write:

```
#include <optional>

#if __cpp_lib_optional >= 202106
constexpr
#endif
void h(std::optional<int>& o) {
    o.reset();
}
```

This way, `h` will be `constexpr` when the appropriate library changes are made, allowing it to be. But... is this better?

I would argue it's not. The language rules for `constexpr` have expanded in every language standard since `constexpr` was introduced. Standard library support will always lag that. Third-party library support likely even more so. So the answer to the question "are there any arguments for which this function can be a constant expression?" can easily be No in C++N but Yes in C++N+1, for a wide variety of functions. Does forcing conscientious library authors to take painstaking care in conditionally marking function `constexpr` provide value to the ecosystem? I'm skeptical that it does.

Moreover, while it's possible to write the above for `std::optional`, I'm not sure that it's common for other library to provide macros that can be used to mark functions conditionally `constexpr` like this. Or, indeed, if there is even another such example. So if I'm a consumer of a library that might have some functionality `constexpr` in one version but more functionality `constexpr` in the next, I always have to lag.

Such diagnosis may have made sense in the C++11 days, but now that we're approaching C++23 where more and more things are `constexpr` and more and more libraries will mark more of their functions `constexpr` because they can be, it seems strictly better to just reserve diagnosing `constexpr` violations to the place where we already have to diagnose them: when you write code that *must* be evaluated at compile time.

Put differently, the current rule is there must be some tuple (function arguments, template arguments) for which a `constexpr` function invocation is a constant expression. But there's really another input here: (function arguments, template arguments, version). The version here might be the language version, it might be a bunch of library versions. Ultimately, it's a question of time. A function may not be `constexpr` today, but it may be `constexpr` soon. Diagnosing it as not being `constexpr` yet seems harmful to the question of evolving code.

§ 4 Sometimes Maybe, Sometimes Always

`constexpr` usually means *maybe* `constexpr`. But sometimes it actually means *always* `constexpr`. That case comes up with explicitly defaulted functions. From 9.5.2 [\[dcl.fct.def.default\]/3](#):

An explicitly-defaulted function that is not defined as deleted may be declared `constexpr` or `constexpr` only if it is `constexpr`-compatible ([special], [class.compare.default]). A function explicitly defaulted on its first declaration is implicitly inline ([dcl.inline]), and is implicitly `constexpr` ([dcl constexpr]) if it is `constexpr`-compatible.

Let's say I'm writing a wrapper class template that I'm intending to be usable during compile time:

```
template <typename T>
struct Wrapper {
    constexpr Wrapper() = default;
    constexpr Wrapper(Wrapper const&) = default;
    constexpr Wrapper(T const& t) : t(t) { }

    constexpr T get() const { return t; }
    constexpr bool operator==(Wrapper const&) const = default;
private:
    T t;
};
```

I might take the strategy of just marking every function `constexpr`. Both for consistency and also as a strategy to avoid forgetting to mark some functions `constexpr`.

But then I try to use it:

```
struct X {
    X();
    bool operator==(X const&) const;
};

Wrapper<X> x;
```

None of this code is trying to evaluate anything during constant evaluation, yet it is already ill-formed. gcc and clang already diagnose at this point. msvc and icc do not, but this rule is a mandatory diagnostic, so they are mistaken. Although, even here, none of the compilers care that I erroneously marked the default constructor `constexpr`. And none of them care that I erroneously marked the copy constructor `constexpr`. gcc and clang are only diagnosing `operator==` here (even though I'm not even using it).

But why do we even have this rule in the first place? Note that if I wrote my equality operator this way:

```
constexpr bool operator==(Wrapper const& rhs) const {
    return t == rhs.t;
}
```

That is, manually writing out what the defaulted version does, even with marking it `constexpr`, this code is perfectly valid C++ code. It doesn't matter that I'm marking this function `constexpr`, because in this context, the only requirement is that *some* instantiation can be a constant expression. But because I want to `= default` it, suddenly *every* instantiation has to be a constant expression?

What this means is that the correct way to write my wrapper type is:

```
template <typename T>
struct Wrapper {
```

```

Wrapper() = default;
Wrapper(Wrapper const&) = default;
constexpr Wrapper(T const& t) : t(t) { }

constexpr T get() const { return t; }
bool operator==(Wrapper const&) const = default;
private:
    T t;
};

```

So I have some functions marked `constexpr` and some not, but all of them are still usable during constant evaluation time (where appropriate based on `T`). The lack of consistency here is a bit jarring. `constexpr` functions should always be *maybe* `constexpr`, not *must be* `constexpr`.

§ 5 Onwards to constexpr classes

We have a proposal in front of us to allow annotating the entire class as being `constexpr`, to avoid all these extra annotations [[P2350R1](#)]. And that proposal currently runs into both issues:

```

template <typename T>
struct Wrapper constexpr {
    Wrapper() = default;
    Wrapper(Wrapper const&) = default;
    Wrapper(T const& t) : t(t) { }

    void reset() { t.reset(); }
    bool operator==(Wrapper const&) const = default;
private:
    std::optional<T> t;
};

```

Are all of these functions okay? I would argue that they *should* all be okay, but per the wording they're currently not.

I want `Wrapper` to be entirely `constexpr` where feasible. Some of those functions may not be `constexpr` for all types, and that's fine. Some of these functions may not be able to be `constexpr` in C++N but may be later, and I don't want to have to go back and either annotate against this (which I don't think P2350 even allows room for) or stop using this feature and go back to manually marking and even more annotations.

§ 6 Getting rid of constexpr-compatible

With the wording suggested in the first revision of this paper [[P2448R0](#)], functions (even defaulted special member functions) could be declared `constexpr` without this leading to either a diagnostic or leading to a program being ill-formed, no diagnostic required.

During the CWG telecon discussing that paper, it was brought up that we can go further. For instance, we have a term *constexpr-compatible*. Currently used by 9.5.2 [[dcl.fct.def.default](#)]/3:

- 3 An explicitly-defaulted function that is not defined as deleted may be declared `constexpr` or `constexpr` only if it is `constexpr-compatible` ([special], [class.compare.default]). A function explicitly defaulted on its first declaration is implicitly inline ([dcl.inline]), and is implicitly `constexpr` ([dcl.constexpr]) if it is `constexpr-compatible`.

Where special member functions are considered `constexpr-compatible` when:

— Comparisons (11.10.1 [class.compare.default]/4):

- 4 A defaulted comparison function is `constexpr-compatible` if it satisfies the requirements for a `constexpr` function ([dcl.constexpr]) and no overload resolution performed when determining whether to delete the function results in a usable candidate that is a non-`constexpr` function.

— Special members (11.4.4 [special]/8):

- 8 A defaulted special member function is `constexpr-compatible` if the corresponding implicitly-declared special member function would be a `constexpr` function.

The special member case depends on the kind of special member function:

- default/copy/move constructor: satisfy the requirements of a `constexpr` constructor (every constructor selected for each base and member is `constexpr`, no virtual base classes)
- copy/move assignment: class is literal, every assignment selected for each base and member is `constexpr`
- destructor: satisfies the requirements for `constexpr` destructor (every destructor selected for each base and member is `constexpr`, no virtual bases)

It would be, within the spirit of this paper, to significantly reduce these restrictions as follows. First, we can remove the restrictions on `constexpr` constructors and destructors (from 9.2.6 [dcl.constexpr]/4 and /5):

- 4 ~~The definition of a `constexpr` constructor whose *function-body* is not `= delete` shall additionally satisfy the following requirements:~~
- (4.1) ~~— for a non-delegating constructor, every constructor selected to initialize non-static data members and base-class subobjects shall be a `constexpr` constructor;~~
- (4.2) ~~— for a delegating constructor, the target constructor shall be a `constexpr` constructor.~~
- 5 ~~The definition of a `constexpr` destructor whose *function-body* is not `= delete` shall additionally satisfy the following requirement:~~
- (5.1) ~~— for every subobject of class type or (possibly multi-dimensional) array thereof, that class type shall have a `constexpr` destructor.~~

After this, if we allow a `constexpr` copy/move assignment even for non-literal classes, then we can basically make all defaulted functions `constexpr` except for constructors and destructors for types that have virtual base classes. This also means that we can remove the term *constexpr-compatible* since we

would no longer need to use it anywhere. That's a nice chunk of specification improvement, removing rules that nobody really needs.

§ 6.1 Going Deeper

We could go one step further and drop further uses of literal type in 9.2.6 [\[dcl.constexpr\]/3](#):

- 3 The definition of a constexpr function shall satisfy the following requirements:
- (3.1) — ~~its return type (if any) shall be a literal type;~~
 - (3.2) — ~~each of its parameter types shall be a literal type;~~
 - (3.3) — it shall not be a coroutine;
 - (3.4) — if the function is a constructor or destructor, its class shall not have any virtual base classes.

The first two sub-bullets are also very much in the spirit of this paper. A type could be not literal yet in C++N but could become literal in C++N+1, it would be nice if we could simply mark such functions `constexpr` regardless (as I've already noted the desire to do for copy/move assignment in the previous section).

§ 6.2 Going Deeper

Once we eliminate those two bullets, we only have two rules for the requirements of a constexpr function: not a coroutine, and not a constructor/destructor of a class that has virtual base classes. I'm not entirely sure why we need the latter rule either, but it could also be moved elsewhere – that is, the problem isn't *declaring* a constexpr constructor for a class with a virtual base, the problem is trying to *initialize* such a type during constant evaluation. Similar to how we removed the restriction on `try/catch` while still disallowing throwing.

This would actually allow further specification cleanup, since now we could just say that all implicit constructors are `constexpr`. But it's a much bigger step and I'm not sure that we should take it at this time.

§ 7 Proposal

Strike two bullets from 9.2.6 [\[dcl.constexpr\]/3](#), as well as paragraphs /4, /5, /6, their examples, and part of 7:

- 3 The definition of a constexpr function shall satisfy the following requirements:
- (3.1) — ~~its return type (if any) shall be a literal type;~~
 - (3.2) — ~~each of its parameter types shall be a literal type;~~
 - (3.3) — it shall not be a coroutine;

- (3.4) — if the function is a constructor or destructor, its class shall not have any virtual base classes.

[Example 2:

```
// ...
```

~~-end example]~~

- 4 ~~The definition of a constexpr constructor whose *function-body* is not `= delete` shall additionally satisfy the following requirements:~~
- (4.1) ~~— for a non-delegating constructor, every constructor selected to initialize non-static data members and base-class subobjects shall be a constexpr constructor;~~
- (4.2) ~~— for a delegating constructor, the target constructor shall be a constexpr constructor.~~

~~{Example 3:~~

```
struct Length {  
—constexpr explicit Length(int i = 0) : val(i) { }  
private:  
—int val;  
};
```

~~—end example]~~

- 5 ~~The definition of a constexpr destructor whose *function-body* is not `= delete` shall additionally satisfy the following requirement:~~
- (5.1) ~~— for every subobject of class type or (possibly multi-dimensional) array thereof, that class type shall have a constexpr destructor.~~
- 6 ~~For a constexpr function or constexpr constructor that is neither defaulted nor a template, if no argument values exist such that an invocation of the function or constructor could be an evaluated subexpression of a core constant expression, or, for a constructor, an evaluated subexpression of the initialization full-expression of some constant-initialized object ([basic.start.static]), the program is ill-formed, no diagnostic required.~~

~~{Example 4:~~

```
constexpr int f(bool b)  
—{ return b ? throw 0 : 0; } // OK  
constexpr int f() { return f(true); } // ill formed, no diagnostic  
required  
  
struct B {  
—constexpr B(int x) : i(0) { } // x is unused  
—int i;  
};  
  
int global;
```

```

struct D : B {
constexpr D() : B(global) {} // ill formed, no diagnostic
required
// lvalue to rvalue conversion on
non-constant global
};

— end example

```

- 7 If the instantiated template specialization of a constexpr function template or member function of a class template would fail to satisfy the requirements for a constexpr function, that specialization is still a constexpr function, even though a call to such a function cannot appear in a constant expression. ~~If no specialization of the template would satisfy the requirements for a constexpr function when considered as a non-template function, the template is ill-formed, no diagnostic required.~~
- 8 An invocation of a constexpr function in a given context produces the same result as an invocation of an equivalent non-constexpr function in the same context in all respects except that
- (8.1) — an invocation of a constexpr function can appear in a constant expression ([expr.const]) and
- (8.2) — copy elision is not performed in a constant expression ([class.copy.elision]).

[Note 3: Declaring a function constexpr can change whether an expression is a constant expression. This can indirectly cause calls to `std::is_constant_evaluated` within an invocation of the function to produce a different value. — end note]

[Note 4: It is possible to write a constexpr function for which no invocation satisfies the requirements of a core constant expression. - end note]

Adjust 9.5.2 [dcl.fct.def.default]/3 and fix the example (which is already wrong at the moment, since default-initializing an `int` during constant evaluation is ok):

- 3 ~~An explicitly defaulted function that is not defined as deleted may be declared constexpr or consteval only if it is constexpr-compatible ([special], [class.compare.default]).~~ A function explicitly defaulted on its first declaration is implicitly inline ([dcl.inline]), and is implicitly constexpr ([dcl constexpr]) if it ~~is constexpr-compatible~~ satisfies the requirements for a constexpr function.

- 4 [Example 1:

```

struct S {
-   constexpr S() = default; // error: implicit S() is not
    constexpr
    S(int a = 0) = default; // error: default argument
    void operator=(const S&) = default; // error: non-matching return type
    ~S() noexcept(false) = default; // OK, despite mismatched
    exception specification
private:
    int i;

```

```

    S(S&);                                // OK: private copy constructor
};
S::S(S&) = default;                       // OK: defines copy constructor

struct T {
    T();
    T(T &&) noexcept(false);
};
struct U {
    T t;
    U();
    U(U &&) noexcept = default;
};
U u1;
U u2 = static_cast<U&&>(u1);               // OK, calls std::terminate if T::
    T(T&&) throws

```

— *end example*]

Strike use of constexpr-compatible in 11.4.4 [\[special\]](#)/8:

- 8 ~~A defaulted special member function is *constexpr-compatible* if the corresponding implicitly-declared special member function would be a constexpr function.~~

Change the rule in 11.4.5.2 [\[class.default.ctor\]](#)/4 (the requirements for constexpr constructor are now just the requirements for constexpr function):

- 4 A default constructor that is defaulted and not defined as deleted is *implicitly defined* when it is odr-used ([term.odr.use]) to initialize an object of its class type ([intro.object]), when it is needed for constant evaluation ([expr.const]), or when it is explicitly defaulted after its first declaration. The implicitly-defined default constructor performs the set of initializations of the class that would be performed by a user-written default constructor for that class with no *ctor-initializer* ([class.base.init]) and an empty *compound-statement*. If that user-written default constructor would be ill-formed, the program is ill-formed. If that user-written default constructor would satisfy the requirements of a constexpr ~~constructor~~ **function** ([dcl.constexpr]), the implicitly-defined default constructor is **constexpr**. Before the defaulted default constructor for a class is implicitly defined, all the non-user-provided default constructors for its base classes and its non-static data members are implicitly defined.

And the same in 11.4.5.3 [\[class.copy.ctor\]](#)/12 for copy/move constructor:

- 12 A copy/move constructor that is defaulted and not defined as deleted is *implicitly defined* when it is odr-used ([term.odr.use]), when it is needed for constant evaluation ([expr.const]), or when it is explicitly defaulted after its first declaration. [Note 5: The copy/move constructor is implicitly defined even if the implementation elided its odr-use ([term.odr.use], [class.temporary]). — *end note*] If the implicitly-defined constructor would satisfy the requirements of a constexpr ~~constructor~~ **function** ([dcl.constexpr]), the implicitly-defined constructor is **constexpr**.

Mark assignment as being constexpr in 11.4.6 [\[class.copy.assign\]](#)/10:

- 10 A copy/move assignment operator for a class *X* that is defaulted and not defined as deleted is *implicitly defined* when it is odr-used ([term.odr.use]) (e.g., when it is selected by overload resolution to assign to an object of its class type), when it is needed for constant evaluation ([expr.const]), or when it is explicitly defaulted after its first declaration. The implicitly-defined copy/move assignment operator is `constexpr`. **if**

- (10.1) — ~~*X* is a literal type, and~~
- (10.2) — ~~the assignment operator selected to copy/move each direct base class subobject is a constexpr function, and~~
- (10.3) — ~~for each non-static data member of *X* that is of class type (or array thereof), the assignment operator selected to copy/move that member is a constexpr function.~~

Change the rule in 11.4.7 [\[class.dtor\]](#)/9 (the requirements for constexpr destructor are now just the requirements for constexpr function):

- 9 A defaulted destructor is a constexpr destructor if it satisfies the requirements for a constexpr ~~destructor~~ `function` ([dcl.constexpr]).

Strike use of constexpr-compatible in 11.10.1 [\[class.compare.default\]](#)/4:

- 4 ~~A defaulted comparison function is *constexpr-compatible* if it satisfies the requirements for a constexpr function ([dcl.constexpr]) and no overload resolution performed when determining whether to delete the function results in a usable candidate that is a non-constexpr function.~~

~~[Note 1: This includes the overload resolutions performed:~~

- (4.1) — ~~for an operator `<=>` whose return type is not `auto`, when determining whether a synthesized three-way comparison is defined,~~
- (4.2) — ~~for an operator `<=>` whose return type is `auto` or for an operator `==`, for a comparison between an element of the expanded list of subobjects and itself, or~~
- (4.3) — ~~for a secondary comparison operator `@`, for the expression `x @ y`.~~

~~—end note]~~

§ 7.1 Feature-test Macro

Update the value of `__cpp_constexpr` in 15.11 [\[cpp.predefined\]](#):

```
- __cpp_constexpr 202110L
+ __cpp_constexpr 2022XXL
```

§ 8 References

[P2231R1] Barry Revzin. 2021-02-12. Add further constexpr support for optional/variant.

<https://wg21.link/p2231r1>

[P2350R1] Andreas Fertig. 2021-07-15. constexpr class.

<https://wg21.link/p2350r1>

[P2448R0] Barry Revzin. 2021-10-14. Relaxing some constexpr restrictions.

<https://wg21.link/p2448r0>

[P2448R1] Barry Revzin. 2022-01-16. Relaxing some constexpr restrictions.

<https://wg21.link/p2448r1>