

P2474R1

views :: repeat

Published Proposal, 2022-01-18

Author:

[Michał Dominiak](#)

Project:

ISO/IEC JTC1/SC22/WG21 14882: Programming Language — C++

Audience:

SG9, LEWG

Table of Contents

1	Introduction
2	Changelog
2.1	R1
2.2	R0
3	Motivation
4	Design
4.1	<code>repeat_view</code>
4.2	<code>views::repeat</code>
4.3	Move-only types and borrowed range
4.4	Category
4.5	Other properties
4.6	<code>views::take</code> and <code>views::drop</code> changes
5	Implementation experience
6	Wording

- 6.1 Addition to `<ranges>`
- 6.2 Repeat view [range.repeat]
 - 6.2.1 Overview [range.repeat.overview]
 - 6.2.2 Class template `repeat_view` [range.repeat.view]
 - 6.2.3 Class template `repeat_view::iterator` [range.repeat.iterator]
- 6.3 Take view [range.take]
 - 6.3.1 Overview [range.take.overview]
- 6.4 Drop view [range.drop]
 - 6.4.1 Overview [range.drop.overview]
- 6.5 Feature-test macro

References

Informative References

§ 1. Introduction

This paper proposes a new range factory, `views::repeat`, which creates a range that repeats the same value either infinitely, or a specified number of times.

§ 2. Changelog

§ 2.1. R1

Elaborate on only having a single factory.

Add the missing Motivation contents.

Drop a bunch of the comparison operators of the iterator type in favor of just having `operator==` and `operator<=>`, since all we are comparing are integer like types. (Thanks to Barry Revzin for pointing out that we can, actually, do that here!)

As a result of SG-9's review of this paper, the constructor overload set of `repeat_view` has been reduced by:

- removing the constructors from a `repeat_view` of a different bound that were only used by `views::take` and `views::drop`, which now use the member of the view directly; and

- replacing the two `in_place_t` overloads with a single `piecewise_construct_t` constructor, to make in-place construction be not ambiguous when a bound that can serve as the first constructor argument to the value type is passed in.

Various fixes of issues found after publishing an R0:

- typos (`iterator_catetogy` etc.);
- `size` was missing a `const` qualifier;
- the definition of the view was using `movable-box` instead of `copyable-box`;
- removed the spurious constraint from the default constructor of the iterator type;
- replaced `&foo` with `addressof(foo)`;
- made the specification of `views::take` and `views::drop` reflect SG-9 review comments;
- added a deduction guide;
- added a constraint that the value type of the range must be an unqualified object type.

§ 2.2. R0

Initial revision.

§ 3. Motivation

Similarly to `views::single`, this range factory can be used to lift values into ranges; however, where `views::single` creates a range of always a single element, `views::repeat` allows to repeat that value either a specified number of times, or infinitely. This is very useful in cases such as: trying to insert a sequence of fill values into a list of ranges being joined together (see [the calendar example from Range-v3](#) for this use), or when trying to add an additional element that stays constant to views such as `views::zip` or `views::cartesian_product`.

§ 4. Design

This paper proposes the following additions to the Ranges library:

1. A new view type, `repeat_view`, a view which repeatedly produces the same value, based on the design of `iota_view`.

2. A new customization point object, `views::repeat`, which returns a `repeat_view`, based on the design of `views::iota`.
3. An extension for the semantics of `views::take` and `views::drop`, to make them return bounded `repeat_view` when passed a `repeat_view`.

[P2214R1] suggests that `repeat` and `repeat_n` could be implemented in terms of `generate` and `generate_n`, however it also points out that the implementation of `generate` in range-v3 contains a data race. To avoid this issue, this paper defines `repeat_view` similarly to how `iota_view` is defined, which avoids the data race in `generate`. (The data race manifests in the implementation of `generate` filling its value cache inside a `const` function. There's a number of ways to resolve this issue, but the author would rather not make solving it a prerequisite for `views::repeat`.)

This paper proposes to only have a single factory, `repeat`. Range-v3 has separate factories for `repeat` and `repeat_n`, but we believe that a single CPO, overloaded similarly to `views::iota`, is sufficient for the standard library, because the uses of the second argument are properly constrained to be integer like, and because users probably already have familiarity with this pattern from `iota`.

§ 4.1. `repeat_view`

`repeat_view` is a class template that's parametrized on the type of the value it produces, and an additional parameter which controls whether it is bounded or not. This view is a common range and a sized range when bounded. It is always a random access range.

§ 4.2. `views::repeat`

`views::repeat` is a customization point object which returns an unbounded `repeat_view` when passed just a value, and a bounded `repeat_view` when passed a value and a bound.

§ 4.3. Move-only types and borrowed range

Currently, there is no support for move-only types to be stored inside views; as is, this impacts `views::single` (which requires the value type to be copyable), and the `transform_view` family of adaptors (which requires the transform function to be copyable). The author proposes that this paper follow the requirements in the other adaptors, but also separately proposes to relax these requirements for both the existing adaptors and for the proposed `views::repeat` in [P2494](#).

This paper also proposes that iterators to `repeat_view` do not store copies of the values. There's several reasons for this. For one, unlike the case of `iota_view`, all the iterators to a `repeat_view` always refer to the same value; copying the values all over to produce the same one from every iterator does not seem ideal. For another, if the iterators stored copies, the relaxation of the concept requirements mentioned above would not be possible. Finally, there is a precedent for this behavior: `repeat_view` in Range-v3 does not copy the values into iterators, even though it still requires that the values be copyable.

This, however, means that `repeat_view` is **not** a borrowed range. This is a tradeoff, but the author believes that it is a worthy one.

§ 4.4. Category

`repeat_view` is always random access, because the variables being incremented while iterating are always integers or integer-like classes.

§ 4.5. Other properties

`repeat_view` is sized when a bound other than `unreachable_sentinel_t` is provided.

`repeat_view` is common when it is sized.

§ 4.6. `views::take` and `views::drop` changes

`views::take` and `views::drop` are specialized for a sized `iota_view`, in which case they return an `iota_view` back. They require that the `iota_view` be sized, because the bound type for `iota_view` can be an arbitrary type, so it is possible to have an `iota_view` that is random access and finite, but for which there exists no way to obtain the size. In such a case, if we attempted to blindly increment the iterators by the value of the second argument of either `take` or `drop`, we could inadvertently reach an iterator that seems valid, but is in fact past the end of the range.

For `repeat_view`, this situation is much clearer: the value is never modified, and the bound is either `unreachable_sentinel_t`, or an integer like type. In both cases we know that we can reuse the value, and set the bound to the appropriate value. Therefore, this paper proposes to extend the specializations of `views::take` and `views::drop` for `repeat_view`, without requiring that it must be sized.

§ 5. Implementation experience

Range-v3 implements both the [bounded](#) and the [unbounded](#) variants of [repeat](#), but exposes them as separate functions and types. The author believes that this facility should instead follow the design of [views::iota](#). The two versions of [views::repeat](#) in Range-v3 differ only by the existence of the size field in the view itself, by the existence of the [size](#) function, and by the variant of the [view_facade](#) base class they inherit from.

§ 6. Wording

§ 6.1. Addition to `<ranges>`

Add the following to 24.2 [range.syn], Header `<ranges>` synopsis:

```
namespace std::ranges {
    // ...

    namespace views { inline constexpr unspecified iota = unspecified; }

    // [range.repeat], repeat view
    template<copy_constructible W, semiregular Bound = unreachable_sentinel_t>
    requires (is_object_v<W> && same_as<W, remove_cv_t<W>>
        && (is_integer_like<Bound> || same_as<Bound, unreachable_sentinel_t>))
    class repeat_view;

    namespace views { inline constexpr unspecified repeat = unspecified; }

    // [range.istream], istream view

    // ...
}
```

§ 6.2. Repeat view [range.repeat]

Add a new section, Repeat view [range.repeat], after Iota view [range.iota].

§ 6.2.1. Overview [range.repeat.overview]

1. `repeat_view` generates a sequence of elements by repeatedly producing the same value.
2. The name `views::repeat` denotes a customization point object ([customization.point.object]). Given subexpressions `E` and `F`, the expressions `views::repeat(E)` and `views::repeat(E, F)` are expression-equivalent to `repeat_view(E)` and `repeat_view(E, F)`, respectively.
3. [Example:

```
for (int i : views::repeat(17, 4))
    cout << i << ' '; // prints: 17 17 17 17
```

-- end example]

§ 6.2.2. Class template `repeat_view` [range.repeat.view]

```
namespace std::ranges {
    template<copy_constructible W, semiregular Bound = unreachable_sentinel_t>
        requires (is_object_v<W> && same_as<W, remove_cv_t<W>>
            && (is_integer_like<Bound> || same_as<Bound, unreachable_sentinel_t>))
        class repeat_view : public view_interface<repeat_view<W, Bound>> {
        private:
            // [range.repeat.iterator], class range_view::iterator
            struct iterator;

            copyable_box<W> value_ = W(); // exposition only, see [range.copy.wrap]
            Bound bound_ = Bound(); // exposition only

        public:
            repeat_view() requires default_initializable<W> = default;

            constexpr explicit repeat_view(const W & value, Bound bound = Bound());
            constexpr explicit repeat_view(W && value, Bound bound = Bound());
            template<class... WArgs, class... BoundArgs>
                requires constructible_from<W, WArgs...>
                    && constructible_from<Bound, BoundArgs...>
            constexpr explicit repeat_view(piecewise_construct_t,
                tuple<WArgs...> value_args, tuple<BoundArgs...> bound_args = tuple<>())

            constexpr iterator begin() const;
            constexpr iterator end() const requires (!same_as<Bound, unreachable_se
```

```
constexpr unreachable_sentinel_t end() const;

constexpr auto size() const requires (!same_as<Bound, unreachable_sentinel_t>);

template<class W, class Bound>
repeat_view(W, Bound) -> repeat_view<W, Bound>;
}
```

```
constexpr explicit repeat_view(const W & value, Bound bound = Bound());
```

1. *Effects*: Initializes `value_` with `value` and `bound_` with `bound`.

```
constexpr explicit repeat_view(W && value, Bound bound = Bound());
```

2. *Effects*: Initializes `value_` with `std::move(value)` and `bound_` with `bound`.

```
template<class... WArgs, class... BoundArgs>
requires constructible_from<W, WArgs...>
&& constructible_from<Bound, BoundArgs...>
constexpr explicit repeat_view(piecewise_construct_t,
tuple value_args, tuple bound_args = tuple<>{});
```

3. *Effects*: Initializes `value_` with arguments of types `WArgs...` obtained by forwarding the elements of `value_args` and initializes `bound_` with arguments of types `BoundArgs...` obtained by forwarding the elements of `bound_args`. (Here, forwarding an element `x` of type `U` within a tuple object means calling `std::forward<U>(x)`.)

```
constexpr iterator begin() const;
```

4. *Effects*: Equivalent to `return iterator{addressof(*value_)};`

```
constexpr iterator end() const requires (!same_as<Bound, unreachable_sentinel_t>);
```


5. *Effects*: Equivalent to `return iterator{addressof(*value), bound_};`

```
constexpr unreachable_sentinel_t end() const;
```

6. *Effects*: Equivalent to `return unreachable_sentinel;`

```
constexpr auto size() const requires (!same_as<Bound, unreachable_sentinel_
```

7. *Effects*: Equivalent to `return to-unsigned-like(bound_);`

§ 6.2.3. Class template `repeat_view::iterator` [range.repeat.iterator]

```
namespace std::ranges {
    template<copy_constructible W, semiregular Bound = unreachable_sentinel_t
        requires is-integer-like<Bound> || same_as<Bound, unreachable_sentinel_t>
    class repeat_view<W, Bound>::iterator {
    private:
        using index_type = // exposition only
            conditional_t<same_as<Bound, unreachable_sentinel_t>,
                ptrdiff_t,
                Bound
            >;
        const W * value_; // exposition only
        index_type current_ = index_type(); // exposition only

    public:
        using iterator_concept = random_access_iterator_tag;
        using iterator_category = random_access_iterator_tag;
        using value_type = W;
        using reference = const W &;
        using difference = see below;

        iterator() = default;

        constexpr explicit iterator(const W * value, index_type b = index_type())
            : value_(value), current_(b) {}

        constexpr const W & operator*() const noexcept;

        constexpr iterator& operator++();
```

```

constexpr iterator operator++(int);

constexpr iterator& operator--();
constexpr iterator operator--(int);

constexpr iterator& operator+=(difference_type n);
constexpr iterator& operator-=(difference_type n);
constexpr const W & operator[](difference_type n) const noexcept;

friend constexpr bool operator==(const iterator& x, const iterator& y);
friend constexpr auto operator<=>(const iterator& x, const iterator& y)
    = default;

friend constexpr iterator operator+(iterator i, difference_type n);
friend constexpr iterator operator+(difference_type n, iterator i);

friend constexpr iterator operator-(iterator i, difference_type n);
friend constexpr difference_type operator-(const iterator& x, const iterator& y);
};
}

```

```

constexpr explicit iterator(const W * value, index_type b = index_type());

```

1. *Effects*: Initializes `value_` with `value` and `bound_` with `b`.

```

constexpr const W & operator*() const noexcept;

```

2. *Effects*: Equivalent to `return *value_;`

```

constexpr iterator& operator++();

```

3. *Effects*: Equivalent to:

```

++current_;
return *this;

```

```

constexpr iterator operator++(int);

```

4. *Effects*: Equivalent to:

```
auto tmp = *this;  
++*this;  
return tmp;
```

```
constexpr iterator& operator--();
```

5. *Effects*: Equivalent to:

```
--current_;  
return *this;
```

```
constexpr iterator operator--(int);
```

6. *Effects*: Equivalent to:

```
auto tmp = *this;  
--*this;  
return tmp;
```

```
constexpr iterator& operator+=(difference_type n);
```

7. *Effects*: Equivalent to:

```
current_ += n;  
return *this;
```

```
constexpr iterator& operator-=(difference_type n);
```

8. *Effects*: Equivalent to:

```
current_ -= n;  
return *this;
```

```
constexpr const W & operator[](difference_type n) const noexcept;
```

9. *Effects*: Equivalent to `return *value_;`

```
friend constexpr bool operator==(const iterator& x, const iterator& y);
```

10. *Effects*: Equivalent to `x.current_ == y.current_;`

```
friend constexpr auto operator<=>(const iterator& x, const iterator& y);
```

11. *Effects*: Equivalent to `x.current <=> y.current_;`

```
friend constexpr iterator operator+(iterator i, difference_type n);  
friend constexpr iterator operator+(difference_type n, iterator i);
```

12. *Effects*: Equivalent to `return iterator{i.value_, i.current_ + n};`

```
friend constexpr iterator operator-(iterator i, difference_type n);
```

13. *Effects*: Equivalent to `return iterator{i.value_, i.current_ - n};`

```
friend constexpr difference_type operator-(const iterator& x, const iterator& y);
```

14. *Effects*: Equivalent to `return x.current_ - y.current_;`

§ 6.3. Take view [range.take]

§ 6.3.1. Overview [range.take.overview]

Modify Overview [range.take.overview] paragraph 2 as follows:

2. The name `views::take` denotes a range adaptor object (`[range.adaptor.object]`). Let `E` and `F` be expressions, let `T` be `remove_cvref_t<decltype((E))>`, and let `D` be `range_difference_t<decltype((E))>`. If `decltype((F))` does not model `convertible_to<D>`, `views::take(E, F)` is ill-formed. Otherwise, the expression `views::take(E, F)` is expression-equivalent to:

1. If `T` is a specialization of `ranges::empty_view` (`[range.empty.view]`), then `((void) F, decay-copy(E))`, except that the evaluations of `E` and `F` are indeterminately sequenced.
2. Otherwise, if `T` models `random_access_range` and `sized_range` and is a specialization of `span` (`[views.span]`), `basic_string_view` (`[string.view]`), or `ranges::subrange` (`[range.subrange]`), then `U(ranges::begin(E), ranges::begin(E) + std::min<D>(ranges::distance(E), F))`, except that `E` is evaluated only once, where `U` is a type determined as follows:
 1. if `T` is a specialization of `span`, then `U` is `span<typename T::element_type>`;
 2. otherwise, if `T` is a specialization of `basic_string_view`, then `U` is `T`;
 3. otherwise, `T` is a specialization of `ranges::subrange`, and `U` is `ranges::subrange<iterator_t<T>>`;
3. Otherwise, if `T` is a specialization of `ranges::iota_view` (`[range.iota.view]`) that models `random_access_range` and `sized_range`, then `ranges::iota_view(*ranges::begin(E), *(ranges::begin(E) + std::min<D>(ranges::distance(E), F)))`, except that `E` is evaluated only once;
4. Otherwise, if `T` is a specialization of `ranges::repeat_view` (`[range.repeat.view]`):
 1. if `T` models `sized_range`, then `ranges::repeat_view<range_value_t<T>, D>(*E.value_, std::min<D>(ranges::distance(E), F))`, except that `E` is evaluated only once;
 2. otherwise, `ranges::repeat_view<range_value_t<T>, D>(E, F)`;
5. Otherwise, `ranges::take_view(E, F)`.

§ 6.4. Drop view `[range.drop]`

§ 6.4.1. Overview `[range.drop.overview]`

Modify Overview `[range.drop.overview]` paragraph 2 as follows:

2. The name `views::drop` denotes a range adaptor object (`[range.adaptor.object]`). Let `E` and `F` be expressions, let `T` be `remove_cvref_t<decltype((E))>`, and let `D` be `range_difference_t<decltype((E))>`. If `decltype((F))` does not model `convertible_to<D>`, `views::drop(E, F)` is ill-formed. Otherwise, the expression `views::drop(E, F)` is expression-equivalent to:

1. If `T` is a specialization of `ranges::empty_view` (`[range.empty.view]`), then `((void) F, decay-copy(E))`, except that the evaluations of `E` and `F` are indeterminately sequenced.
2. Otherwise, if `T` models `random_access_range` and `sized_range` and is
 1. a specialization of `span` (`[views.span]`),
 2. a specialization of `basic_string_view` (`[string.view]`),
 3. a specialization of `ranges::iota_view` (`[range.iota.view]`), or
 4. a specialization of `ranges::subrange` (`[range.subrange]`) where `T::StoreSize` is `false`,

then `U(ranges::begin(E) + std::min<D>(ranges::distance(E), F), ranges::end(E))`, except that `E` is evaluated only once, where `U` is `span<typename T::element_type>` if `T` is a specialization of `span` and `T` otherwise.

3. Otherwise, if `T` is a specialization of `ranges::subrange` (`[range.subrange]`) that models `random_access_range` and `sized_range`, then `T(ranges::begin(E) + std::min<D>(ranges::distance(E), F), ranges::end(E), to-unsigned-like(ranges::distance(E) - std::min<D>(ranges::distance(E), F)))`, except that `E` and `F` are each evaluated only once.

4. Otherwise, if `T` is a specialization of `ranges::repeat_view` (`[range.repeat.view]`):

1. if `T` models `sized_range`, then `ranges::repeat_view<range_value_t<T>, D>(*E.value_, ranges::distance(E) - std::min<D>(ranges::distance(E), F))`;
2. otherwise, `((void) F, decay-copy(E))`, except that the evaluations of `E` and `F` are indeterminately sequenced.

4. Otherwise, `ranges::drop_view(E, F)`.

§ 6.5. Feature-test macro

Add the following macro definition to Header synopsis [version.syn], with the value selected by the editor to reflect the date of adoption of this paper:

```
#define __cpp_lib_ranges_repeat 20XXXXL // also in <ranges>
```

§ References

§ Informative References

[P2214R1]

Barry Revzin, Conor Hoekstra, Tim Song. [A Plan for C++23 Ranges](https://wg21.link/p2214r1). 14 September 2021. URL: <https://wg21.link/p2214r1>