

P2527R1

`std::variant_alternative_index` and `std::tuple_element_index`

Published Proposal, 2022-09-30

This version:

<http://wg21.link/P2527R1>

Author:

[Alex Christensen](#) (Apple)

Audience:

SG18

Project:

ISO/IEC JTC1/SC22/WG21 14882: Programming Language — C++

Source:

<https://github.com/achristensen07/papers/blob/master/source/P2527r1.bs>

Abstract

A description of `std::variant_alternative_index`, `std::variant_alternative_index_v`, `std::tuple_element_index`, and `std::tuple_element_index_v` which polish use of `std::variant` and `std::tuple` in C++.

Table of Contents

- 1 Introduction
- 2 Revision History
- 3 Motivating Use Case: Migrating C code to use `std::variant`
- 4 Motivating Use Case: Simple object serialization

5 Motivation For `std::tuple_element_index_v`

6 Addition to `variant.helper` section

7 Addition to `tuple.helper` section

8 Ill-formed use

9 Possible implementation

§ 1. Introduction

`std::variant` and `std::tuple` seem have a missing piece. `std::get` and `std::get_if` can be used with an index or with a type. There is already a way to get a type from an index (`std::variant_alternative` and `std::tuple_element`) but there is no way to get an index from a type. This adds such a mechanism.

§ 2. Revision History

- r0 Initial version, discussed in the C++ Library Evolution Working Group email list June 27, 2022 through July 13, 2022. This version of the paper was also incorrectly dated 2021-01-18 instead of 2022-01-18.
- r1 Responded to LEWG email feedback by adding `std::tuple_element_index_v`, inheriting from `std::integral_constant`, clarifying what happens with structs and classes that inherit from `std::tuple` and `std::variant`, clarifying what happens with const template parameters, adding spec wording, and possible implementation.

§ 3. Motivating Use Case: Migrating C code to use `std::variant`

Consider the following C program with a unit test:

```
#include <assert.h>

struct NumberStorage {
    enum Type { TYPE_INT, TYPE_DOUBLE } type;
    union {
```

```

        int i;
        double d;
    };
};

struct NumberStorage packageInteger(int i) {
    struct NumberStorage packaged;
    packaged.type = TYPE_INT;
    packaged.i = i;
    return packaged;
}

int main() {
    struct NumberStorage i = packageInteger(5);
    assert(i.type == TYPE_INT);
}

```

In order to migrate it from using a `union` to using a `std::variant` one of the cleanest solutions looks something like this:

```

#include <assert.h>
#include <variant>

// Dear future developers: VariantIndex and NumberStorage must stay in sync
// If you reorder or add to one, you must do the same to the other.
enum class VariantIndex : std::size_t { Int, Double };
using NumberStorage = std::variant<int, double>;

NumberStorage packageInteger(int i) {
    return { i };
}

int main() {
    auto i = packageInteger(5);
    auto expectedIndex = static_cast<std::size_t>(VariantIndex::Int);
    assert(i.index() == expectedIndex);
}

```

Instead, using `std::variant_alternative_index_v` would make the code look cleaner and be easier to maintain:

```
#include <assert.h>
#include <variant>

using NumberStorage = std::variant<int, double>;

NumberStorage packageInteger(int i) {
    return { i };
}

int main() {
    auto i = packageInteger(5);
    auto expectedIndex = std::variant_alternative_index_v<int, NumberStorage>;
    assert(i.index() == expectedIndex);
}
```

§ 4. Motivating Use Case: Simple object serialization

Another place where `std::variant_alternative_index_v` is useful is when we have an index from a source such as deserialization and we want to decide what type it represents without using any magic numbers:

```
struct Reset { };
struct Close { };
struct RunCommand { std::string command; };

using Action = std::variant<Reset, Close, RunCommand>;

void serializeAction(const Action& action, std::vector<uint8_t>& buffer)
{
    buffer.push_back(action.index());
    if (auto* runCommand = std::get_if<RunCommand>(&action))
        serializeString(runCommand->command, buffer);
}

std::optional<Action> deserializeAction(std::span<const uint8_t> source)
{
}
```

```

    if (!source.size())
        return std::nullopt;

    switch (source[0]) {
    case std::variant_alternative_index_v<Reset, Action>:
        return Reset { };
    case std::variant_alternative_index_v<Close, Action>:
        return Close { };
    case std::variant_alternative_index_v<RunCommand, Action>:
        return RunCommand { deserializeString(source.subspan(1)) };
    }

    return std::nullopt;
}

```

Like the other motivating use case, this could be done with an enum class or `#define RESET_INDEX 0` etc., but this is nicer and references the variant instead of requiring parallel metadata. This was the use case that motivated an implementation in [WebKit](#).

§ 5. Motivation For `std::tuple_element_index_v`

Feedback from r0 indicated that while adding `std::variant_alternative_index_v` for variants, it would be symmetric to add `std::tuple_element_index_v` for tuples.

§ 6. Addition to `variant.helper` section

```

template<class T, class Variant> struct variant_alternative_index;

```

All specializations of `variant_alternative_index` meet the `Cpp17UnaryTypeTrait` requirements (21.3.2) with a base characteristic of `integral_constant<size_t, N>` for some `N`.

```

template<class T, class Variant> struct variant_alternative_index<T, const

```

Let VAI denote `variant_alternative_index<T, Variant>` of the cv-unqualified type T. Then each specialization of the template meets the Cpp17UnaryTypeTrait requirements (21.3.2) with a base characteristic of `integral_constant<size_t, VAI::value>`.

```
template<class T, class... Types> struct variant_alternative_index<T, variant<Types>
    : integral_constant<size_t, N> { };
```

Mandates: The type T occurs exactly once in Types.

N is the zero-based index of T in Types.

```
template<class Type, class Variant> inline constexpr size_t variant_alternative_index<Type, Variant>::value;
```

§ 7. Addition to tuple.helper section

```
template<class T, class Tuple> struct tuple_element_index;
```

All specializations of `tuple_element_index` meet the Cpp17UnaryTypeTrait requirements (21.3.2) with a base characteristic of `integral_constant<size_t, N>` for some N.

```
template<class T, class Tuple> struct tuple_element_index<T, const Tuple>;
```

Let TEI denote `tuple_element_index<T, Tuple>` of the cv-unqualified type T. Then each specialization of the template meets the Cpp17UnaryTypeTrait requirements (21.3.2) with a base characteristic of `integral_constant<size_t, TEI::value>`.

```
template<class T, class... Types> struct tuple_element_index<T, tuple<Types>
    : integral_constant<size_t, N> { };
```

Mandates: The type T occurs exactly once in Types.

N is the zero-based index of T in Types.

```
template<class Type, class Tuple> inline constexpr size_t tuple_element_index_v  
    = tuple_element_index<Type, Tuple>::value;
```

§ 8. Ill-formed use

Like the versions of `std::get` that take a type, the program must be ill formed if the type is not a unique element in the types of the `std::variant` or `std::tuple` such as in these four cases:

```
using Example1 = std::variant<int, double, double>;  
auto ambiguous1 = std::variant_alternative_index_v<double, Example1>;  
  
using Example2 = std::variant<int, double>;  
auto missing2 = std::variant_alternative_index_v<float, Example2>;  
  
using Example3 = std::tuple<int, double, double>;  
auto ambiguous3 = std::tuple_element_index_v<double, Example3>;  
  
using Example4 = std::tuple<int, double>;  
auto missing4 = std::tuple_element_index_v<float, Example4>;
```

If the constness of the searched-for type does not match the constness of the type in the `std::variant` or `std::tuple` then there should be a compiler error. This is also the case with `std::get`.

```
using Example5 = std::variant<int, double>;  
auto constDoesNotMatch5 = std::variant_alternative_index_v<const int, Example5>;  
  
using Example6 = std::tuple<int, double>;  
auto constDoesNotMatch6 = std::tuple_element_index_v<const int, Example6>;
```

Like `std::variant_size` and `std::tuple_size` there should be a compiler error if `std::variant_alternative_index` or `std::tuple_element_index_v` are used with classes

or structs that are not `std::variant`s or `std::tuple`s, respectively, including classes or structs that inherit from `std::variant` or `std::tuple`.

```
class Example7 : public std::variant<int, double> { };
auto nonVariantParameter7 = std::variant_alternative_index_v<int, Example7>;
auto nonVariantParameter8 = std::variant_alternative_index_v<int, Example4>;

class Example9 : public std::tuple<int, double> { };
auto nonTupleParameter9 = std::tuple_element_index_v<int, Example9>;
auto nonTupleParameter10 = std::tuple_element_index_v<int, Example2>;
```

§ 9. Possible implementation

```
namespace std {

namespace detail {

template<size_t, class, class> struct alternative_index_helper;

template<size_t index, class Type, class T>
struct alternative_index_helper<index, Type, variant<T>> {
    static constexpr size_t count = is_same_v<Type, T>;
    static constexpr size_t value = index;
};

template<size_t index, class Type, class T, class... Types>
struct alternative_index_helper<index, Type, variant<T, Types...>> {
    static constexpr size_t count = is_same_v<Type, T> + alternative_index_
    static constexpr size_t value = is_same_v<Type, T> ? index : alternativ
};

template<size_t, class, class> struct tuple_element_helper;

template<size_t index, class Type, class T>
struct tuple_element_helper<index, Type, tuple<T>> {
    static constexpr size_t count = is_same_v<Type, T>;
    static constexpr size_t value = index;
};
```



```

template<size_t index, class Type, class T, class... Types>
struct tuple_element_helper<index, Type, tuple<T, Types...>> {
    static constexpr size_t count = is_same_v<Type, T> + tuple_element_help
    static constexpr size_t value = is_same_v<Type, T> ? index : tuple_elem
};

} // namespace detail

template<class T, class Variant> struct variant_alternative_index;

template<class T, class Variant> struct variant_alternative_index<T, const
    : variant_alternative_index<T, Variant> { };

template<class T, class... Types> struct variant_alternative_index<T, varia
    : integral_constant<size_t, detail::alternative_index_helper<0, T, vari
    static_assert(detail::alternative_index_helper<0, T, remove_cv_t<variari
};

template<class T, class Variant> inline constexpr size_t variant_alternativ

template<class T, class Tuple> struct tuple_element_index;

template<class T, class Tuple> struct tuple_element_index<T, const Tuple> :

template<class T, class Tuple> struct tuple_element_index
    : integral_constant<size_t, detail::tuple_element_helper<0, T, remove_c
    static_assert(detail::tuple_element_helper<0, T, remove_cv_t<Tuple>>::c
};

template<class T, class Tuple> inline constexpr size_t tuple_element_index_

} // namespace std

```