

P2663R4

Interleaved complex values support in `std::simd`

Published Proposal, 2023-10-13

This version:

<http://wg21.link/P2663R4.pdf>

Authors:

[Daniel Towner](#) (Intel)

[Ruslan Arutyunyan](#) (Intel)

Audience:

LEWG

Project:

ISO/IEC 14882 Programming Languages — C++, ISO/IEC JTC1/SC22/WG21

Abstract

The paper proposes to support interleaved complex values in `std::simd`

Table of Contents

- 1 Motivation
- 2 Background
- 3 Overview of updates required to support `std::complex` `simd` elements
 - 3.1 `std::simd` base modifications
 - 3.2 Additional complex methods for `std::simd`
 - 3.2.1 Constructors
 - 3.2.2 Real/imag accessors

3.3 Additional free functions

3.3.1 Alternative design for `real` and `imag`

4 Implementation experience

5 Wording

5.1 Modify [`simd.general`]

5.2 Modify [`simd.summary`]

5.3 Modify [`simd.ctor`]

5.4 Add new section [`simd.complex_accessors`]

5.5 Add new section [`simd.complex_math`]

6 Polls

6.1 Kona 2022 SG1 polls

7 Revision History

References

Informative References

§ 1. Motivation

ISO/IEC 19570:2018 (1) introduced data-parallel types to the C++ Extensions for Parallelism TS. [\[P1928R6\]](#) is proposing to make that a part of C++ IS. Intel supports the concept of a standard interface to SIMD instruction capabilities and we have made extra suggestions for other APIs and facilities for `std::simd` in document [\[P2638R0\]](#). One of the extra features we suggested was the ability to work with interleaved complex values. It is now becoming common for processor instruction sets to include native support for these operations (e.g., Intel AVX512-FP16, ARM Neon) and we think that allowing `std::simd` to directly access these features is advantageous.


This document gives more details about the motivation for supporting complex-values, the different storage and implementation alternatives, and some suggestions for a suitable API.

§ 2. Background


Complex-valued mathematics is widely used in scientific computing and many types of engineering, with applications including physical simulations, wireless signal processing, media processing, and

much more besides. C++ already supports complex-valued operations using the `std::complex` template available in the `<complex>` header file and C supports complex values by using the `_Complex` keyword. C++ supports floating point elements, including `std::float16` (C++23), `float`, `double` or `long double`, though in practice compilers permit integer complex values too. Such is the importance of interleaved complex values that some mainstream processor vendors now provide native hardware support for complex-value SIMD instructions (e.g., Intel AVX512-FP16, ARM Neon v8.3).

Any complex value is represented as a pair of values, one for the real component and one for the imaginary component. In C and C++ a complex value is a pair of two values of the appropriate data type, allocated to a single unit containing 2 elements which are stored contiguously. This is illustrated in the figure below. This storage layout is used in other languages too, allowing for easy data interchange between software written in different languages, or with comparable user-defined types. This format may also be used for hardware accelerators or interfaces too:



When many complex values are stored together, such as in a C-style array, a C++ `std::array` or a C++ `std::vector`, then the real and imaginary elements are interleaved in memory:



Many applications, libraries, programming languages and interfaces between diverse software and hardware components will store data in this interleaved format, and it is treated as the default layout for blocks of complex-valued data. To improve the compute efficiency of this data format both Intel and ARM have introduced native hardware support to allow efficient SIMD operations to be performed in this data format without having to resort to reformatting the data into a more SIMD-amenable form. Where the underlying target hardware does not have native support for interleaved complex values it is straight-forward to synthesize a sequence of operations which give the same effect.

Given the popularity of interleaved complex-values as a data exchange and compute format we propose that `std::simd` should be able to directly represent this simd format in a form exemplified as:

```
std::simd<std::complex<float>, 5>
std::simd<std::complex<double>, 9>
```

In all these cases the fundamental element type will be a suitable complex value, and the individual components of each complex element will be worked on as a single unit, according to the rules of complex arithmetic where appropriate. This includes:

- All numeric operators (e.g., `+`, `/`, `-`, `*`) and their derivatives (e.g., assignment operators) will operate as per their standard complex type definition. For example, the multiply operator will invoke a complex multiply for each complex element.
- Any numeric operation will apply the operation on a per-element basis, generating a simd object of the same size as the input, but modifying the element type to be the appropriate return type. For example, when applied to a `simd<complex<T>>`:

- `exp`, `sin`, `log`, `tan`, `cos` and so on will generate a `simd<complex<T>>`
- `abs` or `norm` will generate a `simd<T>` (i.e., real-valued SIMD equivalent).

Note that the mathematical behavior will also be applied appropriately (e.g., if a real or imaginary component is a NaN, then the complete operation for a complex operation will also be NaN).

- The `simd_mask` associated with a `simd<complex<T>>` will have each individual mask bit refer to a complete complex element, not to sub-components of the complex elements. When the `simd_mask` is backed by a compact representation (e.g., AVX-512), then each individual bit will refer to a complete complex element. When the `simd_mask` is backed by an element mask (i.e., multiple bits filling a container of the same size as the simd element) then the size of each bit element will be twice the size of the underlying complex value type (e.g., a `simd_mask<complex<_Float16>>` would be equivalent to something like `simd<uint32_t>`, since `sizeof(uint32_t) == 2 * sizeof(_Float16)`).
- Operations or functions which are invalid for complex values will be removed. This includes relational operators (e.g., `<`, `<=`, `>`, `>=`) and those derived from them such, as `min` or `max`.
- Any operation which moves or reorders elements will move entire complex values. For example, any sort of permute, resize, split, concat, insert, extract or indexing operation works on complete complex elements as though they are atomic units.
- Reduction operations apply at the level of complex values (this follows from the previous bullet), provided the mathematical operation is valid (e.g., reduce-max would not be available).

One of the aims of `std::simd` is to make it possible to write a generic code, which can use either a scalar type or a data-parallel type interchangeably. To this end, `std::simd` provides overloads of many of the standard functions which operate in data-parallel mode. The same should apply to a `simd` of complex values; it should be possible to write an algorithm which uses either `std::complex<T>` or `simd<std::complex<T>>` with only a type replacement, not with major API changes. To this end `std::simd` should include some member functions, such as `real` or `imag`, to mirror those found in `std::complex`.

Note that an alternative way to create parallel complex values is to allow `std::complex` to use `simd` elements, such as `std::complex<simd<float>>`. This storage layout is called separated storage and discussion of this format is outside the scope of this paper.

§ 3. Overview of updates required to support `std::complex` `simd` elements

There are three ways in which `std::simd` needs to change to accommodate `std::complex` elements:

- Modify the definition of vectorizable types and the operations on them to allow for complex elements. These modifications are small in nature and don't change the fundamental `std::simd` API.
- Add a small number of methods to `std::simd` to mimic those found in `std::complex`. These modifications allow a `std::simd<complex<T>>` value to be easily inserted into source code by text or template replacement in place of a `std::complex` value without requiring a rewrite.
- Add a set of overloads and free functions to allow `simd<complex<T>>` to reflect the different behaviors of complex (e.g., `sin`, `cos`, `exp`, `log`).

Each of these points will now be discussed in more detail.

§ 3.1. `std::simd` base modifications

In its current definition, `std::simd` allows the element type to be any cv-unqualified arithmetic type other than `bool`. The first modification is to extend the set of allowable element types to include any type which is valid for `std::complex`.

Any `simd` operation or function which relies only on an element being an atomic container which can be arbitrarily moved or duplicated as a single unit will continue to operate as expected. For example, all the following will work on `simd<complex<T>>` without modification:

- Constructors or `copy_to/copy_from` functions for loading and storing values to and from contiguous iterators
- Broadcast constructor
- Index operations
- Reordering operations, such as `simd_split`, `simd_cat`, `permute`, `resize`, `insert` and `extract`.
- Masking selection operations (using a mask to include or exclude values from an operation or copy).

`simd_mask`'s of complex values do not need to have any special behaviour since the mask is simply a collection of boolean values, and the underlying element type makes no difference.

Constructors, including generator functions, which work on atomic units (e.g., broadcasting constructor) will work without modification. Note that the existing broadcast constructor will already permit a real-valued object to be used in a broadcast, since an individual value may be converted to a complex value with a zero imaginary:

```
auto x = simd<std::complex<float>>>(3.14f);
// [3.14 + 0i, 3.14 + 0i, ...]
```

Numeric operations (binary, unary, and compound-assignment) are mostly covered by [\[P1928R6\]](#) remark:

A `simd` object initialized with the results of applying the indicated operator to `lhs` and `rhs` as a binary element-wise operation

In the case of complex values this has the practical effect of ensuring that operators will perform their complex operations without changing the definition of `std::simd` (e.g., `operator*` will perform complex-valued multiplication). Furthermore, [\[P1928R6\]](#) notes that constraints will be applied as necessary on operators and functions:

Constraints: Application of the indicated operator to objects of type `T` is well-formed.

This will ensure that operators which are not permitted for complex numbers (e.g., `operator%`, `operator<<`, `operator&`) will be removed from the overload set, as will functions which rely on these operators (e.g., `min`, `max`, `clamp`).

§ 3.2. Additional complex methods for `std::simd`

It is desirable for `std::simd` to be source- or template-replaceable with respect to its underlying element type. For example, given a simple code fragment which works with `std::complex`:

```
auto my_fn(auto cmplx_value)
{
    std::complex<float> rotator (0, 1);
    return (cmplx_value * rotator).real();
}
```

In this example the function will work with a `std::complex<float>` input. Ideally it should also work with an input of type `simd<complex<float>>`. For this to happen, firstly the `operator*` must work with a scalar value, and secondly it should be possible for the `real()` method to be invoked on a `simd<complex<T>>` value.

`std::complex` provides a number of member functions:

- Constructors
- `operator=` (assignment)
- `operator+=`, `operator-=`, `operator*=`, `operator/=`
- `real`
- `imag`

The assignment operator and the compound-assignment operators are already provided by `std::simd` so no further action is required. The remaining member functions that are required are considered in the following sub-sections.

§ 3.2.1. Constructors

Conversion and copy methods already exist in `std::simd` and can be used for complex SIMD values. An additional constructor is needed to match the `std::complex` constructor which can build a complex value from separate real and imaginary components: constructed from real and imaginary `simd` values.

```
requires is_complex_number<T>
constexpr basic_simd(const basic_simd<T::value_type, UAbi>& r = {},
```

```
const basic_simd<T::value_type, UAbi>& i = {})
```

This constructor is constrained so that it can only be used for SIMD values with complex elements (some suitable concept will be added to enforce this). Like its `std::complex` counterpart it can be used to build a complex value from real components only, with insertion of zero imaginaries. This constructor can be used as in the following example:

```
simd<float, 8> reals = ...;
simd<float, 8> imaginaries = ...;

// Create a real-valued complex number (i.e., zero imaginaries)
simd<std::complex<float>, 8> realAsComplex (reals);

// Create a complex value from real and imaginary simd inputs
simd<std::complex<float>, 8> cmplx (reals, imaginaries);
```

§ 3.2.2. Real/imag accessors

It should be possible to separately read or write the real and imaginary components. For example, given a simd of `std::complex<float>` values, the real components of the simd will be extracted as a value of type `std::simd<float>` instead. Similarly, given a `simd<float>` value those values can be inserted into the simd as the real components of each respective value.

The read accessors for `std::complex` come in two variants: a free function, and a member function. These would be defined in `std::simd` as follows:

```
// Free functions for accessing real/imaginary components
template <typename T, typename ABI> constexpr auto real(const basic_simd<cc
template <typename T, typename ABI> constexpr auto imag(const basic_simd<cc

// Member functions of std::simd for accessing real/imaginary components.
constexpr simd<T, size()> std::simd<std::complex<T>>::real() const;
constexpr simd<T, size()> std::simd<std::complex<T>>::imag() const;
```


The write accessors for `std::complex` are provided as member functions which allow the real and imaginary components of an existing complex value to be overwritten.

```
template<typename T, typename ABI>
constexpr void real(const basic_simd<T, ABI>& reals);

template<typename T, typename ABI>
constexpr void imag(const basic_simd<T, ABI>& reals);
```

The advantage of making `real` and `imag` members of `std::simd` is an API consistency between `std::complex<T>` and `std::simd<std::complex<T>>` for both getters and setters. A disadvantage though is the `real` and `imag` seem too specific to be provided for `std::simd`. Please see § 3.3.1 [Alternative design for real and imag](#) for more design considerations.

§ 3.3. Additional free functions

The free functions for `std::complex` include numeric operators, such as `+`, `-`, `*` and `/`. These are already proposed in [\[P1928R6\]](#) and need not be considered further.

The remaining free functions which should be specialized for `std::simd<complex<T>>` include:

<code>real(simd<complex>)</code>	returns the real part
<code>imag(simd<complex>)</code>	returns the imaginary part
<code>abs(simd<complex>)</code>	returns the magnitude of a complex number
<code>arg(simd<complex>)</code>	returns the phase angle
<code>norm(simd<complex>)</code>	returns the squared magnitude
<code>conj(simd<complex>)</code>	returns the complex conjugate
<code>proj(simd<complex>)</code>	returns the projection onto the Riemann sphere
<code>polar(simd<complex>)</code>	constructs a complex number from magnitude and phase angle
<code>exp(simd<complex>)</code>	complex base e exponential
<code>log(simd<complex>)</code>	complex natural logarithm with the branch cuts along the negative

	real axis
<code>log10(simd<complex>)</code>	complex common logarithm with the branch cuts along the negative real axis
<code>pow(simd<complex>)</code>	complex power, one or both arguments may be a complex number
<code>sqrt(simd<complex>)</code>	complex square root in the range of the right half-plane
<code>sin(simd<complex>)</code>	computes sine of a complex number
<code>cos(simd<complex>)</code>	computes cosine of a complex number
<code>tan(simd<complex>)</code>	computes tangent of a complex number
<code>asin(simd<complex>)</code>	computes arc sine of a complex number
<code>acos(simd<complex>)</code>	computes arc cosine of a complex number
<code>atan(simd<complex>)</code>	computes arc tangent of a complex number
<code>sinh(simd<complex>)</code>	computes hyperbolic sine of a complex number
<code>cosh(simd<complex>)</code>	computes hyperbolic cosine of a complex number
<code>tanh(simd<complex>)</code>	computes hyperbolic tangent of a complex number
<code>asinh(simd<complex>)</code>	computes area hyperbolic sine of a complex number
<code>acosh(simd<complex>)</code>	computes area hyperbolic cosine of a complex number
<code>atanh(simd<complex>)</code>	computes area hyperbolic tangent of a complex number

All of these functions should operate element-wise in the same way as their scalar counterparts. Note that although most of these functions take complex inputs and generate complex outputs, some of these functions generate real-valued outputs (e.g., `abs` returns the magnitude, which is real-valued), or accept an input which is real-valued (e.g., `conj` can accept a real-valued value and return a complex value).

§ 3.3.1. Alternative design for `real` and `imag`

Instead of making `real` and `imag` member functions we could provide them only as free functions. Free function getters are already included in the proposal, but the setters would be removed as member functions and replaced by the following:

```
// Setters
template <typename T, typename AbiC, typename AbiR>
void real(basic_simd<complex<T>, AbiC>&, basic_simd<T, AbiC>);

template <typename T, typename AbiC, typename AbiR>
void imag(basic_simd<complex<T>, AbiC>&, basic_simd<T, AbiR>);
```

The member function getters would also be removed.

The advantage of that approach is it keeps `std::complex` specific functions outside of `std::simd` class. The disadvantage though is inconsistency with existing `real` and `imag` free functions for `std::complex`, which allow reading only. Please see [§ 3.2.2 Real/imag accessors](#) for initial design.

We would like to hear the feedback of C++ standard committee what design looks more appropriate.

§ 4. Implementation experience

Intel have written an example implementation of `std::simd` which includes the extensions to support interleaved complex values. We have been able to generate efficient code both on targets with native support (e.g., AVX512_FP16), and also on targets without native support which require synthesized code sequences.

§ 5. Wording

The wording relies on [\[P1928R6\]](#) being landed to the Working Draft. Below, substitute the  character with a number the editor finds appropriate for the table, paragraph, section or sub-section.

§ 5.1. Modify `[simd.general]`

: The set of *vectorizable* types comprises all cv-unqualified arithmetic types other than `bool`, and `std::complex<>` specializations. .

§ 5.2. Modify [simd.summary]

◆: Default initialization performs no initialization of the elements , except when the value type is a `std::complex<>` specialization in which case all elements will be value-initialized ; value-initialization initializes each element with `T()`.

§ 5.3. Modify [simd.ctor]

◆ simd constructors [simd.ctor]

[...]

```
template<typename CAbi>
constexpr explicit
basic_simd(const basic_simd<complex-element-type, CAbi> reals = {},
           const basic_simd<complex-element-type, CAbi> imgs = {});
```

Constraints:

- The `value_type` is a complex value (i.e., some specialization of `std::complex<>`).
- The `complex-element-type` is the same as `T::value_type` (where `T` is the `simd`'s own `value_type`).
- `basic_simd<complex-element-type, CAbi>::size` is equal to `basic_simd::size`.

Effects:

- Construct a `simd` of elements of type `value_type` (where `value_type` is a specialization of `std::complex<>`), such that the i^{th} element is equal to the object constructed as `value_type(reals[i], imgs[i])` for all `i` in the range `[0..size)`.

Remarks:

- Where no parameter values are provided this function acts as default initializer which value-initializes all real and imaginary elements.

§ 5.4. Add new section [`simd.complex_accessors`]

◆ `simd` complex accessors [`simd.complex_accessors`]

```
constexpr simd<complex-element-type, size> real() const;
constexpr simd<complex-element-type, size> imag() const;
```

Constraints:

- `T` is a complex value (i.e., any valid instantiation of `std::complex<> template`).

Returns:

- A `simd` with values of `complex-element-type` that is a `value_type` of `std::complex` of the same width. The i^{th} element will be equal to `(*this)[i].real()` or `(*this)[i].imag()` respectively for all i in the range `[0..size)`.

```
template<typename CAbi>
constexpr void real(const basic_simd<complex-element-type, CAbi>& v) noexcept
template<typename CAbi>
constexpr void imag(const basic_simd<complex-element-type, CAbi>& v) noexcept
```

Constraints:

- `T` is a complex value (i.e., any valid instantiation of `std::complex<> template`).
- `complex-element-type` is the same as the `simd` value-type.
- `basic_simd<complex-element-type, CAbi>::size` is equal to `basic_simd::size`.

Effect:

- Modify each element of the `simd` such that the real or imaginary component of the i^{th} element is replaced by the value of `v[i].real` or `v[i].imag()` respectively.

```
template<typename T, typename Abi>
constexpr simd<complex-element-type, size>
real(const basic_simd<typename T, typename Abi>& v) noexcept;
```

```
template<typename T, typename Abi>
constexpr simd<complex-element-type, size>
imag(const basic_simd<typename T, typename Abi>& v) noexcept;
```

Constraints:

- T is a complex value (i.e., any valid instantiation of `std::complex<>` template).

Returns:

- A `simd` with values of complex-element-type that is a `value_type` of `std::complex` of the same width, where the i^{th} element is equal to `v[i].real()` or `v[i].imag()` respectively for all i in the range `[0..v.size)`.

§ 5.5. Add new section [`simd.complex_math`]

◆ `simd complex maths library` [`simd.complex_library`]

For each set of overloaded functions within `<complex>` there shall be additional overloads sufficient to ensure that:

- Any `basic_simd<std::complex<T>, Abi>` type can be used where `std::complex<>` would be used (parameter or return value).
- Any real-valued `simd<T, Abi>` type can be used where T would be used (parameter or return value).

It is unspecified whether a call to these overloads with arguments that are all convertible to `basic_simd<T, Abi>` but are not of type `basic_simd<T, Abi>` is well-formed.

Each function overload produced by the above rules applies the indicated `<complex>` function element-wise. For the mathematical functions, the results per element only need to be approximately equal to the application of the function which is overloaded for the element type.

The result is unspecified if a domain, pole, or range error occurs when the input argument(s) are applied to the indicated `<complex>` function. [Note: Implementations are encouraged to follow the C specification (especially Annex F). — end note]

§ 6. Polls

§ 6.1. Kona 2022 SG1 polls

Poll: After significant experience with the TS, we recommend that the next version (the TS version with improvements) of `std::simd` target the IS (C++26)

SF	F	N	A	SA
10	8	0	0	0

Poll: Future papers and future revisions of existing papers that target `std::simd` should go directly to LEWG. (We do not believe there are SG1 issues with `std::simd` today.)

SF	F	N	A	SA
9	8	0	0	0

§ 7. Revision History

R3 => R4

- Updated wording to reflect changes made to `std::simd` in [P1928R6] (e.g., removal of `fixed_size_simd`, addition of `basic_simd`).

R2 => R3

- Added wording

R1 => R2

- Add more content for proposal overview
- Rewrite to bikeshed

R0 => R1

- Add polls from Kona SG1 2022

§ References

§ Informative References

[P1928R6]

Matthias Kretz. *std::simd - Merge data-parallel types from the Parallelism TS 2*. 19 June 2023.

URL: <https://wg21.link/p1928r6>

[P2638R0]

Daniel Towner. *Intel's response to P1915R0 for std::simd parallelism in TS 2*. 22 September

2022. URL: <https://wg21.link/p2638r0>