

Project: ISO JTC1/SC22/WG21: Programming Language C++
Doc No: WG21 **P3828R0**
Date: 2025-10-06
Reply to: Nicolai Josuttis (nico@josuttis.de)
Co-authors:
Audience: LEWG, LWG
Issues:
Previous:

Rename the to_input view to as_isput

The current name of the "to_input" view is misleading, because this sounds like the elements of the underlying range are actively processed (like with `std::ranges::to`). Instead it only ensures that the underlying range is seen **as** something different for those that later process the elements using this view. For views like this we usually use the name "as_..." (e.g. `as_const` or `as_rvalue`).

This paper proposes to rename the to_input view to as_input. This is both more intuitive and consistent.

Note that in this case this might include to also change the name of the section in the C++ standard and the name of the feature test macro.

Proposed Wording

(All against N4944)

In principle simply rename all occurrences of "to_input" to "as_input" and "to input view" to "as input view."

In **17.3.2 Header <version> synopsis [version.syn]**

Rename as follows:

```
#define __cpp_lib_ranges_toas_input 202502L // freestanding, also in <ranges>
```

In **25.2 Header <ranges> synopsis [ranges.syn]**

Rename as follows:

```
// 25.7.35, to as input view
template<input_range V>
    requires view<V>
class toas_input_view;
template<class V>
    constexpr bool enable_borrowed_range<toas_input_view<V>> =
        enable_borrowed_range<V>;
namespace views { inline constexpr unspecified toas_input = unspecified ; }
```

Rename

25.7.35 ~~To~~ input view [range.~~to~~.input]

to

25.7.35 **As input view [range.**as**.input]**

Rename

25.7.35.1 Overview [range.~~to~~.input.overview]

to

25.7.35.1 Overview [range.to**.input.overview]**

and rename inside:

- 1 `to_as_input_view` presents a view of an underlying sequence as an input-only non-common range.
 [Note 1 : This is useful to avoid overhead that can be necessary to provide support for the operations needed for greater iterator strength. —end note]
- 2 The name `views::to_as_input` denotes a range adaptor object (25.7.2). Let `E` be an expression and let `T` be `decltype(E)`. The expression `views::to_as_input(E)` is expression-equivalent to:
- (2.1) — `views::all(E)` if `T` models `input_range`, does not satisfy `common_range`, and does not satisfy `forward_range`.
- (2.2) — Otherwise, `to_as_input_view(E)`.

Rename

25.7.35.2 Class template `to_input_view` [range.to.input.view]

to

25.7.35.2 Class template `as_input_view` [range.as.input.view]

and rename inside:

```
namespace std::ranges {
    template<input_range V>
        requires view<V>
    class to_as_input_view : public view_interface<to_as_input_view<V>> {
        V base_ = V(); // exposition only
        // 25.7.35.3, class template to_as_input_view::iterator
        template<bool Const> class iterator ; // exposition only
    public:
        to_as_input_view() requires default_initializable<V> = default;
        constexpr explicit to_as_input_view(V base);
        ...

        template<class R>
            to_as_input_view(R&&) -> to_as_input_view<views::all_t<R>>;
    }
    constexpr explicit to_as_input_view(V base);
    1 Effects: Initializes base_ with std::move(base).
```

Rename

25.7.35.3 Class template `to_input_view::iterator` [range.to.input.iterator]

to

25.7.35.3 Class template `as_input_view::iterator` [range.as.input.iterator]

and rename inside:

```
namespace std::ranges {
    template<input_range V>
        requires view<V>
    template<bool Const>
    class to_as_input_view<V>::iterator {
        using Base = maybe_const<Const, V>; // exposition only
        ...
    }
```

Acknowledgements

Thanks to a lot to everybody who helped and gave support to come to finally get this proposal done.

Rev0:

First initial version.