

Class template argument deduction (CTAD) for type template template parameters

Christof Meerwald

Document Number: P3865R0

Date: 2025-10-05

Reply-To: Christof Meerwald <cmeerw@cmeerw.org>

Audience: LEWG, EWG, CWG

Abstract

This paper proposes to update the core language wording to allow CTAD (class template argument deduction) for type template template parameters and treat it as a DR, addressing both CWG 3003 and LWG 4381.

Introduction

[CWG 3003](#) "Naming a deducible template for class template argument deduction" has been raised to clarify that with the current core language wording, class template argument deduction does not work for type template template parameters.

However, the library makes use of this feature in [\[range.utility.conv.to\]](#) (adopted in C++23):

```
template<template<class...> class C, input_range R, class... Args>
    constexpr auto to(R&& r, Args&&... args);
```

...

Let *DEDUCE_EXPR* be defined as follows:

— *C*(*declval*<*R*>(), *declval*<*Args*>()...) if that is a valid expression,

— ...

and all current implementations actually accept it. There is no known fix for the library wording without changes to the core language, see [LWG 4381](#) "std::ranges::to specification using CTAD not supported by core language".

In [Re: \[isocpp-core\] Review of CWG3003 Naming a deducible template for class template argument deduction](#) it was pointed out that it was not the design intent of [P0091R3](#) "Template argument deduction for class templates (Rev. 6)" to disallow CTAD for template template parameters. It should therefore be seen as fixing a wording defect instead of a new feature.

Examples

Simple case:

```
template<typename T>
struct C {
    C(T);
};

template<template<typename> class X>
void f() {
    X x(1);
}

template void f<C>();
```

It seems reasonable for the type of `x` to be deduced as `C<int>`.

But since [P0552R0](#) "DR: Matching of template template-arguments excludes compatible templates", a template template argument doesn't have to match a template template parameter exactly; the template template parameter just needs to be more specialized than the template template argument. For example:

```
template<typename ... T>
struct C {
    C(T ...);
};

template<template<typename> class X>
void f() {
    X x1{1};
    X x2{1, 2};
}

template void f<C>();
```

Again, allowing the type of `x1` to be deduced as `C<int>` seems reasonable, but what about `x2`? If we just substitute `C` into the template and then perform class template argument deduction, we would get `C<int, int>`, even though there is no way to actually specify those template arguments with `X`. That seems unhelpful, so that should be ill-formed, similar to CTAD for alias templates (which adds a deducible constraint).

How should default template arguments for the template template parameter be handled?

```
template<typename T = int>
struct C {
    C(int);
};

template<template<typename = long> class X>
void f() {
    X x(1);
}

template void f<C>();
```

A simple substitution into the template would result in the type of `x` to be deduced as `C<int>`, but `X<>` would use the default argument specified in the template template parameter (i.e., the type would instead be `C<long>`).

CWG 3003 shows another example where the alias template refers to a template template parameter.

```
template <typename T> struct A { A(T); };

template <typename T, template <typename> class TT = A>
using Alias = TT<T>;

template <typename T>
using Alias2 = Alias<T>;

void h() { Alias2 a(42); }
void h2() { Alias a(42); }
```

This currently crashes most implementations, but as the *defining-type-id* of `Alias` doesn't denote a deducible template, it should just be ill-formed.

Status Quo

Current implementations accept the above examples (except for the last one) with the "simple substitution" semantics. This means that default template arguments specified on the template template

parameters are ignored during deduction and that types can be deduced that can't otherwise be written using the name of the template template parameter. This seems confusing.

Proposed Semantics

This paper proposes to respect the default arguments specified on template template parameters and any restrictions resulting from a template template parameter being more specialized than the template template argument. This is consistent with how CTAD for alias templates works, and the proposal is to use those semantics instead of directly substituting the template template argument.

Placeholder deduction for a type template template parameter should be performed as if the type template template parameter were replaced by an alias template (with the same template parameters) denoting the type template template argument in its *defining-type-id*.

For example, for the pack example above:

```
template<typename ... T>
struct C {
    C(T ...);
};

template<template<typename> class X>
void f() {
    X x1{1};
    X x2{1, 2};
}

template<typename T>
using XC = C<T>; // exposition only

template<> void f<C>() {
    XC x1{1};      // OK, deduces X<int>
    XC x2{1, 2};   // error: class template argument deduction fails
}
```

Similarly, for default template arguments:

```
template<typename T = int>
struct C {
    C(int);
};

template<template<typename = long> class X>
void f() {
    X x{1};
}

template<typename T = long>
using XC = C<T>; // exposition only

template<> void f<C>() {
    XC x{1};      // OK, deduces X<long>
}
```

Implementation Experience

None yet for the exact semantics specified in this paper, but all implementations already support the simple case.

Wording (relative to N5014)

Change [\[dcl.type.simple\]](#) paragraph 3

A *placeholder-type-specifier* is a placeholder for a type to be deduced ([\[dcl.spec.auto\]](#)). A *type-specifier* is a placeholder for a deduced class type ([\[dcl.type.class.deduct\]](#)) if either

- it is of the form `typenameopt nested-name-specifieropt template-name` or
- it is of the form `typenameopt splice-specifier` and the *splice-specifier* designates a class template or alias template.

The *nested-name-specifier* or *splice-specifier*, if any, shall be non-dependent and the *template-name* or *splice-specifier* shall designate a deducible template. A *deducible template* is either a class template, [a type template template parameter](#), or is an alias template whose *defining-type-id* is of the form

`typenameopt nested-name-specifieropt templateopt simple-template-id`

where the *nested-name-specifier* (if any) is non-dependent and the *template-name* of the *simple-template-id* names a deducible template [other than a type template template parameter](#).

...

Insert a new paragraph before [\[over.match.class.deduct\]](#) paragraph 3

When resolving a placeholder for a deduced class type where the *template-name* designates a type template template parameter P, let A be an alias template whose template parameter list is that of P and whose *defining-type-id* designates the type template template argument with a *simple-template-id* in which the *template-argument-list* consists of a list of identifiers naming each *template-parameter* of P, with the argument being a pack expansion if the *template-parameter* is a pack. A is then used instead of the original *template-name* to resolve the placeholder.

- 3 When resolving a placeholder for a deduced class type ([\[dcl.type.simple\]](#)) where the *template-name* or *splice-type-specifier* designates an alias template A, ...

Add a new paragraph at the end of [\[over.match.class.deduct\]](#)

```
[Example:
template<typename ... Ts>
struct Y {
    Y();
    Y(Ts ...);
};
template<template<typename T = char> class X>
void f() {
    X x0{};      // OK, deduces Y<char>
    X x1{1};     // OK, deduces Y<int>
    X x2{1, 2};  // error: cannot deduce X<T> from Y<int, int>
};
template void f<Y>();
— end example]
```

References

- Thomas Köppe: [N5014](#) Working Draft, Standard for Programming Language C++
- Hubert Tong: [CWG 3003](#) Naming a deducible template for class template argument deduction
- Jens Maurer: [LWG 4381](#) std::ranges::to specification using CTAD not supported by core language
- James Touton, Hubert Tong: [P0522R0](#) DR: Matching of template template-arguments excludes compatible templates

- Mike Spertus, Faisal Vali, Richard Smith: [P0091R3](#) Template argument deduction for class templates (Rev. 6)
- [paper issue 2443](#) CWG3003 Naming a deducible template for class template argument deduction