

P3953R0

Rename `std::runtime_format`

Published Proposal, 2025-12-28

Author:

[Victor Zverovich](#)

Audience:

LEWG

Project:

ISO/IEC 14882 Programming Languages — C++, ISO/IEC JTC1/SC22/WG21

Table of Contents

- 1 Abstract
- 2 Motivation
- 3 Proposed Naming: `std::dynamic_format`
- 4 Impact on existing code

References

Informative References

There are only two hard things in Computer Science: cache invalidation and naming things.

— Phil Karlton

§ 1. Abstract

[P2918] introduced `std::runtime_format` to allow opting out of compile-time format string checks in `std::format`. Subsequently, [P3391] made `std::format` usable in constant evaluation. As a result, `std::runtime_format` can now be evaluated at compile time, making its name mis-

leading. This paper proposes renaming `std::runtime_format` to `std::dynamic_format` to better reflect its semantics and avoid confusion in `constexpr` contexts.

§ 2. Motivation

The name `std::runtime_format` was accurate when introduced in [P2918], as format strings were not usable in constant evaluation. However, with the adoption of `constexpr std::format`, the term runtime no longer reliably describes the behavior of `std::runtime_format`.

Consider the following code:

```
constexpr auto f(std::string_view fmt, int value) {  
    return std::format(std::runtime_format(fmt), value);  
}
```

Despite its name, `std::runtime_format` can be evaluated at compile time. This creates a semantic mismatch:

- "runtime" suggests evaluation timing
- The facility actually describes how the format string is obtained.

The real distinction is not when formatting occurs, but how the format string is provided and validated. The term runtime conflates it with evaluation time.

§ 3. Proposed Naming: `std::dynamic_format`

The proposed name `std::dynamic_format` reflects the actual semantics:

- The format string is dynamically provided
- The format string is not a compile-time constant
- The validation is deferred (but may still occur during constant evaluation)

This aligns with existing terminology `std::format` such as dynamic format specifiers (`check_dynamic_spec`).

Example with proposed name:

```
constexpr auto f(std::string_view fmt, int value) {  
    return std::format(std::runtime_format(fmt), value);  
}
```

This reads naturally and avoids semantic contradiction.

§ 4. Impact on existing code

If this is adopted for C++26 there will be no impact on existing code since `std::runtime_format` is a C++26 feature.

§ References

§ Informative References

[P2918]

Victor Zverovich. *Runtime format strings II*. URL: <https://www.open-std.org/jtc1/sc22/wg21/docs/papers/2023/p2918r2.html>

[P3391]

Barry Revzin. *`constexpr std::format`*. URL: <https://www.open-std.org/jtc1/sc22/wg21/docs/papers/2025/p3391r2.html>