

Document number: P3982R2
Date: 2026-03-24
Audience: Library Evolution Working Group
Reply-to: *Tomasz Kamiński <tomaszkam at gmail dot com>*
Mark Hoemmen <mark dot hoemmen at gmail dot com>

Split `strided_slice` into `extent_slice` and `range_slice` for C++26

1. Introduction

Addresses [PL007: Define the extent member of the `strided\_slice`](#)

This paper proposes two changes:

1. Rename `strided_slice` to `extent_slice` and adjust the meaning of its `extent` member, to designate the desired number of elements in the range produced by `submdspan`. **This change would be breaking after C++26 is shipped.**
2. Introduce a non-canonical `range_slice` slice type, that expresses the (`first`, `last`, `stride`) interface provided for range slicing in other programming languages. **While this is an extension that can be added in a later standard, this change preserve more ergonomic and familiar interface for `submdspan`.**

Before	After
<code>std::strided_slice{0, 2, 3};</code>	<code>std::extent_slice{0, 1, 3};</code> <code>std::range_slice{0, 2, 3};</code>
<code>std::strided_slice{2, 10, 3};</code>	<code>std::extent_slice{2, 4, 3};</code> <code>std::range_slice{2, 12, 3};</code>

2. Revision history

2.3. Revision 2

Applied wording fixes from LWG review in Croydon.

2.2. Revision 1

- Changed title to better reflect the content.
- Remove the proposal to support any type decomposable into [`first`, `last`, `stride`], as slice type. This change will be proposed for C++29.
- Corrected and updated the wording for `strided_slice` per Charles Hussong suggestions.

2.1. Revision 0

Initial revision.

3. Motivation and Scope

For the invocation of in the form `smd = submdspan(md, strided_slice{offset, extent, stride})`, there are two ranges of indices of elements to which we refer:

- *input span*: size of the range of indices into `md`, that can be accessed by `smd`; and
- *output extent*: size of the range of indices that are valid indices for `smd`.

Given the above, there are two possible interpretations of the `extent` for the above example:

- *input span*, thus *output extent* is $1 + (\text{extent} - 1) / \text{stride}$; or
- *output extent*, thus *input span* is $\text{extent} * \text{stride}$.

In most cases, this two meanings are functionally equivalent and they can be transformed into each other. However, due use of the division in the *input span* interpretation does not support the following:

- stride whose value is zero, that could be used to produce non-unique layouts; or
- specifying the value of *output extent* statically, while keeping the stride dynamic.

As `strided_slice` is used as one of the canonical forms of the slices, we propose to `strided_slice::extent` member should represent the *output extent*.

3.1. Introducing `range_slice`

One argument for using the *input span* as the value of `strided_slice::extent` was consistency with other programming languages' range slicing interface. However, surveying the slicing interface in common languages shows that they all use `first`, `last` instead of `offset`, `length`.

- [Fortran](#): `array(first:last)` and `array(first:last:step)`
- [python](#): `array[first:last]` and `array[first:last:step]`
- [Matlab](#): `array(first:last)` and `array(first:step:last)`
- [rust](#): `array[first..last]`, `array[first..]`, `array[..last]` and `array[..]`.

Based on the intuition built from other languages, `submdspan(md, strided_slice{2, 5, 1})`, should select elements [2, 5), instead of [2, 7) as currently specified.

To provide a interface consistent with existing practice in many languages, we propose to introduce a new vocabulary type for "range" slice:

```
template<typename FirstType, typename LastType, typename StrideType = constant_wrapper<1zu>>
struct range_slice
{
    [[no_unique_address]] FirstType first{};
    [[no_unique_address]] LastType last{};
    [[no_unique_address]] StrideType stride{};
};
```

3.2. Expressing required values directly

Creating a subset of a multidimensional index space (`submdspan`) requires the *output extent* to be known. In the model where user provides an *input span*, the *output extent* computation is performed, and thus duplicated in each layout.

In contrast, with this paper's proposed changes, the members of `strided_slice` directly represent values used by `submdspan` creation. This gives programmers more direct control over the process. In particular, in cases when the value of *output extent* is known, or can be reused between invocations, passing it directly can lead to measurable speed-up. We illustrate this by including benchmark results below.

submdspan(md, prefix_slice{0, span, stride})		
stride \ prefix:span	Before strided:10	After extent:1 + 9 / stride
3	3.03 ns	1.52 ns
1	3.03 ns	1.51 ns
std::cw<3>	1.01 ns	1.01 ns
std::cw<1>	1.02 ns	1.01 ns

As previously mentioned, `range_slice` can be used if passing an *input span* is preferred. Results from a benchmark similar to one used above show no significant performance difference.

submdspan(md, range_slice{0, 10, stride})		
stride	Before	After
3	3.03 ns	3.03 ns
1	3.03 ns	1.52 ns
std::cw<3>	1.01 ns	1.01 ns
std::cw<1>	1.01 ns	1.01 ns

More details about above results may be found [here](#).

3.3. Example of static *output extent* usage

As mentioned before, the current *input span* specification does not give users a way to select a statically sized subset of elements with dynamic stride. For example, imagine that we want to select 5 elements, evenly spaced from the `mdspan md`.

With the proposed change, we can simply express that as:

```
auto smd = sumdspan(md, strided_slice{cw<0>, cw<5>, md.extents()[0] / 5})
```

Note that the number of elements in the `smd` is always known statically, regardless if the source span had static extents.

3.4. Example of zero stride value usage

Using a zero as the value of the stride leads to a non-unique mappings, because incrementing the index does not change the referenced element. Thus, they are not accepted by the standard mappings.

However, `submdspan` can be also used with `mdspan` with user-defined mappings that are not required to be unique. Any mapping can be queried (via `is_always_unique` or `is_unique`) for this property.

One could imagine a `layout_stride_relaxed`¹ layout that is equivalent to `layout_strided`, except that it does not require that the provided strides result in a non-unique mapping. In case of `mdspan` with such mapping, a zero stride may be used to create a layout that "broadcasts" a single element over the given extent.

```
auto smd = submdspan(md, strided_slice{3, 5, 0});
```

For the above example, each of `smd[0]`, `smd[1]`, ..., `smd[4]` results in a reference to `md[3]`.

As mentioned before, such a slice specification is not representable currently. While the paper does not lift the current requirements on the stride value being non-zero, it permits zero strides in the future for a subset of mappings.

¹ A version of `layout_stride_relaxed` was [recently proposed](#) for inclusion in NVIDIA's CCCL library.

3.5. Rename of `strided_slice`

After expanding the set of accepted slice types, the `strided_slice` name does not capture the difference well, as `range_slice` is also strided. Thus, we propose to rename the class to `extent_slice`.

The `extent_slice` name was selected to focus on the fact that its members define the size (extent) of the produced (output) multidimensional index space. That is, it directly reflects the value of `smd.extent(k)`, where `smd` is the `mdspan` produced by `submdspan`, and `k` is the index of the extent to which the slice is applied.

We also avoid using words commonly used to refer to the range like "size," "length" (as in `offset + length`), or "span". The word "size" is particularly overloaded, for example in the `std::ranges::sized_range` concept.

4. Ship vehicle and polls

`r SpanType` denotes `constant_wrapper`, and `StridesType`

This paper proposes two changes:

1. Rename `strided_slice` to `extent_stride` and adjust the meaning of `extent` member, to designate the desired number of elements in the produced range.
2. Introduce a new non-canonical slice type `range_slice`, that expresses the (`first`, `last`, `stride`) interface for range slicing provided by other programming languages.

From the above only the **first change** need to be applied in the C++26 timeframe. The others are extensions that could be applied to future standards.

4.1. Proposed polls

1. Forward P3982R1 as resolution for PL007 NB comment to LWG for inclusion to C++26.
2. Forward P3982R1 without `range_slice` addition as resolution for PL007 NB comment to LWG for inclusion to C++26.

4.2. `extent_slice` needs to target C++26

`strided_slice` is one of the canonical slice types that define the interface between `submdspan` (and potentially other components providing such facility) and custom layouts. Thus, it is important that the interface is both minimal (reducing the burden on layouts implementers) and able to represent a wide range of input without loss of information. As this document explains, the current specification of `strided_slice` fails in both accounts (it incurs cost of division, and cannot be used for non-unique layouts).

We currently reserve rights to introduce additional canonical stride types. We could imagine introducing a separate `canonical_strided_slice` type in a later standard. However, in contrast to amending `strided_slice`, this would essentially duplicate the number of types that layouts would need to handle, as pre-existing code depending on sliceable layout requirements may still produce `strided_slice` objects.

4.3. `range_slice` should target C++26

While `range_slice` could be added later as an extension, the authors strongly believe that the ergonomics of `submdspan` would be severely degraded, without the ability to specify a slice using an *input span*.

During the work on this paper, one of the authors (Tomasz) made the following mistakes, when transforming the *input span* span to an *output extent*:

- using `span / stride`,
- using `(span - 1) / stride` (missing +1),
- not accounting for span equal to zero.

This shows that even for programmers familiar with the topic, such computations remain bug-prone.

5. Impact and Implementability

This paper only impacts the behavior of the `std::submdspan` library function that was introduced in C++26.

Here is a [patch series](#) implementing the proposed wording changes to `submdspan` in `libstdc++`.

6. Proposed Wording

The proposed wording changes refer to N5032 (C++ Working Draft, 2025-12-15).

Apply following changes to section [mdspan.syn] Header <mdspan> synopsis:

```
// [mdspan.sub], submdspan creation
template<class OffsetType, class LengthType, class StrideType>
    struct strided_slice;
template<class FirstType, class LastType,
         class StrideType = std::constant_wrapper<1zu>>
    struct range_slice;

template<class LayoutMapping>
    struct submdspan_mapping_result;
```

Apply following changes to section [mdspan.sub.overview] Overview :

-1- The `submdspan` facilities create a new `mdspan` viewing a subset of elements of an existing input `mdspan`. The subset viewed by the created `mdspan` is determined by the `SliceSpecifier` arguments.

-2- Given a signed or unsigned integer type `IndexType`, a type `S` is a *submdspan slice type for `IndexType`* if at least one of the following holds:

- -2.1- `is_convertible_v<S, full_extent_t>` is true;
- -2.2- `is_convertible_v<S, IndexType>` is true;
- -2.3- `S` is a specialization of `strided_slice` and `is_convertible_v<X, IndexType>` is true for `X` denoting `S::offset_type`, `S::extent_type`, and `S::stride_type`; ~~or~~
- -2.?- `S` is a specialization of `range_slice` and `is_convertible_v<X, IndexType>` is true for `X` denoting type of `S::first`, `S::last`, and `S::stride` members; or
- -2.4- all of the following hold:
 - -2.4.1- the declaration `auto [...ls] = std::move(s)`; is well-formed for some object `s` of type `S`,
 - -2.4.2- `sizeof...(ls)` is equal to 2, and

- -2.4.3- (is_convertible_v<decltype(std::move(ls)), IndexType> && ...) is true.

-3- Given a signed or unsigned integer type IndexType, a type S is a *canonical submdspan index type for IndexType* if S is either IndexType or constant_wrapper<v> for some value v of type IndexType, such that v is greater than or equal to zero.

-4- Given a signed or unsigned integer type IndexType, a type S is a *canonical submdspan slice type for IndexType* if exactly one of the following is true:

- -4.1- S is full_extent_t;
- -4.2- S is a canonical submdspan index type for IndexType; or
- -4.3- S is a specialization of strided_slice where all of the following hold:
 - -4.3.1- S::offset_type, S::extent_type, and S::stride_type are all canonical submdspan index types for IndexType; and
 - -4.2.2- if S::stride_type and S::extent_type are both specializations of constant_wrapper, then S::stride_type::value is greater than zero.

-5- A type S is a *collapsing slice type* if [...]

-6- A type S is a *unit-stride slice type* if [...]

-7- Given an object e of type E that is a specialization of extents, and an object s of type S that is a canonical submdspan slice type for E::index_type, the *submdspan slice range of s for the k^{th} extent of e* is:

- -7.1- [0, e.extent(k)), if S is full_extent_t;
- -7.2- [E::index_type(s.offset), E::index_type(s.offset)), if S is a specialization of strided_slice and E::index_type(s.extent) is zero; otherwise
- -7.2- [E::index_type(s.offset), E::index_type(s.offset + 1 + (s.extent - 1) * s.stride)), if S is a specialization of strided_slice; otherwise
- -7.3- [E::index_type(s), E::index_type(s)+1)

-8- Given a type E that is a specialization of extents, a type S is a *valid submdspan slice type for the k^{th} extent of E* if S is a canonical slice type for E::index_type, and for x equal to E::static_extent(k), either x is equal to dynamic_extent; or

- -8.1- if S is a specialization of strided_slice:
 - -8.1.1- ~~if S::offset_type is a specialization of constant_wrapper, then S::offset_type::value~~ o is less than or equal to x;
 - -8.1.2- ~~if S::extent_type is a specialization of constant_wrapper then S::extent_type::value~~ e is less than or equal to x;
 - -8.1.3- if e is greater than one, then t is greater than zero,
 - -8.1.3- ~~if both S::offset_type and S::extent_type are specializations of constant_wrapper then, S::offset_type::value + S::extent_type::value~~ if e is greater than zero, then o + 1 + (e - 1) * t is less than or equal to x

where

- -8.1.4- o is value of S::offset_type::value if S::offset_type is a specialization of constant_wrapper and 0 otherwise,
- -8.1.5- e is value of S::extent_type::value if S::extent_type is a specialization of constant_wrapper and 0 otherwise,
- -8.1.6- t is value of S::stride_type::value if S::stride_type is a specialization of constant_wrapper and 1 otherwise.
- -8.2- if S is a specialization of constant_wrapper, then S::value is less than x

-9- Given an object e of type E that is a specialization of extents and an object s of type S, s is a *valid submdspan slice for the k^{th} extent of e* if:

- -9.1- S is a valid submdspan slice type for k^{th} extent of E;
- -9.2- the k^{th} interval of e contains the submdspan slice range of s for the k^{th} extent of e; and
- -9.3- if S is a specialization of strided_slice then:
 - -9.3.1- s.extent is greater than or equal to zero, and
 - -9.3.2- either s.extent ~~equals zero~~ is less than two or s.stride is greater than zero.

Apply following changes to section [mdspan.sub.strided.slice] strided_slice:

-1- strided_slice and range slice represents a set of extent regularly spaced integer indices. The indices start at offset and first respectively, and increase by increments of stride.

```
namespace std {
    template<class OffsetType, class ExtentType, class StrideType>
    struct strided_slice {
        using offset_type = OffsetType;
        using extent_type = ExtentType;
        using stride_type = StrideType;

        [[no_unique_address]] offset_type offset{};
        [[no_unique_address]] extent_type extent{};
        [[no_unique_address]] stride_type stride{};
    };

    template<class FirstType, class LastType,
             class StrideType = std::constant_wrapper<1zu>>
    struct range_slice {
        [[no_unique_address]] FirstType first{};
        [[no_unique_address]] LastType last{};
        [[no_unique_address]] StrideType stride{};
    };
}
```

-2- strided_slice and range slice ~~has~~ have the data members and special members specified above. ~~It has~~ They have no base classes or members other than those specified.

-3- *Mandates:* OffsetType, ExtentType, FirstType, LastType, and StrideType are signed or unsigned integer types, or model *integral-constant-like*.

[*Note:* Both strided_slice{ .offset = 1, .extent = ~~10~~4, .stride = 3} and range slice{ .first = 1, .last = 11, .stride = 3} indicates ~~the~~ the indices 1, 4, 7, and 10. Indices are selected from the half-open interval [1, 1 + 10). — *end note*]

Apply following changes to section [mdspan.sub.helpers] Exposition-only helpers:

```
template<class T>
    concept is-strided-slice = see below;
```

-2- The concept *is-strided-slice*<T> is satisfied and modeled if and only if T is a specialization of strided_slice.

```
template<class T>
    concept is-range-slice = see below;
```

-?- The concept *is-range-slice*<T> is satisfied and modeled if and only if T is a specialization of range slice.

```
template<class IndexType, class S>
    constexpr auto canonical_index(S s);
```

-3- *Mandates:* [...];

-4- *Preconditions:* [...];

-5- *Effects:* [...];

```
template<class IndexType, class OffsetType, class SpanType, class... StrideTypes>
    constexpr auto canonical-range-slice(OffsetType offset, SpanType span, StrideTypes... strides);
```

-?- Let:

- StrideType denote
 - constant_wrapper<IndexType(1)> if StrideTypes is an empty pack or SpanType denotes constant_wrapper<IndexType(0)>, otherwise
 - StrideTypes...[0];
- stride be
 - StrideType() if StrideType is a specialization of constant_wrapper, otherwise

- IndexType(1) if span == 0 is true, otherwise
- strides...[0];
- extent-value be 1 + (span - 1) / stride if span != 0 is true, and 0 otherwise;
- extent be cw<IndexType(extent-value)> if both SpanType and StrideType are specializations of constant_wrapper, and IndexType(extent-value) otherwise.

-?- Mandates:

- sizeof...(StrideTypes) <= 1 is true, and
- if StrideType is a specialization of constant_wrapper, then StrideType::value > 0 is true.

-?- Preconditions: stride > 0 is true.

-?- Returns: strided_slice{ .offset = offset, .extent = extent, .stride = stride };

```
template<class IndexType, class S>
constexpr auto canonical-slice(S s);
```

-6- Mandates: S is a submdspan slice type for IndexTye.

-7- Effects: Equivalent to:

```
if constexpr (is_convertible_v<S, full_extent_t>) {
    return static_cast<full_extent_t>(std::move(s));
} else if constexpr (is_convertible_v<S, IndexType>) {
    return canonical-index<IndexType>(std::move(s));
} else if constexpr (is-strided-slice<S>) {
    return strided_slice{
        .offset = canonical-index<IndexType>(std::move(s.extent)),
        .extent = canonical-index<IndexType>(std::move(s.offset)),
        .stride = canonical-index<IndexType>(std::move(s.stride))
    };
    auto c_extent = canonical-index<IndexType>(std::move(s.extent));
    auto c_offset = canonical-index<IndexType>(std::move(s.offset));
    if constexpr (is-same_v<decltype(c_extent), constant_wrapper<IndexType(0)>>) {
        return strided_slice{
            .offset = c_offset,
            .extent = c_extent,
            .stride = cw<IndexType(1)>
        };
    } else {
        return strided_slice{
            .offset = c_offset,
            .extent = c_extent,
            .stride = canonical-index<IndexType>(std::move(s.stride))
        };
    }
} else if constexpr (is-range-slice<S>) {
    auto c_first = canonical-index<IndexType>(std::move(s.first));
    auto c_last = canonical-index<IndexType>(std::move(s.last));
    return canonical-slice-range<IndexType>{
        c_first,
        canonical-index<IndexType>(c_last - c_first),
        canonical-index<IndexType>(std::move(s.stride));
    };
} else {
    auto [s_first, s_last] = std::move(s);
    auto c_first = canonical-index<IndexType>(std::move(s_first));
    auto c_last = canonical-index<IndexType>(std::move(s_last));
    return strided_slice{
        .offset = c_first,
        .extent = canonical-index<IndexType>(c_last - c_first),
        .stride = cw<IndexType(1)>
    };
    return canonical-slice-range<IndexType>{
        c_first,
        canonical-index<IndexType>(c_last - c_first);
    };
}
```

Apply following changes to section [mdspan.sub.extents] submdspan_extents function:

```
template<class IndexType, size_t... Extents, class... SliceSpecifiers>
constexpr auto submdspan_extents(const extents<IndexType, Extents...>& src,
```

SliceSpecifiers... raw_slices);

- 1- Let slices be [...];
- 2- Constraints: [...];
- 3- Mandates: [...];
- 4- Preconditions: [...];
- 5- Let SubExtents be a specialization of extents such that:
 - -5.1- SubExtents::rank() equals `MAP_RANK(slices, Extents::rank())`; and;
 - -5.2- for each rank index k of `Extents extents<IndexType, Extents...>` such that the type of `slices...[k]` is not a collapsing slice type, SubExtents::static_extent(`MAP_RANK(slices, k)`) equals the following, where Σ_k denotes the type of `slices...[k]`:
 - -5.2.1- Extents::static_extent(k) if Σ_k denotes the full_extent_t; otherwise
 - ~~-5.2.2- 0, if Σ_k is a specialization of strided_slice and $\Sigma_k::extent_type$ denotes constant_wrapper<IndexType(0)>; otherwise~~
 - -5.2.3- ~~$1 + ((\Sigma_k::extent_type::value - 1) / \Sigma_k::stride_type::value)$~~ $\Sigma_k::extent_type::value$ if Σ_k is a specialization of strided_slice whose extent_type and stride_type denotes a specialization of constant_wrapper;
 - -5.2.4- otherwise, dynamic_extent.
- 6- Returns: A value ext of type SubExtents such that for each index k of `extents<IndexType, Extents...>`, where the type of `slices...[k]` is not a collapsing slice type, `ext.extent(MAP_RANK(slices, k))` equals the following where σ_k denotes `slices...[k]`:
 - -6.1- ~~$\sigma_k.extent == 0 ? 0 : 1 + (\sigma_k.extent - 1) / \sigma_k.stride$~~ if the type of σ_k is a specialization of strided_slice,
 - -6.2- otherwise, $U-L$, where $[L, U)$ is the submdspan slice range of σ_k for the k^{th} extent of src.

Apply following changes to section [mdspan.sub.map.common] Common:

- 6- Let sub_strides be an array<SubExtents::index_type, SubExtents::rank(>) such that for each rank index k of `extents()` for which the type of `slices...[k]` is not a collapsing slice type, `sub_strides[MAP_RANK(slices,k)]` equals:
 - -6.1- `stride(k) * s.stride` if type of s is a specialization of strided_slice and ~~`s.stride < s.extent`~~ `s.extent > 1` is true, where s is `slices...[k]`;
 - -6.2- otherwise, `stride(k)`.

Replace all occurrences of `strided_slice` and `is-strided-slice` in [mdspan.syn] and [mdspan.sub] with `extent_slice` and `is-extent-slice` respectively.

Update the value of the `__cpp_lib_submdspan` in [version.syn] Header <version> synopsis to reflect the date of approval of this proposal.

7. Acknowledgements

Christian Trott and Charles Hussong offered many useful suggestions and corrections to the proposal.

8. References

1. Poland, "PL007 23.7.3.7 [mdspan.sub] [mdspan.sub] Define the extent member of the strided_slice", (PL007, <https://github.com/cplusplus/nballot/issues/816>)
2. Tomasz Kamiński, "[RFC v2 0/4] libstdc++: Implement P3982R1 range_slice and", (<https://gcc.gnu.org/pipermail/libstdc++/2026-March/065843.html>)
3. Christian Trott, Damien Lebrun-Grandie, Mark Hoemmen, Nevin Liber "Submdspan", (P2630R4, <https://www.open-std.org/jtc1/sc22/wg21/docs/papers/2023/p2630r4.html>)

4. Thomas Köppe, "Working Draft, Standard for Programming Language C++" (N5032, <https://wg21.link/n5032>)