

P0260R10

C++ Concurrent Queues

Published Proposal, 2024-06-26

This version:

<http://wg21.link/P0260R10>

Authors:

Lawrence Crowl

Chris Mysisen

[Detlef Vollmann](#)

Gor Nishanov

Audience:

SG1, LEWG

Project:

ISO/IEC 14882 Programming Languages — C++, ISO/IEC JTC1/SC22/WG21

Source:

gitlab.com/cppz/papers/-/blob/main/source/P0260R10.bs

Abstract

Concurrent queues are a fundamental structuring tool for concurrent programs. We propose concurrent queue concepts and a concrete implementation.

Table of Contents

1	Acknowledgments
2	Revision History
2.1	Discussion Points For This Revision
2.1.1	Discussion Points For SG1
2.1.2	Discussion Points For LEWG

3 Introduction

4 Existing Practice

- 4.1 Concept of a Bounded Queue
- 4.2 Bounded Queues with C++ Interface
 - 4.2.1 Literature
 - 4.2.2 Boost
 - 4.2.3 TBB

5 Conceptual Interface

- 5.1 Error Class
- 5.2 Basic Operations
- 5.3 Asynchronous Operations
- 5.4 Non-Waiting Operations
- 5.5 Closed Queues
- 5.6 Element Type Requirements
- 5.7 Exception Handling

6 Concrete Queues

7 Proposed Wording

- 7.1 Concurrent Queues
 - 7.1.1 General
 - 7.1.2 Header `<experimental/conqueue>` synopsis
 - 7.1.3 Error reporting
 - 7.1.4 Class `conqueue_error`
 - 7.1.5 Basic Concurrent Queue Concept
 - 7.1.6 Concurrent Queue Concept
 - 7.1.7 Asynchronous Queue Concept
 - 7.1.8 Class template `bounded_queue`
 - 7.1.8.1 General
 - 7.1.8.2 Constructor
 - 7.1.8.3 Modifiers

8 Old Revision History

9 Implementation

10 Historic Contents

10.1 Abandoned Interfaces

10.1.1 Re-opening a Queue

10.1.2 Non-Blocking Operations

10.1.3 Push Front Operations

10.1.4 Queue Names

10.1.5 Lock-Free Buffer Queue

10.1.6 Storage Iterators

10.1.7 Empty and Full Queues

10.1.8 Queue Ordering

10.1.9 Lock-Free Implementations

10.2 Abandoned Additional Conceptual Tools

10.2.1 Fronts and Backs

10.2.2 Streaming Iterators

10.2.3 Binary Interfaces

10.2.4 Managed Indirection

10.3 `try_push(T&&, T&)`

References

Informative References

§ 1. Acknowledgments

Thanks to David Goldblatt for his help with the wording!

§ 2. Revision History

This paper revises P0260R9 - 2024-05-19 as follows.

- Implement feedback from SG1 in St. Louis:
- Split concept into three
- Require `try_*` to be lockfree (w/ error code `busy`)

- Drop `is_always_lock_free`
- Drop `capacity()`
- Removed discussion points for SG1
- Removed TS ship vehicle
- General cleanup in the design part

P0260R9 revises P0260R8 - 2024-03-08 as follows.

- Added more wording
- Fixed `capacity`
- Changed push/pop wording to use "strongly happens before"
- Added discussion points
- Removed paragraph about ctors/dtors returning on same thread
- `try_*` now never blocks (even for contention on internal synchronization)
- Wording for spurious failures of `try_*`
- The constructors for `bounded_queue` that pre-fill the queue have been removed
- Reference to P3282 added
- Moved discussion about `try_push(T &&, T &)` to historic contents.

P0260R8 revises P0260R7 - 2023-06-15 as follows.

- Restructured document
- Fix typos
- Implement LEWG feedback to derive `conqueue_errc` from `system_error`
- Implement LEWG feedback to add range constructor and go back to `InputIterator`
- `size_t capacity()` added
- Added TBB `concurrent_bounded_queue` as existing practice
- Moved discussion about `pop()` interface to separate paper
- reintegrated P1958 `buffer_queue`
- Renamed `buffer_queue` to `bounded_queue`
- Added proposed wording (incomplete)
- Updated TS questions

Older revision history was moved to [after the proposed wording](#).

§ 2.1. Discussion Points For This Revision

§ 2.1.1. Discussion Points For SG1

§ 2.1.2. Discussion Points For LEWG

- `pop()` return: `optional` or `expected`? Other operations with `error_code`: return `expected`? This is *Exploring `std::expected` based API alternatives for `buffer_queue` (P2921)*.
- Are value initializing constructors required?
- A concurrent queue is not a container. Which of the requirements in `[container.reqmts]` should be met anyways (`value_type`, `reference`, `get_allocator()`, ...)?
- `async_*`: Is closed condition a stop condition or a special return or an error?

§ 3. Introduction

Queues provide a mechanism for communicating data between components of a system.

The existing `deque` in the standard library is an inherently sequential data structure. Its reference-returning element access operations cannot synchronize access to those elements with other queue operations. So, concurrent pushes and pops on queues require a different interface to the queue structure.

Moreover, concurrency adds a new dimension for performance and semantics. Different queue implementation must trade off uncontended operation cost, contended operation cost, and element order guarantees. Some of these trade-offs will necessarily result in semantics weaker than a serial queue.

Concurrent queues come in a several different flavours, e.g.

- bounded vs. unbounded
- blocking vs. overwriting
- single-ended vs. multi-ended
- strict FIFO ordering vs. priority based ordering

The syntactic concepts proposed here should be valid for all of these flavours, while the concrete semantics might differ.

§ 4. Existing Practice

§ 4.1. Concept of a Bounded Queue

The basic concept of a bounded queue with potentially blocking push and pop operations is very old and widely used. It's generally provided as an operating system level facility, like other concurrency primitives.

POSIX 2001 has `mq` message queues (with priorities and timeout).

FreeRTOS, Mbed, vxWorks provide bounded queues.

§ 4.2. Bounded Queues with C++ Interface

§ 4.2.1. Literature

The first concurrent queue I've seen was in [\[Hughes97\]](#). It was full of bugs and as such shows what will go wrong if C++ doesn't provide a standard queue. It's unbounded.

Anthony Williams provided a queue in [C++ Concurrency in Action](#). It's unbounded.

§ 4.2.2. Boost

Boost has a number of queues, as official library and as example uses of synchronization primitives.

[*Boost Message Queue*](#) only transfers bytes, not objects. It's bounded.

[*Boost Lock-Free Queue*](#) and [*Boost Lock-Free SPSC Queue*](#) have only non-blocking operations.

[*Boost Lock-Free Queue*](#) is bounded or unbounded, [*Boost Lock-Free SPSC Queue*](#) is bounded.

[*Boost Synchronized Queue*](#) is an implementation of an early version of this proposal.

§ 4.2.3. TBB

TBB has `concurrent_bounded_queue` ([*TBB Bounded Queue*](#)) and an unbounded version `concurrent_queue` [*TBB Unbounded Queue*](#).

§ 5. Conceptual Interface

We provide basic queue operations, and then extend those operations to cover other important use cases.

Due to performance issues, the conceptual interface is split into three separate interfaces. The `basic_concurrent_queue` concept provides the interface `push` and `pop` and closing the queue. The `concurrent_queue` concept is based on `basic_concurrent_queue` and provides the additional interface `try_push` and `try_pop`. The `async_concurrent_queue` concept is also based on `basic_concurrent_queue` provides the additional interface `async_push` and `async_pop`.

The concrete queue `bounded_queue` models all these concepts.

§ 5.1. Error Class

By analogy with how `future` defines their errors, we introduce `conqueue_errc` enum and `conqueue_error`:

```
enum class conqueue_errc { empty, full, closed, busy };

const error_category& conqueue_category() noexcept;

class conqueue_error : public system_error;
```

§ 5.2. Basic Operations

The essential solution to the problem of concurrent queuing is to shift to value-based operations, rather than reference-based operations.

The basic operations are:

```
void queue::push(const T& x);
void queue::push(T&& x);
bool queue::push(const T& x, std::error_code& ec);
bool queue::push(T&& x, std::error_code& ec);
```

Pushes `x` onto the queue via copy or move construction (and possibly blocks). The first version throws `std::conqueue_error(conqueue_errc::closed)` if the queue is closed. The second version

returns `true` on success, and `false` and sets `ec` to `error_code(conqueue_errc::closed)` if the queue is closed.

```
T queue::pop();
std::optional<T> queue::pop(std::error_code& ec);
```

Pops a value from the queue via move construction into the return value. The first version throws `std::conqueue_error(conqueue_errc::closed)` if the queue is empty and closed; the second version, if the queue is empty and closed, returns `std::nullopt` and sets `ec` to `std::error_code(conqueue_errc::closed)`. If queue is empty and open, the operation blocks until an element is available.

The exploration of different version of error reporting was moved to a separate paper [\[P2921R0\]](#).

§ 5.3. Asynchronous Operations

```
sender auto queue::async_push(T x);
sender auto queue::async_pop();
```

These operations return a sender that will push or pop the element. Senders must support cancellation and if the receiver is currently waiting on a push or pop operation and no longer interested in performing the operation, it should be removed from any waiting queues, if any, and be completed with `std::execution::set_stopped`.

§ 5.4. Non-Waiting Operations

Waiting on a full or empty queue can take a while, which has an opportunity cost. Avoiding that wait enables algorithms to avoid queuing speculative work when a queue is full, to do other work rather than wait for a push on a full queue, and to do other work rather than wait for a pop on an empty queue.

```
bool queue::try_push(const T& x, std::error_code& ec);
bool queue::try_push(T&& x, std::error_code& ec);
```

If the queue is full or closed, returns `false` and sets the respective status in the `ec`. Otherwise, push the value onto the queue via copy or move construction and returns `true`.

```
optional<T> queue::try_pop(std::error_code& ec);
```

If the queue is empty, returns `nullopt` and set `ec` to `conqueue_errc::empty`. Otherwise, pop the element from the queue via move construction into the optional. Return `true` and set `ec` to `conqueue_errc::success`.

These operations will never block. If they would have to wait for internal synchronization, they return `false` and set `ec` to `conqueue_errc::busy`.

§ 5.5. Closed Queues

Threads using a queue for communication need some mechanism to signal when the queue is no longer needed. The usual approach is add an additional out-of-band signal. However, this approach suffers from the flaw that threads waiting on either full or empty queues need to be woken up when the queue is no longer needed. To do that, you need access to the condition variables used for full/empty blocking, which considerably increases the complexity and fragility of the interface. It also leads to performance implications with additional mutexes or atomics. Rather than require an out-of-band signal, we chose to directly support such a signal in the queue itself, which considerably simplifies coding.

To achieve this signal, a thread may `close` a queue. Once closed, no new elements may be pushed onto the queue. Push operations on a closed queue will either return `conqueue_errc::closed` (when they have `ec` parameter) or throw `conqueue_error(conqueue_errc::closed)` (when they do not). Elements already on the queue may be popped off. When a queue is empty and closed, pop operations will either set `ec` to `conqueue_errc::closed` (when they have a `ec` parameter) or throw `conqueue_error(conqueue_errc::closed)` otherwise.

The additional operations are as follows:

```
void queue::close() noexcept;
```

Close the queue.

```
bool queue::is_closed() const noexcept;
```

Return true iff the queue is closed.

§ 5.6. Element Type Requirements

The above operations require element types with copy/move constructors, and destructor. These operations may be trivial. The copy/move constructors operators may throw, but must leave the objects in a valid state for subsequent operations.

§ 5.7. Exception Handling

`push()` and `pop()` may throw an exceptions of type `conqueue_error` that's derived from `std::system_error` and will contain a `conqueue_errc`.

Concurrent queues cannot completely hide the effect of exceptions thrown by the element type, in part because changes cannot be transparently undone when other threads are observing the queue.

Queues may rethrow exceptions from storage allocation, mutexes, or condition variables.

If the [element type operations required](#) do not throw exceptions, then only the exceptions above are rethrown.

When an element copy/move may throw, some queue operations have additional behavior.

- A push operation shall rethrow and the state of the queue is unaffected.
- A pop operation shall rethrow and the element is popped from the queue. The value popped is effectively lost. (Doing otherwise would likely clog the queue with a bad element.)

§ 6. Concrete Queues

In addition to the concepts, the standard needs at least one concrete queue. This paper proposes a fixed-size `bounded_queue`. It meets both concepts for queues. The constructor takes a parameter specifying the maximum number of elements in the queue and an optional allocator.

`bounded_queue` is only allowed to allocate in its constructor.

[Static Storage for C++ Concurrent bounded_queue \(P3282\)](#) proposes to add a constructor where the queue doesn't own the storage.

§ 7. Proposed Wording

Add a new subclause to clause **[thread]** with the following contents.

§ 7.1. Concurrent Queues

§ 7.1.1. General

Concurrent queues provide a mechanism to transfer objects from one point in a program to another without producing data races.

§ 7.1.2. Header `<experimental/conqueue>` synopsis

```
namespace std::experimental {
    template <class T, class Q>
        concept basic_concurrent_queue = see below;
        concept concurrent_queue = see below;
        concept async_concurrent_queue = see below;

    enum class conqueue_errc {
        empty = implementation-defined,
        full = implementation-defined,
        closed = implementation-defined,
        busy = implementation-defined
    };

    template<> struct is_error_code_enum : public true_type { };
    const error_category& conqueue_category() noexcept;
    error_code make_error_code(conqueue_errc e) noexcept;
    error_condition make_error_condition(conqueue_errc e) noexcept;

    class conqueue_error;

    template <typename T, class Allocator = std::allocator<T>>
        class bounded_queue;
}
```

§ 7.1.3. Error reporting

```
const error_category& conqueue_category() noexcept;
```

1. *Returns:* A reference to an object of a type derived from class `error_category`.
2. The object's `default_error_condition` and `equivalent` virtual functions shall behave as specified for the class `error_category`. The object's `name` virtual function shall return a pointer to the string "conqueue".

```
error_code make_error_code(conqueue_errc e) noexcept;
```

3. *Returns:* `error_code(static_cast<int>(e), conqueue_category())`.

```
error_condition make_error_condition(conqueue_errc e) noexcept;
```

4. *Returns:* `error_condition(static_cast<int>(e), conqueue_category())`.

§ 7.1.4. Class `conqueue_error`

```
namespace std::experimental {  
    class conqueue_error : system_error {  
    public:  
        explicit conqueue_error(conqueue_errc e);  
  
        const error_code& code() const noexcept;  
        const char * what() const noexcept;  
  
    private:  
        error_code ec_;           // exposition only  
    };  
}
```

```
explicit conqueue_error(conqueue_errc e);
```

1. *Effects*: Initializes `ec_` with `make_error_code(e)`.

```
const error_code& code() const noexcept;
```

2. *Returns*: `ec_`.

```
const char * what() const noexcept;
```

3. *Returns*: An `NTBS` incorporating `code().message()`.

§ 7.1.5. Basic Concurrent Queue Concept

1. The `basic_concurrent_queue` concept defines the requirements for a basic queue type.

```
namespace std::experimental {  
    template <class T, class Q>  
        concept basic_concurrent_queue =  
            move_constructible<remove_cvref_t<T>> &&  
            same_as<decay_t<T>, Q::value_type> &&  
            requires (Q q, T &&t, std::error_code ec) {  
                q.is_closed() noexcept -> bool;  
                q.close() noexcept -> void;  
                q.push(std::forward<T>(t)) -> void;  
                q.push(std::forward<T>(t), ec) -> bool;  
                q.pop() -> T;  
                q.pop(ec) -> std::optional<T>;  
            };  
}
```

2. In the following description, `Q` denotes a type conforming to the `basic_concurrent_queue` concept, `q` denotes an object of type `Q`, `t` denotes an object convertible to `Q::value_type` and `ec` denotes an object of type `std::error_code`.
3. The expression `q.is_closed()` has the following semantics:
 1. *Returns*: `true` iff the queue is closed.
4. The expression `q.close()` has the following semantics:
 1. *Effects*: Closes the queue.

5. `push` is a *push operation* and `pop` is a *pop operation*.
6. Concepts that subsume `queue_base` may have additional push and pop operations.
7. Successful push and pop operations will call a constructor of `T`. For the description of concrete queues, *pre-ctor* is the call of the constructor and *post-ctor* is the return of the constructor. Likewise successful pop operations will call the destructor of `T` and we have *pre-dtor* and *post-dtor*.
8. If an object is *deposited* into a queue by a push operation it can be *extracted* from the queue and returned by a pop operation. The *post-ctor* of the push operation of the deposit *strongly happens before* the return of the pop operation. A pop operation on a queue can only extract objects that were deposited into the same queue and each object can only be extracted once.
9. Concrete queues shall specify whether a push may block for space available in the queue (bounded queue) or whether a push may allocate new space (unbounded queue).
10. The expression `q.push(t)` has the following semantics:
 1. *Effects*: If the queue is not closed, `t` is deposited into `q`.
 2. *Throws*: If the queue is closed throw `conqueue_error(conqueue_errc::closed)`. A concrete queue may throw additional exceptions.
11. The expression `q.push(t, ec)` has the following semantics:
 1. *Effects*: If the queue is not closed, `t` is deposited into `q`.
 2. *Returns*:
 - `true` if `t` was deposited into `q`; `false` otherwise.
 3. *Error conditions*:
 - `closed` if the queue is closed.
12. The expression `q.pop()` has the following semantics:
 1. *Effects*: Blocks the current thread until there's an object available in the queue or until the queue is closed. If the queue is closed, throw. Otherwise, if there is an object available in the queue, extract the object and return it.
 2. *Returns*: the available object in the queue.
 3. *Throws*: If the queue is closed throw `conqueue_error(conqueue_errc::closed)`. A concrete queue may throw additional exceptions.
13. The expression `q.pop(ec)` has the following semantics:

1. *Effects*: Blocks the current thread until there's an object available in the queue or until the queue is closed. If there is an object available in the queue, extract the object and return it.
2. *Returns*: `optional<T>(t)` if `t` was the available object in the queue, `optional<T>{}` otherwise.
3. *Error conditions*:
 - `closed` if the queue is closed.

§ 7.1.6. Concurrent Queue Concept

1. The `concurrent_queue` concept defines the requirements for a concurrent queue type.

```
namespace std::experimental {  
    template <class T, class Q>  
        concept concurrent_queue =  
            basic_concurrent_queue<T> &&  
            requires (Q q, T &&t, std::error_code ec) {  
                q.try_push(std::forward<T>(t), ec) -> bool;  
                q.try_pop(ec) -> std::optional<T>;  
            };  
}
```

2. In the following description, `Q` denotes a type conforming to the `concurrent_queue` concept, `q` denotes an object of type `Q`, `t` denotes an object convertible to `Q::value_type` and `ec` denotes an object of type `std::error_code`.
3. `try_push` is a push operation and `try_pop` is a pop operation.
4. In classes modelling this concept `try_push` may return `false` even if the queue has space for the element. Similarly `try_pop` may return `false` even if the queue has an element to be extracted. [Note: This spurious failure is normally uncommon. -- end note] An implementation should ensure that `try_push()` and `try_pop()` do not consistently spuriously fail.
5. The expression `q.try_push(t, ec)` has the following semantics:
 1. *Effects*: If the queue is not closed, and space is available in the queue, `t` is deposited into `q`. The operation will not block.
 2. *Returns*:
 - `true` if `t` was deposited into `q`; `false` otherwise.

3. Error conditions:

- `closed` if the queue is closed.
- `full` if the queue doesn't have space.
- `busy` if the operation would block for internal synchronization.

6. The expression `q.try_pop(ec)` has the following semantics:

1. *Effects:* If there's an object available in the queue it will be extracted from the queue and returned. If the queue is closed an empty `optional` is returned. The operation will not block.
2. *Returns:* `optional<T>(t)` if `t` was the available object in the queue, `optional<T>{}` otherwise.

3. Error conditions:

- `closed` if the queue is closed.
- `empty` if the queue doesn't have an element.
- `busy` if the operation would block for internal synchronization.

§ 7.1.7. Asynchronous Queue Concept

1. The `async_concurrent_queue` concept defines the requirements for an asynchronous queue type.

```
namespace std::experimental {
    template <class T, class Q>
    concept async_concurrent_queue =
        basic_concurrent_queue<T> &&
        requires (Q q, T &&t, std::error_code ec) {
            q.async_push(std::forward<T>(t)) -> std::execution::sender_of
            q.async_pop() -> std::execution::sender_of<T>;
        };
}
```

2. In the following description, `Q` denotes a type conforming to the `async_concurrent_queue` concept, `q` denotes an object of type `Q` and `t` denotes an object convertible to `Q::value_type`.
3. `async_push` is a push operation and `async_pop` is a pop operations.
4. The expression `q.async_push(t)` has the following semantics:

1. *Returns:* A sender object `w` that behaves as follows:

1. When `w` is connected with some receiver `r`, it returns an operation state `op` that behaves as follows:

1. It waits until there's space in the queue or until the queue is closed.
2. If there's space in the queue `t` will be deposited into the queue and `set_value(r)` will be called.
3. If the queue is closed `set_stopped(r)` will be called.

5. The expression `q.async_pop()` has the following semantics:

1. *Returns:* A sender object `w` that behaves as follows:

1. When `w` is connected with some receiver `r`, it returns an operation state `op` that behaves as follows:

1. It waits until there's an object available in the queue or until the queue is closed.
2. If there's an object `t` available in the queue it will be extracted and `set_value(r, t)` will be called.
3. If the queue is closed `set_stopped(r)` will be called.

§ 7.1.8. Class template `bounded_queue`

§ 7.1.8.1. General

1. A `bounded_queue` models `concurrent_queue` and `async_concurrent_queue` and can hold a fixed size of objects which is given at construction time.

```
2. template <typename T,
    class Allocator = std::allocator<T>>
class bounded_queue
{
    bounded_queue() = delete;
    bounded_queue(const bounded_queue&) = delete;
    bounded_queue& operator=(const bounded_queue&) = delete;

public:
    typedef T value_type;
```

```

// construct/destroy
explicit bounded_queue(size_t max_elems, const Allocator& alloc = All

~bounded_queue() noexcept;

// observers
bool is_closed() const noexcept;

// modifiers
void close() noexcept;

void push(const T& x);
void push(T&& x);
bool push(const T& x, std::error_code& ec);
bool push(T&& x, std::error_code& ec);
bool try_push(const T& x, std::error_code& ec);
bool try_push(T&& x, std::error_code& ec);
sender auto async_push(const T&);
sender auto async_push(T&&);

T pop();
optional<T> pop(std::error_code& ec);
optional<T> try_pop(std::error_code& ec);
sender auto async_pop();
};

```

§ 7.1.8.2. Constructor

```
explicit bounded_queue(size_t max_elems, const Allocator& alloc = Allocator
```

3. *Effects*: Constructs an object with no elements, but with storage for `max_elems`. The storage for the elements will be allocated using `alloc`.
4. *Remarks*: The operations of `bounded_queue` will not allocate any memory outside the constructor.

§ 7.1.8.3. Modifiers

```
void push(const T& x);
void push(T&& x);
bool push(const T& x, std::error_code& ec);
bool push(T&& x, std::error_code& ec);
```

5. *Effects*: Blocks the current thread until there's space in the queue or until the queue is closed.
6. Let *Push1* and *Push2* be push operations and *Pop1* and *Pop2* be pop operations, where *Pop1* returns the value of the parameter given to *Push1* and *Pop2* returns the value of the parameter given to *Push2*, then there is a total order consistent with `memory_order::seq_cst` of *pre-ctor*, *post-ctor*, *pre-dtor* and *post-dtor* of *Push1*, *Push2*, *Pop1* and *Pop2*, and moreover if *post-ctor* of *Push1* is before *post-ctor* of *Push2* in the order, then *pre-ctor* of *Pop1* strongly happens before *pre-ctor* of *Pop2*.
7. [Note: This guarantees FIFO behaviour, but for two concurrent pushes the constructors can not determine the order in which the values are enqueued, and the constructors can run concurrently as well. -- end note]
8. [Note: This does not guarantee that constructors or destructors may ever run concurrently. An implementation may decide that two pushes (or to pops) never run concurrently. -- end note]
9. [Note: A constructor can deadlock if it tries a push or pop on the same queue. -- end note]

```
T pop();
optional<T> pop(std::error_code&);
optional<T> try_pop(std::error_code&);
sender auto async_pop();
```

10. *Remarks*: The constructor of the returned object and the destructor of the internal object run on the same thread of execution.

§ 8. Old Revision History

P0260R6 revises P0260R5 - 2023-01-15 as follows.

- Fixing typos.
- Added a scope for the target TS.
- Added questions to be answered by a TS.

- Added asynchronous interface

P0260R5 revises P0260R4 - 2020-01-12 as follows.

- Added more introductory material.
- Added response to feedback by LEWGI at Prague meeting 2020.
- Added section on existing practice.
- Replaced `value_pop` with `pop`.
- Replaced `is_lock_free` with `is_always_lockfree`.
- Removed `is_empty` and `is_full`.
- Added move-into parameter to `try_push(Element&&)`
- Added note that exception thrown by the queue operations themselves are derived from `std::exception`.
- Added a note that the wording is partly invalid.
- Moved more contents into the "Abandoned" part to avoid confusion.

P0260R4 revised P0260R3 - 2019-01-20 as follows.

- Remove the binding of `queue_op_status::success` to a value of zero.
- Correct stale use of the `Queue` template parameter in `shared_queue_front` to `Value`.
- Change the return type of `share_queue_ends` from a `pair` to a custom struct.
- Move the concrete queue proposal to a separate paper, [\[P1958\]](#).

P0260R3 revised P0260R2 - 2017-10-15 as follows.

- Convert `queue_wrapper` to a `function`-like interface. This conversion removes the `queue_base` class. Thanks to Zach Lane for the approach.
- Removed the requirement that element types have a default constructor. This removal implies that statically sized buffers cannot use an array implementation and must grow a vector implementation to the maximum size.
- Added a discussion of checking for output iterator end in the wording.
- Fill in synopsis section.
- Remove stale discussion of `queue_owner`.
- Move all abandoned interface discussion to a new section.
- Update paper header to current practice.

P0260R2 revised P0260R1 - 2017-02-05 as follows.

- Emphasize that non-blocking operations were removed from the proposed changes.
- Correct syntax typos for `noexcept` and template alias.
- Remove `static` from `is_lock_free` for `generic_queue_back` and `generic_queue_front`.

P0260R1 revised P0260R0 - 2016-02-14 as follows.

- Remove pure virtuals from `queue_wrapper`.
- Correct `queue::pop` to `value_pop`.
- Remove nonblocking operations.
- Remove non-locking buffer queue concrete class.
- Tighten up push/pop wording on closed queues.
- Tighten up push/pop wording on synchronization.
- Add note about possible non-FIFO behavior.
- Define `buffer_queue` to be FIFO.
- Make wording consistent across attributes.
- Add a restriction on element special methods using the queue.
- Make `is_lock_free()` for only non-waiting functions.
- Make `is_lock_free()` static for non-indirect classes.
- Make `is_lock_free()` `noexcept`.
- Make `has_queue()` `noexcept`.
- Make destructors `noexcept`.
- Replace "throws nothing" with `noexcept`.
- Make the remarks about the usefulness of `is_empty()` and `is_full` into notes.
- Make the non-static member functions `is_...` and `has_...` functions `const`.

P0260R0 revised N3533 - 2013-03-12 as follows.

- Update links to source code.
- Add wording.
- Leave the name facility out of the wording.

- Leave the push-front facility out of the wording.
- Leave the reopen facility out of the wording.
- Leave the storage iterator facility out of the wording.

N3532 revised N3434 = 12-0043 - 2012-01-14 as follows.

- Add more exposition.
- Provide separate non-blocking operations.
- Add a section on the lock-free queues.
- Argue against push-back operations.
- Add a cautionary note on the usefulness of `is_closed()`.
- Expand the cautionary note on the usefulness of `is_empty()`. Add `is_full()`.
- Add a subsection on element type requirements.
- Add a subsection on exception handling.
- Clarify ordering constraints on the interface.
- Add a subsection on a lock-free concrete queue.
- Add a section on content iterators, distinct from the existing streaming iterators section.
- Swap front and back names, as requested.
- General expository cleanup.
- Add an "Revision History" section.

N3434 revised N3353 = 12-0043 - 2012-01-14 as follows.

- Change the inheritance-based interface to a pure conceptual interface.
- Put `try_...` operations into a separate subsection.
- Add a subsection on non-blocking operations.
- Add a subsection on push-back operations.
- Add a subsection on queue ordering.
- Merge the "Binary Interface" and "Managed Indirection" sections into a new "Conceptual Tools" section. Expand on the topics and their rationale.
- Add a subsection to "Conceptual Tools" that provides for type erasure.
- Remove the "Synopsis" section.

- Add an "Implementation" section.

§ 9. Implementation

An implementation is available at github.com/GorNishanov/conqueue.

A free, open-source implementation of an earlier version of these interfaces is available at the Google Concurrency Library project at github.com/aldasdairmackintosh/google-concurrency-library. The original `buffer_queue` is in [../blob/master/include/buffer_queue.h](https://github.com/aldasdairmackintosh/google-concurrency-library/blob/master/include/buffer_queue.h). The concrete `lock_free_buffer_queue` is in [../blob/master/include/lock_free_buffer_queue.h](https://github.com/aldasdairmackintosh/google-concurrency-library/blob/master/include/lock_free_buffer_queue.h). The corresponding implementation of the conceptual tools is in [../blob/master/include/queue_base.h](https://github.com/aldasdairmackintosh/google-concurrency-library/blob/master/include/queue_base.h).

§ 10. Historic Contents

The Contents in this section is for historic reference only.

§ 10.1. Abandoned Interfaces

§ 10.1.1. Re-opening a Queue

There are use cases for opening a queue that is closed. While we are not aware of an implementation in which the ability to reopen a queue would be a hardship, we also imagine that such an implementation could exist. Open should generally only be called if the queue is closed and empty, providing a clean synchronization point, though it is possible to call open on a non-empty queue. An open operation following a close operation is guaranteed to be visible after the close operation and the queue is guaranteed to be open upon completion of the open call. (But of course, another close call could occur immediately thereafter.)

```
void queue::open();
```

Open the queue.

Note that when `is_closed()` returns false, there is no assurance that any subsequent operation finds the queue closed because some other thread may close it concurrently.

If an open operation is not available, there is an assurance that once closed, a queue stays closed. So, unless the programmer takes care to ensure that all other threads will not close the queue, only a return value of true has any meaning.

Given these concerns with reopening queues, we do not propose wording to reopen a queue.

§ 10.1.2. Non-Blocking Operations

For cases when blocking for mutual exclusion is undesirable, one can consider non-blocking operations. The interface is the same as the try operations but is allowed to also return `queue_op_status::busy` in case the operation is unable to complete without blocking.

```
queue_op_status queue::nonblocking_push(const Element&);\ queue_op_status  
queue::nonblocking_push(Element&&);
```

If the operation would block, return `queue_op_status::busy`. Otherwise, if the queue is full, return `queue_op_status::full`. Otherwise, push the `Element` onto the queue. Return `queue_op_status::success`.

```
queue_op_status queue::nonblocking_pop(Element&);
```

If the operation would block, return `queue_op_status::busy`. Otherwise, if the queue is empty, return `queue_op_status::empty`. Otherwise, pop the `Element` from the queue. The element will be moved out of the queue in preference to being copied. Return `queue_op_status::success`.

These operations will neither wait nor block. However, they may do nothing.

The non-blocking operations highlight a terminology problem. In terms of synchronization effects, `nonwaiting_push` on queues is equivalent to `try_lock` on mutexes. And so one could conclude that the existing `try_push` should be renamed `nonwaiting_push` and `nonblocking_push` should be renamed `try_push`. However, at least Thread Building Blocks uses the existing terminology. Perhaps better is to not use `try_push` and instead use `nonwaiting_push` and `nonblocking_push`.

****In November 2016, the Concurrency Study Group chose to defer non-blocking operations. Hence, the proposed wording does not include these functions. In addition, as these functions were the only ones that returned `busy`, that enumeration is also not included.****

§ 10.1.3. Push Front Operations

Occasionally, one may wish to return a popped item to the queue. We can provide for this with `push_front` operations.

```
void queue::push_front(const Element&);\ void queue::push_front(Element&&);
```

Push the **Element** onto the back of the queue, i.e. in at the end of the queue that is normally popped. Return **queue_op_status::success**.

```
queue_op_status queue::try_push_front(const Element&);\ queue_op_status  
queue::try_push_front(Element&&);
```

If the queue was full, return **queue_op_status::full**. Otherwise, push the **Element** onto the front of the queue, i.e. in at the end of the queue that is normally popped. Return **queue_op_status::success**.

```
queue_op_status queue::nonblocking_push_front(const Element&);\  
queue_op_status queue::nonblocking_push_front(Element&&);
```

If the operation would block, return **queue_op_status::busy**. Otherwise, if the queue is full, return **queue_op_status::full**. Otherwise, push the **Element** onto the front queue. i.e. in at the end of the queue that is normally popped. Return **queue_op_status::success**.

This feature was requested at the Spring 2012 meeting. However, we do not think the feature works.

- The name **push_front** is inconsistent with existing \"push back\" nomenclature.
- The effects of **push_front** are only distinguishable from a regular push when there is a strong ordering of elements. Highly concurrent queues will likely have no strong ordering.
- The **push_front** call may fail due to full queues, closed queues, etc. In which case the operation will suffer contention, and may succeed only after interposing push and pop operations. The consequence is that the original push order is not preserved in the final pop order. So, **push_front** cannot be directly used as an 'undo'.
- The operation implies an ability to reverse internal changes at the front of the queue. This ability implies a loss efficiency in some implementations.

In short, we do not think that in a concurrent environment **push_front** provides sufficient semantic value to justify its cost. Consequently, the proposed wording does not provide this feature.

§ 10.1.4. Queue Names

It is sometimes desirable for queues to be able to identify themselves. This feature is particularly helpful for run-time diagnostics, particularly when 'ends' become dynamically passed around between threads. See [Managed Indirection](#).

```
const char* queue::name();
```

Return the name string provided as a parameter to queue construction.

There is some debate on this facility, but we see no way to effectively replicate the facility. However, in recognition of that debate, the wording does not provide the name facility.

§ 10.1.5. Lock-Free Buffer Queue

We provide a concrete concurrent queue in the form of a fixed-size `lock_free_buffer_queue`. It meets the `NonWaitingConcurrentQueue` concept. The queue is still under development, so details may change.

In November 2016, the Concurrency Study Group chose to defer lock-free queues. Hence, the proposed wording does not include a concrete lock-free queue.

§ 10.1.6. Storage Iterators

In addition to iterators that stream data into and out of a queue, we could provide an iterator over the storage contents of a queue. Such an iterator, even when implementable, would mostly likely be valid only when the queue is otherwise quiescent. We believe such an iterator would be most useful for debugging, which may well require knowledge of the concrete class. Therefore, we do not propose wording for this feature.

§ 10.1.7. Empty and Full Queues

It is sometimes desirable to know if a queue is empty.

```
bool queue::is_empty() const noexcept;
```

Return true iff the queue is empty.

This operation is useful only during intervals when the queue is known to not be subject to pushes and pops from other threads. Its primary use case is assertions on the state of the queue at the end of its lifetime, or when the system is in quiescent state (where there are no outstanding pushes).

We can imagine occasional use for knowing when a queue is full, for instance in system performance polling. The motivation is significantly weaker though.

```
bool queue::is_full() const noexcept;
```

Return true iff the queue is full.

Not all queues will have a full state, and these would always return false.

§ 10.1.8. Queue Ordering

The conceptual queue interface makes minimal guarantees.

- The queue is not empty if there is an element that has been pushed but not popped.
- A push operation *synchronizes with* the pop operation that obtains that element.
- A close operation *synchronizes with* an operation that observes that the queue is closed.
- There is a sequentially consistent order of operations.

In particular, the conceptual interface does not guarantee that the sequentially consistent order of element pushes matches the sequentially consistent order of pops. Concrete queues could specify more specific ordering guarantees.

§ 10.1.9. Lock-Free Implementations

Lock-free queues will have some trouble waiting for the queue to be non-empty or non-full. Therefore, we propose two closely-related concepts. A full concurrent queue concept as described above, and a non-waiting concurrent queue concept that has all the operations except `push`, `wait_push`, `value_pop` and `wait_pop`. That is, it has only non-waiting operations (presumably emulated with busy wait) and non-blocking operations, but no waiting operations. We propose naming these `WaitingConcurrentQueue` and `NonWaitingConcurrentQueue`, respectively.

NOTE: Adopting this conceptual split requires splitting some of the facilities defined later.

For generic code it's sometimes important to know if a concurrent queue has a lock free implementation.

```
constexpr static bool queue::is_always_lock_free() noexcept;
```

Return true iff the has a lock-free implementation of the non-waiting operations.

§ 10.2. Abandoned Additional Conceptual Tools

There are a number of tools that support use of the conceptual interface. These tools are not part of the queue interface, but provide restricted views or adapters on top of the queue useful in implementing concurrent algorithms.

§ 10.2.1. Fronts and Backs

Restricting an interface to one side of a queue is a valuable code structuring tool. This restriction is accomplished with the classes `generic_queue_front` and `generic_queue_back` parameterized on the concrete queue implementation. These act as pointers with access to only the front or the back of a queue. The front of the queue is where elements are popped. The back of the queue is where elements are pushed.

```
void send( int number, generic_queue_back<buffer_queue<int>> arv );
```

These fronts and backs are also able to provide `begin` and `end` operations that unambiguously stream data into or out of a queue.

§ 10.2.2. Streaming Iterators

In order to enable the use of existing algorithms streaming through concurrent queues, they need to support iterators. Output iterators will push to a queue and input iterators will pop from a queue. Stronger forms of iterators are in general not possible with concurrent queues.

Iterators implicitly require waiting for the advance, so iterators are only supportable with the `WaitingConcurrentQueue` concept.

```
void iterate(  
    generic_queue_back<buffer_queue<int>>::iterator bitr,  
    generic_queue_back<buffer_queue<int>>::iterator bend,  
    generic_queue_front<buffer_queue<int>>::iterator fitr,  
    generic_queue_front<buffer_queue<int>>::iterator fend,  
    int (*compute)( int ) )  
{
```

```

while ( fitr != fend && bitr != bend )
    *bitr++ = compute(*fitr++);
}

```

Note that contrary to existing iterator algorithms, we check both iterators for reaching their end, as either may be closed at any time.

Note that with suitable renaming, the existing standard front insert and back insert iterators could work as is. However, there is nothing like a pop iterator adapter.

§ 10.2.3. Binary Interfaces

The standard library is template based, but it is often desirable to have a binary interface that shields client from the concrete implementations. For example, `std::function` is a binary interface to callable object (of a given signature). We achieve this capability in queues with type erasure.

We provide a `queue_base` class template parameterized by the value type. Its operations are virtual. This class provides the essential independence from the queue representation.

We also provide `queue_front` and `queue_back` class templates parameterized by the value types. These are essentially `generic_queue_front<queue_base<Value>>` and `generic_queue_back<queue_base<Value>>`, respectively.

To obtain a pointer to `queue_base` from an non-virtual concurrent queue, construct an instance the `queue_wrapper` class template, which is parameterized on the queue and derived from `queue_base`. Upcasting a pointer to the `queue_wrapper` instance to a `queue_base` instance thus erases the concrete queue type.

```

extern void seq_fill( int count, queue_back<int> b );

buffer_queue<int> body( 10 /*elements*/, /*named*/ "body" );
queue_wrapper<buffer_queue<int>> wrap( body );
seq_fill( 10, wrap.back() );

```

§ 10.2.4. Managed Indirection

Long running servers may have the need to reconfigure the relationship between queues and threads. The ability to pass '\ends\' of queues between threads with automatic memory management eases

programming.

To this end, we provide `shared_queue_front` and `shared_queue_back` template classes. These act as reference-counted versions of the `queue_front` and `queue_back` template classes.

The `share_queue_ends(Args ... args)` template function will provide a pair of `shared_queue_front` and `shared_queue_back` to a dynamically allocated `queue_object` instance containing an instance of the specified implementation queue. When the last of these fronts and backs are deleted, the queue itself will be deleted. Also, when the last of the fronts or the last of the backs is deleted, the queue will be closed.

```
auto x = share_queue_ends<buffer_queue<int>>>( 10, "shared" );
shared_queue_back<int> b(x.back());
shared_queue_front<int> f(x.front());
f.push(3);
assert(3 == b.value_pop());
```

§ 10.3. `try_push(T&&, T&)`

REVISITED in Varna

The following version was introduced in response to LEWG-I concerns about losing the element if an rvalue cannot be stored in the queue.

```
queue_op_status queue::try_push(T&&, T&);
```

However, SG1 reaffirmed the APIs above with the following rationale:

It seems that it is possible not to lose the element in both versions:

```
T x = get_something();
if (q.try_push(std::move(x))) ...
```

With two parameter version:

```
T x;
if (q.try_push(get_something(), x)) ...
```

Ergonomically they are roughly identical. API is slightly simpler with one argument version, therefore, we reverted to original one argument version.

§ References

§ Informative References

[BoostLFQ]

Boost Lock-Free Queue. URL:

https://www.boost.org/doc/libs/1_85_0/doc/html/boost/lockfree/queue.html

[BoostLFSPSCQ]

Boost Lock-Free SPSC Queue. URL:

https://www.boost.org/doc/libs/1_85_0/doc/html/boost/lockfree/spsc_queue.html

[BoostMQ]

Boost Message Queue. URL:

https://www.boost.org/doc/libs/1_85_0/doc/html/boost/interprocess/message_queue_t.html

[BoostSQ]

Boost Synchronized Queue. URL: https://www.boost.org/doc/libs/1_85_0/doc/html/thread/sd-s.html

[Hughes97]

Cameron Hughes; Tracey Hughes. *Object-Oriented Multithreading Using C++*.

[P1958]

C++ Concurrent Buffer Queue (P1958). URL: <https://wg21.link/P1958>

[P2921]

Exploring std::expected based API alternatives for buffer_queue (P2921). URL: <https://wg21.link/P2921>

[P2921R0]

Gor Nishanov, Detlef Vollmann. *Exploring std::expected based API alternatives for buffer_queue*. 5 July 2023. URL: <https://wg21.link/p2921r0>

[P3282]

Static Storage for C++ Concurrent bounded_queue (P3282). URL: <https://wg21.link/P3282>

[TBBQB]

TBB Bounded Queue. URL: https://spec.oneapi.io/versions/latest/elements/oneTBB/source/containers/concurrent_bounded_queue_cls.html

[TBBQUB]

TBB Unbounded Queue. URL:

https://spec.oneapi.io/versions/latest/elements/oneTBB/source/containers/concurrent_queue_-

[cls.html](#)

[Williams17]

Anthony Williams. *C++ Concurrency in Action*.