

Table of contents

- [Introduction and motivation](#)
- [Changes](#)
- [Previous polls](#)
- [Intention for wording changes](#)
 - [Question answered by SG1](#)
 - [Question for LEWG](#)
- [Example](#)
- [Proposed changes to wording](#)
 - [Feature test macro](#)
- [Implementation experience](#)
- [Impact on existing code](#)

constexpr atomic<T> and atomic_ref<T>

Introduction and motivation

This paper proposes marking most of `atomic<T>` methods and associated functions `constexpr` to allow usage of atomic code without changes in a `constexpr` and `constexpr` code.

Proposed changes will allow implementing other types (`std::shared_ptr<T>`, persistent data structures with atomic pointers) and algorithms (thread safe data-processing, like scanning data with atomic counter) with just sprinkling `constexpr` to their specification.

Changes

- [R0](#) → R1: Make `wait` and `notify` functions as requested by SG1. Wording changed accordingly. Updated link to implementation on Compiler Explorer.

Previous polls

SG1: Forward P3309 to LEWG with the following notes:

- *Add `constexpr` to the `wait` and `notify` functions in the next revision of P3309*
- *`atomic<shared_ptr>` should be supported in `constexpr` whenever `shared_ptr` is supported in `constexpr` (whichever paper lands second should have this change)*
- *`is_lock_free()` should not be made `constexpr`*

SF	F	N	A	SA
2	10	4	0	0