

Doc. no. P0085R3

Audience: EWG, LEWG

Date: 01-07-2025

Project: ISO JTC1/SC22/WG21: Programming Language C++, evolution group

Reply to: Jolly Chen <Jolly.Chen@cern.ch>, Axel Naumann <Axel.Naumann@cern.ch>, Michael Jonker <Michael.Jonker@cern.ch>,

Oo... adding a coherent character sequence to begin octal-literals

Revision History

Since [P0085R2](#)

- Replace broken unicode character with accent
- Update Wikipedia quote
- Fix octal value of none in Table 149 specification
- Do not look at `std::format` in this paper
- Wording changes

Since [P0085R1](#)

- Fix mismatch in technical specification of integer literals and lexical conventions
- Extend examples with common traps where octal-literals are assumed to be decimals by the programmer
- Extend effects on existing code
- Fix encoding of ' '

Since [P0085R0](#)

- Rebase Technical Specification onto [N5008](#)
- Align grammar with C's [N3353](#)
- Propose deprecation of original octal literal
- Remove proposed change "Technical Specification C run time library functions: `strtol`, `scanf`". This has been handled by C in [N3353](#).
- Remove proposed change to Addendum, character literals. Octals in escape sequences have been added by [P2290R3](#)
- Add open question on `std::format` with the `#` option for octal literals

Proposal

Proposal to **add** `0o` and `00` as an alternative (and preferred) sequence to introduce octal-literals and **deprecate** use of the old prefix `0` for non-zero octal-literals.

The syntax rule to interpret integer literals starting with a zero as octal-literals might be called a 'historical mistake'. It can be easily misunderstood by novice programmers and can lead to surprising errors.

To allow future generations (of developers if not compilers) to correct this feature, we propose to add the character sequence `0o` and `00` as preferred sequences to introduce an octal-literal. The prefix `0o` follows the

model set by the prefix `0x` to introduce a hex-literal, and (since c++14) `0b` to introduce a binary-literal.

Additionally, we propose to deprecate the use of octal integer literals with the `0` prefix, *apart from `0` itself*; this is similar to C declaring the use of nonzero octal integer literals without the prefix `0o` or `00` an obsolescent feature (see 6.11.5 in [C2y draft](#)). This opens the door for compilers to warn about the use of the deprecated `0` prefix, and eventually (on the scale of a few releases), potentially interpret numbers with leading zeroes as decimals.

From <http://en.wikipedia.org/wiki/Octal/en.wikipedia.org/wiki/Octal>: "*Newer languages have been abandoning the prefix `0`, as decimal numbers are often represented with leading zeroes. The prefix `q` was introduced to avoid the prefix `o` being mistaken for a zero, while the prefix `0o` was introduced to avoid starting a numerical literal with an alphabetic character (like `o` or `q`), since these might cause the literal to be confused with a variable name. The prefix `0o` also follows the model set by the prefix `0x` used for hexadecimal literals in the C language; it is supported by Haskell,[19] OCaml,[20] Python as of version 3.0,[21] Raku,[22] Ruby,[23] Tcl as of version 9,[24] PHP as of version 8.1,[25] Rust[26] and ECMAScript as of ECMAScript 6[27] (the prefix `0` originally stood for base 8 in JavaScript but could cause confusion,[28] therefore it has been discouraged in ECMAScript 3 and dropped in ECMAScript 5[29]).*"

This proposal now reflects a recent corresponding change in C ([N3353](#)) that was triggered by an earlier version of this proposal.

It was observed that changes are needed in the specification of `std::format` and streams to support the new octal-literal prefix for input/output. This proposal does not address that and leaves them to a future proposal.

Examples

Padding

Padding leading zeros are often (attempted to be) used to nicely align numbers. This leads to surprising results if the programmer expected the number to be interpreted as a decimal. For example:

- Table of numbers:

```
std::array<std::array<int, 2>, 2> table = {
    { 100, 042 },
    { 107, 000 }
};
```

In this case, the programmer intended to write the decimal numbers 100, 42, 107, and 0. However, the values 000 and 042 are interpreted as octal-literals. While the octal-literal 000 is equivalent to the intended decimal number 0, the octal-literal 042 is equivalent to the decimal number 34, triggering bugs that are hard to find by the octal-unaware programmer or reader of code.

- Examples for issued caused by padding version numbers:
 - <https://github.com/AcademySoftwareFoundation/OpenColorIO/issues/1818>
 - <https://github.com/ThePhD/sol2/issues/265>

After this proposal

Following this proposal, these literals all specify the same number:

Literal	Before	After
Hex	0x2A	0x2A
Binary	0b00101010	0b00101010

Octal	052	0o52
-------	-----	------

The old octal literal 052 will remain valid but deprecated.

Effects on existing code

This proposal introduces 0o and 00 as new prefixes for octal-literals. Under the current standard, any sequence starting with 0o or 00 is illegal. Consequently, the proposed additions 0o and 00 will not break existing code.

Additionally, this proposal deprecates the existing error-prone syntax rule for non-zero integer literals starting with a zero, following the example of C ([N3353](#)). This would affect existing, traditional octal-literals (i.e. with a leading 0), for instance when defining POSIX file permissions (sometimes padded with multiple leading zeros), as seen in popular repositories (>500 stars) e.g., [ROOT](#), [Qt Creator](#), [node-android](#), [KDiff3](#).

We have received concerns that this deprecation leads to warnings for octal-literals that have the same value whether interpreted as octal or decimal. Examples of such literals are: 01, 02, 03, 04, 05, 06, 07. To keep the door open for a future proposal introducing 01...09 as decimal literals (typical use case: 1970y/January/01d), implementations might choose to not diagnose 01..07.

Technical Specification

We propose the feature test macro name `__cpp_0o_octals` for this feature.

To match [N3353](#), make the following edits (relative to [N5008](#)), highlighting the **insertions** and **removals**:

5.13.2 Integer literals [lex.icon]

```

octal-literal
0
octal-literal 'opt octal-digit
prefixed-octal-literal
unprefixed-octal-literal

unprefixed-octal-literal:
0
0 'opt octal-digit-sequence

prefixed-octal-literal:
octal-prefix octal-digit-sequence

```

Before *hexadecimal-prefix* insert

```

octal-prefix: one of
0o 00

```

Before *hexadecimal-digit-sequence* insert

```

octal-digit-sequence:
octal-digit
octal-digit-sequence 'opt octal-digit

```

Under paragraph 2, replace the text:

2 The hexadecimal-digits a through f and A through F have decimal values ten through fifteen. [Example 1 : The number twelve can be written 12, 014, 0o14, 0XC, or 0b1100. The integer-literals 1048576, 1'048'576, 0X100000, 0x10'0000, and 0'004'000'000 0o0'004'000'000, all have the same value. - end example]

After paragraph 4, add the paragraph:

An unprefixed-octal-literal ([lex.icon],[gram.lex]) of the form

0 'opt octal-digit-sequence

is deprecated. [depr.oct]

31.12.8.4 Enum class perm [fs.enum.perms]

Table 149 - Enum class perms [tab:fs.enum.perms]

Name	Value (octal)	POSIX macro	Definition or notes
none	000		There are no permissions set for the file.
owner_read	00400	S_IRUSR	Read permission, owner
owner_write	00200	S_IWUSR	Write permission, owner
owner_exec	00100	S_IXUSR	Execute/search permission, owner
owner_all	00700	S_IRWXU	Read, write, execute/search by owner; owner_read owner_write owner_exec
group_read	0040	S_IRGRP	Read permission, group
group_write	0020	S_IWGRP	Write permission, group
group_exec	0010	S_IXGRP	Execute/search permission, group
group_all	0070	S_IRWXG	Read, write, execute/search by group; group_read group_write group_exec
others_read	004	S_IROTH	Read permission, others
others_write	002	S_IWOTH	Write permission, others
others_exec	001	S_IXOTH	Execute/search permission, others
others_all	007	S_IRWXO	Read, write, execute/search by others; others_read others_write others_exec
all	00777		owner_all group_all others_all
set_uid	004000	S_ISUID	Set-user-ID on execution
set_gid	002000	S_ISGID	Set-group-ID on execution
sticky_bit	001000	S_ISVTX	Operating system dependent.
mask	007777		all set_uid set_gid sticky_bit
unknown	0xFFFF		The permissions are not known, such as when a file_status object is created without specifying the permissions

Annex D (normative) Compatibility features [depr]

Add a new section

D??. Deprecated unprefixed octal literal [depr.oct]

1 An *unprefixed-octal-literal* ([lex.icon],[gram.lex]) of the form

0 'opt octal-digit-sequence

is deprecated.

[Note 1: Use of *unprefixed octal literals*, except the literal 0, are deprecated because they are often confused with decimals. --end note].

[Example 1:

```
int zero = 0;           // OK  
int more zeroes = 000;  // deprecated  
int unprefixed octal = 042; // deprecated  
int prefixed octal = 0o42; // OK
```

--end example].

Acknowledgements

Thanks to Erich Keane and Thomas Köppe for reviewing the draft. The document style was borrowed from Doc. no. [N4340](#)