

P2319R5

Prevent path presentation problems

Published Proposal, 2025-06-17

Author:

[Victor Zverovich](#)

Audience:

LWG

Project:

ISO/IEC 14882 Programming Languages — C++, ISO/IEC JTC1/SC22/WG21

Table of Contents

- 1 Introduction**
- 2 Changes since R4**
- 3 Changes since R3**
- 4 Changes since R2**
- 5 Changes since R1**
- 6 Changes since R0**
- 7 LEWG poll results for R3**
- 8 SG16 poll results for R2**
- 9 SG16 poll results for R0**
- 10 Problem**
- 11 Proposal**

12 Wording

References

Informative References

"We are stuck with technology when what we really want is just stuff that works." — Douglas Adams

§ 1. Introduction

[P2845] made it possible to format and print `std::filesystem::path` with correct handling of Unicode. Unfortunately, some common path accessors still exhibit broken behavior, which results in mojibake and data loss. This paper proposes deprecating these accessors, making the path API more reliable and eliminating a common source of bugs.

§ 2. Changes since R4

- Simplified the Annex D entry by defining `string` and `generic_string` in terms of `system_encoded_string` and `generic_system_encoded_string` respectively.
- Changed the format of the Annex D entry for consistency with other similar entries such as [\[depr.move.iter.elem\]](#).
- Added instructions to bump the `__cpp_lib_format_path` feature test macro.

§ 3. Changes since R3

- Reintroduced `system_string` and `display_string` accessors per LEWG feedback.
- Renamed `system_string` to `system_encoded_string`.
- Added LEWG poll results for R3.

§ 4. Changes since R2

- Added SG16 poll results for R2.

§ 5. Changes since R1

- Added SG16 poll results for R0.

§ 6. Changes since R0

- Removed `system_string` and `display_string` per SG16 feedback focusing just on deprecating broken accessors.

§ 7. LEWG poll results for R3

POLL: Re-add the function `system_string` which was presented in P2319R0

SF	F	N	A	SA
7	7	4	1	3

Outcome: Consensus in favor

POLL: Re-add the function `display_string` (result of calling `format`) which was presented in P2319R0

SF	F	N	A	SA
13	7	2	0	0

Outcome: Strong consensus in favor

POLL: Approve the design (re-add `display_string`, `system_string`) presented in "P2319R3 Prevent path presentation problems" (deprecating functions in `path`).

SF	F	N	A	SA
10	8	2	1	2

Outcome: Consensus in favor

§ 8. SG16 poll results for R2

Poll 1: P2319R2: Forward to LEWG.

SF	F	N	A	SA
----	---	---	---	----

2	6	0	0	0
---	---	---	---	---

Strong consensus in favor.

From <https://github.com/cplusplus/papers/issues/1987#issuecomment-2482417123>:

The general consensus of the group is that portable code should be written to use `std::format()` to format paths or to use the `native()` member function and convert appropriately to the desired encoding.

§ 9. SG16 poll results for R0

Poll 1: P2319R0: The `string()` member function of `std::filesystem::path` should be deprecated.

SF	F	N	A	SA
2	4	1	0	0

Outcome: Consensus

Poll 2: P2319R0: The proposed `system_string()` member function should be added to `std::filesystem::path`.

SF	F	N	A	SA
0	2	4	1	0

Outcome: No consensus

§ 10. Problem

Consider the following example:

```
std::filesystem::path p(L"Выявы"); // Выявы is Images in Belarusian.
std::cout << p << std::endl;
std::cout << p.string() << std::endl;
```

Even if all code pages and localization settings are set to Belarusian and both the source and literal encodings are UTF-8, this still results in mojibake on Windows:

```
"Т√ Т√"  
Т√ Т√
```

Unfortunately, we cannot change the behavior of iostreams but at least the new facilities such as `std::format` and `std::print` correctly handle Unicode in paths. For example:

```
std::filesystem::path p(L"Выявы");  
std::print("{}\n", p);
```

prints

```
Выявы
```

However, the `string()` accessor still exhibits the broken behavior, e.g.

```
std::filesystem::path p(L"Выявы");  
std::print("{}\n", p.string());
```

prints

```
?????
```

The reason for this is that `std::filesystem::path::string()` transcodes the path into the native encoding (`[fs.path.type.cvt]`) defined as:

The native encoding of an ordinary character string is the operating system dependent current encoding for pathnames (`[fs.class.path]`).

It is neither the literal encoding nor a locale encoding, and transcoding is usually lossy, which makes it almost never what you want. For example:

```
std::filesystem::path p(L"Obrazy");  
std::string s = p.string();
```

throws `std::runtime_error` with the message "unknown error" on the same system which is a terrible user experience.

The string can be passed to system-specific APIs that accept paths provided that the system encoding hasn't changed in the meantime. But even this use case is limited because the transcoding is lossy, and it's better to use an equivalent `std::filesystem` API or `native()` instead.

On Windows, the native encoding is effectively the Active Code Page (ACP), which is separate from the console code page. This is why paths often cannot be correctly displayed. Even Windows documentation ([\[CODE-PAGES\]](#)) cautions against using code pages:

New Windows applications should use Unicode to avoid the inconsistencies of varied code pages and for ease of localization.

Encoding bugs are even present in standard library implementations, see e.g. [\[LWG4087\]](#), where a path in the "native" encoding is incorrectly combined with text in literal and potentially other encodings when constructing an exception message.

Moreover, the result of `string()` is affected by a runtime setting and may work in a test environment but easily break after deployment. This is similar to one of the problems with `std::locale` but worse because in this case C++ doesn't even provide a way to set or query the encoding. It disproportionately affects non-English C++ users making the language not as attractive for writing internationalized and localized software.

To summarize, `std::filesystem::path::string()` has the following problems:

- It uses encoding that is generally incompatible with nearly all standard text processing and I/O facilities including iostreams, `std::format` and `std::print`.
- It is extremely error-prone, causing easy to miss transcoding issues that may arise after the program is deployed in a different environment or after a runtime configuration change.
- It makes writing portable code hard because the issues may not be obvious on POSIX platforms where `string()` is just an inefficient equivalent of `native()` with extra memory allocation and copy.

§ 11. Proposal

The current paper proposes deprecating the `std::filesystem::path::string()`, providing alternatives that make the target encoding clear:

- `system_encoded_string()` returning `std::string` in the operating system dependent current encoding for pathnames (native ordinary encoding). Similarly to the current `string()`, it is lossy and only useful for passing to legacy system APIs.
- `display_string()` returning `std::string` in the literal encoding suitable for display, e.g. formatting with `std::format` and printing with `std::print`. It is lossless if the literal encoding is UTF-8 and the path is valid Unicode which is almost all paths on Windows.

We use "system" instead of "native" because the latter is ambiguous: it can either refer to encoding or format (path separators, etc.)

Similarly, `generic_string()`, which has the same problems, is also deprecated with `generic_system_encoded_string()` and `generic_display_string()` alternatives provided.

`system_encoded_string()` can be used to simplify bulk bug-to-bug compatible migration of a large existing codebase. This will make problematic call sites easy to grep and fix incrementally, prioritizing more critical parts of the codebase where potential data loss due to transcoding is especially undesirable.

There is usually a better way to accomplish the same task with non-legacy APIs, e.g. using the lossless `std::filesystem::remove` that takes a path object instead of `std::remove`:

```
std::filesystem::remove(p); // Lossless, portable and more efficient.
```

Ideally, `std::remove` should be deprecated but this is out of scope of the current paper.

For lossless display, deprecated accessors can be replaced with `display_string()` or formatting `path` using new facilities such as `std::format` or `std::print`.

§ 12. Wording

Update the value of the feature-testing macro `__cpp_lib_format_path` to the date of adoption in [\[version.syn\]](#).

Modify [\[https://eel.is/c++draft/fs.class.path.general\]](https://eel.is/c++draft/fs.class.path.general):

```
...

// [fs.path.native.obs], native format observers
const string_type& native() const noexcept;
```

```

const value_type* c_str() const noexcept;
operator string_type() const;

template<class EcharT, class traits = char_traits<EcharT>,
        class Allocator = allocator<EcharT>>
    basic_string<EcharT, traits, Allocator>
        string(const Allocator& a = Allocator()) const;
std::string string() const;
std::string display_string() const;
std::string system_encoded_string() const;
std::wstring wstring() const;
std::u8string u8string() const;
std::u16string u16string() const;
std::u32string u32string() const;

// [fs.path.generic.obs], generic format observers
template<class EcharT, class traits = char_traits<EcharT>,
        class Allocator = allocator<EcharT>>
    basic_string<EcharT, traits, Allocator>
        generic_string(const Allocator& a = Allocator()) const;
std::string generic_string() const;
std::string generic_display_string() const;
std::string generic_system_encoded_string() const;
std::wstring generic_wstring() const;
std::u8string generic_u8string() const;
std::u16string generic_u16string() const;
std::u32string generic_u32string() const;

...

```

Modify `[fs.path.native.obs]`:

...

```

std::string string() const;
std::string system_encoded_string() const;
std::wstring wstring() const;
std::u8string u8string() const;
std::u16string u16string() const;
std::u32string u32string() const;

```

Returns: `native()`.

Remarks: Conversion, if any, is performed as specified by [fs.path.cvt].

```
std::string display_string() const;
```

Returns: `format("{} ", *this)`.

[*Note:* The returned string is suitable for use with formatting ([format.functions]) and print functions ([print.fun]). — *end note*]

Modify [fs.path.generic.obs]:

...

```
std::string generic_string() const;  
std::string generic_system_encoded_string() const;  
std::wstring generic_wstring() const;  
std::u8string generic_u8string() const;  
std::u16string generic_u16string() const;  
std::u32string generic_u32string() const;
```

Returns: The pathname in the generic format.

Remarks: Conversion, if any, is specified by [fs.path.cvt].

```
std::string generic_display_string() const;
```

Returns: `format("{:g} ", *this)`.

[*Note:* The returned string is suitable for use with formatting ([format.functions]) and print functions ([print.fun]). — *end note*]

Add a new subclause in Annex D:

Deprecated filesystem path format observers [depr.fs.path.obs]

The following members are declared in addition to those members specified in [fs.path.member]:

```
namespace std::filesystem {  
    class path {  
    public:  
        std::string string() const;
```

```
std::string generic_string() const;  
};  
}
```

```
std::string string() const;
```

Returns: `system_encoded_string()`.

```
std::string generic_string() const;
```

Returns: `generic_system_encoded_string()`.

§ References

§ Informative References

[CODE-PAGES]

Windows App Development / Code Pages. URL: <https://learn.microsoft.com/en-us/windows/win32/intl/code-pages>

[LWG4087]

LWG Issue 4087: Standard exception messages have unspecified encoding. URL: <https://cplusplus.github.io/LWG/issue4087>

[P2845]

Victor Zverovich. *Formatting of `std::filesystem::path`*. URL: <https://wg21.link/p2845>